

BS ISO 15740:2013



BSI Standards Publication

# Photography — Electronic still picture imaging — Picture transfer protocol (PTP) for digital still photography devices

**bsi.**

...making excellence a habit.™

**National foreword**

This British Standard is the UK implementation of ISO 15740:2013. It supersedes BS ISO 15740:2008 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee CPW/42, Photography.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2013. Published by BSI Standards Limited 2013

ISBN 978 0 580 82308 4

ICS 37.040.99

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2013.

**Amendments issued since publication**

Date	Text affected
------	---------------

---

---

---

**Photography — Electronic still  
picture imaging — Picture transfer  
protocol (PTP) for digital still  
photography devices**

*Photographie — Imagerie des prises de vue électroniques —  
Protocole de transfert d'images (PTP) pour les appareils  
photographiques électroniques numériques*





**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

<b>Foreword</b> .....	<b>v</b>
<b>Introduction</b> .....	<b>vi</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Digital still photography device model</b> .....	<b>5</b>
4.1 Overview.....	5
4.2 Baseline requirements.....	6
<b>5 Data format specification</b> .....	<b>6</b>
5.1 General format.....	6
5.2 Data types.....	7
5.3 Simple types.....	9
5.4 Arrays.....	11
5.5 Data sets.....	12
<b>6 Image and data object formats</b> .....	<b>21</b>
6.1 Object usage.....	21
6.2 Thumbnail formats.....	22
6.3 ObjectFormatCodes.....	23
6.4 Object format version identification.....	23
6.5 Data object association.....	24
<b>7 Transport requirements</b> .....	<b>26</b>
7.1 Disconnection events.....	26
7.2 Reliable, error-free channel.....	27
7.3 Asynchronous event support.....	27
7.4 Device discovery and enumeration.....	27
7.5 Specific transports.....	27
<b>8 Persistent storage</b> .....	<b>27</b>
8.1 StorageID.....	27
8.2 Data object referencing.....	28
8.3 Receiver object placement.....	29
<b>9 Communication protocol</b> .....	<b>30</b>
9.1 Device roles.....	30
9.2 Sessions.....	30
9.3 Transactions.....	30
9.4 Operation flow.....	33
9.5 Vendor extensions.....	33
<b>10 Operations</b> .....	<b>35</b>
10.1 Operation overview.....	35
10.2 Operation parameters.....	35
10.3 OperationCode format.....	35
10.4 OperationCode summary.....	35
10.5 Operation descriptions.....	35
<b>11 Responses</b> .....	<b>60</b>
11.1 ResponseCode format.....	60
11.2 ResponseCode summary.....	60
11.3 Response descriptions.....	61
<b>12 Events</b> .....	<b>66</b>
12.1 Event usage.....	66
12.2 Event types.....	66

12.3	Event data set.....	66
12.4	EventCode format.....	67
12.5	EventCode summary.....	67
12.6	Event descriptions.....	67
<b>13</b>	<b>Device properties.....</b>	<b>71</b>
13.1	Device property usage.....	71
13.2	Values of a device property.....	71
13.3	Device property management requirements.....	72
13.4	Device property identification.....	72
13.5	Device property descriptions.....	76
<b>14</b>	<b>Streaming (PTP v1.1 only).....</b>	<b>92</b>
14.1	Streaming overview.....	92
14.2	Stream transfer.....	92
14.3	Multiplexing.....	92
14.4	Discovering and configuring stream capabilities.....	93
14.5	Data transfer mechanism.....	93
14.6	Packet layout.....	94
14.7	Frame layout.....	95
14.8	Enumerating supported streams.....	95
14.9	Retrieving stream information.....	95
<b>15</b>	<b>Conformance section.....</b>	<b>95</b>
<b>Annex A (informative) Optional device features.....</b>		<b>98</b>
<b>Annex B (normative) Object referencing and format codes.....</b>		<b>100</b>
<b>Annex C (informative) Operation flow example scenarios.....</b>		<b>102</b>
<b>Annex D (informative) Filesystem implementation examples.....</b>		<b>106</b>
<b>Annex E (informative) Reference to OSI model.....</b>		<b>109</b>
<b>Annex F (informative) SendObject implementation example.....</b>		<b>112</b>
<b>Bibliography.....</b>		<b>115</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. [www.iso.org/directives](http://www.iso.org/directives)

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. [www.iso.org/patents](http://www.iso.org/patents)

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

The committee responsible for this document is ISO/TC 42, *Photography*.

This third edition cancels and replaces the second edition (ISO 15740:2008), of which it constitutes a minor revision with the following changes:

- as the vendor extension ID registry formerly maintained by the I3A has been transferred to another organization, term [3.21](#) (I3A) was removed and the remaining terms renumbered;
- in [9.5.1](#), the fourth and fifth sentences were amended and combined to reflect that a new organization assigns and maintains VendorExtensionIDs.

## Introduction

This third edition of ISO 15740 (hereinafter designated PTP v1.1) provides optional support for new increased performance and compatibility. All new constructs are fully backward compatible with the first edition (hereinafter designated PTP v1.0) and are optional. See [5.5.2](#) for standard version.

For the purposes of this International Standard, digital still photography devices (DSPDs) are defined as devices with persistent storage which capture a digital two-dimensional image at a discrete point in time. Most DSPDs include interfaces that can be used to connect to a host computer or other imaging device, such as a printer. A number of high speed interface transports has been developed, including USB, TCP/IP and IEEE 1394 (FireWire). This International Standard is designed to provide requirements for communicating with DSPDs. This includes communications with any type of device, including host computers, direct printers and other DSPDs over a suitable transport. The requirements include standard image referencing behaviour, operations, responses, events, device properties, data sets and data formats to ensure interoperability. This International Standard also provides optional operations and formats, as well as extension mechanisms.

This International Standard specifies the following:

- behaviour requirements for DSPDs; this includes the baseline features a device needs to support in order to provide interoperability over conforming transports;
- functional requirements needed by a transport to facilitate the creation of a transport-dependent implementation specification that conforms to this International Standard;
- a high-level protocol for communicating with and between DSPDs consisting of operation, data and response phases;
- sets of suggested data codes and their usages including
  - OperationCodes,
  - ResponseCodes,
  - ObjectFormatCodes,
  - DevicePropCodes,
  - EventCodes,
  - required data sets and their usages,
  - a means of describing data object associations and filesystems and
  - mechanisms for implementing extensibility.

This International Standard does not attempt to define any of the following:

- any sort of device discovery, enumeration or transport aggregation methods; implementation of this functionality is left to the transports and the platforms upon which support for this International Standard is implemented;
- an application programming interface; this is left to the platforms upon which support for this International Standard is implemented.

This International Standard has been designed to appropriately support popular image formats used in digital still cameras, including the Exif and TIFF/EP formats defined in ISO 12234-1<sup>[15]</sup> and ISO 12234-2, as well as the Design Rule for Camera Filesystem (DCF) and the Digital Print Order Format (DPOF).

The technical content of this International Standard is closely related to PIMA 15740:2000. The main difference is that PIMA 15740:2000 includes an informative annex describing a USB implementation of



ISO 15740. This information is not included in this International Standard, which instead references the USB still device class document developed by the Device Working Group of the USB Implementers Forum.

PTP v1.1 provides optional support for new increased performance and compatibility. All new constructs are fully backward compatible with PTP v1.0 and are optional.

— Performance Enhancements:

- Support for retrieval of ObjectHandles in enumerated chunks, via specification of three new optional operations and a new response code. This may reduce long response times for some initiators that possess large numbers of objects.
- Support for optional arbitrary resizing prior to image transmission via specification of a new operation GetResizedImageObject. In PTP v1.0, image sizes might be requested in full-resolution or thumbnail size only.
- Support for arrays of data sets. This can be used to reduce the number of required transactions necessary for device characterization from being a function of the number of objects on the device to one.
- An optional fast file characterization operation called GetFilesystemManifest that exploits data set arrays to request, in a single transaction, only the minimum data required to characterize a typical filesystem. Many initiators, particularly in printing scenarios, are interested in fast filesystem characterization for access to a specifically named file in a particular place. This capability can significantly improve end-user workflow latency. This single operation replaces the typical series of many GetObjectInfo requests with a binary filesystem manifest. This manifest is defined as a simple array of a subset of the standard ObjectInfo data set called the ObjectFilesystemInfo data set. This operation replaces the need for many GetObjectInfo calls, while also avoiding the need for responders to perform many internal file-opens on the fly, or to cache ObjectInfo image data that is often held persistently only “inside” internal image files (e.g. TIFF tags inside EXIF JPEGs), to quickly communicate only the fast filesystem information.

— Compatibility Enhancements:

- An optional mechanism to support multiple vendor extension sets. This is specified via the new VendorExtensionMap data set, and two new optional operations that may be invoked outside of a session (GetVendorExtensionMaps and GetVendorDeviceInfo).
- The optional fast file characterization method GetFilesystemManifest natively supports extremely large objects, by requiring 8-bytes for object size (UINT64), as opposed to the standard 4-bytes.
- A new standard ObjectFormatCode to support the Digital Negative file format (DNG).

— Feature Enhancement:

- An optional mechanism for handling streaming content. This is specified via the new StreamInfo data set, as well as the supporting GetStreamInfo and GetStream operations, as well as some optional new supporting DeviceProperties. This is described in a new Clause 14.



# Photography — Electronic still picture imaging — Picture transfer protocol (PTP) for digital still photography devices

## 1 Scope

This International Standard provides a common communication protocol for exchanging images with and between digital still photography devices (DSPDs). This includes communication between DSPDs and host computers, printers, other digital still devices, telecommunications kiosks and image storage and display devices.

This protocol is transport- and platform-independent.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8601, *Data elements and interchange formats — Information interchange — Representation of dates and times*

ISO 12234-2, *Electronic still-picture imaging — Removable memory — Part 2: TIFF/EP image data format*

ISO/IEC 10646, *Information technology — Universal Coded Character Set (UCS)*

ISO/IEC 10918-1:1994, *Information technology — Digital compression and coding of continuous-tone still images: Requirements and guidelines*

IEC 61966-2-1, *Multimedia systems and equipment — Colour measurement and management — Part 2-1: Colour management — Default RGB colour space — sRGB*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### **album**

end-user-created object used to logically group data objects according to some user-defined criteria

Note 1 to entry: An album might or might not be a physical folder in a filesystem. In this International Standard, an album is a type of association.

### 3.2

#### **association**

logical construct used to expose a relationship between discrete objects

Note 1 to entry: Associations are used to indicate that separate data objects are related. Associations are represented like folders, and can be nested using a standard branched hierarchical tree structure.

EXAMPLE A time sequence, or user-defined groupings by content or capture session.

### 3.3

#### **connection**

transport-provided mechanism for establishing paths for transferring data between devices