# INTERNATIONAL STANDARD

ISO 18168

First edition 2015-12-15

## Textile floor coverings — Colour fastness to shampooing

Revêtements de sol textiles — Solidité des coloris au shampooing



#### ISO 18168:2015(E)



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Foreword			Page
			iv
1	Scop	pe	1
2	Normative references  Terms and definitions		1
3			1
4	Principle		
5	Appa 5.1 5.2 5.3 5.4	Testing frame Auxiliary equipment Shampoo solution Adjacent fabrics 5.4.1 Textile floor coverings 5.4.2 Yarns or loose fibres 5.4.3 Tufts Grey scales	
6	Prep 6.1 6.2 6.3 6.4	General Textile floor covering Yarns Loose fibres and tufts	
7	Procedure		3
8	Test report		4
Rihl	ingrank	hv	5

## **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. <a href="www.iso.org/directives">www.iso.org/directives</a>

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. <a href="www.iso.org/patents">www.iso.org/patents</a>

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 219, *Floor coverings*.

## Textile floor coverings — Colour fastness to shampooing

## 1 Scope

This International Standard describes a method for determining the colour fastness of textile floor coverings and yarns, loose fibres and tufts extracted from textile floor coverings, to the action of a reference shampoo solution.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2424, Textile floor coverings — Vocabulary

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2424 apply.

## 4 Principle

A specimen of a textile floor covering, yarn, loose fibre or tuft, in contact with specified adjacent fabrics, is immersed under pressure in a shampoo solution buffered to a pH of  $(7.5 \pm 0.2)$ . The specimen and the adjacent fabric are dried separately. The change in colour of the specimen and the staining of the adjacent fabrics are assessed using the grey scales.

## 5 Apparatus and reagents

#### **5.1** Testing frame

The device consists of a stainless steel frame into which a mass of 5 kg with a base of 60 mm  $\times$  115 mm fits closely so that a pressure of 12,5 kPa can be applied on test specimens (40 mm  $\times$  100 mm), placed between glass or acrylic resin plates. If the mass is removed during the test, the testing device shall be constructed so that the pressure of 12,5 kPa remains unchanged.

Other devices may be used provided that the same results are obtained as with the apparatus described in <u>Clause 5</u>.

#### 5.2 Auxiliary equipment

- **5.2.1 Flat-bottomed dish**, approximately 150 mm × 150 mm × 50 mm.
- **5.2.2** Mass, 5 kg with a base of  $60 \text{ mm} \times 115 \text{ mm}$ .
- **5.2.3 pH meter,** with an accuracy of 0,02 units.
- **5.2.4 Oven**, maintained at  $(40 \pm 2)$  °C.