



BSI Standards Publication

Characteristics of DAB receivers

National foreword

This British Standard is the UK implementation of IEC 62104:2015. It supersedes BS EN 62104:2007, which is withdrawn.

This standard has not been adopted by CENELEC as the standard series has been agreed as exempt from parallel procedure. Therefore, BS EN 62104:2007 has been withdrawn to allow for the publication of BS IEC 62104:2015.

The UK participation in its preparation was entrusted to Technical Committee EPL/100, Audio, video and multimedia systems and equipment.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019
Published by BSI Standards Limited 2019

ISBN 978 0 580 81581 2

ICS 33.160.20

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 June 2019.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



IEC 62104

Edition 3.0 2015-07

INTERNATIONAL STANDARD

Characteristics of DAB receivers

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.060.20

ISBN 978-2-8322-2812-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	6
1 Scope.....	8
2 Normative references.....	8
3 Terms and definitions	10
4 Basic implementation and functional performance requirements	13
4.1 Automatic mode selection.....	13
4.1.1 General	13
4.1.2 Requirements	13
4.2 Frequency bands	13
4.3 Channel decoder.....	13
4.3.1 Standard receiver.....	13
4.3.2 Multimedia receiver.....	13
4.4 Service selection.....	13
4.4.1 General	13
4.4.2 Requirements	14
4.5 Receiver reactions to a multiplex reconfiguration	14
4.6 Audio decoder.....	14
4.6.1 General	14
4.6.2 DAB services	15
4.6.3 DAB+ services	15
4.7 Automatic switching to another ensemble	15
4.8 Response to conditional access (CA) services	15
4.8.1 General	15
4.8.2 Requirements for DAB receivers without CA capabilities	15
4.9 Output for audio and other services	15
4.9.1 General	15
4.9.2 Requirements	16
4.10 Display	16
4.10.1 Standard receiver.....	16
4.10.2 Multimedia receiver.....	16
4.11 Text labels	16
4.11.1 Standard receiver.....	16
4.11.2 Multimedia receiver.....	16
4.12 Data applications	17
4.12.1 Standard receiver.....	17
4.12.2 Multimedia receiver.....	17
5 Interfaces.....	17
5.1 General.....	17
5.2 RF input.....	17
5.2.1 General	17
5.2.2 Domestic and portable receivers	17
5.2.3 Automotive receivers.....	18
5.3 Analogue audio interface (see IEC 61938).....	19
5.4 Digital audio interface (see IEC 60958-3).....	19
6 Options	19
6.1 General.....	19

6.2	Service lists	19
6.3	Display	20
6.3.1	General	20
6.3.2	Service labels and service component labels	20
6.3.3	Dynamic label	20
6.3.4	Signal quality indicator	20
6.3.5	Audio coding information	20
6.4	Other receiver features	21
6.4.1	Time and date	21
6.4.2	Service following	21
6.4.3	Announcements	21
6.4.4	Dynamic range control (DRC)	21
6.5	Data features	21
6.5.1	Journaline	21
6.5.2	Broadcast website (BWS)	22
6.5.3	TPEG services	22
7	Minimum performance levels and measuring methods	22
7.1	General conditions	22
7.1.1	General – Published specifications for receivers	22
7.1.2	Power supply	22
7.1.3	Atmospheric conditions	22
7.1.4	BER measurement conditions	22
7.1.5	Acoustic onset of impairment (OOI) measurement conditions	23
7.1.6	DAB signal	23
7.1.7	Receiver classification	23
7.2	Audio part – Performance requirements	24
7.2.1	General	24
7.2.2	DAB services	24
7.2.3	DAB+ services	24
7.3	RF part – Sensitivity test methods	24
7.3.1	General	24
7.3.2	Baseband stream and RF conditions for BER and OOI testing	24
7.3.3	Baseband stream and listening conditions for acoustic OOI testing	24
7.4	Sensitivity requirement using a conducted signal at node “A”	25
7.4.1	General	25
7.4.2	Method of measurement (Gaussian channel) using BER	25
7.4.3	Presentation of results using BER	25
7.4.4	Requirements – Receiver types A2, C2, D, E2 using BER	26
7.4.5	Method of measurement (Gaussian channel) using acoustic OOI	26
7.4.6	Presentation of results using acoustic OOI	26
7.4.7	Requirements – Receiver types A2, C2, D, E2 using acoustic OOI	26
7.5	Sensitivity using radiated electromagnetic wave at node “N”	27
7.5.1	General	27
7.5.2	Link budget transmission assumption – Non-automotive receivers	27
7.5.3	Method of measurement – Non-automotive types A1, B, C1, C2 and A2 with optional antenna	27
7.5.4	Presentation of results	29
7.5.5	Requirements – Types A1, B, C1, C2 and A2 with optional antenna	29
7.5.6	Link budget transmission assumption – Automotive types D, E1, E2	29

7.6	RF part – Maximum input power	29
7.6.1	General	29
7.6.2	Method of measurement (Gaussian channel)	29
7.6.3	Presentation of results	29
7.6.4	Requirements	29
7.7	RF part – Selectivity	30
7.7.1	General	30
7.7.2	Adjacent channel selectivity	30
7.7.3	Rejection of unwanted signals (far-off selectivity).....	32
7.8	RF part – Performance in a Rayleigh channel	33
7.8.1	General	33
7.8.2	Sensitivity	33
7.8.3	Method of measurement – Conducted input signal only	33
7.8.4	Presentation of results	35
7.8.5	Requirements	35
7.9	RF part – Acquisition time after synchronization loss.....	35
7.9.1	General	35
7.9.2	Method of measurement.....	35
7.9.3	Presentation of results	36
7.9.4	Requirements	36
Annex A (informative) Recommended centre frequencies.....		37
Annex B (normative) Characteristics of a Rayleigh channel.....		39
B.1	Simulation of the mobile radio channel.....	39
B.2	Doppler spectrum types.....	39
B.2.1	General	39
B.2.2	Doppler spectrum: CLASS.....	40
B.2.3	Doppler spectrum: GAUS1	40
B.2.4	Doppler spectrum: GAUS2	40
B.2.5	Doppler spectrum: GAUSDAB	40
B.2.6	Doppler spectrum: RICE.....	40
B.3	Propagation models	40
B.3.1	General	40
B.3.2	Typical rural (non-hilly) area (RA).....	41
B.3.3	Typical urban (non-hilly) area (TU)	41
B.4	Tap setting for hardware simulators	42
Annex C (informative) Basic characteristics and functionality for accessibility for blind and visually impaired users		44
Bibliography		45
Figure 1 – Example of a functional block diagram of a DAB receiver		12
Figure 2 – Block diagram for the measurement of the sensitivity and the maximum input power, using BER.....		25
Figure 3 – Block diagram for the measurement of the sensitivity and the maximum input power, using acoustic OOI.....		26
Figure 4 – Block diagram for the measurement of free field sensitivity.....		27
Figure 5 – Free field screened chamber measurement – Features and setup.....		28
Figure 6 – Spectrum mask of the DAB signal for selectivity measurements.....		30
Figure 7 – Block diagram for BER method selectivity measurements		31

Figure 8 – Block diagram for OOI method selectivity measurements.....	32
Figure 9 – Block diagram for measuring the performance in a Rayleigh channel	34
Figure 10 – Block diagram for measuring acquisition time after synchronization loss	35
Figure B.1 – Continuous delay power profile $P(\tau)$ for RA	41
Figure B.2 – Continuous delay power profile $P(\tau)$ for TU	41
Table 1 – Performance requirement for an automotive active antenna	18
Table 2 – Classification of receiver types	23
Table 3 – Conditions for BER and OOI testing	24
Table 4 – Conditions for acoustic OOI testing	25
Table 5 – Conditions for uniform signal level	28
Table 6 – Minimum requirements for maximum input power (conducted)	30
Table 7 – Difference between the centre frequencies of the DAB ensembles	31
Table 8 – Minimum requirement for adjacent channel selectivity	32
Table 9 – Channel simulation profiles related to frequency band and mode	34
Table A.1 – Recommended centre frequencies for DAB (1 of 2)	37
Table B.1 – Four tap setting for typical rural (non-hilly) area (RA)	42
Table B.2 – Six tap setting for typical rural (non-hilly) area (RA)	42
Table B.3 – Twelve tap setting for typical urban (non-hilly) area (TU)	43
Table B.4 – Six tap setting for typical urban (non-hilly) area (TU)	43
Table B.5 – Tap setting for single-frequency networks (SFN) in VHF bands.....	43

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CHARACTERISTICS OF DAB RECEIVERS**FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62104 has been prepared by technical area 1, Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This third edition cancels and replaces the second edition published in 2003. This edition constitutes a technical revision.

The main changes with respect to the previous edition are as follows.

- The document has been updated in line with the development of the DAB system, and in particular the introduction of DAB+ audio services (see ETSI TS 102 563).¹
- Requirements for displays, text and data applications have been introduced to reflect market trends.

¹ For an overview of the DAB standards, see ETSI TR 101 495.

- Additional test methods have been introduced to allow R.F. measurements to be made on receivers with integrated antennas and/or no external BER indicators by using an acoustic impairment method.
- Clause 6 has been updated to reflect the development of the market and to provide better guidance for the implementation of optional features.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/2502/FDIS	100/2541/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

CHARACTERISTICS OF DAB RECEIVERS

1 Scope

This International Standard describes the digital audio broadcasting (DAB) receiver characteristics for consumer equipment intended for terrestrial and cable reception operating in VHF band III. Dedicated receivers for specific applications are not within the scope of this standard. This standard describes the characteristics for different classes and categories of DAB receivers such as standard and multimedia receivers and domestic, automotive and adapter receivers.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60169-10, *Radio-frequency connectors – Part 10: R.F. coaxial connectors with inner diameter of outer conductor 3 mm (0,12 in) with snap-on coupling – Characteristic impedance 50 ohms (Type SMB)*

IEC 60315-1, *Methods of measurement on radio receivers for various classes of emission – Part 1: General considerations and methods of measurement, including audio-frequency measurements*

IEC 60315-4, *Methods of measurement on radio receivers for various classes of emission – Part 4: Receivers for frequency-modulated sound-broadcasting emissions*

IEC 60958-3, *Digital audio interface – Part 3: Consumer applications*

IEC 61169-2:2007, *Radio-frequency connectors – Part 2: Sectional specification – Radio frequency coaxial connectors of type 9,52*

IEC 61169-24, *Radio-frequency connectors – Part 24: Sectional specification – Radio frequency coaxial connectors with screw coupling, typically for use in 75 ohm cable networks (type F)*

IEC 61606 (all parts), *Audio and audiovisual equipment – Digital audio parts – Basic measurement methods of audio characteristics*

IEC 61938, *Multimedia systems – Guide to the recommended characteristics of analogue interfaces to achieve interoperability*

IEC 62106:2009, *Specification of the radio data system (RDS) for VHF/FM sound broadcasting in the frequency range from 87,5 MHz to 108,0 MHz*

ISO/IEC 10646, *Information technology – Universal Coded Character Set (UCS)*

ISO/IEC 11172-3, *Information technology – Coding of moving pictures and associated audio for digital storage media at up to about 1,5 Mbit/s – Part 3: Audio*