



Edition 5.0 2021-04

INTERNATIONAL STANDARD

Primary batteries – Part 3: Watch batteries





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.





Edition 5.0 2021-04

INTERNATIONAL STANDARD

Primary batteries – Part 3: Watch batteries

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.220.10; 39.040.10

ISBN 978-2-8322-9686-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FC	DREWO	RD	4
IN	TRODU	ICTION	6
1	Scop	e	7
2	Norm	native references	7
3	Term	is and definitions	7
4	Phys	ical requirements	8
	4.1	Battery dimensions, symbols and size codes	
	4.2	Terminals	
	4.3	Projection of the negative terminal (h_5)	
	4.4	Shape of battery	
	4.5	Mechanical resistance to pressure	
	4.6	Deformation	
	4.7	Leakage	.12
	4.8	Marking	.12
	4.8.1	General	.12
	4.8.2	Disposal	.13
5	Elect	rical requirements	.13
	5.1	Electrochemical system, nominal voltage, end-point voltage and open-circuit	
		voltage	
	5.2	Closed circuit voltage U_{CC} (CCV), internal resistance and impedance	
	5.3	Capacity	
~	5.4	Capacity retention	
6		oling and quality assurance	
7		methods	
	7.1	Shape and dimensions	
	7.1.1		
	7.2	Electrical characteristics	
	7.2.1		
	7.2.2 7.2.3	- 1	
	7.2.3		. 15
	1.2.7	voltage U_{CC} (CCV)	16
	7.2.5		
	7.2.6		.17
	7.2.7	Calculation of the internal resistance <i>R_i</i> during discharge in case of method A (optional)	10
	7.3	Test methods for determining the resistance to leakage	
	7.3.1	Preconditioning and initial visual examination	
	7.3.2	-	
	7.3.3		
8		al examination and acceptance conditions	
	8.1	Preconditioning	
	8.2	Magnification	
	8.3	Leakage levels and classification	
	8.4	Acceptance conditions	.22

Annex A (normative)	Designation	23
Bibliography		24

Figure 1 – Dimensional drawing	8
Figure 2 – Shape of battery	11
Figure 3 – Shape requirement	14
Figure 4 – Schematic voltage transient	15
Figure 5 – Curve: $U = f(t)$	16
Figure 6 – Circuitry principle	16
Figure 7 – Circuitry principle for method A	18
Figure 8 – Circuitry principle for method B	19
Figure 9 – Test by temperature cycles	20

Table 1 – Zinc systems L and S dimensions and size codes	9
Table 2 – Lithium systems B and C dimensions and size codes	10
Table 3 – Values of l ₁	11
Table 4 – Applied force F by battery dimensions	12
Table 5 – Standardised electrochemical systems	13
Table 6 – Test method for U_{CC} (CCV) measurement	17
Table 7 – Test method A for U_{CC} (CCV) measurement	18
Table 8 – Storage conditions for the recommended test	20
Table 9 – Storage conditions for optional test	20
Table 10 – Leakage levels and classification	21

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRIMARY BATTERIES –

Part 3: Watch batteries

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60086-3 has been prepared by IEC technical committee 35: Primary cells and batteries, and ISO technical committee 114: Horology.

This fifth edition cancels and replaces the fourth edition published in 2016. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) reformatted Table 1 and Table 2. The reformatted tables are now divided by system. Dimensional tolerances were changed when appropriate. Cell sizes were removed or added based on the size prevalence in the market place;
- b) in Table 3 the minimum values of l_1 were reformatted;
- c) the minimum OCV for the S system in Table 5 was changed to 1,55 V.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
35/1467/FDIS	35/1470/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 60086 series, published under the general title *Primary batteries*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This part of IEC 60086 provides specific requirements and information for primary watch batteries. This part of IEC 60086 was prepared through joint work between the IEC and ISO to benefit primary battery users, watch designers and battery manufacturers by ensuring the best compatibility between batteries and watches.

This part of IEC 60086 will remain under continual scrutiny to ensure that the publication is kept up to date with the advances in both battery and watch technologies.

NOTE Safety information is available in IEC 60086-4 and IEC 60086-5.

PRIMARY BATTERIES –

Part 3: Watch batteries

1 Scope

This part of IEC 60086 specifies dimensions, designation, methods of tests and requirements for primary batteries for watches. In several cases, a menu of test methods is given. When presenting battery electrical characteristics and/or performance data, the manufacturer specifies which test method was used.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60086-1, Primary batteries – Part 1: General

IEC 60086-2, Primary batteries – Part 2: Physical and electrical specifications

IEC 60086-4, Primary batteries – Part 4: Safety of lithium batteries

IEC 60086-5, Primary batteries – Part 5: Safety of batteries with aqueous electrolyte

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60086-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1

capacitive reactance

part of the internal resistance that leads to a voltage drop during the first seconds under load

3.2

capacity

electric charge (quantity of electricity) which a cell or battery can deliver under specified discharge conditions

Note 1 to entry: The SI unit for electric charge is the coulomb (1 C = 1 As) but, in practice, capacity is usually expressed in ampere hours (Ah).

3.3 fresh battery

undischarged battery 60 days maximum after date of manufacture