
**Acoustics — Field measurement of
sound insulation in buildings and of
building elements —**

**Part 3:
Façade sound insulation**

*Acoustique — Mesurage in situ de l'isolement acoustique
des bâtiments et des éléments de construction —
Partie 3: Isolement aux bruits de façades*





COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	2
3 Terms and definitions	3
4 Instrumentation	8
4.1 General.....	8
4.2 Calibration.....	8
4.3 Verification.....	8
5 Frequency range	9
6 General	9
7 Indoor sound pressure level measurements	11
7.1 General.....	11
7.2 Default procedure.....	11
7.2.1 Fixed microphone positions.....	11
7.2.2 Mechanized continuously-moving microphone.....	11
7.2.3 Manually scanned microphone.....	11
7.2.4 Minimum distances for microphone positions.....	13
7.2.5 Averaging times.....	13
7.2.6 Calculation of energy-average sound pressure levels.....	14
7.3 Low-frequency procedure (element or global loudspeaker methods).....	15
7.3.1 General.....	15
7.3.2 Microphone positions.....	15
7.3.3 Averaging time.....	15
7.3.4 Calculation of low-frequency energy-average sound pressure levels.....	16
7.4 Background noise (default and low-frequency procedure).....	16
7.4.1 General.....	16
7.4.2 Correction to the signal level for background noise.....	17
8 Reverberation time measurements in the receiving room (default and low-frequency procedure)	17
8.1 General.....	17
8.2 Generation of sound field.....	17
8.3 Default procedure.....	18
8.4 Low-frequency procedure.....	18
8.5 Interrupted noise method.....	18
8.6 Integrated impulse response method.....	18
9 Outdoor measurements using a loudspeaker as a sound source (default and low-frequency procedure)	19
9.1 General.....	19
9.2 Generation of the sound field.....	19
9.3 Loudspeaker requirements.....	19
9.4 Loudspeaker positions.....	20
9.5 Element loudspeaker method.....	20
9.5.1 Outdoor sound pressure level measurements on the test surface.....	20
9.6 Global loudspeaker method.....	21
9.6.1 Outdoor sound pressure level measurements near the façade.....	21
9.6.2 Large rooms or façades comprising more than one outside wall.....	21
9.6.3 Calculation of measurement results.....	21
10 Outdoor measurements using road traffic as a sound source (default procedure)	21
10.1 General.....	21

10.2	Test requirements	22
10.3	Element road traffic method	22
10.3.1	General	22
10.3.2	Requirements on road traffic and façade geometry	22
10.3.3	Outdoor sound pressure level measurements on the test surface	23
10.4	Global road traffic method	23
10.4.1	Outdoor sound pressure level measurements at a distance of 2 m in front of the façade	23
10.4.2	Calculation of measurement results	24
11	Conversion to octave bands	24
12	Expression of results	25
13	Uncertainty	26
14	Test report	26
Annex A	(normative) Determination of area, S	27
Annex B	(normative) Control of sound transmission through the wall surrounding the test specimen	28
Annex C	(normative) Requirements for loudspeakers	29
Annex D	(informative) Examples of verification of test requirements	30
Annex E	(informative) Measurements with aircraft and railway traffic noise (default procedure)	31
Annex F	(informative) Forms for recording results	35
Bibliography	37

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 43, *Acoustics*, Subcommittee SC 2, *Building acoustics*.

This first edition cancels and replaces ISO 140-5:1998 and ISO 140-14:2004, which have been technically revised.

ISO 16283 consists of the following parts, under the general title *Acoustics — Field measurement of sound insulation in buildings and of building elements*:

- *Part 1: Airborne sound insulation*
- *Part 2: Impact sound insulation*
- *Part 3: Façade sound insulation*

Introduction

ISO 16283 (all parts) describes procedures for field measurements of sound insulation in buildings. Airborne, impact, and façade sound insulation are described in ISO 16283-1, ISO 16283-2, and in this part of ISO 16283, respectively.

Field sound insulation measurements that were described previously in ISO 140-4, ISO 140-5, and ISO 140-7 were (a) primarily intended for measurements where the sound field could be considered to be diffuse and (b) not explicit as to whether operators could be present in the rooms during the measurement. ISO 16283 differs from ISO 140-4, ISO 140-5, and ISO 140-7 in that (a) it applies to rooms in which the sound field can or cannot approximate to a diffuse field, (b) it clarifies how operators can measure the sound field using a hand-held microphone or sound level metre, and (c) it includes additional guidance that was previously contained in ISO 140-14.

NOTE Survey test methods for field measurements of façade sound insulation are dealt with in ISO 10052.

Acoustics — Field measurement of sound insulation in buildings and of building elements —

Part 3: Façade sound insulation

1 Scope

This part of ISO 16283 specifies procedures to determine the airborne sound insulation of façade elements (element methods) and whole façades (global methods) using sound pressure measurements. These procedures are intended for room volumes in the range from 10 m³ to 250 m³ in the frequency range from 50 Hz to 5 000 Hz.

The test results can be used to quantify, assess, and compare the airborne sound insulation in unfurnished or furnished rooms where the sound field can or cannot approximate to a diffuse field. The measured airborne sound insulation is frequency-dependent and can be converted into a single number quantity to characterize the acoustic performance using the rating procedures in ISO 717-1.

The element methods aim to estimate the sound reduction index of a façade element, for example, a window. The most accurate element method uses a loudspeaker as an artificial sound source. Other less accurate element methods use available traffic noise. The global methods, on the other hand, aim to estimate the outdoor/indoor sound level difference under actual traffic conditions. The most accurate global methods use the actual traffic as sound source. A loudspeaker can be used as an artificial sound source when there is insufficient level from traffic noise inside the room. An overview of the methods is given in [Table 1](#).

The element loudspeaker method yields an apparent sound reduction index which, under certain circumstances, can be compared with the sound reduction index measured in laboratories in accordance with ISO 10140. This method is the preferred method when the aim of the measurement is to evaluate the performance of a specified façade element in relation to its performance in the laboratory.

The element road traffic method will serve the same purposes as the element loudspeaker method. It is particularly useful when, for different practical reasons, the element loudspeaker method cannot be used. These two methods will often yield slightly different results. The road traffic method tends to result in lower values of the sound reduction index than the loudspeaker method. In [Annex D](#), this road traffic method is supplemented by the corresponding aircraft and railway traffic methods.

The global road traffic method yields the real reduction of a façade in a given place relative to a position 2 m in front of the façade. This method is the preferred method when the aim of the measurement is to evaluate the performance of a whole façade, including all flanking paths, in a specified position relative to nearby roads. The result cannot be compared with that of laboratory measurements.

The global loudspeaker method yields the sound reduction of a façade relative to a position that is 2 m in front of the façade. This method is particularly useful when, for practical reasons, the real source cannot be used; however, the result cannot be compared with that of laboratory measurements.