

ETSI TS 125 101 V12.10.0 (2016-04)



**Universal Mobile Telecommunications System (UMTS);
User Equipment (UE) radio transmission and reception (FDD)
(3GPP TS 25.101 version 12.10.0 Release 12)**



Reference

RTS/TSGR-0425101vca0

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	14
1 Scope	15
2 References	15
3 Definitions, symbols and abbreviations	15
3.1 Definitions	15
3.2 Abbreviations	17
4 General	19
4.1 Relationship between Minimum Requirements and Test Requirements	19
4.2 Power Classes.....	19
4.3 Control and monitoring functions	19
4.3.1 Minimum requirement	20
4.4 RF requirements in later releases	20
5 Frequency bands and channel arrangement.....	20
5.1 General	20
5.2 Frequency bands.....	20
5.3 TX-RX frequency separation	22
5.4 Channel arrangement.....	23
5.4.1 Channel spacing.....	23
5.4.2 Channel raster	24
5.4.3 Channel number.....	24
5.4.4 UARFCN	26
6 Transmitter characteristics	27
6.1 General	27
6.2 Transmit power	27
6.2.1 UE maximum output power.....	27
6.2.1A UE maximum output power for UL OLTD	29
6.2.1B UE maximum output power for UL CLTD	30
6.2.1C UE maximum output power for UL MIMO.....	30
6.2.2 UE maximum output power with HS-DPCCH and E-DCH.....	31
6.2.2A UE maximum output power for DC-HSUPA.....	32
6.2.2B UE maximum output power with HS-DPCCH and E-DCH for UL OLTD.....	33
6.2.2C UE maximum output power with HS-DPCCH and E-DCH for UL CLTD	33
6.2.2D UE maximum output power with HS-DPCCH and E-DCH for UL MIMO	34
6.2.3 UE Relative code domain power accuracy	34
6.2.3A UE Relative code domain power accuracy for DC-HSUPA	35
6.2.3B UE Relative code domain power accuracy for UL OLTD	36
6.2.3C UE Relative code domain power accuracy for UL CLTD	36
6.2.3D UE Relative code domain power accuracy for UL MIMO	36
6.3 Frequency Error.....	36
6.3A Frequency Error for DC-HSUPA	36
6.3B Frequency error for UL OLTD	36
6.3C Frequency error for UL CLTD	36
6.3D Frequency error for UL MIMO	37
6.4 Output power dynamics.....	37
6.4.1 Open loop power control	37
6.4.1.1 Minimum requirement	37
6.4.1.1A Additional requirement for DC-HSUPA	37
6.4.2 Inner loop power control in the uplink.....	37
6.4.2.1 Power control steps	37

6.4.2.1.1	Minimum requirement	37
6.4.2.1.1A	Additional requirement for DC-HSUPA	39
6.4.2.1.1B	Additional requirement for UL OLTD	39
6.4.2.1.1C	Additional requirement for UL CLTD	39
6.4.2.1.1D	Additional requirement for UL MIMO.....	39
6.4.3	Minimum output power	39
6.4.3.1	Minimum requirement	39
6.4.3.1A	Additional requirement for DC-HSUPA.....	40
6.4.3.1B	Additional requirement for UL OLTD	40
6.4.3.1C	Additional requirement for UL CLTD	40
6.4.3.1D	Additional requirement for UL MIMO	40
6.4.4	Out-of-synchronization handling of output power.....	40
6.4.4.1	Minimum requirement	40
6.4.4.1A	Additional requirement for UL OLTD	41
6.4.4.1B	Additional requirement for UL CLTD	41
6.4.4.1C	Additional requirement for UL MIMO	41
6.4.4.2	Test case.....	41
6.4A	Output pattern dynamics	43
6.4A.1	Out-of-quality handling of TPI applicability	43
6.4A.1.1	Minimum requirement	43
6.4A.1.2	Test case.....	43
6.5	Transmit ON/OFF power	45
6.5.1	Transmit OFF power.....	45
6.5.1.1	Minimum requirement	45
6.5.1.1A	Additional requirement for DC-HSUPA	45
6.5.1.1B	Additional requirement for UL OLTD	46
6.5.1.1C	Additional requirement for UL CLTD	46
6.5.1.1D	Additional requirement for UL MIMO	46
6.5.2	Transmit ON/OFF Time mask	46
6.5.2.1	Minimum requirement	46
6.5.2.1A	Additional requirement for UL OLTD	49
6.5.2.1B	Additional requirement for UL CLTD	49
6.5.2.1C	Additional requirement for UL MIMO	49
6.5.3	Change of TFC	49
6.5.3.1	Minimum requirement	49
6.5.3.1A	Additional requirement for UL OLTD	51
6.5.3.1B	Additional requirement for UL CLTD	51
6.5.4	Power setting in uplink compressed mode.....	51
6.5.4.1	Minimum requirement	51
6.5.4.1A	Additional requirement for UL OLTD	53
6.5.4.1B	Additional requirement for UL CLTD.....	53
6.5.5	HS-DPCCH.....	53
6.5.5.1	Minimum requirement	53
6.5.5.1A	Additional requirement for UL OLTD	55
6.5.5.1B	Additional requirement for UL CLTD	55
6.5.5.1C	Additional requirement for UL MIMO	55
6.6	Output RF spectrum emissions.....	55
6.6.1	Occupied bandwidth	55
6.6.1A	Occupied bandwidth for DC-HSUPA.....	55
6.6.1B	Occupied bandwidth for UL OLTD.....	56
6.6.1C	Occupied bandwidth for UL CLTD	56
6.6.1D	Occupied bandwidth for UL MIMO	56
6.6.2	Out of band emission	56
6.6.2.1	Spectrum emission mask	56
6.6.2.1.1	Minimum requirement	56
6.6.2.1A	Additional Spectrum emission mask for DC-HSUPA	58
6.6.2.1A.1	Minimum requirement	58
6.6.2.1A.2	Additional requirement for band II, IV, V, X, XXV and XXVI.....	58
6.6.2.1B	Additional requirement for UL OLTD	59
6.6.2.1C	Additional requirement for UL CLTD	59
6.6.2.1D	Additional requirement for UL MIMO	59
6.6.2.2	Adjacent Channel Leakage power Ratio (ACLR).....	59

6.6.2.2.1	Minimum requirement	59
6.6.2.2.1A	Additional requirement for DC-HSUPA	59
6.6.2.2.1B	Additional requirement for UL OLTD	60
6.6.2.2.1C	Additional requirement for UL CLTD	60
6.6.2.2.1D	Additional requirement for UL MIMO.....	60
6.6.3	Spurious emissions	60
6.6.3.1	Minimum requirement	60
6.6.3.1.1	Additional requirement.....	66
6.6.3.1A	Additional requirement for DC-HSUPA	67
6.6.3.1A.1	Additional requirement for DC-HSUPA	72
6.6.3.1B	Additional requirement for UL OLTD	72
6.6.3.1C	Additional requirement for UL CLTD	72
6.6.3.1D	Additional requirement for UL MIMO	73
6.7	Transmit intermodulation	73
6.7.1	Minimum requirement	73
6.7.1A	Additional requirement for DC-HSUPA.....	73
6.7.1B	Additional requirement for UL OLTD.....	73
6.7.1C	Additional requirement for UL CLTD	73
6.7.1D	Additional requirement for UL MIMO	74
6.8	Transmit modulation	74
6.8.1	Transmit pulse shape filter.....	74
6.8.1A	Additional requirement for UL OLTD.....	74
6.8.1B	Additional requirement for UL CLTD	74
6.8.1C	Additional requirement for UL MIMO	74
6.8.2	Error Vector Magnitude.....	74
6.8.2.1	Minimum requirement	75
6.8.2.1A	Additional requirement for DC-HSUPA.....	75
6.8.2.1B	Additional requirement for UL OLTD.....	76
6.8.2.1C	Additional requirement for UL CLTD	76
6.8.2.1D	Additional requirement for UL MIMO	76
6.8.3	Peak code domain error	77
6.8.3.1	Minimum requirement	77
6.8.3.1A	Additional requirement for UL OLTD.....	77
6.8.3.1B	Additional requirement for UL CLTD	77
6.8.3a	Relative code domain error.....	77
6.8.3a.1	Relative Code Domain Error.....	77
6.8.3a.1.1	Minimum requirement	78
6.8.3a.1.1a	Additional requirement for DC-HSUPA	79
6.8.3a.1.1b	Additional requirement for UL OLTD	79
6.8.3a.1.1c	Additional requirement for UL CLTD	79
6.8.3a.1.1d	Additional requirement for UL MIMO.....	79
6.8.3b	In-band emission for DC-HSUPA	79
6.8.3b.1	Minimum requirement for DC-HSUPA	79
6.8.4	Phase discontinuity for uplink DPCH.....	80
6.8.4.1	Minimum requirement	80
6.8.4.1A	Additional requirement for UL OLTD	80
6.8.4.1B	Additional requirement for UL CLTD	80
6.8.5	Phase discontinuity for HS-DPCCH	80
6.8.5.1	Minimum requirement	81
6.8.5.1A	Additional requirement for UL OLTD	81
6.8.5.1B	Additional requirement for UL CLTD	81
6.8.6	Phase discontinuity for E-DCH	81
6.8.6.1	Minimum requirement	82
6.8.6.1A	Additional requirement for UL OLTD	82
6.8.6.1B	Additional requirement for UL CLTD	83
6.8.7	Time alignment error for DC-HSUPA	83
6.8.7.1	Minimum requirement	83
6.8.7A	Time alignment error for UL OLTD.....	83
6.8.7A.1	Minimum requirement	83
6.8.7B	Time alignment error for UL CLTD	83
6.8.7B.1	Minimum requirement	83
6.8.7C	Time alignment error for UL MIMO	83

6.8.7C.1	Minimum requirement	83
7	Receiver characteristics	83
7.1	General	83
7.2	Diversity characteristics	85
7.3	Reference sensitivity level.....	85
7.3.1	Minimum requirement	85
7.3.2	Additional requirement for DC-HSDPA.....	87
7.3.3	Additional requirement for DB-DC-HSDPA.....	89
7.3.4	Additional requirement for single band 4C-HSDPA	90
7.3.5	Additional requirement for dual band 4C-HSDPA	91
7.3.6	Additional requirement for single band 8C-HSDPA	91
7.3.7	Additional requirement for single band NC-4C-HSDPA	92
7.4	Maximum input level	93
7.4.1	Minimum requirement for DPCH reception	93
7.4.2	Minimum requirement for HS-PDSCH reception.....	93
7.4.2.1	Minimum requirement for 16QAM.....	93
7.4.2.2	Minimum requirement for 64QAM.....	94
7.4.3	Additional requirement for DC-HSDPA and DB-DC-HSDPA	95
7.4.3.1	Additional requirement for 16QAM.....	95
7.4.3.2	Additional requirement for 64QAM.....	95
7.4.4	Additional requirement for single band/dual band 4C-HSDPA or single band 8C-HSDPA and single band NC-4C-HSDPA.....	96
7.4.4.1	Additional requirement for 16QAM.....	96
7.4.4.2	Additional requirement for 64QAM.....	97
7.5	Adjacent Channel Selectivity (ACS)	97
7.5.1	Minimum requirement	98
7.5.2	Additional requirement for DC-HSDPA and DB-DC-HSDPA	98
7.5.3	Additional requirement for single band/dual band 4C-HSDPA.....	99
7.5.4	Additional requirement for single band 8C-HSDPA	102
7.5.5	Additional requirement for single band NC-4C-HSDPA	103
7.6	Blocking characteristics	104
7.6.1	Minimum requirement (In-band blocking)	105
7.6.1A	Additional requirement for DC-HSDPA and DB-DC-HSDPA (In-band blocking)	106
7.6.1B	Additional requirement for DC-HSUPA (In-band blocking).....	108
7.6.1C	Additional requirement for single band 4C-HSDPA (In-band blocking)	110
7.6.1C.1	Single uplink operation	110
7.6.1C.2	Dual uplink operation.....	111
7.6.1D	Additional requirement for dual band 4C-HSDPA (In-band blocking)	112
7.6.1D.1	Single uplink operation	112
7.6.1D.2	Dual uplink operation.....	113
7.6.1E	Additional requirement for single band 8C-HSDPA (In-band blocking)	115
7.6.1E.1	Single uplink operation	115
7.6.1E.2	Dual uplink operation.....	115
7.6.1F	Additional requirement for single band NC-4C-HSDPA (In-band blocking).....	116
7.6.1F.1	Single uplink operation	116
7.6.1F.2	Dual uplink operation.....	117
7.6.2	Minimum requirement (Out-of-band blocking)	118
7.6.2A	Additional requirement for DC-HSDPA (Out-of-band blocking)	120
7.6.2B	Additional requirement for DB-DC-HSDPA (Out-of-band blocking).....	122
7.6.2C	Additional requirement for single band 4C-HSDPA (Out-of-band blocking)	123
7.6.2D	Additional requirement for dual band 4C-HSDPA (Out-of-band blocking).....	124
7.6.2E	Additional requirement for single band 8C-HSDPA (Out-of-band blocking)	126
7.6.2F	Additional requirement for single band NC-4C-HSDPA (Out-of-band blocking)	127
7.6.3	Minimum requirement (Narrow band blocking).....	128
7.6.3A	Additional requirement for DC-HSDPA and DB-DC-HSDPA (Narrow band blocking).....	128
7.6.3B	Additional requirement for DC-HSUPA (Narrow band blocking)	129
7.6.3C	Additional requirement for single band 4C-HSDPA (Narrow band blocking)	129
7.6.3C.1	Single uplink operation	129
7.6.3C.2	Dual uplink operation.....	130
7.6.3D	Additional requirement for dual band 4C-HSDPA (Narrow band blocking).....	130
7.6.3D.1	Single uplink operation	131

7.6.3D.2	Dual uplink operation.....	131
7.6.3E	Additional requirement for single band NC-4C-HSDPA (Narrow band blocking).....	132
7.6.3E.1	Single uplink operation	132
7.6.3E.2	Dual uplink operation.....	133
7.7	Spurious response.....	134
7.7.1	Minimum requirement	134
7.7.2	Additional requirement for DC-HSDPA, DB-DC-HSDPA, single band/dual band 4C-HSDPA and single band 8C-HSDPA and single band NC-4C-HSDPA	135
7.8	Intermodulation characteristics	135
7.8.1	Minimum requirement	135
7.8.1A	Additional requirement for DC-HSDPA and DB-DC-HSDPA	136
7.8.1B	Additional requirement for DC-HSUPA.....	136
7.8.1C	Additional requirement for single band 4C-HSDPA	138
7.8.1C.1	Single uplink operation	138
7.8.1C.2	Dual uplink operation.....	138
7.8.1D	Additional requirement for dual band 4C-HSDPA	139
7.8.1D.1	Single uplink operation	139
7.8.1D.2	Dual uplink operation.....	140
7.8.1E	Additional requirement for single band 8C-HSDPA	141
7.8.1E.1	Single uplink operation	141
7.8.1E.2	Dual uplink operation.....	142
7.8.1F	Additional requirement for single band NC-4C-HSDPA	143
7.8.1F.1	Single uplink operation	143
7.8.1F.2	Dual uplink operation.....	143
7.8.2	Minimum requirement (Narrow band).....	144
7.8.2A	Additional requirement for DC-HSDPA and DB-DC-HSDPA (Narrow band).....	145
7.8.2B	Additional requirement for DC-HSUPA (Narrow band)	145
7.8.2C	Additional requirement for single band 4C-HSDPA (Narrow band).....	146
7.8.2C.1	Single uplink operation	146
7.8.2C.2	Dual uplink operation.....	147
7.8.2D	Additional requirement for dual band 4C-HSDPA (Narrow band)	147
7.8.2D.1	Single uplink operation	147
7.8.2D.2	Dual uplink operation.....	148
7.8.2E	Additional requirement for single band NC-4C-HSDPA (Narrow band)	150
7.8.2E.1	Single uplink operation	150
7.8.2E.2	Dual uplink operation.....	150
7.9	Spurious emissions	151
7.9.1	Minimum requirement	151
7.9.1A	Minimum requirement	152
7.10	Reference input power adjustment for a dual band device.....	153
8	Performance requirement	153
8.1	General	153
8.2	Demodulation in static propagation conditions	154
8.2.1	(void)	154
8.2.2	(void)	154
8.2.3	Demodulation of Dedicated Channel (DCH).....	154
8.2.3.1	Minimum requirement	154
8.2.4	Demodulation of Dedicated Channel (DCH) when DL_DCH_FET_Config [10] is configured by higher layers.....	154
8.2.4.1	Minimum requirement	155
8.3	Demodulation of DCH in multi-path fading propagation conditions	155
8.3.1	Single Link Performance	155
8.3.1.1	Minimum requirement	155
8.3.2	Single Link Performance when DL_DCH_FET_Config [10] is configured by higher layers	158
8.3.2.1	Minimum requirement	158
8.4	Demodulation of DCH in moving propagation conditions.....	160
8.4.1	Single link performance.....	160
8.4.1.1	Minimum requirement	160
8.5	Demodulation of DCH in birth-death propagation conditions	161
8.5.1	Single link performance.....	161
8.5.1.1	Minimum requirement	161

8.5A	Demodulation of DCH in high speed train condition	161
8.5A.1	General.....	161
8.5A.2	Minimum requirement	161
8.6	Demodulation of DCH in downlink Transmit diversity modes.....	162
8.6.1	Demodulation of DCH in open-loop transmit diversity mode	162
8.6.1.1	Minimum requirement	162
8.6.2	Demodulation of DCH in closed loop transmit diversity mode.....	163
8.6.2.1	Minimum requirement	163
8.6.3	(void)	164
8.7	Demodulation in Handover conditions.....	164
8.7.1	Demodulation of DCH in Inter-Cell Soft Handover	164
8.7.1.1	Minimum requirement	164
8.7.1A	Demodulation of DCH in Inter-Cell Soft Handover when DL_DCH_FET_Config [10] is configured by higher layers.....	165
8.7.1A.1	Minimum requirement	165
8.7.2	Combining of TPC commands from radio links of different radio link sets.....	166
8.7.2.1	Minimum requirement	166
8.7.2A	Combining of TPC commands from radio links of different radio link sets when DL_DCH_FET_Config [10] is configured by higher layers	166
8.7.2A.1	Minimum requirement	166
8.7.2B	Combining of TPC commands from radio links of different radio link sets when DPCCH2 is configured	167
8.7.2B.1	Minimum requirement	167
8.7.3	Combining of reliable TPC commands from radio links of different radio link sets	168
8.7.3.1	Minimum requirement	168
8.7.4	Combining of reliable TPC commands from radio links of different radio link sets when DL_DCH_FET_Config [10] is configured by higher layers	169
8.7.4.1	Minimum requirement	169
8.8	Power control in downlink	170
8.8.1	Power control in the downlink, constant BLER target	170
8.8.1.1	Minimum requirements	170
8.8.1A	Power control in the downlink, constant BLER target when DL_DCH_FET_Config [10] is configured by higher layers	172
8.8.1A.1	Minimum requirements	172
8.8.2	Power control in the downlink, initial convergence	173
8.8.2.1	Minimum requirements	173
8.8.2A	Power control in the downlink, initial convergence when DL_DCH_FET_Config [10] is configured by higher layers	175
8.8.2A.1	Minimum requirements	175
8.8.3	Power control in downlink, wind up effects	176
8.8.3.1	Minimum requirements	176
8.8.3A	Power control in downlink, wind up effects when DL_DCH_FET_Config [10] is configured by higher layers	177
8.8.3A.1	Minimum requirements	177
8.8.4	Power control in the downlink, different transport formats	179
8.8.4.1	Minimum requirements	179
8.8.4A	Power control in the downlink, different transport formats	180
8.8.4A.1	Minimum requirements	180
8.8.5	Power control in the downlink for F-DPCH	182
8.8.5.1	Minimum requirements	182
8.9	Downlink compressed mode	182
8.9.1	Single link performance	182
8.9.1.1	Minimum requirements	183
8.10	Blind transport format detection	183
8.10.1	Minimum requirement	183
8.11	Detection of Broadcast channel (BCH)	184
8.11.1	Minimum requirement without transmit diversity	184
8.11.2	Minimum requirement with open loop transmit diversity	185
8.11A	Detection of Broadcast channel (BCH) mapped to S-CCPCH	185
8.11A.1	Minimum requirement without transmit diversity	185
8.11.2	Minimum requirement with open loop transmit diversity	186
8.12	Demodulation of Paging Channel (PCH)	186

8.12.1	Minimum requirement	186
8.13	Detection of Acquisition Indicator (AI)	187
8.13.1	Minimum requirement	187
8.13A	Detection of E-DCH Acquisition Indicator (E-AI)	187
8.13A.1	Minimum requirement	187
8.14	UE UL power control operation with discontinuous UL DPCCH transmission operation	188
8.14.1	Minimum requirement	188
8.15	(void).....	189
8.16	(void).....	189
9	Performance requirement (HSDPA)	189
9.1	(void).....	190
9.2	Demodulation of HS-DSCH (Fixed Reference Channel).....	190
9.2.1	Single Link performance	204
9.2.1.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 1/2/3/3A/3B/3C/3E	204
9.2.1.2	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 1/2/3	206
9.2.1.3	Minimum requirement QPSK, Fixed Reference Channel (FRC) H-Set 4/5.....	207
9.2.1.4	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 6/6A/6B/6C/6E	208
9.2.1.5	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 6/6A/6B/6C/6E	210
9.2.1.6	Requirement 64QAM, Fixed Reference Channel (FRC) H-Set 8/8A/8B/8C/8E	212
9.2.1.7	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 10/10A/10B/10C/10E	214
9.2.1.8	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 10/10A/10B/10C/10E	215
9.2.2	Open Loop Diversity performance	216
9.2.2.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 1/2/3/3A/3B/3C/3E	216
9.2.2.2	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 1/2/3/3A/3B/3C/3E	217
9.2.2.3	Minimum requirement QPSK, Fixed Reference Channel (FRC) H-Set 4/5.....	218
9.2.3	Closed Loop Diversity Performance.....	219
9.2.3.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 1/2/3	219
9.2.3.2	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 1/2/3	221
9.2.3.3	Minimum requirement QPSK, Fixed Reference Channel (FRC) H-Set 4/5.....	222
9.2.3.4	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 6	223
9.2.3.5	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 6	223
9.2.4	MIMO Performance.....	224
9.2.4.1	Requirement Fixed Reference Channel (FRC) H-Set 9/9A/9B/9C/9E	224
9.2.4.2	Requirement Fixed Reference Channel (FRC) H-Set 11/11A/11B/11C/11E	226
9.2.4A	MIMO only with single-stream restriction Performance	228
9.2.4A.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 1/1A/1B/1C/1E	228
9.2.4A.2	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 1/1A/1B/1C/1E	230
9.2.4B	Four Transmit Antennas MIMO Performance	232
9.2.4B.1	Requirement Fixed Reference Channel (FRC) H-Set 13A/13C	232
9.2.4B.2	Requirement Fixed Reference Channel (FRC) H-Set 14A/14C	233
9.2.4C	MIMO Mode with Four Transmit Antennas Only With Dual-stream Restriction Performance	234
9.2.4C.1	Requirement Fixed Reference Channel (FRC) H-Set 9A/9C	234
9.2.4C.2	Requirement Fixed Reference Channel (FRC) H-Set 11A/11C	235
9.2.5	Multiflow HSDPA performance	236
9.2.5.1	Requirement Fixed Reference Channel (FRC) H-Set 6 16QAM/QPSK	236
9.3	Reporting of Channel Quality Indicator	237
9.3.1	Single Link Performance	238
9.3.1.1	AWGN propagation conditions.....	238
9.3.1.1.1	Minimum Requirement – UE HS-DSCH categories 1-20	238
9.3.1.1.2	Minimum Requirement – UE HS-DSCH categories 13,14,17,18, 19 and 20	238
9.3.1.1.3	Additional Requirements – UE HS-DSCH categories 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 35 and 36	239
9.3.1.2	Fading propagation conditions	240
9.3.1.2.1	Minimum Requirement – UE HS-DSCH categories 1-20	240
9.3.1.2.2	Minimum Requirement – UE HS-DSCH categories 13,14,17,18, 19 and 20	241
9.3.1.2.3	Additional Requirements – UE HS-DSCH categories 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 35 and 36	242
9.3.1.3	Periodically varying radio conditions.....	243
9.3.1.3.1	Minimum Requirement – UE HS-DSCH categories 1-20	243
9.3.2	Open Loop Diversity Performance	245
9.3.2.1	AWGN propagation conditions.....	245

9.3.2.1.1	Minimum Requirement – UE HS-DSCH categories 1-20	245
9.3.2.1.2	Additional Requirements – UE HS-DSCH categories 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 35 and 36	245
9.3.2.2	Fading propagation conditions	246
9.3.2.2.1	Minimum Requirement – UE HS-DSCH categories 1-20	246
9.3.2.2.2	Additional Requirements – UE HS-DSCH categories 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 35 and 36	247
9.3.2.3	Periodically varying radio conditions.....	247
9.3.2.3.1	Minimum Requirement – UE HS-DSCH categories 1-20	248
9.3.3	Closed Loop Diversity Performance.....	249
9.3.3.1	AWGN propagation conditions.....	249
9.3.3.1.1	Minimum Requirement – UE HS-DSCH categories 1-20	249
9.3.3.2	Fading propagation conditions	250
9.3.3.2.1	Minimum Requirement – UE HS-DSCH categories 1-20	250
9.3.3.3	Periodically varying radio conditions.....	251
9.3.3.3.1	Minimum Requirement – UE HS-DSCH categories 1-20	251
9.3.4	MIMO Performance.....	253
9.3.4.1	MIMO Single Stream Fading Conditions	253
9.3.4.1.1	Minimum Requirement - UE HS-DSCH categories 15-20.....	253
9.3.4.1.2	Additional Requirement – UE HS-DSCH categories 25-28, 30, 32 and 36	254
9.3.4.2	MIMO Dual Stream Fading Conditions.....	255
9.3.4.2.1	Minimum Requirement – UE HS-DSCH categories 15-20	256
9.3.4.2.2	Minimum Requirement – UE HS-DSCH categories 19-20	257
9.3.4.2.3	Additional Requirement – UE HS-DSCH categories 25-28, 30, 32 and 36	258
9.3.4.2.4	Additional Requirement – UE HS-DSCH categories 27, 28, 30, 32 and 36.....	260
9.3.4.3	MIMO Dual Stream Static Orthogonal Conditions.....	261
9.3.4.3.1	Minimum Requirement –UE HS-DSCH categories 15-20.....	262
9.3.4.3.2	Minimum Requirement –UE HS-DSCH categories 19-20	262
9.3.4.3.3	Additional Requirement – UE HS-DSCH categories 25-28, 30, 32 and 36	263
9.3.4.3.4	Additional Requirement – UE HS-DSCH categories 27, 28, 30, 32 and 36.....	264
9.3.5	MIMO only with single-stream restriction Performance	265
9.3.5.1	MIMO only with single-stream restriction Fading Conditions	265
9.3.5.1.1	Minimum Requirement	265
9.3.6	Multiflow HSDPA performance	266
9.3.6.1	Fading propagation conditions	266
9.3.6.1.1	Minimum Requirement	267
9.3.7	MIMO Performance with four transmit antennas	267
9.3.7.1	Four Streams Static Orthogonal Conditions.....	267
9.3.7.1.1	Minimum Requirement – UE HS-DSCH categories 37 and 38.....	268
9.3.8	MIMO with Four Transmit Antennas only with Dual-Stream Restriction Performance	269
9.3.8.1	MIMO with four transmit antennas only with dual-stream restriction fading conditions	269
9.3.8.1.1	Minimum Requirement	270
9.4	HS-SCCH Detection Performance	271
9.4.1	HS-SCCH Type 1 Single Link Performance	272
9.4.2	HS-SCCH Type 1 Open Loop Diversity Performance	272
9.4.3	HS-SCCH Type 3 Performance	273
9.4.4	HS-SCCH Type 3 Performance for MIMO only with single-stream restriction.....	275
9.4.5	HS-SCCH Type 4 Performance	277
9.4.6	HS-SCCH Type 4 Performance for MIMO mode with Four Transmit Antennas Only with Dual- stream Restriction	278
9.5	HS-SCCH-less demodulation of HS-DSCH (Fixed Reference Channel).....	279
9.5.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 7	280
9.6	Requirements for HS-DSCH and HS-SCCH reception in CELL_FACH state	280
9.6.1	HS-DSCH demodulation requirements (Single Link)	280
9.6.1.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 3	281
9.6.2	HS-SCCH Detection Performance.....	281
9.6.2.1	HS-SCCH Type 1 Single Link Performance.....	281
10	Performance requirement (E-DCH)	282
10.1	General	282
10.2	Detection of E-DCH HARQ ACK Indicator Channel (E-HICH).....	282
10.2.1	Single link performance.....	282

10.2.1.1	Performance requirement	282
10.2.2	Detection in Inter-Cell Handover conditions	283
10.2.2.1	Performance requirement for RLS not containing the Serving E-DCH cell	283
10.2.2.2	Performance requirement for RLS containing the serving E-DCH cell	285
10.3	Detection of E-DCH Relative Grant Channel (E-RGCH)	286
10.3.1	Single link performance	286
10.3.1.1	Performance requirement	286
10.3.2	Detection in Inter-Cell Handover conditions	288
10.3.2.1	Performance requirement for Non-serving E-DCH RL	288
10.3A	Determination of common E-RGCH radio links in CELL_FACH state	289
10.3A.1	Introduction.....	289
10.3A.2	Requirements	289
10.3A.2.1	Determination when a cell for common E-RGCH RL has been already identified.....	289
10.3A.2.2	Determination when a cell for common E-RGCH RL has not been identified	290
10.4	Demodulation of E-DCH Absolute Grant Channel (E-AGCH)	291
10.4.1	Single link performance	291
10.4.1.1	Performance requirement	292
10.4A	Demodulation of E-DCH Absolute Grant Channel (E-AGCH) with Time Multiplexed UE grants.....	292
10.4A.1	Single link performance	292
10.4A.1.1	Performance requirement	292
11	Performance requirement (MBMS).....	293
11.1	Demodulation of MCCH	294
11.1.1	Minimum requirement	294
11.1.2	Minimum requirement for MBSFN	294
11.2	Demodulation of MTCH	295
11.2.1	Minimum requirement	295
11.2.2	Minimum requirement for MBSFN	295
11.3	Demodulation of MTCH and cell identification.....	296
11.3.1	Minimum requirement	296
Annex A (normative):	Measurement channels	297
A.1	General	297
A.2	UL reference measurement channel	297
A.2.1	UL reference measurement channel (12.2 kbps)	297
A.2.2	UL reference measurement channel (64 kbps)	298
A.2.3	UL reference measurement channel (144 kbps)	299
A.2.4	UL reference measurement channel (384 kbps)	300
A.2.5	UL reference measurement channel (768 kbps)	301
A.2.5A	UL reference measurement channel (768 kbps)	301
A.2.6	UL E-DCH reference measurement channel for DC-HSUPA using BPSK modulation	302
A.2.7	UL E-DCH reference measurement channel for DC-HSUPA using 16QAM modulation.....	303
A.2.8	Combinations of UL E-DCH reference measurement channel for DC-HSUPA tests	304
A.3	DL reference measurement channel	304
A.3.0	DL reference measurement channel (0 kbps)	304
A.3.1	DL reference measurement channel (12.2 kbps)	305
A.3.2	DL reference measurement channel (64 kbps)	306
A.3.3	DL reference measurement channel (144 kbps)	307
A.3.4	DL reference measurement channel (384 kbps)	308
A.3.5	DL reference measurement channel 2 (64 kbps)	309
A.3A	DL reference measurement channel	310
A.3A.0	DL reference measurement channel (0 kbps without DCCH)	310
A.3A.1	DL reference measurement channel (0 kbps with DCCH)	311
A.3A.2	DL reference measurement channel (12.2 kbps without DCCH)	312
A.3A.3	DL reference measurement channel (12.2 kbps with DCCH)	313
A.4	DL reference measurement channel for BTFD performance requirements	315
A.4A	Reference parameters for discontinuous UL DPCCH transmission.....	317
A.5	DL reference compressed mode parameters.....	317

A.6	DL reference parameters for PCH tests.....	319
A.7	DL reference channel parameters for HSDPA tests	320
A.7.1	Fixed Reference Channel (FRC)	320
A.7.1.1	Fixed Reference Channel Definition H-Set 1/1A/1B/1C/1E	320
A.7.1.2	Fixed Reference Channel Definition H-Set 2	321
A.7.1.3	Fixed Reference Channel Definition H-Set 3/3A/3B/3C/3E	322
A.7.1.4	Fixed Reference Channel Definition H-Set 4	323
A.7.1.5	Fixed Reference Channel Definition H-Set 5	324
A.7.1.6	Fixed Reference Channel Definition H-Set 6/6A/6B/6C/6E	325
A.7.1.7	Fixed Reference Channel Definition H-Set 7	326
A.7.1.8	Fixed Reference Channel Definition H-Set 8/8A/8B/8C/8E	327
A.7.1.9	Fixed Reference Channel Definition H-Set 9/9A/9B/9C/9E	328
A.7.1.10	Fixed Reference Channel Definition H-Set 10/10A/10B/10C/10E	329
A.7.1.11	Fixed Reference Channel Definition H-Set 11/11A/11B/11C/11E	331
A.7.1.12	Fixed Reference Channel Definition H-Set 12	332
A.7.1.13	Fixed Reference Channel Definition H-Set 13/13A/13C.....	333
A.7.1.14	Fixed Reference Channel Definition H-Set 14/14A/14C.....	334
A.8	DL reference parameters for MBMS tests.....	335
A.8.1	MCCH	335
A.8.1	MTCH	336
A.9	DL reference parameters for combined MTCH demodulation and cell identification.....	336
Annex B (normative) :	Propagation conditions.....	338
B.1	(void)	338
B.2	Propagation Conditions	338
B.2.1	Static propagation condition.....	338
B.2.2	Multi-path fading propagation conditions	338
B.2.3	Moving propagation conditions.....	341
B.2.4	Birth-Death propagation conditions	342
B.2.5	High speed train condition.....	342
B.2.6	MIMO propagation conditions	343
B.2.6.1	MIMO Single Stream Fading Conditions	344
B.2.6.2	MIMO Dual Stream Fading Conditions.....	345
B.2.6.3	MIMO Dual Stream Static Orthogonal Conditions	346
B.2.7	Propagation conditions for MIMO with four transmit antennas.....	346
B.2.7.1	MIMO with Four Transmit Antennas and Four Streams Static Orthogonal Conditions.....	347
B.2.7.2	MIMO with Four Transmit Antennas Only With Dual Stream Fading Conditions	347
Annex C (normative):	Downlink Physical Channels.....	349
C.1	General	349
C.2	Connection Set-up	349
C.3	During connection	349
C.3.1	Measurement of Rx Characteristics.....	349
C.3.2	Measurement of Performance requirements.....	350
C.3.3	Connection with open-loop transmit diversity mode.....	351
C.3.4	Connection with closed loop transmit diversity mode.....	351
C.3.5	(void)	352
C.4	W-CDMA Modulated Interferer	352
C.5	HSDPA DL Physical channels	353
C.5.1	Downlink Physical Channels connection set-up.....	353
C.5.2	OCNS Definition	363
C.5.3	Test Definition for Enhanced Performance Type 3i	364
C.5.3.1	Transmitted code and power characteristics for serving cell	364
C.5.3.2	Transmitted code and power characteristics for interfering cells.....	366
C.5.3.3	Model for power control sequence generation.....	367
C.5.4	Simplified Multi Carrier HSDPA testing method	367

C.5.4A	Simplified Multiflow HSDPA testing method	368
C.5.5	Test Definition for Multiflow HSDPA.....	368
C.5.5.1	Test configuration when 2 cells are configured in Multiflow mode	368
C.5.5.2	Test configuration when 3 cells are configured in Multiflow mode	370
C.5.5.3	Test configuration when 4 cells are configured in Multiflow mode	370
C.6	MBMS DL Physical channels	371
C.6.1	Downlink Physical Channels connection set-up.....	371
C.6.2	Downlink Physical Channels connection set-up for MBSFN	371
Annex D (normative) :	Environmental conditions	372
D.1	General	372
D.2	Environmental requirements	372
D.2.1	Temperature	372
D.2.2	Voltage	372
D.2.3	Vibration.....	373
Annex E (informative):	UARFCN numbers	374
E.1	General	374
E.2	List of UARFCN used for UTRA FDD bands	374
Annex F (informative):	Change history	378
	History	384

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document establishes the minimum RF characteristics of the FDD mode of UTRA for the User Equipment (UE).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] (void)
- [2] ITU-R Recommendation SM.329: "Unwanted emissions in the spurious domain".
- [3] (void)
- [4] 3GPP TS 25.433: "UTRAN Iub Interface NBAP Signalling".
- [5] ETSI ETR 273: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement of radiated methods of measurement (using test sites) and evaluation of the corresponding measurement uncertainties; Part 1: Uncertainties in the measurement of mobile radio equipment characteristics; Sub-part 2: Examples and annexes".
- [6] 3GPP TS 45.004: "Modulation".
- [7] 3GPP TS 25.331: "Radio Resource Control (RRC); Protocol Specification".
- [8] 3GPP TS25.214: "Physical layer procedures (FDD)".
- [9] 3GPP TS 25.307: "Requirements on User Equipments (UEs) supporting a release-independent frequency band".
- [10] 3GPP TS25.212: "Multiplexing and channel coding (FDD)".
- [11] 3GPP TS 36.101: "E-UTRA User Equipment (UE) radio transmission and reception".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following definitions apply:

Assisting secondary serving HS-DSCH Cell: In addition to the serving HS-DSCH cell, a cell in the secondary downlink frequency, where the UE is configured to simultaneously monitor a HS-SCCH set and receive HS-DSCH if it is scheduled in that cell.