

ETSI TS 129 273 V13.2.0 (2016-03)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Evolved Packet System (EPS);
3GPP EPS AAA interfaces
(3GPP TS 29.273 version 13.2.0 Release 13)**



Reference

RTS/TSGC-0429273vd20

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important noticeThe present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	10
Introduction	10
1 Scope	11
2 References	11
3 Definitions, symbols and abbreviations	13
3.1 Definitions	13
3.1.1 General.....	13
3.1.2 Handling of Information Elements	13
3.2 Abbreviations	14
4 SWa Description	14
4.1 Functionality.....	14
4.1.1 General.....	14
4.1.2 Procedure Descriptions	15
4.1.2.1 SWa Authentication and Authorization procedure.....	15
4.1.2.1.1 General	15
4.1.2.1.2 3GPP AAA Server Detailed Behaviour.....	16
4.1.2.1.3 3GPP AAA Proxy Detailed Behaviour.....	17
4.1.2.2 SWa HSS/AAA Initiated Detach	17
4.1.2.3 SWa Non-3GPP Access Network Initiated Detach.....	17
4.1.2.4 SWa Re-Authentication and Re-Authorization Procedure.....	17
4.1.2.4.1 General	17
4.1.2.4.2 3GPP AAA Server Detailed Behaviour.....	19
4.1.2.4.3 3GPP AAA Proxy Detailed Behaviour.....	19
4.2 Protocol Specification	19
4.2.1 General.....	19
4.2.2 Commands	20
4.2.2.1 Commands for SWa authentication and authorization procedures.....	20
4.2.2.1.1 Diameter-EAP-Request (DER) Command	20
4.2.2.1.2 Diameter-EAP-Answer (DEA) Command	20
4.2.2.2 Commands for SWa HSS/AAA Initiated Detach.....	21
4.2.2.3 Commands for Untrusted non-3GPP Access network Initiated Session Termination	21
4.2.2.4 Commands for SWa Re-Authentication and Re-Authorization Procedures.....	21
4.2.2.4.1 Re-Auth-Request (RAR) Command.....	21
4.2.2.4.2 Re-Auth-Answer (RAA) Command	21
4.2.2.4.3 Diameter-EAP-Request (DER) Command	21
4.2.2.4.4 Diameter-EAP-Answer (DEA) Command	21
4.2.3 Information Elements	21
4.2.4 Session Handling	22
5 STa Description.....	22
5.1 Functionality.....	22
5.1.1 General.....	22
5.1.2 Procedures Description	22
5.1.2.1 STa Access Authentication and Authorization.....	22
5.1.2.1.1 General	22
5.1.2.1.2 3GPP AAA Server Detailed Behaviour.....	31
5.1.2.1.3 3GPP AAA Proxy Detailed Behaviour.....	35
5.1.2.1.4 Trusted non-3GPP access network Detailed Behaviour	36
5.1.2.2 HSS/AAA Initiated Detach on STa.....	37

5.1.2.2.1	General	37
5.1.2.2.2	3GPP AAA Server Detailed Behaviour.....	38
5.1.2.2.3	3GPP AAA Proxy Detailed Behaviour.....	39
5.1.2.3	STa Re-Authorization and Re-Authentication Procedures.....	39
5.1.2.3.1	General	39
5.1.2.3.2	3GPP AAA Server Detailed Behaviour.....	46
5.1.2.3.3	3GPP AAA Proxy Detailed Behaviour.....	46
5.1.2.3.4	Trusted Non-3GPP Access Network Detailed Behaviour	47
5.1.2.4	Non-3GPP Access Network Initiated Session Termination	47
5.1.2.4.1	General	47
5.1.2.4.2	3GPP AAA Server Detailed Behaviour.....	48
5.1.2.4.3	3GPP AAA Proxy Detailed Behaviour.....	48
5.2	Protocol Specification	48
5.2.1	General.....	48
5.2.2	Commands	49
5.2.2.1	Commands for STa PMIPv6 or GTPv2 authentication and authorization procedures.....	49
5.2.2.1.1	Diameter-EAP-Request (DER) Command	49
5.2.2.1.2	Diameter-EAP-Answer (DEA) Command	50
5.2.2.2	Commands for STa HSS/AAA Initiated Detach for Trusted non-3GPP Access	50
5.2.2.2.1	Abort-Session-Request (ASR) Command	50
5.2.2.2.2	Abort-Session-Answer (ASA) Command	51
5.2.2.2.3	Session-Termination-Request (STR) Command	51
5.2.2.2.4	Session-Termination-Answer (STA) Command	51
5.2.2.3	Commands for Re-Authentication and Re-Authorization Procedure	52
5.2.2.3.1	Re-Auth-Request (RAR) Command.....	52
5.2.2.3.2	Re-Auth-Answer (RAA) Command	52
5.2.2.3.3	AA-Request (AAR) Command	52
5.2.2.3.4	AA-Answer (AAA) Command.....	53
5.2.2.3.5	Diameter-EAP-Request (DER) Command	53
5.2.2.3.6	Diameter-EAP-Answer (DEA) Command	53
5.2.2.4	Commands for Trusted non-3GPP Access network Initiated Session Termination.....	53
5.2.2.4.1	Session-Termination-Request (STR) Command	53
5.2.2.4.2	Session-Termination-Answer (STA) Command	54
5.2.3	Information Elements	54
5.2.3.1	General	54
5.2.3.2	Mobile-Node-Identifier	56
5.2.3.3	MIP6-Feature-Vector	56
5.2.3.4	QoS Capability.....	57
5.2.3.5	Service-Selection	57
5.2.3.6	RAT-Type.....	57
5.2.3.7	ANID.....	57
5.2.3.8	AMBR.....	57
5.2.3.9	AN-Trusted	57
5.2.3.10	Feature-List-ID AVP.....	58
5.2.3.11	Feature-List AVP	58
5.2.3.12	MIP-FA-RK	58
5.2.3.13	MIP-FA-RK-SPI	58
5.2.3.14	Full-Network-Name	58
5.2.3.15	Short-Network-Name.....	58
5.2.3.16	Void.....	58
5.2.3.17	Void.....	58
5.2.3.18	WLAN-Identifier	58
5.2.3.19	Transport-Access-Type	59
5.2.3.20	DER-Flags.....	59
5.2.3.21	DEA-Flags	59
5.2.3.22	SSID.....	59
5.2.3.23	HESSID.....	59
5.2.3.24	Access-Network-Info	60
5.2.3.25	TWAN-Connection-Mode	60
5.2.3.26	TWAN-Connectivity-Parameters.....	60
5.2.3.27	Connectivity-Flags	61
5.2.3.28	TWAN-PCO.....	61

5.2.3.29	TWAG-CP-Address	62
5.2.3.30	TWAG-UP-Address	62
5.2.3.31	TWAN-S2a-Failure-Cause.....	62
5.2.3.32	SM-Back-Off-Timer	62
5.2.3.33	WLCP-Key.....	63
5.2.3.34	Default-Access-Type.....	63
5.2.4	Session Handling	63
6	SWd Description	63
6.1	Functionality.....	63
6.1.1	General.....	63
6.1.2	Procedures Description	64
6.1.2.1	Trusted non-3GPP Access / Access Gateway related procedures	64
6.1.2.1.1	Trusted Non-3GPP Access Authentication and Authorization.....	64
6.1.2.1.2	HSS/AAA Initiated Detach for Trusted non-3GPP Access	66
6.1.2.1.3	Access and Service Authorization information update.....	66
6.1.2.1.4	Trusted non-3GPP Access Network Initiated Session Termination	67
6.1.2.2	Untrusted non-3GPP Access / ePDG related procedures	67
6.1.2.3	PDN GW related procedures.....	68
6.2	Protocol Specification	68
6.2.1	General.....	68
6.2.2	Commands	69
6.2.2.1	Commands used in connection with the STa interface	69
6.2.2.1.1	Commands for STa PMIPv6 or GTPv2 authentication and authorization procedures	69
6.2.2.1.1.1	Diameter-EAP-Request (DER) Command	69
6.2.2.1.1.2	Diameter-EAP-Answer (DEA) Command.....	70
6.2.2.1.2	Commands for STa HSS/AAA Initiated Detach for Trusted non-3GPP Access	70
6.2.2.1.3	Commands for STa Access and Service Authorization Update Procedure	70
6.2.2.1.4	Commands for Trusted non-3GPP Access network Initiated Session Termination	70
6.2.2.2	Commands used in connection with the SWm interface.....	70
6.2.2.3	Commands used in connection with the S6b interface.....	70
6.2.3	Information Elements	71
6.2.3.1	General	71
7	SWm Description	72
7.1	Functionality.....	72
7.1.1	General.....	72
7.1.2	Procedures Description	73
7.1.2.1	Authentication and Authorization Procedures	73
7.1.2.1.1	General	73
7.1.2.1.2	3GPP AAA Server Detailed Behaviour.....	76
7.1.2.1.3	3GPP AAA Proxy Detailed Behaviour.....	78
7.1.2.1.4	ePDG Detailed Behaviour	78
7.1.2.2	Authorization Procedures.....	79
7.1.2.2.1	General	79
7.1.2.2.2	3GPP AAA Server Detailed Behaviour.....	82
7.1.2.2.3	3GPP AAA Proxy Detailed Behaviour.....	82
7.1.2.2.4	ePDG Detailed Behaviour	82
7.1.2.3	ePDG Initiated Session Termination Procedures	83
7.1.2.3.1	General	83
7.1.2.3.2	3GPP AAA Server Detailed Behavior.....	83
7.1.2.3.3	3GPP AAA Proxy Detailed Behavior.....	84
7.1.2.4	3GPP AAA Server Initiated Session Termination Procedures.....	84
7.1.2.4.1	General	84
7.1.2.4.2	3GPP AAA Server Detailed Behaviour.....	85
7.1.2.4.3	3GPP AAA Proxy Detailed Behaviour.....	85
7.1.2.5	Authorization Information Update Procedures	85
7.1.2.5.1	General	85
7.1.2.5.2	3GPP AAA Server Detailed Behaviour.....	86
7.1.2.5.3	ePDG Detailed Behaviour	86
7.2	Protocol Specification	87
7.2.1	General.....	87

7.2.2	Commands	87
7.2.2.1	Commands for SWm Authentication and Authorization Procedures.....	87
7.2.2.1.1	Diameter-EAP-Request (DER) Command	87
7.2.2.1.2	Diameter-EAP-Answer (DEA) Command	88
7.2.2.1.3	Diameter-AA-Request (AAR) Command	88
7.2.2.1.4	Diameter-AA-Answer (AAA) Command.....	88
7.2.2.2	Commands for ePDG Initiated Session Termination	89
7.2.2.2.1	Session-Termination-Request (STR) Command	89
7.2.2.2.2	Session-Termination-Answer (STA) Command	89
7.2.2.3	Commands for 3GPP AAA Server Initiated Session Termination.....	89
7.2.2.3.1	Abort-Session-Request (ASR) Command	89
7.2.2.3.2	Abort-Session-Answer (ASA) Command	90
7.2.2.3.3	Session-Termination-Request (STR) Command	90
7.2.2.3.4	Session-Termination-Answer (STA) Command	90
7.2.2.4	Commands for Authorization Information Update	91
7.2.2.4.1	Re-Auth-Request (RAR) Command.....	91
7.2.2.4.2	Re-Auth-Answer (RAA) Command.....	91
7.2.3	Information Elements	91
7.2.3.1	General	91
7.2.3.2	Feature-List-ID AVP.....	93
7.2.3.3	Feature-List AVP	93
7.2.3.4	Emergency-Indication	93
7.2.4	Session Handling	93
8	SWx Description	93
8.1	Functionality.....	93
8.1.1	General.....	93
8.1.2	Procedures Description	94
8.1.2.1	Authentication Procedure.....	94
8.1.2.1.1	General	94
8.1.2.1.2	Detailed behaviour.....	97
8.1.2.2	Location Management Procedures	98
8.1.2.2.1	General	98
8.1.2.2.2	UE/PDN Registration/DeRegistration Notification.....	98
8.1.2.2.2.1	General.....	98
8.1.2.2.2.2	Detailed behaviour	100
8.1.2.2.3	Network Initiated De-Registration by HSS, Administrative	102
8.1.2.2.3.1	General.....	102
8.1.2.2.3.2	Detailed behaviour	103
8.1.2.3	HSS Initiated Update of User Profile	103
8.1.2.3.1	General	103
8.1.2.3.2	HSS Detailed behaviour	105
8.1.2.3.3	3GPP AAA Server Detailed behaviour	105
8.1.2.4	Fault Recovery Procedures	106
8.1.2.4.1	HSS Reset Indication.....	106
8.1.2.4.1.1	General.....	106
8.1.2.4.1.2	HSS Detailed behaviour	107
8.1.2.4.1.3	3GPP AAA Server Detailed behaviour	107
8.1.2.4.2	HSS Restoration	107
8.1.2.4.2.1	General	107
8.1.2.4.2.2	HSS Detailed behaviour	109
8.1.2.4.2.3	3GPP AAA Server Detailed behaviour	109
8.2	Protocol Specification	109
8.2.1	General.....	109
8.2.2	Commands	109
8.2.2.1	Authentication Procedure.....	109
8.2.2.2	HSS Initiated Update of User Profile Procedure.....	110
8.2.2.3	Non-3GPP IP Access Registration Procedure	111
8.2.2.4	Network Initiated De-Registration by HSS Procedure.....	112
8.2.3	Information Elements	112
8.2.3.0	General	112
8.2.3.1	Non-3GPP-User-Data	114

8.2.3.2	Subscription-ID	115
8.2.3.3	Non-3GPP-IP-Access	115
8.2.3.4	Non-3GPP-IP-Access-APN	115
8.2.3.5	RAT-Type	116
8.2.3.6	Session-Timeout	116
8.2.3.7	APN-Configuration	116
8.2.3.8	ANID	116
8.2.3.9	SIP-Auth-Data-Item	116
8.2.3.10	Confidentiality-Key	116
8.2.3.11	Integrity-Key	116
8.2.3.12	Server-Assignment-Type AVP	116
8.2.3.13	Trace-Info	117
8.2.3.14	Trace-Data	117
8.2.3.15	Feature-List-ID AVP	117
8.2.3.16	Feature-List AVP	117
8.2.3.17	PPR-Flags	118
8.2.3.18	TWAN-Default-APN-Context-Id	119
8.2.3.19	TWAN-Access-Info	119
8.2.3.20	Access-Authorization-Flags	119
8.2.3.21	AAA-Failure-Indication	120
8.2.3.22	OC-Supported-Features	120
8.2.3.23	OC-OLR	120
8.2.3.24	3GPP-AAA-Server-Name	120
8.2.3.25	DRMP	120
8.2.4	Session Handling	120
8.3	User identity to HSS resolution	121
9	S6b and H2 Description	121
9.1	Functionality	121
9.1.1	General	121
9.1.2	Procedures Description	122
9.1.2.1	Authentication and Authorization Procedures when using DSMIPv6	122
9.1.2.1.1	General	122
9.1.2.1.2	PDN GW Detailed Behaviour	125
9.1.2.1.3	3GPP AAA Server Detailed Behaviour	126
9.1.2.1.4	3GPP AAA Proxy Detailed Behaviour	127
9.1.2.2	Authorization Procedures when using PMIPv6 or GTPv2	127
9.1.2.2.1	General	127
9.1.2.2.2	PDN GW Detailed Behaviour	130
9.1.2.2.3	3GPP AAA Server Detailed Behaviour	130
9.1.2.2.4	3GPP AAA Proxy Detailed Behaviour	131
9.1.2.3	PDN GW Initiated Session Termination Procedures	132
9.1.2.3.1	General	132
9.1.2.3.2	PDN GW Detailed Behaviour	132
9.1.2.3.3	3GPP AAA Server Detailed Behaviour	132
9.1.2.3.4	3GPP AAA Proxy Detailed Behaviour	133
9.1.2.4	3GPP AAA Initiated Session Termination Procedures	133
9.1.2.4.1	General	133
9.1.2.4.2	PDN GW Detailed Behaviour	134
9.1.2.4.3	3GPP AAA Server Detailed Behaviour	134
9.1.2.4.4	3GPP AAA Proxy Detailed Behaviour	135
9.1.2.5	Service Authorization Information Update Procedures	135
9.1.2.5.1	General	135
9.1.2.5.2	Detailed Behaviour	138
9.1.2.6	Authorization Procedures when using MIPv4 FACoA	139
9.1.2.6.1	General	139
9.1.2.6.2	PDN GW Detailed Behaviour	140
9.1.2.6.3	3GPP AAA Server Detailed Behaviour	141
9.1.2.6.4	3GPP AAA Proxy Detailed Behaviour	142
9.2	Protocol Specification	142
9.2.1	General	142
9.2.2	Commands	142

9.2.2.1	Commands for S6b DSMIPv6 Authorization Procedures.....	142
9.2.2.1.1	Diameter-EAP-Request (DER) Command	142
9.2.2.1.2	Diameter-EAP-Answer (DEA) Command	143
9.2.2.2	Commands for S6b PMIPv6, GTPv2 or DSMIPv6 Authorization Procedures.....	143
9.2.2.2.1	AA-Request (AAR) Command	143
9.2.2.2.2	AA-Answer (AAA) Command.....	144
9.2.2.3	Commands for PDN GW Initiated Session Termination	145
9.2.2.3.1	Session-Termination-Request (STR) Command	145
9.2.2.3.2	Session-Termination-Answer (STA) Command	145
9.2.2.4	Commands for 3GPP AAA Server Initiated Session Termination.....	145
9.2.2.4.1	Abort-Session-Request (ASR) Command	145
9.2.2.4.2	Abort-Session-Answer (ASA) Command	146
9.2.2.4.3	Session-Termination-Request (STR) Command	146
9.2.2.4.4	Session-Termination-Answer (STA) Command	146
9.2.2.5	Commands for S6b MIPv4 FACoA Authorization Procedures	146
9.2.2.5.1	AA-Request (AAR) Command	146
9.2.2.5.2	AA-Answer (AAA) Command.....	147
9.2.2.6	Commands for S6b Service Authorization Information Update Procedures.....	147
9.2.2.6.1	Re-Auth-Request (RAR) Command.....	147
9.2.2.6.2	Re-Auth-Answer (RAA) Command.....	148
9.2.3	Information Elements	148
9.2.3.1	S6b DSMIPv6 procedures.....	148
9.2.3.1.1	General	148
9.2.3.1.2	Visited-Network-Identifier	149
9.2.3.1.3	Void.....	149
9.2.3.1.4	Void.....	149
9.2.3.1.5	RAR-Flags.....	149
9.2.3.2	S6b PMIPv6 or GTPv2 procedures	149
9.2.3.2.1	General	149
9.2.3.2.2	MIP6-Agent-Info	150
9.2.3.2.3	MIP6-Feature-Vector	150
9.2.3.2.4	QoS-Capability	150
9.2.3.2.5	QoS-Resources	150
9.2.3.2.6	Origination-Time-Stamp	151
9.2.3.2.7	Maximum-Wait-Time.....	151
9.2.3.3	S6b Re-used Diameter AVPs	151
9.2.3.4	Feature-List-ID AVP.....	151
9.2.3.5	Feature-List AVP.....	151
9.2.3.6	S6b MIPv4 FACoA procedures	152
9.2.3.6.1	General	152
9.2.3.6.2	MIP6-Agent-Info	152
9.2.3.6.3	MIP6-Feature-Vector	153
9.2.3.6.4	QoS-Capability	153
9.2.3.6.5	QoS-Resources	153
9.2.3.6.6	MIP-MN-HA-SPI.....	153
9.2.3.6.7	MIP-Session-Key	153
9.2.3.7	DER-S6b-Flags.....	153
9.2.4	Session Handling	153
10	Result-Code and Experimental-Result Values	154
10.1	General	154
10.2	Success	154
10.3	Permanent Failures	154
10.3.1	General.....	154
10.3.2	DIAMETER_ERROR_USER_UNKNOWN (5001).....	154
10.3.3	DIAMETER_ERROR_IDENTITY_NOT_REGISTERED (5003).....	154
10.3.4	DIAMETER_ERROR_ROAMING_NOT_ALLOWED (5004).....	154
10.3.5	DIAMETER_ERROR_IDENTITY_ALREADY_REGISTERED (5005).....	154
10.3.6	DIAMETER_ERROR_USER_NO_NON_3GPP_SUBSCRIPTION (5450).....	154
10.3.7	DIAMETER_ERROR_USER_NO_APN_SUBSCRIPTION (5451).....	154
10.3.8	DIAMETER_ERROR_RAT_TYPE_NOT_ALLOWED (5452).....	155
10.3.9	DIAMETER_ERROR_LATE_OVERLAPPING_REQUEST (5453).....	155

10.3.10	DIAMETER_ERROR_TIMED_OUT_REQUEST (5454)	155
10.4	Transient Failures	155
10.4.1	General.....	155
Annex A (informative): Trusted WLAN authentication and authorization procedure.....		156
A.1	General	156
A.2	Call Flow for SCM and EPC-routed access	156
A.3	Call Flow for MCM for EPC-routed access and/or NSWO	159
A.4	Call Flow for TSCM and EPC-routed access	160
Annex B (normative): Diameter overload control mechanism		163
B.1	General	163
B.2	SWx interface.....	163
B.2.1	General.....	163
B.2.2	HSS behaviour	163
B.2.3	3GPP AAA server behaviour.....	163
B.3	STa interface	163
B.3.1	General.....	163
B.3.2	3GPP AAA server behaviour.....	164
B.3.3	Trusted non 3GPP access network behaviour.....	164
B.4	S6b interface.....	164
B.4.1	General.....	164
B.4.2	3GPP AAA server behaviour.....	164
B.4.3	PDN-GW behaviour	164
B.5.	SWa Interface.....	165
B.5.1	General.....	165
B.5.2	3GPP AAA server behaviour.....	165
B.5.3	untrusted non-3GPP access network behaviour.....	165
B.6	SWm Interface.....	165
B.6.1	General.....	165
B.6.2	3GPP AAA server behaviour.....	165
B.6.3	ePDG behaviour.....	165
Annex C (Informative): Diameter overload control node behaviour		166
C.1	Introduction	166
C.2	Message prioritization over SWx	166
C.3	Message prioritisation over STa, SWm and SWa	166
C.4	Message prioritization over S6b.....	167
Annex D (normative): Diameter message priority mechanism.....		169
D.1	General	169
D.2	SWa, STa, SWd, SWm, SWx, S6b interfaces	169
Annex E (informative): Change history		170
History		174

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present specification details the stage 3 work related to all 3GPP AAA reference points used by the different non-3GPP accesses included in EPS; it will also cover H2 reference point defined in I-WLAN mobility.

1 Scope

The present document defines the stage-3 protocol description for several reference points for the non-3GPP access in EPS.

The present document is applicable to:

- The SWa reference point between an un-trusted non-3GPP IP access and the 3GPP AAA Server/Proxy.
- The STa reference point between a trusted non-3GPP IP access and the 3GPP AAA Server/Proxy.
- The SWd reference point between the 3GPP AAA Proxy and 3GPP AAA Server.
- The SWx reference point between the 3GPP AAA Server and the HSS.
- The S6b reference point between the 3GPP AAA Server/Proxy and the PDN GW.
- The H2 reference point between the 3GPP AAA Server and the HA.
- The SWm reference point between the 3GPP AAA Server/Proxy and the ePDG.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] IETF RFC 5779: "Diameter Proxy Mobile IPv6: Mobility Access Gateway and Local Mobility Anchor Interaction with Diameter Server".
- [3] 3GPP TS 23.402: "Architecture enhancements for non-3GPP accesses".
- [4] IETF RFC 4005: "Diameter Network Access Server Application".
- [5] IETF RFC 4072: "Diameter Extensible Authentication Protocol (EAP) Application".
- [6] IETF RFC 5447: "Diameter Mobile IPv6: Support for Network Access Server to Diameter Server Interaction".
- [7] IETF RFC 3588: "Diameter Base Protocol".
- [8] IETF RFC 3748: "Extensible Authentication Protocol (EAP)".
- [9] IETF RFC 5777: "Traffic Classification and Quality of Service (QoS) Attributes for Diameter".
- [10] 3GPP TS 33.234: "3G security; Wireless Local Area Network (WLAN) interworking security".
- [11] IETF RFC 5778: "Diameter Mobile IPv6: Support for Home Agent to Diameter Server Interaction".
- [12] 3GPP TS 23.327: "Mobility between 3GPP-Wireless Local Area Network (WLAN) Interworking and 3GPP Systems".