

ETSI EN 300 444 v2.4.1 (2013-07)



**Digital Enhanced Cordless Telecommunications (DECT);
Generic Access Profile (GAP)**

Reference

REN/DECT-000299

Keywordsaccess, DECT, generic, IMT-2000, mobility,
profile, radio, synchronization, TDD, TDMA***ETSI***

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	10
Foreword.....	10
1 Scope	11
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions, symbols and abbreviations	12
3.1 Definitions	12
3.2 Symbols.....	15
3.3 Abbreviations	15
4 Feature definitions.....	17
4.1 NetWorK (NWK) features	17
4.2 Speech coding and audio features	19
4.3 Application features	20
5 Service definitions.....	20
5.1 DLC service definitions.....	20
5.2 MAC service definitions	21
6 Inter-operability requirements	22
6.1 General	22
6.2 NWK features.....	22
6.3 DLC services	23
6.4 MAC services	24
6.5 PHysical Layer (PHL) services	24
6.6 Application features	24
6.7 Speech coding and audio features	25
6.8 Feature/service to procedure mapping.....	25
6.8.1 NWK feature to procedure mapping.....	25
6.8.2 DLC service to procedure mapping	28
6.8.3 MAC service to procedure mapping	29
6.8.4 Application feature to procedure mapping.....	30
6.8.5 Speech coding and audio feature to procedure mapping.....	30
6.9 General requirements	30
6.9.1 NWK layer message contents	30
6.9.2 Transaction identifier.....	30
6.9.3 Length of a NWK layer message	30
6.9.4 Handling of error and exception conditions.....	30
6.9.5 GAP default setup attributes	31
6.9.6 Coexistence of MM and CC procedures	31
6.9.7 Coding rules for information elements	31
7 Procedure description	32
8 NWK layer procedures	32
8.1 Summary of outgoing call messages, normal cases.....	32
8.2 Outgoing call request.....	34
8.2.1 Associated procedures	34
8.2.1.1 Timer P-<CC.03> management	34
8.2.2 Exceptional cases.....	35
8.2.2.1 Timer P-<CC.03> expiry	35
8.2.2.2 PT releases the outgoing call request	35
8.2.2.3 FT rejects the outgoing call request	36
8.3 Overlap sending.....	36
8.3.1 Associated procedure	37

8.3.1.1	Timer F-<CC.01> management	37
8.3.2	Exceptional cases.....	37
8.3.2.1	PT releases the outgoing call request	37
8.3.2.2	FT rejects the outgoing call request	37
8.3.2.3	Timer F-<CC.01> expiry	38
8.3.2.4	FT releases the outgoing call request	38
8.4	Outgoing call proceeding	38
8.4.1	Exceptional cases.....	39
8.4.1.1	PT releases the outgoing call request	39
8.4.1.2	FT releases the outgoing call request	39
8.5	Outgoing call confirmation.....	40
8.5.1	Exceptional cases.....	40
8.5.1.1	PT releases the outgoing call request	40
8.5.1.2	FT releases the outgoing call request	41
8.6	Outgoing call connection.....	41
8.7	Normal call release	42
8.7.1	Associated procedures	42
8.7.1.1	Timer P-<CC.02> management	42
8.7.1.2	Timer F-<CC.02> management	43
8.7.2	Exceptional cases.....	43
8.7.2.1	Release collisions	43
8.7.2.2	Timer F-<CC.02> expiry	44
8.7.2.3	Timer P-<CC.02> expiry	44
8.8	Abnormal call release	44
8.9	Partial release	45
8.10	Sending keypad information.....	46
8.11	Summary of incoming call related messages, normal cases	47
8.12	Incoming call request	48
8.12.1	Associated procedure	49
8.12.1.1	Timer F-<CC.03> management	49
8.12.2	Exceptional cases.....	50
8.12.2.1	FT releases the incoming call request	50
8.12.2.2	PT rejects the incoming call request	50
8.12.2.3	Timer F-<CC.03> expiry	51
8.12.3	Collective and group ringing	51
8.13	Incoming call confirmation	51
8.13.1	Exceptional cases.....	52
8.13.1.1	FT releases the incoming call transaction	52
8.13.1.2	PT releases the incoming call transaction	52
8.14	PT alerting	53
8.15	Incoming call connection	53
8.15.1	Associated procedure	54
8.15.1.1	Timer P-<CC.05> management	54
8.15.2	Exceptional cases.....	54
8.15.2.1	FT releases the incoming call transaction	54
8.15.2.2	PT releases the incoming call transaction	55
8.15.2.3	Timer P-<CC.05> expiry	55
8.16	Display	56
8.17	Terminal capability indication.....	56
8.18	Internal call setup	57
8.19	Internal call keypad	58
8.20	Service call setup.....	58
8.21	Service call keypad.....	58
8.22	Identification of PP.....	58
8.22.1	Associated procedure	60
8.22.1.1	Timer F-<MM_ident.2> management.....	60
8.22.2	Exceptional cases.....	60
8.22.2.1	Identity not existing in the PT	60
8.22.2.2	Timer F-<MM_ident.2> expiry	60
8.23	Authentication of FT using DSAA.....	60
8.23.1	Associated procedure	61
8.23.1.1	Timer P-<MM_auth.1> management.....	61

8.23.2	Exceptional cases.....	61
8.23.2.1	Authentication algorithm/key not supported	61
8.23.2.2	FT Authentication failure (authentication challenge RES2 has wrong value)	62
8.23.2.3	Timer P-<MM_auth.1> expiry.....	62
8.24	Authentication of PP using DSAA	62
8.24.1	Associated procedure.....	64
8.24.1.1	Timer F-<MM_auth.1> management.....	64
8.24.2	Exceptional cases.....	64
8.24.2.1	Authentication algorithm/key not supported	64
8.24.2.2	Timer F-<MM_auth.1> expiry.....	64
8.23.2.3	PP Authentication failure (authentication challenge RES1 has wrong value).....	64
8.25	Authentication of user using DSAA.....	65
8.25.1	Associated procedure.....	65
8.25.1.1	Timer F-<MM_auth.2> management.....	65
8.25.2	Exceptional cases.....	66
8.25.2.1	Authentication algorithm/key not supported	66
8.25.2.2	Timer F-<MM_auth.2> expiry.....	66
8.26	Incrementing the ZAP value.....	66
8.27	Storing the DCK.....	67
8.28	Location registration.....	67
8.28.1	Associated procedures	69
8.28.1.1	Timer P-<MM_locate.1> management	69
8.28.1.2	Timer F-<MM_ident.1> management.....	69
8.28.2	Exceptional cases.....	69
8.28.2.1	FT rejects the location registration procedure	69
8.28.2.2	Failure of location registration procedure	70
8.28.2.3	PT rejects the identity assignment.....	70
8.28.2.4	Timer F-<MM_identity.1> expiry.....	70
8.29	Location update	70
8.30	Obtaining access rights.....	71
8.30.1	Associated procedure.....	73
8.30.1.1	Timer P-<MM_access.1> management	73
8.30.2	Exceptional cases.....	73
8.30.2.1	FT rejects the access rights	73
8.30.2.2	Timer P-<MM_access.1> expiry.....	74
8.31	FT terminating access rights.....	74
8.31.1	Associated procedure.....	75
8.31.1.1	Timer F-<MM_access.2> management	75
8.31.2	Exceptional cases.....	75
8.31.2.1	PT rejects the termination request	75
8.31.2.2	Timer F-<MM_access.2> expiry.....	75
8.32	Key allocation	76
8.32.1	Associated procedures	77
8.32.1.1	Timer F-<MM_key.1> management.....	77
8.32.1.2	Timer P-<MM_auth.1> management.....	78
8.32.2	Exceptional cases.....	78
8.32.2.1	Timer F-<MM_key.1> expiry.....	78
8.32.2.2	Timer P-<MM_auth.1> expiry.....	78
8.32.2.3	Allocation-type element is unacceptable.....	78
8.32.2.4	Authentication of PT fails	79
8.32.2.5	Authentication of FT fails	79
8.33	Cipher-switching initiated by FT using DSC	79
8.33.1	Associated procedure.....	81
8.33.1.1	Timer F-<MM_cipher.1> management.....	81
8.33.2	Exceptional cases.....	81
8.33.2.1	PT rejects the cipher request	81
8.33.2.2	Timer F-<MM_cipher.1> expiry.....	81
8.34	Cipher-switching initiated by PT using DSC	82
8.34.1	Associated procedure.....	83
8.34.1.1	Timer P-<MM_cipher.2> management.....	83
8.34.2	Exceptional cases.....	83
8.34.2.1	FT rejects the cipher request	83

8.34.2.2	Timer P-<MM_cipher.2> expiry	84
8.35	Indirect FT initiated link establishment	84
8.35.1	Associated procedure	85
8.35.1.1	Timer F-<LCE.03> management	85
8.35.2	Exceptional cases	85
8.35.2.1	The IPUI received in the {LCE-PAGE-RESPONSE} does not match	85
8.35.2.2	Timer <LCE.03> expiry	86
8.35.2.3	Release from the higher entity	86
8.36	Direct PT initiated link establishment	86
8.36.1	Exceptional case	88
8.36.1.1	Link establishment failure	88
8.37	Link release "normal"	88
8.37.1	Associated procedure	90
8.37.1.1	Timer <LCE.01> management	90
8.37.2	Exceptional cases	90
8.37.2.1	Timer <LCE.01> expiry	90
8.37.2.2	Outstanding data has been discarded	90
8.38	Link release "abnormal"	91
8.39	Link release "maintain"	91
8.39.1	Associated procedure	91
8.39.1.1	Timer <LCE.02> management	91
8.40	Enhanced FT initiated U- plane connection	92
8.41	Calling Line Identification Presentation (CLIP) Indication	92
8.42	Calling Name Identification Presentation (CNIP) Indication	93
8.43	Internal Call Calling Line Identification Presentation (CLIP)	93
8.44	Internal Call Calling Name Identification Presentation (CNIP)	94
8.45	Enhanced security procedures	96
8.45.1	Encryption of all calls	96
8.45.2	Re-keying during a call	96
8.45.3	Early encryption	97
8.45.4	Subscription requirements	98
8.45.5	Enhanced security regarding legacy devices	98
8.45.5.1	Behaviour of FPs regarding legacy PPs	99
8.45.5.2	Behaviour of PPs regarding legacy FPs	99
8.45.5.3	Behaviour regarding legacy 'repeater' devices	100
8.45.6	Authentication of FT using DSAA2	100
8.45.6.1	Associated procedure	102
8.45.6.1.1	Timer P-<MM_auth.1> management	102
8.45.6.2	Exceptional cases	102
8.45.6.2.1	Authentication algorithm/key not supported	102
8.45.6.2.2	FT Authentication failure (authentication challenge RES2 has wrong value)	102
8.45.6.2.3	Timer P-<MM_auth.1> expiry	103
8.45.7	Authentication of PP using DSAA2	103
8.45.7.1	Associated procedure	105
8.45.7.1.1	Timer F-<MM_auth.1> management	105
8.45.7.2	Exceptional cases	105
8.45.7.2.1	Authentication algorithm/key not supported	105
8.45.7.2.2	Timer F-<MM_auth.1> expiry	105
8.45.7.2.3	PP Authentication failure (authentication challenge RES1 has wrong value)	105
8.45.8	Authentication of user using DSAA2	106
8.45.8.1	Associated procedure	106
8.45.8.1.1	Timer F-<MM_auth.2> management	106
8.45.8.2	Exceptional cases	106
8.45.8.2.1	Authentication algorithm/key not supported	106
8.45.8.2.2	Timer F-<MM_auth.2> expiry	107
8.45.9	Key allocation using DSAA2	107
8.45.9.1	Associated procedures	109
8.45.9.1.1	Timer F-<MM_key.1> management	109
8.45.9.1.2	Timer P-<MM_auth.1> management	109
8.45.9.2	Exceptional cases	110
8.45.9.2.1	Timer F-<MM_key.1> expiry	110
8.45.9.2.2	Timer P-<MM_auth.1> expiry	110

8.45.9.2.3	Allocation-type element is unacceptable	110
8.45.9.2.4	Authentication of PT fails.....	110
8.45.9.2.5	Authentication of FT fails.....	111
8.45.10	Cipher-switching initiated by FT using DSC2.....	111
8.45.10.1	Associated procedure	112
8.45.10.1.1	Timer F-<MM_cipher.1> management	112
8.45.10.2	Exceptional cases	112
8.45.10.2.1	PT rejects the cipher request.....	112
8.45.10.2.2	Timer F-<MM_cipher.1> expiry	113
8.45.11	Cipher-switching initiated by PT using DSC2.....	113
8.45.11.1	Associated procedure	115
8.45.11.1.1	Timer P-<MM_cipher.2> management	115
8.45.11.2	Exceptional cases	115
8.45.11.2.1	FT rejects the cipher request.....	115
8.45.11.2.2	Timer P-<MM_cipher.2> expiry	115
9	DLC layer procedures	116
9.1	Class A link establishment.....	116
9.1.1	Associated procedures	117
9.1.1.1	Timer P<DL.07> management.....	117
9.1.1.2	Re-transmission counter management.....	117
9.1.1.3	Multiple frame operation variables management.....	117
9.1.1.4	Lower Layer Management Entity (LLME) establishment of a MAC connection.....	117
9.1.2	Exceptional cases.....	119
9.1.2.1	Timer P<DL.07> expiry.....	119
9.1.2.2	Receipt of a request for link release	119
9.1.2.3	Receipt of an indication for a connection release.....	119
9.2	Class A Acknowledged Information transfer	119
9.2.1	Acknowledgement with an I_frame	120
9.2.2	Acknowledgement with a RR_frame	121
9.2.3	Class A acknowledged information transfer with segment reassemble	121
9.2.4	Associated procedures	122
9.2.4.1	Timer <DL.04> management.....	122
9.2.4.2	Re-transmission counter management.....	122
9.2.4.3	Multiple frame operation variables management.....	122
9.2.5	Exceptional cases.....	122
9.2.5.1	Timer <DL.04> expiry	122
9.2.5.2	Receipt of a request for link release	123
9.2.5.3	Receipt of an indication for a connection release.....	123
9.2.5.4	DLC wants to make a connection handover.....	123
9.3	Class A link release	123
9.3.1	Associated procedures	123
9.3.1.1	LLME U-plane release	123
9.3.1.2	LLME release a MAC connection	123
9.4	Class A link re-establishment.....	123
9.5	C _S channel fragmentation and recombination	124
9.6	Normal broadcast	124
9.7	Class A basic connection handover.....	125
9.7.1	Voluntary handover	125
9.7.2	Associated procedure	125
9.7.2.1	LLME connection handover management	125
9.7.3	Exceptional case	125
9.7.3.1	Receipt of a request for link release	125
9.8	Encryption switching.....	126
9.8.1	Associated procedure	126
9.8.1.1	Providing Encryption key to the MAC layer.....	126
9.8.2	Exceptional cases	126
9.8.2.1	Encryption fails	126
9.8.2.2	Connection handover of ciphered connections.....	126
9.9	U-plane class 0/min delay	126
9.9.1	Associated procedure	127
9.9.1.1	LLME U-plane establishment	127

9.10	FU1 frame operation	127
10	MAC layer procedures	127
10.1	General	127
10.2	Downlink broadcast.....	128
10.2.1	N_T message	128
10.2.2	Q_T - static system information	128
10.2.3	Q_T - FP capabilities.....	129
10.2.3.1	Q_T - Extended FP capabilities	129
10.2.3.2	Q_T - Extended FP capabilities (part 2)	130
10.2.4	Q_T - SARI list contents	130
10.3	Paging broadcast	131
10.3.1	Short page, normal/extended paging.....	131
10.3.2	Zero page, normal/extended paging.....	131
10.3.3	Blind slot information.....	132
10.3.4	Bearer handover information	132
10.4	Setup of basic connection, basic bearer setup (A-field)	132
10.4.1	M_T message.....	133
10.4.2	Associated procedures	133
10.4.2.1	Timer T200 management	133
10.4.2.2	Counter N200 management.....	133
10.4.3	Exceptional cases.....	134
10.4.3.1	Bearer setup attempt fails N200+1 times	134
10.4.3.2	Timer T200 expiry	135
10.5	Connection/bearer release	135
10.5.1	M_T message.....	136
10.6	Bearer handover request.....	136
10.6.1	M_T message.....	136
10.7	Connection handover request	136
10.7.1	M_T message.....	137
10.8	C_S channel data.....	137
10.9	Q2 bit setting	137
10.10	RFPI handshake.....	137
10.11	Antenna diversity	137
10.12	Sliding collision.....	137
10.13	Encryption process - initialization and synchronization.....	137
10.14	Encryption mode control	138
10.14.1	M_T message.....	138
10.15	Handover encryption process	138
10.16	Extended frequency allocation	138
10.17	Re-keying	139
10.18	Early Encryption	139
10.19	AES/DSC2 Encryption.....	139
11	Physical Layer (PHL) requirements	139
11.1	General	139
11.2	Minimum Normal Transmit Power (NTP)	139
11.3	Radio receiver sensitivity	139
11.4	Z-field.....	139
11.5	Sliding collision detection	140
11.6	Physical channel availability	140
11.7	Synchronization window	140
12	Requirements regarding the speech transmission.....	140
12.1	General	140
12.2	User controlled volume control	140
13	Management procedures.....	140
13.1	Management of MM procedures	140
13.2	Location registration initiation	141
13.3	Assigned individual TPUI management.....	141
13.4	PMID management.....	141
13.5	DCK management	141

13.6	Broadcast attributes management	142
13.6.1	Higher layer capabilities	142
13.6.2	Extended higher layer capabilities	142
13.6.3	Extended higher layer capabilities (part 2)	142
13.7	Storage of subscription related data	143
14	Application procedures.....	143
14.1	Subscription control	143
14.2	AC to bitstring mapping	143
14.3	Manual entry of the PARK.....	144
14.4	Terminal Identity number assignment in mono cell system	145
14.4.1	General.....	145
14.4.2	Procedure description	145
14.4.3	Related Procedures	146
Annex A (informative):	PP locking procedure for on-air subscription	147
Annex B (informative):	Tones, progress indicator and U-plane connection.....	149
B.1	General	149
B.2	Connection of U-plane and provision of tones.....	149
B.3	Provision of tones before connection of the U-plane	149
B.4	Provision of tones and <>Progress indicator>> information element.....	149
B.5	Summary	150
Annex C (normative):	Synchronization requirements for fixed parts	151
Annex D (informative):	Change history	152
History	153	

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is based on EN 300 175, parts 1 [1] to 8 [8]. General attachment requirements and speech attachment requirements are based on EN 301 406 [11] (replacing TBR 006 [i.1]) and EN 300 176-2 [10] (previously covered by TBR 010 [i.2]).

The present document has been developed in accordance to the rules of documenting a profile specification as described in ISO/IEC 9646-6 [i.4].

National transposition dates	
Date of adoption of this EN:	22 July 2013
Date of latest announcement of this EN (doa):	31 October 2013
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2014
Date of withdrawal of any conflicting National Standard (dow):	30 April 2014

1 Scope

The present document specifies the set of technical requirements for Digital Enhanced Cordless Telecommunications (DECT) Fixed Part (FP) and DECT Portable Part (PP) necessary for the support of the Generic Access Profile (GAP).

The GAP is applicable to all DECT Portable radio Terminations (PT) and Fixed radio Terminations (FT) which under the scope of EN 300 176-2 [10] (i.e. 3,1 kHz telephony teleservice) and specifies the minimum functionality that is supported by all other 3,1 kHz voice profiles.

The objective of the present document is to ensure the Air Interface (AI) inter-operability of DECT equipment capable of 3,1 kHz telephony applications, in such a way that any DECT PT conforming to the procedures described in the present document is inter-operable with any DECT FT conforming to the procedures described in the present document.

The profile consists of the minimum mandatory requirements that allow a 3,1 kHz teleservice connection to be established, maintained and released between a FT and a PT with the appropriate access rights, irrespective of whether the FP provides residential, business or public access services.

In addition, the present document defines the features, services, procedures etc. for both the FT and the PT, which are provision mandatory either in the PT or in the FT, as well as some elements that are provision optional but still process mandatory.

Mobility Management (MM) procedures at the DECT AI to support incoming calls and outgoing calls are included.

Inter-working between the FT and the attached network is outside the scope of the present document.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical layer (PHL)".
- [3] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
- [5] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [6] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".