

# ETSI EN 300 676 V1.3.1 (2003-03)

---

*European Standard (Telecommunications series)*

**Electromagnetic compatibility  
and Radio spectrum Matters (ERM);  
Ground-based VHF hand-held, mobile and fixed radio  
transmitters, receivers and transceivers for the VHF  
aeronautical mobile service using amplitude modulation;  
Technical characteristics and methods of measurement**

---



---

Reference

REN/ERM-TG25-020

---

Keywords

aeronautical, AM, DSB, radio, testing, VHF

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

[editor@etsi.org](mailto:editor@etsi.org)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2003.  
All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup> and **UMTS**<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members.  
**TIPHON**<sup>TM</sup> and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.  
**3GPP**<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

# Contents

Intellectual Property Rights .....	7
Foreword.....	7
Introduction .....	7
1 Scope .....	8
2 References .....	8
3 Definitions and abbreviations.....	8
3.1 Definitions .....	8
3.2 Abbreviations .....	9
4 General requirements .....	9
4.1 Controls and indicators.....	9
4.2 Class of emission and modulation characteristics .....	10
4.3 Warm up.....	10
5 Test conditions, power sources and ambient temperatures .....	10
5.1 Normal and extreme test conditions .....	10
5.2 Test power source.....	10
5.3 Normal test conditions.....	10
5.3.1 Normal temperature and humidity .....	10
5.3.2 Normal power sources .....	11
5.3.2.1 Mains voltage and frequency .....	11
5.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	11
5.3.2.3 Other power sources.....	11
5.4 Extreme test conditions .....	11
5.4.1 Extreme temperatures .....	11
5.4.2 Extreme values of test power sources .....	11
5.4.2.1 Mains voltage.....	11
5.4.2.2 Other power sources.....	11
5.4.3 Extended temperatures.....	11
5.5 Performance test .....	12
5.6 Environmental tests .....	12
5.6.1 General.....	12
5.6.2 Procedure for tests at extreme temperatures .....	12
5.6.3 Temperature tests .....	12
5.6.3.1 High temperature.....	13
5.6.3.2 Low temperature .....	13
6 General conditions of measurement .....	13
6.1 Receiver test signal arrangement.....	13
6.1.1 Test signal sources .....	13
6.1.2 Nominal frequency .....	13
6.1.3 Normal test signal .....	13
6.1.4 Squelch .....	13
6.1.5 Normal audio output power .....	13
6.1.6 Audio AGC.....	14
6.2 Transmitter test signal arrangement .....	14
6.2.1 Coaxial termination.....	14
6.2.2 Signal sources .....	14
6.2.3 Normal test signal .....	14
6.3 Test channels.....	14
7 Transmitter .....	14
7.1 Protection of the transmitter .....	14
7.1.1 Definition.....	14
7.1.2 Method of measurement .....	14

7.1.3	Requirement.....	14
7.2	Frequency error .....	15
7.2.1	Definition.....	15
7.2.2	Method of measurement .....	15
7.2.3	Limits.....	15
7.3	Carrier power.....	15
7.3.1	Definitions .....	15
7.3.2	Method of measurement .....	15
7.3.3	Tolerances.....	16
7.3.3.1	Normal test conditions .....	16
7.3.3.2	Extreme test conditions .....	16
7.4	Amplitude modulation characteristic.....	16
7.4.1	Modulation depth (speech) .....	16
7.4.1.1	Definitions.....	16
7.4.1.2	Method of measurement.....	16
7.4.1.3	Limits .....	16
7.4.1.4	Modulation depth (data mode).....	16
7.4.1.5	Method of measurement.....	16
7.4.1.6	Limits .....	16
7.4.2	Modulation compression (speech mode) .....	17
7.4.2.1	Definition .....	17
7.4.2.2	Method of measurement.....	17
7.4.2.3	Limits .....	17
7.4.3	Amplitude modulation distortion.....	17
7.4.3.1	Definition .....	17
7.4.3.2	Method of measurement.....	17
7.4.3.3	Limits .....	17
7.4.4	Audio frequency response .....	18
7.4.4.1	Definition .....	18
7.4.4.2	Method of measurement.....	18
7.4.4.3	Limits 8,33 kHz channel spacing .....	18
7.4.4.4	Limits 25 kHz channel spacing .....	18
7.4.5	Group delay variation (data mode only) .....	19
7.4.5.1	Definition .....	19
7.4.5.2	Transmitter method of measurement.....	19
7.4.5.3	Limits .....	19
7.5	Adjacent channel power .....	20
7.5.1	Definition.....	20
7.5.2	Measurement.....	20
7.5.3	Limits.....	20
7.6	Broadband noise measurement.....	21
7.6.1	Definition.....	21
7.6.2	Method of measurement .....	21
7.6.3	Limit .....	21
7.7	Conducted spurious emissions .....	22
7.7.1	Definition.....	22
7.7.2	Method of measurement .....	22
7.7.3	Limits.....	22
7.8	Intermodulation attenuation.....	23
7.8.1	Definition.....	23
7.8.2	Method of measurement .....	23
7.8.3	Limits.....	23
7.9	RF power attack time and release time.....	24
7.9.1	Definitions .....	24
7.9.2	Method of measurement .....	24
7.9.2.1	Attack time .....	24
7.9.2.2	Release time .....	25
7.9.3	Limits.....	25
7.10	Keying Transient frequency behaviour of the transmitter .....	25
7.10.1	Definitions .....	25
7.10.2	Method of measurement .....	26
7.10.3	Limits.....	26

8	Receiver.....	26
8.1	Sensitivity.....	26
8.1.1	Definition.....	26
8.1.2	Method of measurement .....	27
8.1.3	Limits.....	27
8.2	Harmonic distortion.....	27
8.2.1	Definition.....	27
8.2.2	Method of measurement .....	27
8.2.3	Limits.....	27
8.3	Audio frequency response.....	28
8.3.1	Definition.....	28
8.3.2	Method of measurement .....	28
8.3.3	Limits.....	28
8.3.4	Limit for ACARS operation.....	28
8.4	Audio noise .....	28
8.4.1	Definition.....	28
8.4.2	Method of measurement .....	28
8.4.3	Limits.....	28
8.5	Effective acceptance bandwidth .....	29
8.5.1	Definition.....	29
8.5.2	Method of measurement .....	29
8.5.3	Limits.....	29
8.6	Adjacent channel rejection .....	29
8.6.1	Definition.....	29
8.6.2	Method of measurement .....	29
8.6.3	Limits.....	30
8.7	Spurious response rejection.....	30
8.7.1	Definition.....	30
8.7.2	Introduction to the method of measurement .....	30
8.7.3	Method of search of the limited frequency range .....	31
8.7.4	Method of measurement .....	31
8.7.5	Limit .....	31
8.8	Intermodulation response rejection .....	31
8.8.1	Definition.....	31
8.8.2	Method of measurement .....	32
8.8.3	Limit .....	32
8.9	Blocking or desensitization .....	32
8.9.1	Definition.....	32
8.9.2	Method of measurement .....	32
8.9.3	Limit .....	33
8.10	Conducted spurious emissions .....	33
8.10.1	Definition.....	33
8.10.2	Method of measuring the power level .....	33
8.10.3	Limits.....	33
8.11	Squelch operation.....	34
8.11.1	Definition.....	34
8.11.2	Method of measurement .....	34
8.11.3	Limits.....	34
8.12	Cross modulation rejection.....	35
8.12.1	Definition.....	35
8.12.2	Method of measurement .....	35
8.12.3	Limits.....	35
8.13	Receiver dynamic range .....	35
8.13.1	Definition.....	35
8.13.2	Method of measurement .....	35
8.13.3	Limit .....	36
8.14	AGC attack time and release time (data mode only).....	36
8.14.1	Definitions .....	36
8.14.2	Method of measurement .....	36
8.14.2.1	Attack time.....	36
8.14.2.2	AGC Decay time .....	36
8.14.3	Limits.....	36

8.15	AF AGC .....	37
8.15.1	Definition .....	37
8.15.2	Method of measurement .....	37
8.15.3	Limit .....	37
8.16	Group delay variation (data mode only) .....	37
8.16.1	Definition .....	37
8.16.2	Receiver method of measurement .....	37
8.16.3	Limits .....	38
9	Measurement uncertainty and interpretation of the measured results .....	38
9.1	Maximum measurement uncertainties .....	38
9.2	Interpretation of the measurement results .....	39
<b>Annex A (normative):</b>	<b>Auxiliary cables .....</b>	<b>40</b>
<b>Annex B (normative):</b>	<b>Specification for adjacent channel power measurement arrangements .....</b>	<b>41</b>
B.1	Power measuring receiver specification .....	41
B.1.1	IF filter .....	41
B.1.2	Attenuation indicator .....	42
B.1.3	RMS value indicator .....	42
B.1.4	Oscillator and amplifier .....	42
<b>Annex C (informative):</b>	<b>Bibliography .....</b>	<b>43</b>
History .....		44

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

All published ETSI deliverables shall include information which directs the reader to the above source of information.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

<b>National transposition dates</b>	
Date of adoption of this EN:	28 March 2003
Date of latest announcement of this EN (doa):	30 June 2003
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 2003
Date of withdrawal of any conflicting National Standard (dow):	31 December 2003

---

## Introduction

The present document states the minimum performance requirements for ground based radio transmitters, transceivers and receivers for the aeronautical mobile service operating in the VHF band (118 MHz to 136,975 MHz), using Double Sideband Amplitude Modulation with 8,33 kHz or 25 kHz channel spacing.

The present document may be used by accredited test laboratories for the assessment of the performance of the equipment. The performance of the equipment submitted for type testing should be representative for the performance of the corresponding production model.

The present document has been written on the assumption that:

- the type test measurements will be performed only once, in an accredited test laboratory and the measurements accepted by the various authorities in order to grant type approval;
- if equipment available on the market is required to be checked it will be tested in accordance with the methods of measurement specified in the present document.

---

# 1 Scope

The present document states the minimum performance requirements for radio transmitters receivers and transceivers at ground-based aeronautical stations operating in the VHF band (118 MHz to 136,975 MHz) allocated to the aeronautical mobile service.

The present document applies to DSB AM systems, with channel separations of 8,33 kHz or 25 kHz intended for analogue speech and ground base stations with a channel spacing of 25 kHz intended for ACARS data communication.

The scope of the present document is limited to ground base stations, ground mobile and hand held radios for ground use.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] ETSI ETR 028: "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".
- [2] ICAO annex 10 volume V (1996): "Aeronautical Radio Frequency Spectrum Utilization".
- [3] ITU-T Recommendation P.53: "Psophometer for use on telephone-type circuits".
- [4] ISO 7637 (parts 1 and 2): "Road vehicles - Electrical disturbances from conduction and coupling".

---

# 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**aeronautical mobile service:** mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate

**conducted measurements:** measurements which are made using a direct RF connection to the equipment under test

**radiated measurements:** measurements which involve the measurement of a radiated field

**integral antenna equipment:** radio communications equipment with an antenna integrated into the equipment without the use of an external connector and considered to be part of the equipment

NOTE: An integral antenna may be internal or external to the equipment. In equipment of this type, a 50  $\Omega$  RF connection point shall be provided for test purposes. A connection point for an AF modulating input and for AF output measurements shall also be provided.

**ground base station:** aeronautical station equipment, in the aeronautical mobile service, for use with an external antenna and intended for use at a fixed location