



Edition 3.0 2017-10

TECHNICAL REPORT



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

Radio interference characteristics of overhead power lines and high-voltage equipment –

Part 1: Description of phenomena





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



CISPR TR 18-1

Edition 3.0 2017-10

TECHNICAL REPORT



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

Radio interference characteristics of overhead power lines and high-voltage equipment –

Part 1: Description of phenomena

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.100.01 ISBN 978-2-8322-4896-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

F	DREWO	RD	5		
IN	TRODU	CTION	7		
1	Scop	e	9		
2	Norm	ative references	9		
3	Terms and definitions				
4	Radio	o noise from HV AC overhead power lines	10		
	4.1	General	10		
	4.2	Physical aspects of radio noise	11		
	4.2.1	Mechanism of formation of a noise field	11		
	4.2.2	Definition of noise	13		
	4.2.3	Influence of external parameters	14		
	4.3	Main characteristics of the noise field resulting from conductor corona	14		
	4.3.1	General			
	4.3.2	1			
	4.3.3	•			
	4.3.4				
5	Effec	ts of corona from conductors			
	5.1	Physical aspects of corona from conductors			
	5.1.1				
	5.1.2	3			
	5.2	Methods of investigation of corona by cages and test lines			
	5.2.1	General			
	5.2.2 5.2.3	•			
	5.2.3 5.3	Test lines Methods of predetermination			
	5.3.1				
	5.3.1				
	5.3.3				
	5.4	Catalogue of standard profiles			
	5.4.1	General			
	5.4.2				
6	Radio	o noise levels due to insulators, hardware and substation equipment			
	(excl	uding bad contacts)			
	6.1	Physical aspects of radio noise sources	24		
	6.1.1	General			
	6.1.2	3 · · · · · · · · · · · · · · · · · · ·			
	6.1.3		25		
	6.2	Correlation between radio noise voltage and the corresponding field strength for distributed and individual sources	26		
	6.2.1	General			
	6.2.2				
	6.2.3	·			
	6.2.4	,			
	6.3	Influence of ambient conditions			
7		king due to bad contacts			
	7.1	Physical aspects of the radio noise phenomenon			
		· · · · · · · · · · · · · · · · · · ·			

	1.2	Example of gap sources	S I
8	Radio	o noise from HVDC overhead power lines	32
	8.1	General [56, 57]	32
	8.1.1	Description of electric field physical phenomena of HVDC transmission systems	32
	8.1.2		
	8.2	Physical aspects of DC corona	
	8.3	Formation mechanism of a noise field from a DC line	
	8.4	Characteristics of the radio noise from DC lines	
	8.4.1	General	
	8.4.2		
	8.4.3	Lateral profile	
	8.4.4	Statistical distribution	
	8.5	Factors influencing the radio noise from DC lines	
	8.5.1	General	
	8.5.2		
	8.5.3	Conductor surface gradient	
	8.5.4	Polarity	
	8.5.5	Weather conditions	
	8.5.6	Subjective effects	
	8.6	Calculation of the radio noise level due to conductor corona	
	8.7	Radio noise due to insulators, hardware and substation equipment	
	8.8	Valve firing effects	
9	Figur	es	
		informative) Calculation of the voltage gradient at the surface of a conductor head line	54
Ar	nnex B (informative) Catalogue of profiles of radio noise field due to conductor certain types of power line	
Ar	nex C (informative) Summary of the catalogue of radio noise profiles according to mendations of the CISPR	
ы	bilograp	hy	/ 6
Fi	gure 1 -	· Typical lateral attenuation curves for high voltage lines, normalized to a	
lat	eral dis	tance of $y_0 = 15$ m, distance in linear scale	42
Fi dii	gure 2 - rect dist	Typical lateral attenuation curves for high voltage lines, normalized to a ance of D_0 = 20 m, distance in logarithmic scale	43
		Examples of statistical yearly distributions of radio-noise levels recorded sly under various overhead lines	44
		Examples of statistical yearly distributions of radio-noise levels recorded sly under various overhead lines	45
Fi	gure 5 –	Example of statistical yearly distributions of radio-noise levels recorded sly under various overhead lines	
Fi	gure 6 -	Examples of statistical yearly distributions of radio-noise levels recorded sly under various overhead lines	
		Equipotential lines for clean and dry insulation units	
Fi	- gure 8 –	Determination of the magnetic field strength from a perpendicular to a a line, at a distance x from the point of injection of noise current I	
			∓∪
		 Longitudinal noise attenuation versus distance from noise source (from test various experiments frequencies around 0,5 MHz) 	49

Figure 10 – Lateral profile of the radio noise field strength produced by distributed discrete sources on a 420 kV line of infinite length	50
Figure 11 – Impulsive radio-noise train of gap-type discharges	51
Figure 12 – Example of relative strength of radio noise field as a function of frequency below 1 GHz using QP detector	
Figure 13 – Example of relative strength of radio noise field due to gap discharge as a function of frequency 200 MHz to 3 GHz using peak detector	52
Figure 14 – Example of relative strength of radio noise field as a function of the distance from the line	52
Figure 15 – Unipolar and bipolar space charge regions of a HVDC transmission line	53
Figure 16 – The corona current and radio interference field	53
Figure B.1 – Triangular formation (1)	59
Figure B.2 – Triangular formation (2)	60
Figure B.3 – Flat formation	61
Figure B.4 – Arched formation	62
Figure B.5 – Flat wide formation	63
Figure B.6 – Vertical formation (480 (Rail) X 4B)	64
Figure B.7 – Flat formation	65
Figure B.8 – Flat formation	66
Figure B.9 – Arched formation	67
Figure B.10 – Flat formation	68
Figure B.11 – Arched formation	69
Figure B.12 – Flat formation	70
Figure B.13 – Vertical formation (480 (Cardinal) X 6B)	71
Figure B.14 – Typical frequency spectra for the radio noise fields of high voltage power lines	72
Figure B.15 – Prediction of radio noise level of a transmission line for various types of weather	73
Figure C.1 – Examples of transformations of the profiles of Figures B.1 to B.13 using the direct distance of 20 m as reference	75
Table B.1 – List of profiles	58
Table C.1 – Radio noise profiles	74

INTERNATIONAL ELECTROTECHNICAL COMMISSION INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

RADIO INTERFERENCE CHARACTERISTICS OF OVERHEAD POWER LINES AND HIGH-VOLTAGE EQUIPMENT –

Part 1: Description of phenomena

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

CISPR 18-1, which is a technical report, has been prepared by CISPR subcommittee B: Interference relating to industrial, scientific and medical radio-frequency apparatus, to other (heavy) industrial equipment, to overhead power lines, to high voltage equipment and to electric traction.

This third edition cancels and replaces the second edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) updated description of the RF characteristics of spark discharges which might contain spectral radio noise components up to the GHz frequency range;
- b) addition of state of the art in HVDC converter technology

The text of this technical report is based on the following documents:

DTR	Report on voting
CIS/B/653/DTR	CIS/B/674/RVDTR

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the CISPR 18 series can be found, under the general title *Radio* interference characteristics of overhead power lines and high-voltage equipment, on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed.
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This Technical Report is the first of a three-part series dealing with radio noise generated by electrical power transmission and distribution facilities (overhead lines and substations). It contains information in relation of the physical phenomena involved in the generation of electromagnetic noise fields. It also includes a description of the main properties of such fields and their numerical values. Its content was adjusted such as to allow for use of the lateral distance y for the establishment of standard profiles for the lateral radio noise field emanating from HV overhead power lines.

The technical data given in this Part 1 of the CISPR 18 series are intended to be a useful aid to overhead line designers and also to anyone concerned with checking the radio noise performance of a line to ensure satisfactory protection of wanted radio signals. The data should facilitate the use of the recommendations given in its Parts 2 and 3 dealing with

- methods of measurement and procedures for determining limits, and a
- code of practice for minimizing the generation of radio noise.

The CISPR 18 series does not deal with biological effects on living matter or any issues related to exposure to electromagnetic fields.

This document has been prepared in order to provide information on the many factors involved in protecting the reception of radio, especially (but not limited to) analogue television, and digital terrestrial television broadcasting, hereafter denominated as digital television broadcasting, from interference due to background noise generated by AC and DC high voltage overhead power lines, distribution lines, and associated equipment. The information given should be of assistance when means of avoiding or abating radio noise are being considered.

Information is mainly given on the generation and characteristics of radio noise from AC power lines and equipment operating at 1 kV and above, in the frequency ranges 0,15 MHz to 30 MHz (a.m. sound broadcasting), 30 MHz to 300 MHz (f.m. sound broadcasting, analogue television broadcasting) and in the range 470 MHz to 950 MHz (digital television broadcasting). The special aspect of spark discharges due to bad contacts or defects is taken into account. Information is also given on interference due to DC overhead power lines for which corona and interference conditions are different from those of AC power lines. The radio broadcast services mentioned above are examples only and the information in this document relates, in a technology-neutral way, to protection of radio reception in general, for the given frequency ranges.

The general procedure for establishing the limits of the radio noise from overhead power lines and associated equipment is given, together with typical values as examples, and methods of measurement.

The clause on limits for conductor corona, which may occur in normal operation of power lines, concentrates on the low frequency and medium frequency bands as it is only in these bands where ample evidence, based on established practice, is available. Examples of limits to protect radio reception in the frequency band 30 MHz to 300 MHz are not given, as measuring methods and certain other aspects of the problems in this band have not yet been fully resolved. Site measurements and service experience have shown that levels of noise from power lines generated by conductor corona at frequencies higher than 300 MHz are so low that interference is unlikely to be caused to analogue television reception.

Presently, there are no limits for radio noise due to spark discharges, which may occur at bad contacts or on the surface of polluted insulators, to protect radio reception in the UHF band (around 470 MHz to 950 MHz) for digital television broadcasting. The characteristics of spark discharges in the UHF band are not fully understood yet. Furthermore, digital television systems employ error-correction functions, and the true effects of spark discharges to image quality are consequently not quite known.

-8-

The values of limits given as examples are calculated to provide a reasonable degree of protection to the reception of e.g. radio broadcasting at the edges of the recognized service areas of the appropriate transmitters in the a.m. radio frequency bands, in the least favourable conditions likely to be generally encountered. These limits are intended to provide guidance at the planning stage of the line and national standards or other specifications against which the performance of the line may be checked after construction and during its useful life.

Recommendations are made on the design, routing, construction and maintenance of the lines and equipment forming part of the power distribution system to minimize interference and it is hoped that this document will aid other radio services in the consideration of the problems of interference.

RADIO INTERFERENCE CHARACTERISTICS OF OVERHEAD POWER LINES AND HIGH-VOLTAGE EQUIPMENT –

Part 1: Description of phenomena

1 Scope

This part of CISPR 18, which is a Technical Report, applies to radio noise from overhead power lines, associated equipment, and high-voltage equipment which may cause interference to radio reception. The scope of this document includes the causes, measurement and effects of radio interference, design aspects in relation to this interference, methods and examples for establishing limits and prediction of tolerable levels of interference from high voltage overhead power lines and associated equipment, to the reception of radio signals and services.

The frequency range covered is 0,15 MHz to 3 GHz.

Radio frequency interference caused by the pantograph of overhead railway traction systems is not considered in this document.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-161, International Electrotechnical Vocabulary (IEV) – Chapter 161: Electromagnetic compatibility

CISPR 16-1-1, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus

CISPR TR 18-2:___1, Radio interference characteristics of overhead power lines and high-voltage equipment – Part 2: Methods of measurement and procedure for determining limits

ISO IEC Guide 99, International vocabulary of metrology – Basic and general concepts and associated terms (VIM)

NOTE Informative references are listed in the Bibliography.

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-161 and the ISO IEC Guide 99 apply.

¹ Under preparation. Stage at the time of publication: CISPR/RPUB 18-2:2017.