

TECHNICAL REPORT



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

Specification for radio disturbance and immunity measuring apparatus and methods –

Part 4-5: Uncertainties, statistics and limit modelling – Conditions for the use of alternative test methods





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.



TECHNICAL REPORT



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

Specification for radio disturbance and immunity measuring apparatus and methods –

Part 4-5: Uncertainties, statistics and limit modelling – Conditions for the use of alternative test methods

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.100.10; 33.100.20

ISBN 978-2-8322-1047-0

Warning! Make sure that you obtained this publication from an authorized distributor.

REDLINE VERSION



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

Specification for radio disturbance and immunity measuring apparatus and methods –

Part 4-5: Uncertainties, statistics and limit modelling – Conditions for the use of alternative test methods



CONTENTS

1	Scope	8
2	Normative references	8
3	Terms and definitions	8
4	Symbols and abbreviated terms	10
5	Introduction	11
6	Procedure to derive limits for an alternative test method.....	12
6.1	Overview	12
6.2	Select the reference quantity X	17
6.3	Describe the test methods and measurands	18
6.4	Determine the deviations of the measured quantities from the reference quantity	18
6.5	Determine the average values of the deviations	18
6.6	Estimate the standard uncertainties of the test methods	19
6.7	Estimate the expanded uncertainties of the test methods	20
6.8	Calculate the average conversion factor	21
6.9	Verify the calculated values	22
6.10	Apply the conversion	22
7	Measurement-based procedure to derive limits for an alternative test method based on measurement results	22
7.1	General	22
7.2	Application of practical measurement results to determine the conversion factors	23
7.2.1	The conversion factor	23
7.2.2	Estimation of SCU by measurement	24
7.2.3	Applying the conversion factor	24
8	Derivation of limits for the use of reverberation chambers as ATM for radiated disturbance measurements based on a statistical analysis of all essential factors	26
8.1	Conversion factor	26
8.2	Measurement uncertainty	27
	Annex A (informative) Remarks on EUT modelling	29
A.1	Types of EUTs	29
A.2	Application of statistics	29
	Annex B (informative) Examples of application of the test method comparison procedure	30
B.1	Example 1 – Measurements at 3 m-separation in fully anechoic room compared to 10 m-separation measurements on open-area test site	30
B.1.1	Small EUTs without cables	30
B.1.2	Small EUTs with cables	49
B.2	Example 2 – 3 m open-area test site measurements compared to 10 m open-area test site measurements	49
B.2.1	Small EUTs without cables	49
B.2.2	Small EUTs with cables	59
B.3	Example 3 – reverberation chamber measurement results compared to 10 m open-area test site results	59
	Annex C (informative) Example of the application of the test method comparison procedure based on measurement results	60
C.1	General	60

C.2	Measurement of conducted disturbance using CDNEs	60
C.3	Measured disturbance field strength	61
C.4	Conversion factor for the measurement with a CDNE	62
C.4.1	The conversion factor	62
C.4.2	Uncertainty of the conversion factor	63
Annex D	Annex D (informative) Statistical method for conversion of disturbance limits from radiated disturbance established test methods to the RC test method	66
D.1	General	66
D.2	Models for EUT directivity	67
D.3	Results of modelling	68
D.4	Instrumentation uncertainty for radiated disturbance measurement results in an RC	73
D.4.1	Measurand for radiated disturbance measurements using an RC	73
D.4.2	Symbols of input quantities common to all disturbance measurements	73
D.4.3	Symbols of input quantities specific to RC measurements	73
D.4.4	Input quantities to be considered for radiated disturbance measurements using an RC	74
D.4.5	Uncertainty budget for radiated disturbance measurement results using an RC	74
D.4.6	Rationale for the estimates of input quantities for radiated disturbance measurement results using an RC	76
Figure 1	– Overview of quantities to estimate for use in conversion procedure	14
Figure 2	– Overview of limit conversion procedure using estimated quantities	16
Figure B.1	– Example reference quantity	30
Figure B.2	– EUT and antenna set-up for fully anechoic room emission measurement	31
Figure B.3	– EUT and antenna set-up for open-area test site measurement	31
Figure B.4	– Radiation characteristics of elementary radiator (left), and scheme of EUT-model (right)	32
Figure B.5	– Maximum average deviations for 3 m FAR (top) and 10 m OATS (bottom)	35
Figure B.6	– Sample cumulative distribution function	37
Figure B.7	– Uncertainties due to the unknown EUT characteristic for 3 m FAR (top) and 10 m OATS (bottom)	39
Figure B.8	– Expanded uncertainties ($k = 2$) of alternative (3 m FAR, top) and established (10 m OATS, bottom) test methods	43
Figure B.9	– Maximum average conversion factors for different volumes	44
Figure B.10	– Photo (left) and cut-view of simulation model (right) of the specimen EUT	46
Figure B.11	– Deviations of the specimen EUT: 3 m fully anechoic room (top) and 10 m open area test site (bottom)	47
Figure B.12	– Sample FAR measurement	48
Figure B.13	– OATS 10 m limit line converted to FAR 3 m conditions	48
Figure B.14	– Expanded uncertainties	48
Figure B.15	– Comparison of the measured values with the corrected converted limit	49
Figure B.16	– EUT and antenna set-up of 3 m open area test site measurement	50
Figure B.17	– Maximum average deviations for 3 m OATS	51
Figure B.18	– Uncertainties due to the unknown EUT characteristic for 3 m OATS	52
Figure B.19	– Expanded uncertainties ($k = 2$) of alternative test method [OATS (3 m)]	54
Figure B.20	– Maximum average conversion factors	55

Figure B.21 – Deviations of the specimen EUT: Open area test site (3 m).....	57
Figure B.22 – Sample OATS (3 m) measurement.....	58
Figure B.23 – OATS (10 m) limit line converted to OATS (3 m) conditions	58
Figure B.24 – Expanded uncertainties.....	59
Figure B.25 – Comparison of the corrected values with the converted limit	59
Figure C.1 – EUTs used during RRT	60
Figure C.2 – Measurement results of the asymmetrical voltage using both CDNEs	61
Figure C.3 – Measured disturbance field strength	62
Figure C.4 – Conversion factors of all measurements	63
Figure C.5 – Mean conversion factors for each EUT	63
Figure C.6 – Measured polarization	63
Figure C.7 – Comparison with CISPR 15:2013.....	63
Figure C.8 – Deviation of the conversion factors from the average conversion factor of each EUT.....	64
Figure C.9 – Deviation of the conversion factors from the trend line [poly (mean value $K(f)$)].....	64
Figure D.1 – Simulated radiation pattern of an electrically large emitter (50 cm radius, $ka = 10,5$ at 1 GHz) in a single plane (X-plane) (Wilson [17])	66
Figure D.2 – Comparison of different expressions for maximum directivity of antennas and unintentional emitters as a function of electrical size ka . μ is the polarization mismatch factor	68
Figure D.3 – Conversion factors (mean and quantile values) from OATS/SAC (measurement distance of 10 m) results to RC results and different radii a of the surrounding sphere as a function of frequency.....	69
Figure D.4 – Conversion factors (mean and quantile values) from FSOATS/FAR ($d = 3$ m measurement distance) results to RC results and different radii a of the surrounding sphere as a function of frequency	71
Figure D.5 – Conversion factor (mean and quantile values) from FSOATS/FAR results to RC results for $d = 3$ m measurement distance as a function of electrical EUT size ka	72
Figure D.6 – Deviation of the QP detector level indication from the signal level at receiver input for two cases: sine-wave signal, and impulsive signal (PRF 100 Hz).....	78
Figure D.7 – Deviation of the peak detector level indication from the signal level at receiver input for two cases: sine-wave signal, and impulsive signal (PRF 100 Hz).....	79
Table 1 – Summary of steps in conversion procedure	12
Table 2 – Overview of quantities and defining equations for conversion process.....	17
Table B.1 – Instrumentation uncertainty of the 3 m fully anechoic chamber test method	36
Table B.2 – Uncertainties in dB due to the unknown EUT characteristic for 3 m FAR	41
Table B.3 – Uncertainties in dB due to the unknown EUT characteristic for 10 m OATS.....	42
Table B.4 – Maximum average conversion factors in dB between 10 m OATS and 3 m FAR	45
Table B.5 – Uncertainties in dB due to the unknown EUT characteristic for 3 m OATS.....	53
Figure B.20 – Maximum average conversion factors Table B.6 – Maximum average conversion factors in dB between 10 m and 3 m OATS	55
Table D.1 – Overview of EUT diameters ($= 2a$) at the transition from electrically small to electrically large (from [17])	67
Table D.2 – Conversion factors (mean, quantile values, and standard deviation σ) for $a = 0,1$ m	69

Table D.3 – Conversion factors (mean, quantile values, and standard deviation σ) for $a = 0,75$ m	70
Table D.4 – Conversion factors (mean, quantile values, and standard deviation σ) for $a = 2,5$ m	70
Table D.5 – Example of disturbance limits for $a = 0,75$ m (EUT diameter 1,5 m) for the residential environment.....	70
Table D.6 – Conversion factors (mean, quantile values, and standard deviation σ) for $a = 0,1$ m	71
Table D.7 – Conversion factors (mean, quantile values, and standard deviation σ) for $a = 0,75$ m	71
Table D.8 – Conversion factors (mean, quantile values, and standard deviation σ) for $a = 2,5$ m	72
Table D.9 – Example of disturbance limits for $a = 0,75$ m (EUT diameter 1,5 m) for the residential environment.....	72
Table D.10 – Comparison of $K_{lin\ mean}(f)$ and $K_{log\ mean}(f)$ for the conversion of OATS/SAC ($d = 10$ m) results to RC results for $a = 0,75$ m	73
Table D.11 – Comparison of $K_{lin\ mean}(f)$ and $K_{log\ mean}(f)$ for the conversion of FOATS/FAR ($d = 3$ m) results to RC results for $a = 0,75$ m	73
Table D.12 – Uncertainty budget for radiated disturbance measurement results using an RC from 80 MHz to 1 000 MHz (example)	75
Table D.13 – Uncertainty budget for radiated disturbance measurement results using an RC from 1 GHz to 6 GHz (example)	75
Table D.14 – Values of P_{lim} for 30 MHz to 1 000 MHz (E_{lim} from [20])	78
Table D.15 – Values of P_{lim} for 1 GHz to 6 GHz (E_{lim} from [20])	78

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**SPECIFICATION FOR RADIO DISTURBANCE
AND IMMUNITY MEASURING APPARATUS AND METHODS –****Part 4-5: Uncertainties, statistics and limit modelling –
Conditions for the use of alternative test methods**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendments has been prepared for user convenience.

CISPR TR 16-4-5 edition 1.2 contains the first edition (2006-10) [documents CISPR/A/665/DTR and CISPR/A/685/RVC], its amendment 1 (2014-07) [documents CISPR/A/1050/DTR and CISPR/A/1069/RVC] and its amendment 2 (2021-10) [documents CIS/A/1321/DTR and CIS/A/1324/RVDTR].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendments 1 and 2. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

CISPR 16-4-5, which is a technical report, has been prepared by CISPR subcommittee A: Radio-interference measurements and statistical methods.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the CISPR 16-4 series, published under the general title *Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainties, statistics and limit modelling*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY MEASURING APPARATUS AND METHODS –

Part 4-5: Uncertainties, statistics and limit modelling – Conditions for the use of alternative test methods

1 Scope

This part of CISPR 16-4 specifies a method to enable product committees to develop limits for alternative test methods, using conversions from established limits. This method is generally applicable for all kinds of disturbance measurements, but focuses on radiated disturbance measurements (i.e. field strength and total radiated power), for which several alternative methods are presently specified. These limits development methods are intended for use by product committees and other groups responsible for defining emissions limits in situations where it is decided to use alternative test methods and the associated limits in product standards.

2 Normative references

IEC 60050-161:1990, *International Electrotechnical Vocabulary (IEV) – Chapter 161: Electromagnetic compatibility*

CISPR 16-1-1:2019, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*

~~CISPR 16-4-1:2003, Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-1: Uncertainties, statistics and limit modelling – Uncertainty in standardized EMC tests~~

CISPR 16-4-2:2003/2011, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modelling –~~Uncertainty in EMC measurements~~ Measurement instrumentation uncertainty*

CISPR 16-4-2:2011/AMD1:2014

CISPR 16-4-2:2011/AMD2:2018

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-161 and the following apply.

3.1

established test method

test method described in a basic standard with established emissions limits defined in corresponding product or generic standards. An established test method consists of a specific test procedure, a specific test set-up, a specific test facility or site, and an established emissions limit

NOTE The following test methods have been considered to be established test methods in CISPR:

- conducted disturbance measurements at mains ports using an AMN in the frequency range 9 kHz to 30 MHz; ~~test~~ this method is defined in CISPR 16-2-1:2003, Clause 7;
- radiated disturbance measurements ~~up~~ in the frequency range 30 MHz to 1 GHz at 10 m distance on an OATS or in a SAC; ~~the test~~ this method is defined in CISPR 16-2-3:7.2.1;