

CONTENTS

INTRODUCTION.....	4
1 Scope and object.....	5
2 Normative references.....	6
3 Terms and definitions	6
4 Conditions during testing.....	7
5 Product documentation	8
6 Applicability	8
7 Emission requirements	8
8 Application of limits in tests for conformity of equipment in series production.....	8
9 Measurement uncertainty.....	9
Annex ZA (normative) Normative references to international publications with their corresponding European publications.....	12
Annex ZZ (informative) Coverage of Essential Requirements of EC Directives.....	13
Bibliography.....	11
Figure 1 – Examples of ports.....	6
Table 1 – Emission.....	10

INTRODUCTION

IEC 61000 is published in separate parts according to the following structure:

Part 1: General

General considerations (introduction, fundamental principles)
Definitions, terminology

Part 2: Environment

Description of the environment
Classification of the environment
Compatibility levels

Part 3: Limits

Emission limits
Immunity limits (insofar as they do not fall under the responsibility of the product committees)

Part 4: Testing and measurement techniques

Measurement techniques
Testing techniques

Part 5: Installation and mitigation guidelines

Installation guidelines
Mitigation methods and devices

Part 6: Generic standards

Part 9: Miscellaneous

Each part is further subdivided into several parts published either as International Standards or technical reports/specifications, some of which have already been published as sections. Others will be published with the part number followed by a dash and a second number identifying the subdivision (example: 61000-6-1).

ELECTROMAGNETIC COMPATIBILITY (EMC) –

Part 6-4: Generic standards – Emission standard for industrial environments

1 Scope and object

This part of IEC 61000 for EMC emission requirements applies to electrical and electronic apparatus intended for use in industrial environments as described below.

Emission requirements in the frequency range 0 Hz to 400 GHz are covered. No measurement needs to be performed at frequencies where no requirement is specified.

This generic EMC emission standard is applicable if no relevant dedicated product or product-family EMC emission standard exists.

This standard applies to a apparatus intended to be connected to a power network supplied from a high or medium voltage transformer dedicated to the supply of an installation feeding manufacturing or similar plant, and intended to operate in or in proximity to industrial locations, as described below. This standard applies also to apparatus, which is battery operated and intended to be used in industrial locations.

The environments encompassed by this standard are industrial, both indoor and outdoor.

Industrial locations are in addition characterised by the existence of one or more of the following examples:

- industrial, scientific and medical (ISM)¹⁾ apparatus;
- heavy inductive or capacitive loads that are frequently switched;
- high currents and associated magnetic fields.

The object of this standard is to define the emission test requirements for apparatus defined in the scope in relation to continuous and transient, conducted and radiated disturbances.

The emission requirements have been selected so as to ensure that disturbances generated by apparatus operating normally in industrial locations do not exceed a level that could prevent other apparatus from operating as intended. Fault conditions of apparatus are not taken into account. Not all disturbance phenomena have been included for testing purposes in this standard but only those considered as relevant for the equipment covered by this standard. These requirements represent essential electromagnetic compatibility emission requirements.

Requirements are specified for each port considered.

NOTE 1 Safety considerations are not covered by this standard.

NOTE 2 In special cases, situations will arise where the levels specified in this standard will not offer adequate protection; for example where a sensitive receiver is used in close proximity to an apparatus. In these instances, special mitigation measures may have to be employed.

¹⁾ As defined in CISPR 11.