

ETSI TS 136 306 V12.6.0 (2015-10)



**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio access capabilities
(3GPP TS 36.306 version 12.6.0 Release 12)**



Reference

RTS/TSGR-0236306vc60

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	8
1 Scope	9
2 References	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols.....	10
3.3 Abbreviations	10
4 UE radio access capability parameters	11
4.1 ue-Category	12
4.1A ue-CategoryDL and ue-CategoryUL	14
4.1B ue-CategorySL-C and ue-CategorySL-D	18
4.2 Parameters set by the field ue-Category and ue-CategoryDL / ue-CategoryUL	19
4.2.1 Transport channel parameters in downlink	19
4.2.1.1 Maximum number of DL-SCH transport block bits received within a TTI	19
4.2.1.2 Maximum number of bits of a DL-SCH transport block received within a TTI	19
4.2.1.3 Total number of DL-SCH soft channel bits	19
4.2.1.4 Maximum number of bits of a MCH transport block received within a TTI	19
4.2.2 Transport channel parameters in uplink.....	19
4.2.2.1 Maximum number of bits of an UL-SCH transport block transmitted within a TTI.....	19
4.2.2.2 Maximum number of UL-SCH transport block bits transmitted within a TTI.....	19
4.2.3 Physical channel parameters in downlink (DL).....	20
4.2.3.1 Maximum number of supported layers for spatial multiplexing in DL.....	20
4.2.4 Physical channel parameters in uplink (UL).....	20
4.2.4.1 Support for 64QAM in UL.....	20
4.2.5 Total layer 2 buffer size	20
4.2.6 Half-duplex FDD operation type	20
4.2A Parameters set by ue-CategorySL-C / ue-CategorySL-D.....	20
4.2A.1 Transport channel parameters in sidelink (SL)	20
4.2A.1.1 Maximum number of SL-SCH transport block bits received within a TTI.....	20
4.2A.1.2 Maximum number of bits of a SL-SCH transport block received within a TTI.....	20
4.2A.1.3 Maximum number of SL-DCH transport block bits received within a TTI.....	20
4.2A.1.4 Maximum number of bits of a SL-DCH transport block received within a TTI.....	20
4.2A.1.5 Maximum number of bits of a SL-SCH transport block transmitted within a TTI	21
4.2A.1.6 Maximum number of SL-SCH transport block bits transmitted within a TTI	21
4.2A.1.7 Maximum number of bits of a SL-DCH transport block transmitted within a TTI.....	21
4.2A.1.8 Maximum number of SL-DCH transport block bits transmitted within a TTI.....	21
4.2A.2 Physical channel parameters in sidelink (SL)	21
4.2A.2.1 Maximum number of supported layers for spatial multiplexing in SL-C	21
4.2A.2.2 Maximum number of supported layers for spatial multiplexing in SL-D	21
4.3 Parameters independent of the field <i>ue-Category</i> and <i>ue-CategoryDL / ue-CategoryUL</i>	21
4.3.1 PDCP Parameters.....	21
4.3.1.1 supportedROHC-Profiles	21
4.3.1.2 maxNumberROHC-ContextSessions	22
4.3.1.3 pdcp-SN-Extension	22
4.3.1.4 supportRohcContextContinue	22
4.3.2 RLC parameters	22
4.3.2.1 Void.....	22
4.3.2.2 extended-RLC-LI-Field-r12	22
4.3.3 Void	22
4.3.4 Physical layer parameters	22

4.3.4.1	ue-TxAntennaSelectionSupported	22
4.3.4.2	ue-SpecificRefSigsSupported.....	22
4.3.4.3	Void.....	22
4.3.4.4	enhancedDualLayerFDD.....	22
4.3.4.5	enhancedDualLayerTDD	22
4.3.4.6	supportedMIMO-CapabilityUL-r10.....	23
4.3.4.7	supportedMIMO-CapabilityDL-r10.....	23
4.3.4.8	two-AntennaPortsForPUCCH-r10	23
4.3.4.9	tm9-With-8Tx-FDD-r10	23
4.3.4.10	pmi-Disabling-r10.....	23
4.3.4.11	crossCarrierScheduling-r10.....	23
4.3.4.12	simultaneousPUCCH-PUSCH-r10.....	23
4.3.4.13	multiClusterPUSCH-WithinCC-r10.....	23
4.3.4.14	nonContiguousUL-RA-WithinCC-Info-r10.....	24
4.3.4.15	crs-InterfHandl-r11	24
4.3.4.16	Void.....	24
4.3.4.17	Void.....	24
4.3.4.18	ePDCCH-r11.....	24
4.3.4.19	multiACK-CSI-Reporting-r11	24
4.3.4.20	ss-CCH-InterfHandl-r11	24
4.3.4.21	tdd-SpecialSubframe-r11	24
4.3.4.22	txDiv-PUCCH1b-ChSelect-r11.....	24
4.3.4.23	ul-CoMP-r11	24
4.3.4.24	<i>tm5-FDD</i>	24
4.3.4.25	<i>tm5-TDD</i>	24
4.3.4.26	interBandTDD-CA-WithDifferentConfig-r11	25
4.3.4.27	e-HARQ-Pattern-FDD-r12.....	25
4.3.4.28	tdd-FDD-CA-PCellDuplex-r12.....	25
4.3.4.29	csi-SubframeSet-r12.....	25
4.3.4.30	phy-TDD-ReConfig-FDDPCell-r12.....	25
4.3.4.31	phy-TDD-ReConfig-TDDPCell-r12	25
4.3.4.32	pusch-SRS-PowerControl-SubframeSet-r12.....	25
4.3.4.33	enhanced-4TxCodebook-r12.....	25
4.3.4.34	pusch-FeedbackMode-r12.....	25
4.3.4.35	naics-Capability-List-r12	25
4.3.4.36	noResourceRestrictionForTTIBundling-r12	26
4.3.4.37	Void.....	26
4.3.4.38	discoverySignalsInDeactSCell-r12	26
4.3.4.39	ul-64QAM-r12	26
4.3.4.40	supportedMIMO-CapabilityDL-r12.....	26
4.3.5	RF parameters	26
4.3.5.1	supportedBandListEUTRA	26
4.3.5.2	supportedBandCombination.....	26
4.3.5.3	multipleTimingAdvance	27
4.3.5.4	simultaneousRx-Tx	27
4.3.5.5	supportedCSI-Proc-r11	27
4.3.5.6	freqBandRetrieval-r11.....	27
4.3.5.7	dl-256QAM-r12	27
4.3.5.8	supportedNAICS-2CRS-AP-r12	27
4.3.5.9	dc-Support-r12	28
4.3.5.9.1	asynchronous-r12	28
4.3.5.10	modifiedMPR-Behavior-r10	28
4.3.5.11	freqBandPriorityAdjustment-r12	28
4.3.5.12	commSupportedBandsPerBC-r12	28
4.3.5.13	supportedCSI-Proc-r12	28
4.3.5.14	fourLayerTM3-TM4-r10.....	28
4.3.5.15	fourLayerTM3-TM4-perCC-r12	28
4.3.6	Measurement parameters	28
4.3.6.1	interFreqNeedForGaps and interRAT-NeedForGaps.....	28
4.3.6.2	rsrqMeasWideband	29
4.3.6.3	timerT312-r12.....	29
4.3.6.4	alternativeTimeToTrigger-r12	29

4.3.6.5	benefitsFromInterruption-r11	29
4.3.6.6	incMonEUTRA-r12	29
4.3.6.7	incMonUTRA-r12	29
4.3.6.8	extendedMaxMeasId-r12	29
4.3.6.9	crs-DiscoverySignalsMeas-r12	29
4.3.6.10	csi-RS-DiscoverySignalsMeas-r12	29
4.3.6.11	extendedRSRQ-LowerRange-r12	29
4.3.6.12	rsrqOnAllSymbols-r12	30
4.3.7	Inter-RAT parameters	30
4.3.7.1	Support of UTRA FDD	30
4.3.7.2	supportedBandListUTRA-FDD	30
4.3.7.3	Support of UTRA TDD 1.28 Mcps	30
4.3.7.4	supportedBandListUTRA-TDD128	30
4.3.7.5	Support of UTRA TDD 3.84 Mcps	30
4.3.7.6	supportedBandListUTRA-TDD384	30
4.3.7.7	Support of UTRA TDD 7.68 Mcps	30
4.3.7.8	supportedBandListUTRA-TDD768	30
4.3.7.9	Support of GERAN	30
4.3.7.10	supportedBandListGERAN	31
4.3.7.11	interRAT-PS-HO-ToGERAN	31
4.3.7.12	Support of HRPD	31
4.3.7.13	supportedBandListHRPD	31
4.3.7.14	tx-ConfigHRPD	31
4.3.7.15	rx-ConfigHRPD	31
4.3.7.16	Support of 1xRTT	31
4.3.7.17	supportedBandList1XRTT	31
4.3.7.18	tx-Config1XRTT	31
4.3.7.19	rx-Config1XRTT	31
4.3.7.20	e-CSFB-1XRTT	31
4.3.7.21	e-CSFB-ConcPS-Mob1XRTT	31
4.3.7.22	e-RedirectionUTRA	32
4.3.7.23	e-RedirectionGERAN	32
4.3.7.24	<i>dtm</i>	32
4.3.7.25	e-CSFB-dual-1XRTT	32
4.3.7.26	e-RedirectionUTRA-TDD	32
4.3.7.27	cdma2000-NW-Sharing-r11	32
4.3.7.28	<i>mfb</i> -UTRA	32
4.3.8	General parameters	32
4.3.8.1	accessStratumRelease	32
4.3.8.2	deviceType	32
4.3.9	Void	32
4.3.10	CSG Proximity Indication parameters	32
4.3.10.1	intraFreqProximityIndication	32
4.3.10.2	interFreqProximityIndication	33
4.3.10.3	utran-ProximityIndication	33
4.3.11	Neighbour cell SI acquisition parameters	33
4.3.11.1	intraFreqSI-AcquisitionForHO	33
4.3.11.2	interFreqSI-AcquisitionForHO	33
4.3.11.3	utran-SI-AcquisitionForHO	33
4.3.12	SON parameters	33
4.3.12.1	rach-Report	33
4.3.13	UE-based network performance measurement parameters	33
4.3.13.1	loggedMeasurementsIdle	33
4.3.13.2	standaloneGNSS-Location	33
4.3.13.3	Void	33
4.3.13.4	loggedMBSFNMeasurements-r12	33
4.3.14	IMS Voice parameters	34
4.3.14.1	voiceOver-PS-HS-UTRA-FDD	34
4.3.14.2	voiceOver-PS-HS-UTRA-TDD128	34
4.3.14.3	srvcc-FromUTRA-FDD-ToGERAN	34
4.3.14.4	srvcc-FromUTRA-FDD-ToUTRA-FDD	34
4.3.14.5	srvcc-FromUTRA-TDD128-ToGERAN	34

4.3.14.6	srvcc-FromUTRA-TDD128-ToUTRA-TDD128	34
4.3.15	Other parameters	34
4.3.15.1	Void	34
4.3.15.2	inDeviceCoexInd-r11	34
4.3.15.3	powerPrefInd-r11	34
4.3.15.4	ue-Rx-TxTimeDiffMeasurements-r11	34
4.3.15.5	Void	35
4.3.15.6	Void	35
4.3.15.7	Void	35
4.3.15.8	inDeviceCoexInd-UL-CA-r11	35
4.3.16	Positioning parameters	35
4.3.16.1	otdoa-UE-assisted	35
4.3.16.2	interFreqRSTDmeasurement	35
4.3.17	MBMS parameters	35
4.3.17.1	mbms-SCell-r11	35
4.3.17.2	mbms-NonServingCell-r11	35
4.3.17.3	mbms-AsyncDC-r12	35
4.3.18	RAN-assisted WLAN interworking parameters	35
4.3.18.1	wlan-IW-RAN-Rules-r12	35
4.3.18.2	wlan-IW-ANDSF-Policies-r12	36
4.3.19	MAC parameters	36
4.3.19.1	longDRX-Command-r12	36
4.3.19.2	logicalChannelSR-ProhibitTimer-r12	36
4.3.20	Dual Connectivity parameters	36
4.3.20.1	drb-TypeSplit-r12	36
4.3.20.2	drb-TypeSCG-r12	36
4.3.21	Sidelink parameters	36
4.3.21.1	commSupportedBands-r12	36
4.3.21.2	commSimultaneousTx-r12	36
4.3.21.3	discSupportedBands-r12	36
4.3.21.4	discScheduledResourceAlloc-r12	36
4.3.21.5	disc-UE-SelectedResourceAlloc-r12	37
4.3.21.6	disc-SLSS-r12	37
4.3.21.7	discSupportedProc-r12	37
5	Void	37
6	Optional features without UE radio access capability parameters	37
6.1	CSG features	37
6.2	PWS features	37
6.2.1	ETWS	37
6.2.2	CMAS	37
6.2.3	KPAS	37
6.2.4	EU-Alert	38
6.3	MBMS features	38
6.3.1	MBMS Service Continuity	38
6.3.2	MBMS reception with 256QAM	38
6.4	Void	38
6.5	Positioning features	38
6.5.0	Void	38
6.5.1	Void	38
6.6	UE receiver features	38
6.6.1	MMSE with IRC receiver	38
6.6.2	MMSE with IRC receiver for PDSCH transmission mode 9	38
6.7	RRC Connection	38
6.7.1	RRC Connection Reject with deprioritisation	38
6.7.2	RRC Connection Establishment Failure Temporary Qoffset	38
6.8	Other features	39
6.8.1	System Information Block Type 16	39
6.9	Void	39
6.10	SON features	39
6.10.1	Radio Link Failure Report for inter-RAT MRO	39

6.11	Mobility state features	39
6.11.1	Mobility history information storage	39
7	Conditionally Mandatory features	39
7.1	Access control features	39
7.1.1	SSAC	39
7.1.2	CSFB Access Barring Control	39
7.1.3	Extended Access Barring	39
7.2	Emergency call features	39
7.2.1	IMS emergency call	39
7.3	MAC features	40
7.3.1	SR mask	40
7.3.2	Power Management Indicator in PHR	40
7.4	Inter-RAT Mobility features	40
7.4.1	High Priority CSFB redirection	40
7.4.2	GERAN A/Gb mode to E-UTRAN Inter RAT handover (PS Handover)	40
7.4.3	SRVCC to E-UTRAN from GERAN	40
7.5	Delay Tolerant Access Features	40
7.5.1	extendedWaitTime	40
7.6	RRC Connection	40
7.6.1	Void	40
7.7	Physical layer features	41
7.7.1	Different UL/ DL configuration for TDD inter-band carrier aggregation	41
7.7.2	Full duplex for TDD and FDD carrier aggregation	41
7.8	Positioning features	41
7.8.1	OTDOA Inter-frequency RSTD measurement indication	41
7.9	Void	41
7.9.1	Void	41
Annex A (informative):	 Guideline on maximum number of DL PDCP SDUs per TTI	42
Annex B (informative):	 Change history	43
History		46

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document defines the E-UTRA UE Radio Access Capability Parameters.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 36.323: "Evolved Universal Terrestrial Radio Access (E-UTRA) Packet Data Convergence Protocol (PDCP) specification".
- [3] 3GPP TS 36.322: "Evolved Universal Terrestrial Radio Access (E-UTRA) Radio Link Control (RLC) specification".
- [4] 3GPP TS 36.321: "Evolved Universal Terrestrial Radio Access (E-UTRA) Medium Access Control (MAC) specification".
- [5] 3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA) Radio Resource Control (RRC) specification".
- [6] 3GPP TS 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA) radio transmission and reception".
- [7] IETF RFC 4995: "The RObust Header Compression (ROHC) Framework".
- [8] IETF RFC 4996: "RObust Header Compression (ROHC): A Profile for TCP/IP (ROHC-TCP)".
- [9] IETF RFC 3095: "RObust Header Compression (RoHC): Framework and four profiles: RTP, UDP, ESP and uncompressed".
- [10] IETF RFC 3843: "RObust Header Compression (RoHC): A Compression Profile for IP".
- [11] IETF RFC 4815: "RObust Header Compression (ROHC): Corrections and Clarifications to RFC 3095".
- [12] IETF RFC 5225: "RObust Header Compression (ROHC) Version 2: Profiles for RTP, UDP, IP, ESP and UDP Lite".
- [13] 3GPP TS 36.355: "Evolved Universal Terrestrial Radio Access (E-UTRA) LTE Positioning Protocol (LPP)".
- [14] 3GPP TS 36.304: "Evolved Universal Terrestrial Radio Access (E-UTRA); UE Procedures in Idle Mode".
- [15] 3GPP TS 37.320: "Universal Terrestrial Radio Access (UTRA) and Evolved Universal Terrestrial Radio Access (E-UTRA); Radio measurement collection for Minimization of Drive Tests (MDT); Overall description; Stage 2".
- [16] 3GPP TS 36.133: "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for support of radio resource management".