

---

---

**Intelligent transport systems - Traffic  
and travel information (TTI) via  
transport protocol experts group,  
generation 2 (TPEG2) —**

**Part 23:  
Roads and multimodal routes  
(TPEG2-RMR)**

*Systèmes intelligents de transport — Informations sur le trafic et le  
tourisme via le groupe expert du protocole de transport, génération 2  
(TPEG2) —*

*Partie 23: Routes et routes multimodales (TPEG2-RMR)*



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

# Contents

Page

<b>Foreword</b> .....	<b>v</b>
<b>Introduction</b> .....	<b>vi</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Abbreviated terms</b> .....	<b>2</b>
<b>5 Application specific constraints</b> .....	<b>3</b>
5.1 Application identification.....	3
5.2 Version number signalling.....	3
5.3 Ordered components.....	3
5.4 Extendibility.....	4
5.5 TPEG Service Component Frame.....	4
<b>6 RMR structure</b> .....	<b>4</b>
6.1 Message structure.....	4
6.2 Scenarios, features and requirements.....	6
6.2.1 General.....	6
6.2.2 Broadcast scenario.....	6
6.2.3 P2P scenario.....	6
<b>7 RMR Message components</b> .....	<b>8</b>
7.1 RMRMessage.....	8
7.2 Route.....	9
7.3 RouteSegment.....	10
7.4 Parking.....	11
7.5 SegmentLocation.....	11
7.6 PointLocation.....	12
7.7 SegmentDetails.....	12
7.8 RoadTravelDetails.....	12
7.9 PTTravelDetails.....	12
7.10 PedestrianTravelDetails.....	13
7.11 RMRRequestMessage.....	13
7.12 RMRReqParams.....	13
7.13 RMRListReqParams.....	13
7.14 RMRRouteReqParams.....	14
7.15 RMRActivateRouteReqParams.....	14
7.16 TerminateRMRSession.....	15
7.17 RoutePreferences.....	15
7.18 MessageManagementContainerLink.....	15
7.19 RMRLocRef.....	15
7.20 LocationReferencingContainerLink.....	16
7.21 MMCLinkReq.....	16
<b>8 RMR datatypes</b> .....	<b>16</b>
8.1 EnergyConsumption.....	16
8.2 Operator.....	16
8.3 PredefConnection.....	17
8.4 WGS84Coordinate.....	17
8.5 MessageLink.....	17
<b>9 RMR Tables</b> .....	<b>18</b>
9.1 rmr001:RouteType.....	18
9.2 rmr002:ModeType.....	18
9.3 rmr003:ParkType.....	19
9.4 rmr005:RouteObjectives.....	19

9.5	rmr006:RouteCause .....	20
9.6	rmr007:AccessType.....	20
9.7	rmr008:OccTendency.....	20
9.8	rmr009:EnergyType.....	21
9.9	rmr099:ErrorCode.....	21
<b>Annex A (normative) TPEG application — TPEG-Binary Representation .....</b>		<b>22</b>
<b>Annex B (normative) TPEG application — TPEG-ML Representation .....</b>		<b>33</b>
<b>Bibliography .....</b>		<b>43</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 204, *Intelligent transport systems*.

A list of all the parts in the ISO 21219 series, can be found on the ISO website.

## Introduction

### History

TPEG technology was originally proposed by the European Broadcasting Union (EBU) Broadcast Management Committee, who established the B/TPEG project group in the autumn of 1997 with a brief to develop, as soon as possible, a new protocol for broadcasting traffic and travel-related information in the multimedia environment. TPEG technology, its applications and service features were designed to enable travel-related messages to be coded, decoded, filtered and understood by humans (visually and/or audibly in the user's language) and by agent systems. Originally, a byte-oriented data stream format, which may be carried on almost any digital bearer with an appropriate adaptation layer, was developed. Hierarchically structured TPEG messages from service providers to end-users were designed to transfer information from the service provider database to an end-user's equipment.

One year later, in December 1998, the B/TPEG group produced its first EBU specifications. Two documents were released. Part 2 (TPEG-SSF, which became ISO/TS 18234-2) described the Syntax, Semantics and Framing structure, which was used for all TPEG applications. Meanwhile, Part 4 (TPEG-RTM, which became ISO/TS 18234-4) described the first application for Road Traffic Messages.

Subsequently, in March 1999, CEN/TC 278, in conjunction with ISO/TC 204, established a group comprising members of the former EBU B/TPEG and this working group continued development work. Further parts were developed to make the initial set of four parts enabling the implementation of a consistent service. Part 3 (TPEG-SNI, ISO/TS 18234-3) described the Service and Network Information Application used by all service implementations to ensure appropriate referencing from one service source to another.

Part 1 (TPEG-INV, ISO/TS 18234-1) completed the series by describing the other parts and their relationship; it also contained the application IDs used within the other parts. Additionally, Part 5, the Public Transport Information Application (TPEG-PTI, ISO/TS 18234-5), was developed. The so-called TPEG-LOC Location Referencing method, which enabled both map-based TPEG-decoders and non-map-based ones to deliver either map-based Location Referencing or human readable text information, was issued as ISO/TS 18234-6 to be used in association with the other applications parts of the ISO/TS 18234- series to provide Location Referencing.

The ISO/TS 18234- series has become known as TPEG Generation 1.

### TPEG Generation 2

When the Traveller Information Services Association (TISA), derived from former forums, was inaugurated in December 2007, TPEG development was taken over by TISA and continued in the TPEG applications working group.

It was about this time that the (then) new Unified Modelling Language (UML) was seen as having major advantages for the development of new TPEG Applications in communities who would not necessarily have binary physical format skills required to extend the original TPEG TS work. It was also realized that the XML format for TPEG described within the ISO/TS 24530- series (now superseded) had a greater significance than previously foreseen, especially in the content-generation segment and that keeping two physical formats in synchronism, in different standards series, would be rather difficult.

As a result, TISA set about the development of a new TPEG structure that would be UML based. This has subsequently become known as TPEG Generation 2.

TPEG2 is embodied in the ISO/TS 21219- series and it comprises many parts that cover introduction, rules, toolkit and application components. TPEG2 is built around UML modelling and has a core of rules that contain the modelling strategy covered in ISO/TS 21219-2, ISO/TS 21219-3, ISO/TS 21219-4 and the conversion to two current physical formats: binary and XML; others could be added in the future. TISA uses an automated tool to convert from the agreed UML model XMI file directly into an MS Word document file, to minimize drafting errors, that forms the Annex for each physical format.

TPEG2 has a three container conceptual structure: Message Management (ISO/TS 21219-6), Application (several Parts) and Location Referencing (ISO/TS 21219-7<sup>1</sup>). This structure has flexible capability and can accommodate many differing use cases that have been proposed within the TTI sector and wider for hierarchical message content.

TPEG2 also has many Location Referencing options as required by the service provider community, any of which may be delivered by vectoring data included in the Location Referencing container.

The following classification provides a helpful grouping of the different TPEG2 parts according to their intended purpose.

- Toolkit parts: TPEG2-INV (ISO/TS 21219-1), TPEG2-UML (ISO/TS 21219-2), TPEG2-UBCR (ISO/TS 21219-3), TPEG2-UXCR (ISO/TS 21219-4), TPEG2-SFW (ISO/TS 21219-5), TPEG2-MMC (ISO/TS 21219-6), TPEG2-LRC (ISO/TS 21219-7), TPEG2-LTE (ISO/TS 21219-24<sup>2</sup>);
- Special applications: TPEG2-SNI (ISO/TS 21219-9), TPEG2-CAI (ISO/TS 21219-10);
- Location Referencing: TPEG2-ULR (ISO/TS 21219-11<sup>3</sup>), TPEG2-GLR (ISO/TS 21219-21<sup>4</sup>), TPEG2-OLR (ISO/TS 21219-22<sup>5</sup>);
- Applications: TPEG2-PKI (ISO/TS 21219-14), TPEG2-TEC (ISO/TS 21219-15), TPEG2-FPI (ISO/TS 21219-16), TPEG2-TFP (ISO/TS 21219-18), TPEG2-WEA (ISO/TS 21219-19), TPEG2-RMR (ISO/TS 21219-23<sup>6</sup>), TPEG2-EMI (ISO/TS 21219-25<sup>7</sup>).

TPEG2 has been developed to be broadly (but not totally) backward compatible with TPEG1 to assist in transitions from earlier implementations, while not hindering the TPEG2 innovative approach and being able to support many new features, such as dealing with applications having both long-term, unchanging content and highly dynamic content, such as Parking Information.

This document is based on the TISA specification technical/editorial version reference:

SP13010/1.0/001

- 
- 1) Under development.
  - 2) To be published.
  - 3) Under development.
  - 4) Under development.
  - 5) Under development.
  - 6) To be published.
  - 7) To be published.





# Intelligent transport systems - Traffic and travel information (TTI) via transport protocol experts group, generation 2 (TPEG2) —

## Part 23: Roads and multimodal routes (TPEG2-RMR)

### 1 Scope

New mobility services like car sharing, car rental or park and ride as well as the integration of different transport modes by multimodal or off-board navigation are gaining increasing importance. Furthermore, the cooperative management of the transport infrastructure requires the provision of precise information and guidance on dedicated routes from a central knowledge base to a traveller's mobile device.

Such use cases are addressed by the TPEG application defined in this document. The Road and Multimodal Routes (RMR) application enables the service provision for road routes as well as multimodal routes including more than one transport mode and parking. For example, an optimal multimodal route may include a drive by car to a train station with parking facility, a train connection to a station nearby the destination and a local public transport ride from the train station to the traveller's destination.

The standardized delivery, via TPEG technology, of routing information has some potential benefits for the users of an RMR TPEG service, for instance:

- Enabling of specialized routing services like scenic routing or Eco routing;
- The best use of the overall transport network, i.e. not only the road network;
- Cost and time savings to traveller;
- Harmonization of in-car navigation and traffic management, e.g. routing advices by variable message signs;
- Personalized service provisioning, i.e. information services considering the specific characteristics of a user.

Some of the use cases above, in particular personalized service, may require a Peer-to-Peer (P2P) communication while others may apply a broadcast communication approach, e.g. city routing.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/TS 18234-11:2013, *Intelligent transport systems — Traffic and Travel Information (TTI) via transport protocol experts group, generation 1 (TPEG1) binary data format — Part 11: Location Referencing Container (TPEG1-LRC)*

ISO/TS 21219-1, *Intelligent transport systems — Traffic and travel information (TTI) via transport protocol experts group, generation 2 (TPEG2) — Part 1: Introduction, numbering and versions (TPEG2-INV)*

ISO/TS 21219-5, *Intelligent transport systems - Traffic and travel information (TTI) via transport protocol experts group, generation 2 (TPEG2) — Part 5: Service framework (TPEG2-SFW)*