



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
General Packet Radio Service (GPRS);
GPRS Tunnelling Protocol (GTP)
across the Gn and Gp interface
(3GPP TS 29.060 version 13.7.0 Release 13)**



Reference

RTS/TSGC-0429060vd70

Keywords

GSM,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	9
1 Scope	10
2 References	10
3 Definitions and abbreviations.....	12
3.1 Definitions	12
3.2 Abbreviations	13
4 General	14
4.1 General Description.....	14
4.2 Removing support for GTPv1 to GTPv0 interworking	16
5 Transmission Order and Bit Definitions.....	16
6 GTP Header.....	16
6.1 Extension headers.....	18
6.1.1 PDCP PDU Number	18
6.1.2 Suspend Request.....	19
6.1.3 Suspend Response	19
6.1.4 MBMS support indication	20
6.1.5 MS Info Change Reporting support indication	20
7 GTP Messages and Message Formats	21
7.1 Message Formats.....	21
7.1.1 Presence requirements of Information Elements	23
7.2 Path Management Messages.....	23
7.2.0 General.....	23
7.2.1 Echo Request	23
7.2.2 Echo Response.....	23
7.2.3 Version Not Supported	24
7.2.4 Supported Extension Headers Notification.....	24
7.3 Tunnel Management Messages	24
7.3.1 Create PDP Context Request	24
7.3.2 Create PDP Context Response.....	28
7.3.3 Update PDP Context Request	32
7.3.4 Update PDP Context Response.....	37
7.3.5 Delete PDP Context Request	41
7.3.6 Delete PDP Context Response.....	43
7.3.7 Error Indication.....	44
7.3.8 PDU Notification Request	44
7.3.9 PDU Notification Response.....	45
7.3.10 PDU Notification Reject Request	46
7.3.11 PDU Notification Reject Response.....	47
7.3.12 Initiate PDP Context Activation Request.....	47
7.3.13 Initiate PDP Context Activation Response	48
7.4 Location Management Messages	49
7.4.0 General.....	49
7.4.1 Send Routeing Information for GPRS Request	49
7.4.2 Send Routeing Information for GPRS Response	50
7.4.3 Failure Report Request	50
7.4.4 Failure Report Response.....	51
7.4.5 Note MS GPRS Present Request	51
7.4.6 Note MS GPRS Present Response	52
7.5 Mobility Management Messages.....	52

7.5.0	General.....	52
7.5.1	Identification Request	52
7.5.2	Identification Response.....	53
7.5.3	SGSN Context Request.....	54
7.5.4	SGSN Context Response	55
7.5.5	SGSN Context Acknowledge	59
7.5.6	Forward Relocation Request.....	60
7.5.7	Forward Relocation Response	64
7.5.8	Forward Relocation Complete	66
7.5.9	Relocation Cancel Request	66
7.5.10	Relocation Cancel Response.....	67
7.5.11	Forward Relocation Complete Acknowledge	67
7.5.12	Forward SRNS Context Acknowledge	68
7.5.13	Forward SRNS Context	68
7.5.14	RAN Information Management Messages.....	68
7.5.14.0	General	68
7.5.14.1	RAN Information Relay	69
7.5.15	UE Registration Query Request.....	69
7.5.16	UE Registration Query Response	69
7.5A	MBMS Messages	70
7.5A.0	General.....	70
7.5A.1	UE Specific MBMS Messages.....	70
7.5A.1.1	MBMS Notification Request.....	70
7.5A.1.2	MBMS Notification Response	71
7.5A.1.3	MBMS Notification Reject Request	71
7.5A.1.4	MBMS Notification Reject Response	72
7.5A.1.5	Create MBMS Context Request.....	73
7.5A.1.6	Create MBMS Context Response	75
7.5A.1.7	Update MBMS Context Request.....	76
7.5A.1.8	Update MBMS Context Response	78
7.5A.1.9	Delete MBMS Context Request.....	79
7.5A.1.10	Delete MBMS Context Response	80
7.5A.2	Service Specific MBMS Messages.....	81
7.5A.2.1	MBMS Registration Request	81
7.5A.2.2	MBMS Registration Response	82
7.5A.2.3	MBMS De-registration Request.....	83
7.5A.2.4	MBMS De-Registration Response	84
7.5A.2.5	MBMS Session Start Request	84
7.5A.2.6	MBMS Session Start Response.....	86
7.5A.2.7	MBMS Session Stop Request	87
7.5A.2.8	MBMS Session Stop Response.....	88
7.5A.2.9	MBMS Session Update Request	88
7.5A.2.10	MBMS Session Update Response.....	89
7.5B.1	MS Info Change Reporting Messages	90
7.5B.1.0	General	90
7.5B.1.1	MS Info Change Notification Request	90
7.5B.1.2	MS Info Change Notification Response.....	92
7.6	Reliable Delivery of Signalling Messages.....	93
7.7	Information Elements	94
7.7.0	General.....	94
7.7.0A	Information Element with an IE Type Extension field	98
7.7.A	Handling ASN.1/PER encoded parameters	98
7.7.1	Cause	98
7.7.2	International Mobile Subscriber Identity (IMSI)	102
7.7.3	Routeing Area Identity (RAI)	103
7.7.4	Temporary Logical Link Identity (TLLI)	103
7.7.5	Packet TMSI (P-TMSI)	103
7.7.6	Reordering Required.....	104
7.7.7	Authentication Triplet.....	104
7.7.8	MAP Cause	104
7.7.9	P-TMSI Signature	105
7.7.10	MS Validated.....	105

7.7.11	Recovery	105
7.7.12	Selection Mode	105
7.7.13	Tunnel Endpoint Identifier Data I.....	106
7.7.14	Tunnel Endpoint Identifier Control Plane.....	106
7.7.15	Tunnel Endpoint Identifier Data II.....	107
7.7.16	Teardown Ind.....	107
7.7.17	NSAPI.....	108
7.7.18	RANAP Cause	108
7.7.19	RAB Context	108
7.7.20	Radio Priority SMS.....	109
7.7.21	Radio Priority.....	109
7.7.22	Packet Flow Id	109
7.7.23	Charging Characteristics.....	110
7.7.24	Trace Reference	110
7.7.25	Trace Type	110
7.7.25A	MS Not Reachable Reason	110
7.7.25B	Radio Priority LCS	111
7.7.26	Charging ID	111
7.7.27	End User Address	111
7.7.28	MM Context.....	114
7.7.29	PDP Context	117
7.7.30	Access Point Name	120
7.7.31	Protocol Configuration Options.....	120
7.7.32	GSN Address	120
7.7.33	MS International PSTN/ISDN Number (MSISDN)	121
7.7.34	Quality of Service (QoS) Profile.....	121
7.7.35	Authentication Quintuplet.....	122
7.7.36	Traffic Flow Template (TFT)	122
7.7.37	Target Identification	123
7.7.38	UTRAN Transparent Container.....	124
7.7.39	RAB Setup Information	124
7.7.40	Extension Header Type List.....	125
7.7.41	Trigger Id.....	125
7.7.42	OMC Identity.....	126
7.7.43	RAN Transparent Container	126
7.7.44	Charging Gateway Address	126
7.7.45	PDP Context Prioritization	127
7.7.45A	Additional RAB Setup Information	127
7.7.46	Private Extension	128
7.7.47	SGSN Number	128
7.7.48	Common Flags.....	129
7.7.49	APN Restriction.....	130
7.7.50	RAT Type	130
7.7.51	User Location Information (ULI)	131
7.7.52	MS Time Zone	132
7.7.53	International Mobile Equipment Identity (and Software Version) (IMEI(SV))	133
7.7.54	CAMEL Charging Information Container	133
7.7.55	MBMS UE Context	134
7.7.56	Temporary Mobile Group Identity.....	135
7.7.57	RIM Routing Address.....	135
7.7.58	MBMS Protocol Configuration Options	136
7.7.59	MBMS Session Duration	136
7.7.60	MBMS Service Area.....	136
7.7.61	Source RNC PDCP context info	136
7.7.62	Additional Trace Info.....	137
7.7.63	Hop Counter.....	137
7.7.64	Selected PLMN ID.....	138
7.7.65	MBMS Session Identifier	138
7.7.66	MBMS 2G/3G Indicator	139
7.7.67	Enhanced NSAPI	139
7.7.68	Additional MBMS Trace Info.....	140
7.7.69	MBMS Session Repetition Number.....	140

7.7.70	MBMS Time To Data Transfer.....	140
7.7.71	(void)	141
7.7.72	BSS Container	141
7.7.73	Cell Identification	141
7.7.74	PDU Numbers.....	142
7.7.75	BSSGP Cause	143
7.7.76	Required MBMS Bearer Capabilities	143
7.7.77	RIM Routing Address Discriminator	143
7.7.78	List of set-up PFCs	143
7.7.79	PS Handover XID Parameters	144
7.7.80	MS Info Change Reporting Action.....	144
7.7.81	Direct Tunnel Flags	145
7.7.82	Correlation-ID.....	145
7.7.83	Bearer Control Mode	146
7.7.84	MBMS Flow Identifier	146
7.7.85	MBMS IP Multicast Distribution.....	146
7.7.86	MBMS Distribution Acknowledgement	147
7.7.87	Reliable INTER RAT HANDOVER INFO.....	147
7.7.88	RFSP Index.....	148
7.7.89	PDP Type.....	148
7.7.90	Fully Qualified Domain Name (FQDN)	148
7.7.91	Evolved Allocation/Retention Priority I	149
7.7.92	Evolved Allocation/Retention Priority II.....	149
7.7.93	Extended Common Flags.....	150
7.7.94	User CSG Information (UCI).....	150
7.7.95	CSG Information Reporting Action.....	151
7.7.96	CSG ID.....	152
7.7.97	CSG Membership Indication (CMI).....	152
7.7.98	APN Aggregate Maximum Bit Rate (APN-AMBR)	152
7.7.99	UE Network Capability	153
7.7.100	UE-AMBR.....	153
7.7.101	APN-AMBR with NSAPI.....	153
7.7.102	GGSN Back-Off Time	154
7.7.103	Signalling Priority Indication.....	154
7.7.104	Signalling Priority Indication with NSAPI	155
7.7.105	Higher bitrates than 16 Mbps flag.....	155
7.7.106	(void)	156
7.7.107	Additional MM context for SRVCC.....	156
7.7.108	Additional flags for SRVCC.....	156
7.7.109	STN-SR	156
7.7.110	C-MSISDN	157
7.7.111	Extended RANAP Cause	157
7.7.112	eNodeB ID.....	157
7.7.114	ULI Timestamp.....	158
7.7.115	Local Home Network ID (LHN-ID) with NSAPI.....	159
7.7.116	CN Operator Selection Entity	159
7.7.117	UE Usage Type.....	159
7.7.118	Extended Common Flags II	160
7.7.119	Node Identifier.....	160
7.7.120	Void	160
7.7.121	Void	160
7.7.122	IOV_updates counter	160
8	Control Plane (GTP-C).....	161
8.1	Control Plane Protocol	161
8.2	Usage of the GTP-C Header.....	161
9	GTP-U	163
9.1	GTP-U Protocol Entity	163
9.1.1	Handling of Sequence Numbers	163
9.2	GTP-U Service Access Points and Primitives	164
9.2.1	GTP-U-CONTROL SAP	164

9.2.1.1	GTP-U-CONTROL-RX primitives	164
9.2.1.1.1	GTP-U-CONTROL-RX-SETUP.request	164
9.2.1.1.2	GTP-U-CONTROL-RX-SETUP.confirm	164
9.2.1.1.3	GTP-U-CONTROL-RX-RELEASE.request	165
9.2.1.1.4	GTP-U-CONTROL-RX-RELEASE.confirm	165
9.2.1.1.5	GTP-U-CONTROL-RX-ERROR.indication	165
9.2.1.2	GTP-U-CONTROL-TX primitives	165
9.2.1.2.1	GTP-U-CONTROL-TX-SETUP.request	165
9.2.1.2.2	GTP-U-CONTROL-TX-SETUP.confirm	165
9.2.1.2.3	GTP-U-CONTROL-TX-RELEASE.request	165
9.2.1.2.4	GTP-U-CONTROL-TX-RELEASE.confirm	165
9.2.1.2.5	GTP-U-CONTROL-TX-ERROR.indication	165
9.2.2	GTP-U-UNIT-DATA SAP and Primitives	165
9.2.2.1	GTP-U-UNIT-DATA.request	166
9.2.2.2	GTP-U-UNIT-DATA.indication	166
9.3	Protocol Stack	166
9.3.1	Usage of the GTP-U Header	166
9.3.1.1	Usage of Sequence Number	167
9.4	Tunnelling between SGSNs	167
9.5	Tunnelling between Source RNC and Target RNC	168
9.6	Tunnelling between GGSNs	168
10	Path Protocols	168
10.1	UDP/IP	168
10.1.1	UDP Header	168
10.1.1.1	Request Messages	168
10.1.1.2	Response Messages	168
10.1.1.3	Encapsulated T-PDUs	168
10.1.1.4	Error Indication, RAN Information Relay, Version Not Supported and Supported Extension Headers Notification	168
10.1.2	IP Header	168
10.1.2.1	Request Messages and Encapsulated T-PDUs	169
10.1.2.2	Response Messages	169
10.1.2.3	Error Indication, RAN Information Relay, Version Not supported and Supported Extension Headers Notification	169
11	Error Handling	169
11.1	Protocol Errors	169
11.1.1	Different GTP Versions	170
11.1.2	GTP Message Length Errors	170
11.1.3	Unknown GTP Signalling Message	170
11.1.4	Unexpected GTP Signalling Message	170
11.1.5	Missing Mandatorily Present Information Element	170
11.1.6	Invalid IE Length	170
11.1.7	Invalid Mandatory Information Element	171
11.1.8	Invalid Optional Information Element	171
11.1.9	Unknown Information Element	171
11.1.10	Out of Sequence Information Elements	171
11.1.11	Unexpected Information Element	171
11.1.12	Repeated Information Elements	172
11.1.13	Incorrect Optional Information Elements	172
11.2	Path Failure	172
11.3	MS Detach	172
11.4	Restoration and Recovery	172
12	Security provided to GTP Communication over Gn and Gp Interfaces	172
13	IP, The Networking Technology used by GTP	172
13.1	IP Version	172
13.2	IP Fragmentation	173
13.2.1	MO Direction	173
13.2.2	MT Direction	173
13.2.3	Tunnelling from old to new SGSN	173

14	GTP Parameters.....	174
14.1	Timers	174
14.2	Others	174
15	Mapping of BSSGP and RANAP causes	174
Annex A (informative):	A method for sequence number checking.....	176
Annex B (Normative):	SGSN mapping table between Gn/Gp and NAS Cause values	177
Annex C (informative):	Change history	180
History		190

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document defines the Gn and Gp interfaces for the General Packet Radio Service (GPRS) within the 3GPP system.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document defines the second version of GTP used on:

- the Gn and Gp interfaces of the General Packet Radio Service (GPRS);
- the Iu, Gn and Gp interfaces of the UMTS system.

NOTE: The version number used in the message headers is 0 for the first version of GTP described in GSM 09.60, and 1 for the second version in 3GPP TS 29.060.

From release 8 onwards, the normative specification of the user plane of GTP version 1 is 3GPP TS 29.281 [41]. All provisions about GTPv1 user plane in the present document shall be superseded by 3GPP TS 29.281 [41].

The present document specifies functions, procedures and information which apply to GERAN Iu mode. However, functionality related to GERAN Iu mode is neither maintained nor enhanced.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.003: "Numbering, addressing and identification".
- [3] 3GPP TS 23.007: "Restoration procedures".
- [4] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2".
- [5] 3GPP TS 24.008: "Mobile radio interface Layer 3 specification; Core network protocols; Stage 3".
- [6] 3GPP TS 29.002: "Mobile Application Part (MAP) specification".
- [7] 3GPP TS 25.413: "UTRAN Iu interface RANAP signalling".
- [8] 3GPP TS 33.102: "3G security; Security architecture".
- [9] 3GPP TS 43.020: "Security related network functions".
- [10] Void.
- [11] 3GPP TS 44.064: "Mobile Station - Serving GPRS Support Node (MS-SGSN) Logical Link Control (LLC) layer specification".
- [12] IETF RFC 791 (STD 0005): "Internet Protocol", J. Postel.
- [13] IETF RFC 768 (STD 0006): "User Datagram Protocol", J. Postel.
- [14] IETF RFC 3232: "Assigned numbers", J. Reynolds.
- [15] Void.
- [16] Void.