



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
General Packet Radio Service (GPRS);
GPRS Tunnelling Protocol (GTP)
across the Gn and Gp interface
(3GPP TS 29.060 version 14.3.0 Release 14)**



Reference

RTS/TSGC-0429060vE30

Keywords

GSM,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.

All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	9
1 Scope	10
2 References	10
3 Definitions and abbreviations.....	12
3.1 Definitions	12
3.2 Abbreviations	14
4 General	14
4.1 General Description.....	14
4.2 Removing support for GTPv1 to GTPv0 interworking	16
5 Transmission Order and Bit Definitions.....	16
6 GTP Header.....	16
6.1 Extension headers.....	19
6.1.1 PDCP PDU Number	19
6.1.2 Suspend Request.....	19
6.1.3 Suspend Response	19
6.1.4 MBMS support indication	20
6.1.5 MS Info Change Reporting support indication	20
7 GTP Messages and Message Formats	21
7.1 Message Formats.....	21
7.1.1 Presence requirements of Information Elements	23
7.2 Path Management Messages.....	23
7.2.0 General.....	23
7.2.1 Echo Request	23
7.2.2 Echo Response.....	23
7.2.3 Version Not Supported	24
7.2.4 Supported Extension Headers Notification.....	24
7.3 Tunnel Management Messages	24
7.3.1 Create PDP Context Request	24
7.3.2 Create PDP Context Response.....	28
7.3.3 Update PDP Context Request	32
7.3.4 Update PDP Context Response.....	37
7.3.5 Delete PDP Context Request	41
7.3.6 Delete PDP Context Response.....	43
7.3.7 Error Indication.....	44
7.3.8 PDU Notification Request	44
7.3.9 PDU Notification Response.....	45
7.3.10 PDU Notification Reject Request	46
7.3.11 PDU Notification Reject Response.....	47
7.3.12 Initiate PDP Context Activation Request.....	47
7.3.13 Initiate PDP Context Activation Response	48
7.4 Location Management Messages	49
7.4.0 General.....	49
7.4.1 Send Routeing Information for GPRS Request	49
7.4.2 Send Routeing Information for GPRS Response	50
7.4.3 Failure Report Request	50
7.4.4 Failure Report Response.....	51
7.4.5 Note MS GPRS Present Request	51
7.4.6 Note MS GPRS Present Response	52
7.5 Mobility Management Messages.....	52

7.5.0	General.....	52
7.5.1	Identification Request	52
7.5.2	Identification Response.....	53
7.5.3	SGSN Context Request.....	54
7.5.4	SGSN Context Response	55
7.5.5	SGSN Context Acknowledge	59
7.5.6	Forward Relocation Request.....	61
7.5.7	Forward Relocation Response	65
7.5.8	Forward Relocation Complete	66
7.5.9	Relocation Cancel Request	66
7.5.10	Relocation Cancel Response.....	67
7.5.11	Forward Relocation Complete Acknowledge	67
7.5.12	Forward SRNS Context Acknowledge	68
7.5.13	Forward SRNS Context	68
7.5.14	RAN Information Management Messages.....	69
7.5.14.0	General	69
7.5.14.1	RAN Information Relay	69
7.5.15	UE Registration Query Request.....	69
7.5.16	UE Registration Query Response	70
7.5A	MBMS Messages	70
7.5A.0	General.....	70
7.5A.1	UE Specific MBMS Messages.....	70
7.5A.1.1	MBMS Notification Request.....	70
7.5A.1.2	MBMS Notification Response	71
7.5A.1.3	MBMS Notification Reject Request	72
7.5A.1.4	MBMS Notification Reject Response	72
7.5A.1.5	Create MBMS Context Request.....	73
7.5A.1.6	Create MBMS Context Response	75
7.5A.1.7	Update MBMS Context Request.....	77
7.5A.1.8	Update MBMS Context Response	78
7.5A.1.9	Delete MBMS Context Request.....	80
7.5A.1.10	Delete MBMS Context Response	81
7.5A.2	Service Specific MBMS Messages.....	82
7.5A.2.1	MBMS Registration Request	82
7.5A.2.2	MBMS Registration Response	83
7.5A.2.3	MBMS De-registration Request.....	84
7.5A.2.4	MBMS De-Registration Response	85
7.5A.2.5	MBMS Session Start Request	85
7.5A.2.6	MBMS Session Start Response.....	87
7.5A.2.7	MBMS Session Stop Request	88
7.5A.2.8	MBMS Session Stop Response.....	89
7.5A.2.9	MBMS Session Update Request	89
7.5A.2.10	MBMS Session Update Response.....	90
7.5B.1	MS Info Change Reporting Messages	91
7.5B.1.0	General	91
7.5B.1.1	MS Info Change Notification Request	91
7.5B.1.2	MS Info Change Notification Response.....	93
7.6	Reliable Delivery of Signalling Messages.....	94
7.7	Information Elements	95
7.7.0	General.....	95
7.7.0A	Information Element with an IE Type Extension field	99
7.7.A	Handling ASN.1/PER encoded parameters	99
7.7.1	Cause	99
7.7.2	International Mobile Subscriber Identity (IMSI)	103
7.7.3	Routeing Area Identity (RAI)	104
7.7.4	Temporary Logical Link Identity (TLLI)	104
7.7.5	Packet TMSI (P-TMSI)	104
7.7.6	Reordering Required.....	105
7.7.7	Authentication Triplet.....	105
7.7.8	MAP Cause	105
7.7.9	P-TMSI Signature	106
7.7.10	MS Validated.....	106

7.7.11	Recovery	106
7.7.12	Selection Mode	106
7.7.13	Tunnel Endpoint Identifier Data I.....	107
7.7.14	Tunnel Endpoint Identifier Control Plane.....	107
7.7.15	Tunnel Endpoint Identifier Data II.....	108
7.7.16	Teardown Ind.....	108
7.7.17	NSAPI.....	109
7.7.18	RANAP Cause	109
7.7.19	RAB Context	109
7.7.20	Radio Priority SMS.....	110
7.7.21	Radio Priority.....	110
7.7.22	Packet Flow Id	110
7.7.23	Charging Characteristics.....	111
7.7.24	Trace Reference	111
7.7.25	Trace Type	111
7.7.25A	MS Not Reachable Reason	111
7.7.25B	Radio Priority LCS	112
7.7.26	Charging ID	112
7.7.27	End User Address	112
7.7.28	MM Context.....	115
7.7.29	PDP Context	119
7.7.30	Access Point Name	122
7.7.31	Protocol Configuration Options.....	122
7.7.32	GSN Address	122
7.7.33	MS International PSTN/ISDN Number (MSISDN)	123
7.7.34	Quality of Service (QoS) Profile.....	123
7.7.35	Authentication Quintuplet.....	124
7.7.36	Traffic Flow Template (TFT)	124
7.7.37	Target Identification	125
7.7.38	UTRAN Transparent Container.....	126
7.7.39	RAB Setup Information	126
7.7.40	Extension Header Type List.....	127
7.7.41	Trigger Id.....	127
7.7.42	OMC Identity.....	128
7.7.43	RAN Transparent Container	128
7.7.44	Charging Gateway Address	128
7.7.45	PDP Context Prioritization	129
7.7.45A	Additional RAB Setup Information	129
7.7.46	Private Extension	130
7.7.47	SGSN Number	130
7.7.48	Common Flags.....	130
7.7.49	APN Restriction.....	131
7.7.50	RAT Type	131
7.7.51	User Location Information (ULI)	132
7.7.52	MS Time Zone	134
7.7.53	International Mobile Equipment Identity (and Software Version) (IMEI(SV))	135
7.7.54	CAMEL Charging Information Container	135
7.7.55	MBMS UE Context	135
7.7.56	Temporary Mobile Group Identity.....	136
7.7.57	RIM Routing Address.....	137
7.7.58	MBMS Protocol Configuration Options	137
7.7.59	MBMS Session Duration	137
7.7.60	MBMS Service Area.....	138
7.7.61	Source RNC PDCP context info	138
7.7.62	Additional Trace Info.....	138
7.7.63	Hop Counter.....	139
7.7.64	Selected PLMN ID.....	139
7.7.65	MBMS Session Identifier	140
7.7.66	MBMS 2G/3G Indicator	140
7.7.67	Enhanced NSAPI	141
7.7.68	Additional MBMS Trace Info.....	141
7.7.69	MBMS Session Repetition Number.....	142

7.7.70	MBMS Time To Data Transfer.....	142
7.7.71	(void)	142
7.7.72	BSS Container	142
7.7.73	Cell Identification	143
7.7.74	PDU Numbers.....	143
7.7.75	BSSGP Cause	144
7.7.76	Required MBMS Bearer Capabilities	144
7.7.77	RIM Routing Address Discriminator.....	144
7.7.78	List of set-up PFCs	145
7.7.79	PS Handover XID Parameters	145
7.7.80	MS Info Change Reporting Action.....	146
7.7.81	Direct Tunnel Flags	146
7.7.82	Correlation-ID.....	147
7.7.83	Bearer Control Mode	147
7.7.84	MBMS Flow Identifier	147
7.7.85	MBMS IP Multicast Distribution.....	148
7.7.86	MBMS Distribution Acknowledgement	149
7.7.87	Reliable INTER RAT HANDOVER INFO.....	149
7.7.88	RFSP Index.....	149
7.7.89	PDP Type.....	150
7.7.90	Fully Qualified Domain Name (FQDN)	150
7.7.91	Evolved Allocation/Retention Priority I	150
7.7.92	Evolved Allocation/Retention Priority II.....	151
7.7.93	Extended Common Flags.....	151
7.7.94	User CSG Information (UCI).....	152
7.7.95	CSG Information Reporting Action.....	153
7.7.96	CSG ID.....	153
7.7.97	CSG Membership Indication (CMI).....	154
7.7.98	APN Aggregate Maximum Bit Rate (APN-AMBR)	154
7.7.99	UE Network Capability	154
7.7.100	UE-AMBR.....	155
7.7.101	APN-AMBR with NSAPI.....	155
7.7.102	GGSN Back-Off Time	155
7.7.103	Signalling Priority Indication.....	156
7.7.104	Signalling Priority Indication with NSAPI	156
7.7.105	Higher bitrates than 16 Mbps flag.....	157
7.7.106	(void)	157
7.7.107	Additional MM context for SRVCC.....	157
7.7.108	Additional flags for SRVCC.....	157
7.7.109	STN-SR	158
7.7.110	C-MSISDN	158
7.7.111	Extended RANAP Cause	158
7.7.112	eNodeB ID.....	159
7.7.114	ULI Timestamp.....	160
7.7.115	Local Home Network ID (LHN-ID) with NSAPI.....	160
7.7.116	CN Operator Selection Entity	160
7.7.117	UE Usage Type.....	161
7.7.118	Extended Common Flags II	161
7.7.119	Node Identifier.....	162
7.7.120	CIoT Optimizations Support Indication.....	162
7.7.121	SCEF PDN Connection	162
7.7.122	IOV_updates counter	163
8	Control Plane (GTP-C).....	163
8.1	Control Plane Protocol	163
8.2	Usage of the GTP-C Header.....	164
9	GTP-U	165
9.1	GTP-U Protocol Entity	165
9.1.1	Handling of Sequence Numbers	166
9.2	GTP-U Service Access Points and Primitives	166
9.2.1	GTP-U-CONTROL SAP	166

9.2.1.1	GTP-U-CONTROL-RX primitives	167
9.2.1.1.1	GTP-U-CONTROL-RX-SETUP.request	167
9.2.1.1.2	GTP-U-CONTROL-RX-SETUP.confirm	167
9.2.1.1.3	GTP-U-CONTROL-RX-RELEASE.request	167
9.2.1.1.4	GTP-U-CONTROL-RX-RELEASE.confirm	167
9.2.1.1.5	GTP-U-CONTROL-RX-ERROR.indication	167
9.2.1.2	GTP-U-CONTROL-TX primitives	167
9.2.1.2.1	GTP-U-CONTROL-TX-SETUP.request	167
9.2.1.2.2	GTP-U-CONTROL-TX-SETUP.confirm	168
9.2.1.2.3	GTP-U-CONTROL-TX-RELEASE.request	168
9.2.1.2.4	GTP-U-CONTROL-TX-RELEASE.confirm	168
9.2.1.2.5	GTP-U-CONTROL-TX-ERROR.indication	168
9.2.2	GTP-U-UNIT-DATA SAP and Primitives	168
9.2.2.1	GTP-U-UNIT-DATA.request	168
9.2.2.2	GTP-U-UNIT-DATA.indication	168
9.3	Protocol Stack	168
9.3.1	Usage of the GTP-U Header	169
9.3.1.1	Usage of Sequence Number	169
9.4	Tunnelling between SGSNs	170
9.5	Tunnelling between Source RNC and Target RNC	170
9.6	Tunnelling between GGSNs	170
10	Path Protocols	170
10.1	UDP/IP	170
10.1.1	UDP Header	170
10.1.1.1	Request Messages	170
10.1.1.2	Response Messages	171
10.1.1.3	Encapsulated T-PDUs	171
10.1.1.4	Error Indication, RAN Information Relay, Version Not Supported and Supported Extension Headers Notification	171
10.1.2	IP Header	171
10.1.2.1	Request Messages and Encapsulated T-PDUs	171
10.1.2.2	Response Messages	171
10.1.2.3	Error Indication, RAN Information Relay, Version Not supported and Supported Extension Headers Notification	171
11	Error Handling	172
11.1	Protocol Errors	172
11.1.1	Different GTP Versions	172
11.1.2	GTP Message Length Errors	172
11.1.3	Unknown GTP Signalling Message	172
11.1.4	Unexpected GTP Signalling Message	172
11.1.5	Missing Mandatorily Present Information Element	173
11.1.6	Invalid IE Length	173
11.1.7	Invalid Mandatory Information Element	173
11.1.8	Invalid Optional Information Element	173
11.1.9	Unknown Information Element	174
11.1.10	Out of Sequence Information Elements	174
11.1.11	Unexpected Information Element	174
11.1.12	Repeated Information Elements	174
11.1.13	Incorrect Optional Information Elements	174
11.2	Path Failure	174
11.3	MS Detach	174
11.4	Restoration and Recovery	174
12	Security provided to GTP Communication over Gn and Gp Interfaces	175
13	IP, The Networking Technology used by GTP	175
13.1	IP Version	175
13.2	IP Fragmentation	175
13.2.1	MO Direction	175
13.2.2	MT Direction	175
13.2.3	Tunnelling from old to new SGSN	176

14	GTP Parameters.....	176
14.1	Timers	176
14.2	Others	176
15	Mapping of BSSGP and RANAP causes	176
Annex A (informative): A method for sequence number checking.....		179
Annex B (Normative): SGSN mapping table between Gn/Gp and NAS Cause values		180
Annex C (informative): Change history		183
History		193

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The present document defines the Gn and Gp interfaces for the General Packet Radio Service (GPRS) within the 3GPP system.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document defines the second version of GTP used on:

- the Gn and Gp interfaces of the General Packet Radio Service (GPRS);
- the Iu, Gn and Gp interfaces of the UMTS system.

NOTE: The version number used in the message headers is 0 for the first version of GTP described in GSM 09.60, and 1 for the second version in 3GPP TS 29.060.

From release 8 onwards, the normative specification of the user plane of GTP version 1 is 3GPP TS 29.281 [41]. All provisions about GTPv1 user plane in the present document shall be superseded by 3GPP TS 29.281 [41].

The present document specifies functions, procedures and information which apply to GERAN Iu mode. However, functionality related to GERAN Iu mode is neither maintained nor enhanced.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.003: "Numbering, addressing and identification".
- [3] 3GPP TS 23.007: "Restoration procedures".
- [4] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2".
- [5] 3GPP TS 24.008: "Mobile radio interface Layer 3 specification; Core network protocols; Stage 3".
- [6] 3GPP TS 29.002: "Mobile Application Part (MAP) specification".
- [7] 3GPP TS 25.413: "UTRAN Iu interface RANAP signalling".
- [8] 3GPP TS 33.102: "3G security; Security architecture".
- [9] 3GPP TS 43.020: "Security related network functions".
- [10] Void.
- [11] 3GPP TS 44.064: "Mobile Station - Serving GPRS Support Node (MS-SGSN) Logical Link Control (LLC) layer specification".
- [12] IETF RFC 791 (STD 0005): "Internet Protocol", J. Postel.
- [13] IETF RFC 768 (STD 0006): "User Datagram Protocol", J. Postel.
- [14] IETF RFC 3232: "Assigned numbers", J. Reynolds.
- [15] Void.
- [16] Void.