

ETSI EN 302 769 V1.3.1 (2015-10)



**Digital Video Broadcasting (DVB);
Frame structure channel coding and modulation
for a second generation digital transmission system
for cable systems (DVB-C2)**

EBU
OPERATING EUROVISION

DVB[®]
Digital Video
Broadcasting

Reference

REN/JTC-DVB-353

Keywords

audio, broadcasting, cable, data, digital, DVB,
MPEG, TV, video

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

© European Broadcasting Union 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Symbols.....	11
3.3 Abbreviations	14
4 DVB-C2 System architecture.....	16
4.1 System overview	16
4.2 System architecture	16
4.3 Target performance	19
5 Input processing	19
5.1 Mode adaptation.....	19
5.1.0 Overview	19
5.1.1 Input Formats.....	20
5.1.2 Input Interface.....	20
5.1.3 Input Stream Synchronization (Optional).....	21
5.1.4 Null Packet Deletion (optional, for TS only, NM and HEM).....	21
5.1.5 CRC-8 encoding (for GFPS and TS, NM only).....	22
5.1.6 Baseband Header (BBHeader) insertion	22
5.1.7 Mode adaptation sub-system output stream formats.....	24
5.2 Stream adaptation.....	27
5.2.0 Overview	27
5.2.1 Scheduler	27
5.2.2 Padding	27
5.2.3 BB scrambling	27
6 Bit-interleaved coding and modulation	28
6.1 FEC encoding.....	28
6.1.0 Overview	28
6.1.1 Outer encoding (BCH).....	29
6.1.2 Inner encoding (LDPC)	30
6.1.2.0 Overview	30
6.1.2.1 Inner coding for normal FECFrame	30
6.1.2.2 Inner coding for short FECFrame	32
6.1.3 Bit Interleaver	32
6.2 Mapping bits onto constellations.....	34
6.2.0 Overview	34
6.2.1 Bit to cell word demultiplexer	35
6.2.2 Cell word mapping into IQ constellations	38
7 Data Slice Packet Generation	45
7.0 Overview	45
7.1 Data Slice Packets for Data Slice Type 1	45
7.2 Data Slice Packets for Data Slice Type 2.....	45
7.2.0 Overview	45
7.2.1 FECFrame header signalling data.....	46
7.2.2 Coding of the FECFrame header	47
7.2.2.0 Overview.....	47

7.2.2.1	Error Coding	48
7.2.2.2	Cyclic Delay	48
7.2.2.3	Scrambling of the lower branch	48
7.2.3	Mapping onto QAM constellations	49
7.2.3.0	Overview	49
7.2.3.1	Robust FECFrame header	49
7.2.3.2	High efficiency FECFrame header	49
7.2.4	Mapping of the XFECFrame cells	49
7.2.5	Length of the Data Slice Packet for Data Slice Type 2	49
7.2.6	Stuffing Data Slice Packets	50
8	Generation, coding and modulation of Layer 1 part 2 signalling	51
8.1	Overview	51
8.2	Preamble Header	51
8.3	L1 signalling part 2 data	53
8.3.0	Overview	53
8.3.1	L1 block padding	58
8.3.2	CRC for the L1 signalling part 2	58
8.3.3	L1 padding	58
8.4	Modulation and error correction coding of the L1 part 2 data	59
8.4.1	Overview	59
8.4.2	Parameters for FEC encoding of L1 part 2 data	61
8.4.3	FEC Encoding	63
8.4.3.1	Zero padding of BCH information bits	63
8.4.3.2	BCH encoding	64
8.4.3.3	LDPC encoding	64
8.4.3.4	Puncturing of LDPC parity bits	65
8.4.3.5	Removal of zero padding bits	65
8.4.3.6	Bit interleaving for L1 signalling part 2	66
8.4.4	Mapping bits onto constellations	66
8.4.4.0	Overview	66
8.4.4.1	Demultiplexing of L1 signalling part 2	66
8.4.4.2	Mapping onto QAM constellations	67
8.5	Time interleaving of L1 signalling part 2 data	67
9	Frame Builder	69
9.0	Introduction	69
9.1	C2 Frame structure	69
9.1.0	Overview	69
9.1.1	Duration of the C2 Frame	70
9.2	Pilot Reference Sequence	70
9.2.1	Data Scrambling Sequence	70
9.2.2	Pilot Scrambling Sequence	70
9.2.3	Pilot Reference Sequence	71
9.3	Preamble Symbol	71
9.3.1	Preamble Symbol overview	71
9.3.2	Frequency Interleaving	72
9.3.3	Pilot insertion	72
9.3.3.0	Overview	72
9.3.3.1	Locations of the preamble pilots	73
9.3.3.2	Amplitude and modulation of the preamble pilots	73
9.3.4	Mapping and scrambling of the signalling data	73
9.3.5	Notches within Preamble Symbols	74
9.3.5.0	Overview	74
9.3.5.1	Narrowband Notches	74
9.3.5.2	Broadband Notches	74
9.4	Data Slice generation	75
9.4.0	Overview	75
9.4.1	Location of Data Slices	75
9.4.1.1	Start and end OFDM carrier of Data Slices	75
9.4.1.2	Maximum width of Data Slices	75
9.4.1.3	Minimum width of Data Slices	75

9.4.1.4	Notches within Data Slices	75
9.4.2	Number of payload cells in Data Slice.....	76
9.4.3	Mapping of the Data Slice Packets	76
9.4.4	Time Interleaving.....	76
9.4.5	Frequency Interleaving	80
9.5	Stuffing Data Slices	81
9.6	Pilot Insertion	81
9.6.1	Introduction.....	81
9.6.2	Scattered pilot insertion	82
9.6.2.0	Overview	82
9.6.2.1	Locations of the scattered pilots.....	82
9.6.2.2	Amplitudes of the scattered pilots	82
9.6.2.3	Modulation of the scattered pilots	82
9.6.3	Continual pilot insertion	83
9.6.3.0	Overview	83
9.6.3.1	Locations of the continual pilots	83
9.6.3.2	Amplitudes of the Continual Pilots	83
9.6.3.3	Modulation of the Continual Pilots	83
9.6.4	Edge pilot insertion	83
9.6.4.0	Overview	83
9.6.4.1	Locations of the edge pilots	83
9.6.4.2	Amplitudes of the Edge Pilots.....	84
9.6.4.3	Modulation of the Edge Pilots.....	84
9.7	Dummy carrier reservation.....	85
10	OFDM generation	85
10.0	Introduction	85
10.1	IFFT - OFDM Modulation	85
10.2	Guard interval insertion.....	87
10.3	Spectrum characteristics	87
Annex A (normative): Addresses of parity bit accumulators for Nldpc = 64 800		89
Annex B (normative): Addresses of parity bit accumulators for Nldpc = 16 200.....		95
Annex C (normative): Input stream synchronizer		97
Annex D (normative): Input Remultiplexing Subsystem: Splitting of input MPEG-2 Transport Streams into Data PLPs, generation of a Common PLP of a group of PLPs and insertion of Null Packets into Transport Streams		99
D.1	Overview	99
D.2	Splitting of a group of input TSs into TSPSS streams and a TSPSC stream	100
D.2.1	General	100
D.2.2	Extraction of the Common PLP from a group of TS.....	100
D.2.3	Insertion of additional Null Packets into TSPSS.....	101
D.3	Receiver Implementation Considerations.....	102
D.3.0	Introduction	102
D.3.1	Recombination of TSPSS and TSPSC in a receiver.....	102
Annex E (normative): Calculation of the CRC word.....		104
Annex F (normative): Bundling of PLPs		105
Annex G (informative): Transport Stream regeneration and clock recovery using ISCR.....		107
Annex H (informative): Pilot patterns.....		108
Annex I (informative): Bibliography		111
History		112

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by Joint Technical Committee (JTC) Broadcast of the European Broadcasting Union (EBU), Comité Européen de Normalisation ELECTrotechnique (CENELEC) and the European Telecommunications Standards Institute (ETSI).

NOTE: The EBU/ETSI JTC Broadcast was established in 1990 to co-ordinate the drafting of standards in the specific field of broadcasting and related fields. Since 1995 the JTC Broadcast became a tripartite body by including in the Memorandum of Understanding also CENELEC, which is responsible for the standardization of radio and television receivers. The EBU is a professional association of broadcasting organizations whose work includes the co-ordination of its members' activities in the technical, legal, programme-making and programme-exchange domains. The EBU has active members in about 60 countries in the European broadcasting area; its headquarters is in Geneva.

European Broadcasting Union
CH-1218 GRAND SACONNEX (Geneva)
Switzerland
Tel: +41 22 717 21 11
Fax: +41 22 717 24 81

The Digital Video Broadcasting Project (DVB) is an industry-led consortium of broadcasters, manufacturers, network operators, software developers, regulatory bodies, content owners and others committed to designing global standards for the delivery of digital television and data services. DVB fosters market driven solutions that meet the needs and economic circumstances of broadcast industry stakeholders and consumers. DVB standards cover all aspects of digital television from transmission through interfacing, conditional access and interactivity for digital video, audio and data. The consortium came together in 1993 to provide global standardization, interoperability and future proof specifications.

National transposition dates	
Date of adoption of this EN:	22 October 2015
Date of latest announcement of this EN (doa):	31 January 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2016
Date of withdrawal of any conflicting National Standard (dow):	31 January 2019

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

Since 1994 enhanced digital transmission technologies have evolved somewhat:

- New channel coding schemes, combined with higher order modulation, promise more powerful alternatives to the DVB-C coding and modulation schemes. The result is a capacity gain in the order of 30 % at a given cable channel bandwidth and CATV network performance.
- Variable Coding and Modulation (VCM) may be applied to provide different levels of error protection to different services (e.g. SDTV and HDTV, audio, multimedia).
- In the case of interactive and point-to-point applications, the VCM functionality may be combined with the use of return channels, to achieve Adaptive Coding and Modulation (ACM). This technique provides more exact channel protection and dynamic link adaptation to propagation conditions, targeting each individual receiving terminal.
- DVB-C is strictly focused on a unique data format, the MPEG Transport Stream (ISO/IEC 13818-1 [i.1] or a reference to it). Extended flexibility to cope with other input data formats (such as multiple Transport Streams, or generic data formats) is now possible without significant complexity increase.

Version 1.2.1 of the present document defines a "second generation" modulation and channel coding system (denoted the "C2 System" or "DVB-C2" for the purposes of the present document) to make use of the improvements listed above. DVB-C2 is a single, very flexible standard, covering a variety of applications by cable, as described below. It is characterized by:

- a flexible input stream adapter, suitable for operation with single and multiple input streams of various formats (packetized or continuous);
- a powerful FEC system based on LDPC (Low-Density Parity Check) codes concatenated with BCH (Bose Chaudhuri Hocquenghem) codes, allowing Quasi Error Free operation close to the Shannon limit, depending on the transmission mode (AWGN channel, modulation constrained Shannon limit);
- a wide range of code rates (from 2/3 up to 9/10); 5 constellations, ranging in spectrum efficiency from 1 to 10,8 bit/s/Hz, optimized for operation in cable networks;
- Adaptive Coding and Modulation (ACM) functionality, optimizing channel coding and modulation on a frame-by-frame basis.

DVB-C [i.4] was introduced as a European Norm in 1994. It specifies single carrier QAM modulation and Reed-Solomon channel coding and is used today by many cable operators worldwide for television and data broadcasting as well as for forward channel transmission of the Data Over Cable System defined in [i.7].

Version 1.3.1 of this specification (the present document) made a number of clarifications and corrections to the wording. No changes have been made to existing features. Three new technical features have been added:

- Early Warning System signalling
- DVB-C2 version number
- Additional MODCOD 4/5 for 4096-QAM

The new features are defined backward compatible. This means that receivers compliant to version 1.2.1 are not affected when receiving a 1.3.1 compliant signal, which does not include additional MODCOD 4/5 for 4096-QAM or extended PLP Bundling over several C2-Systems.

New signalling elements (EWS and C2-versioning) are deemed to be ignored by 1.2.1 compliant receivers.

Further details of the specification of PLP bundling have been added in annex F, especially addressing the optimization of the buffer size, both at transmitter and at receiver side. Furthermore a new mechanism is defined to allow PLP bundling also over several **C2_Systems**.

1 Scope

The present document describes a second generation baseline transmission system for digital television broadcasting via Hybrid Fibre Coax (HFC) cable networks and Master Antenna Television (MATV) installations. It specifies the channel coding, modulation and lower layer signalling protocol system intended for the provision of digital television services and generic data streams.

The scope is as follows:

- it gives a general description of the Baseline System for digital cable TV;
- it specifies the digital signal processing in order to establish compatibility between pieces of equipment developed by different manufacturers. This is achieved by describing in detail the signal processing at the transmitting side, while the processing at the receiving side is left open to individual implementations. However, for the purpose of securing interoperability it is necessary in this text to refer to certain implementation aspects of the receiving end.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 101 162: "Digital Video Broadcasting (DVB); Allocation of identifiers and codes for Digital Video Broadcasting (DVB) systems".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ISO/IEC 13818-1: "Information technology - Generic coding of moving pictures and associated audio information: Systems".
- [i.2] ETSI TS 102 606: "Digital Video Broadcasting (DVB); Generic Stream Encapsulation (GSE) Protocol".
- [i.3] ETSI EN 302 307: "Digital Video Broadcasting (DVB); Second generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications (DVB-S2)".
- [i.4] ETSI EN 300 468: "Digital Video Broadcasting (DVB); Specification for Service Information (SI) in DVB systems".