

# ETSI EN 301 908-10 V4.2.2 (2016-11)



**Electromagnetic compatibility and  
Radio spectrum Matters (ERM);  
Base Stations (BS), Repeaters and User Equipment (UE) for  
IMT-2000 Third-Generation cellular networks;  
Part 10: Harmonised Standard for IMT-2000,  
FDMA/TDMA (DECT) covering the essential requirements  
of article 3.2 of the Directive 2014/53/EU**

---

**Reference**REN/DECT-000302-C1

---

**Keywords**

---

DECT, digital, generic, IMT-2000, radio,  
regulation, testing**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	10
Foreword.....	10
Modal verbs terminology.....	11
1 Scope .....	12
2 References .....	12
2.1 Normative references .....	12
2.2 Informative references.....	13
3 Definitions, symbols and abbreviations .....	14
3.1 Definitions.....	14
3.2 Symbols.....	17
3.3 Abbreviations .....	17
4 Technical requirements specifications .....	18
4.1 Environmental profile.....	18
4.2 Overview .....	18
4.2.0 General.....	18
4.2.1 Test suites .....	18
4.2.2 Test groups.....	19
4.2.3 Test cases .....	19
4.3 Applicant's declaration .....	19
4.4 Applicability of test suites.....	20
4.4.1 Introduction.....	20
4.4.2 Equipment that includes only a DECT RF receiver.....	20
4.4.3 Equipment that includes a radio transmitter .....	20
4.4.4 CTAs.....	20
4.4.5 Equipment with combined FT and PT functionality.....	20
4.4.5.1 Introduction.....	20
4.4.5.2 Wireless Relay Station .....	20
4.4.5.3 Direct PP to PP communication .....	20
4.4.5.4 Distributed communications .....	21
4.4.6 Equipment that is capable of using higher level modulation .....	21
4.5 Conformance requirements .....	21
4.5.1 General.....	21
4.5.2 Accuracy and stability of RF carriers .....	21
4.5.2.1 Definition of nominal position of RF carriers .....	21
4.5.2.2 Limits .....	21
4.5.2.3 Conformance .....	22
4.5.3 Accuracy and stability of timing parameters .....	22
4.5.3.0 General .....	22
4.5.3.1 Definitions.....	22
4.5.3.1.1 Slot structure.....	22
4.5.3.1.2 Definition of the position of p0 .....	22
4.5.3.2 Limits .....	22
4.5.3.2.1 Reference timer accuracy and stability .....	22
4.5.3.2.2 RFP transmission jitter .....	22
4.5.3.2.3 PP reference timer synchronization .....	23
4.5.3.3 Conformance .....	23
4.5.4 Transmission burst.....	23
4.5.4.1 Definitions.....	23
4.5.4.1.1 Introduction .....	23
4.5.4.1.2 Physical packets.....	24
4.5.4.1.3 Transmitted power.....	24
4.5.4.1.4 Normal Transmitted Power (NTP) .....	24
4.5.4.1.5 Transmitter attack time.....	24
4.5.4.1.6 Transmitter release time .....	24

4.5.4.1.7	Minimum power .....	24
4.5.4.1.8	Maximum power .....	24
4.5.4.1.9	Maintenance of transmission after packet end.....	24
4.5.4.1.10	Transmitter idle power output .....	24
4.5.4.2	Limits .....	24
4.5.4.2.1	Transmitter attack time.....	24
4.5.4.2.2	Transmitter release time .....	24
4.5.4.2.3	Minimum power .....	24
4.5.4.2.4	Maximum power .....	25
4.5.4.2.5	Maintenance of transmission after packet end.....	25
4.5.4.2.6	Transmitter idle power output .....	25
4.5.4.3	Conformance.....	25
4.5.5	Transmitted power .....	25
4.5.5.1	Definitions.....	25
4.5.5.1.1	PP and RFP with an integral antenna .....	25
4.5.5.1.2	PP and RFP with external connections for all antennas .....	25
4.5.5.1.3	PP and RFP with both integral and external antennas .....	25
4.5.5.2	Limits .....	25
4.5.5.3	Conformance.....	25
4.5.6	RF carrier modulation.....	26
4.5.6.1	Definition .....	26
4.5.6.2	Limits .....	26
4.5.6.3	Conformance.....	26
4.5.7	Unwanted RF power radiation .....	26
4.5.7.1	General .....	26
4.5.7.2	Emissions due to modulation .....	26
4.5.7.2.1	Definition.....	26
4.5.7.2.2	Limits .....	27
4.5.7.2.3	Conformance .....	27
4.5.7.3	Emissions due to transmitter transients .....	27
4.5.7.3.1	Definition.....	27
4.5.7.3.2	Limits .....	27
4.5.7.3.3	Conformance .....	27
4.5.7.4	Emissions due to intermodulation .....	27
4.5.7.4.1	Definition.....	27
4.5.7.4.2	Limits .....	28
4.5.7.4.3	Conformance .....	28
4.5.7.5	Spurious emissions when allocated a transmit channel.....	28
4.5.7.5.1	Definition.....	28
4.5.7.5.2	Limits .....	28
4.5.7.5.3	Conformance .....	28
4.5.8	Radio receiver testing .....	28
4.5.8.1	Radio receiver sensitivity .....	28
4.5.8.1.1	Definition.....	28
4.5.8.1.2	Limits .....	28
4.5.8.1.3	Conformance .....	29
4.5.8.2	Radio receiver reference BER and FER.....	29
4.5.8.2.1	Definition.....	29
4.5.8.2.2	Limits .....	29
4.5.8.2.3	Conformance .....	29
4.5.8.3	Radio receiver interference performance .....	29
4.5.8.3.1	Definition.....	29
4.5.8.3.2	Limits .....	29
4.5.8.3.3	Conformance .....	29
4.5.8.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies .....	30
4.5.8.4.1	Definition.....	30
4.5.8.4.2	Limits .....	30
4.5.8.4.3	Conformance .....	30
4.5.8.5	Radio receiver blocking case 2: owing to signals occurring at a different time .....	30
4.5.8.5.1	Definition.....	30
4.5.8.5.2	Limits .....	30

4.5.8.5.3	Conformance .....	30
4.5.8.6	Receiver intermodulation performance .....	31
4.5.8.6.1	Definition.....	31
4.5.8.6.2	Limits .....	31
4.5.8.6.3	Conformance .....	31
4.5.8.7	Spurious emissions when the PP has no allocated transmit channel .....	31
4.5.8.7.1	Definition.....	31
4.5.8.7.2	Limits .....	31
4.5.8.7.3	Conformance .....	31
4.5.9	Channel access.....	32
4.5.9.1	Channel selection .....	32
4.5.9.2	Channel confirmation.....	32
4.5.9.2.1	For the PT.....	32
4.5.9.2.2	For the FT .....	32
4.5.9.3	Channel release .....	32
4.5.9.4	General .....	33
4.5.9.5	Channel selection and confirmation for DECT ULE .....	33
4.5.9.5.1	General .....	33
4.5.9.5.2	For the PT.....	33
4.5.9.5.3	For the FT.....	33
4.5.10	WRS testing.....	33
4.5.10.1	General requirements .....	33
4.5.10.2	Testing as a PP .....	34
4.5.10.3	Testing as an RFP .....	34
4.5.10.4	Additional requirements.....	34
4.5.10.5	Conformance.....	38
4.5.11	Requirements for PPs with direct PP to PP communication mode .....	38
4.5.11.1	General requirements .....	38
4.5.11.2	Setting the EUT in direct communications mode.....	38
4.5.11.3	When the EUT has not initiated a call.....	39
4.5.11.4	When the EUT initiates a call .....	39
4.5.11.5	Conformance.....	39
4.5.12	Distributed communications .....	39
4.5.12.1	General requirements .....	39
4.5.12.2	Testing as a PP .....	40
4.5.12.3	Testing as an RFP .....	40
4.5.12.4	Conformance.....	40
4.5.13	Higher level modulation options.....	40
4.5.13.1	Requirements .....	40
4.5.13.2	Conformance.....	41
5	Testing for compliance with technical requirements.....	41
5.1	General test requirements .....	41
5.1.1	Test philosophy.....	41
5.1.2	Standard position .....	42
5.1.3	Test antenna of the LT .....	43
5.1.4	Substitution antenna.....	43
5.1.5	Test fixture.....	43
5.1.5.1	Description .....	43
5.1.5.2	Calibration of the test fixture for the measurement of transmitter characteristics.....	44
5.1.5.3	Calibration of the test fixture for the measurement of receiver characteristics .....	44
5.1.5.4	Mode of use.....	45
5.1.6	Equipment with a temporary or internal permanent antenna connector.....	45
5.1.6.1	General .....	45
5.1.6.2	Equipment with a temporary antenna connector .....	45
5.1.7	Lower Tester (LT) .....	45
5.1.7.1	Description .....	45
5.1.7.2	Connections between the EUT and the LT .....	46
5.1.7.3	Functions and abilities.....	46
5.1.7.4	Signal generation uncertainty.....	46
5.1.7.5	Modulated DECT-like carrier .....	47
5.1.7.6	CW interferers.....	47

5.1.7.7	DECT RF signal.....	47
5.1.7.8	Test modulation signals.....	47
5.1.8	Upper Tester (UT) .....	47
5.1.8.1	Description of the UT.....	47
5.1.8.2	The test standby mode.....	47
5.1.8.3	Test messages.....	48
5.1.8.4	Dummy setting when EUT is a RFP and it is in Test Standby Mode (TSM).....	48
5.1.9	Description of the Lower Tester FT and PT .....	48
5.1.10	General test methods.....	48
5.1.10.1	General .....	48
5.1.10.2	Sampling the RF signal .....	49
5.1.10.2.1	Introduction .....	49
5.1.10.2.2	Sampling method.....	49
5.1.10.3	Determining the reference position .....	49
5.1.10.3.0	General .....	49
5.1.10.3.1	Case 1: EUTs that cannot transmit .....	49
5.1.10.3.2	Case 2: EUTs that can transmit .....	49
5.1.10.4	Bit error rate (BER) and Frame Error Ratio (FER) measurements .....	49
5.1.11	Test setup.....	50
5.1.11.1	General .....	50
5.1.11.2	Test setup 1 .....	50
5.1.11.3	Test setup 2 .....	50
5.1.11.4	Test setup 3 .....	51
5.1.11.5	Test setup 4 .....	51
5.1.11.6	Test setup 5 .....	51
5.1.12	Test arrangements for intermodulation measurements .....	52
5.1.12.1	PT to PT arrangement .....	52
5.1.12.2	FT to FT arrangement .....	53
5.1.12.3	FT to PT arrangement .....	53
5.1.13	Test conditions, power supply and ambient temperatures .....	54
5.1.13.1	General .....	54
5.1.13.2	Nominal test conditions.....	54
5.1.13.3	Extreme test conditions .....	55
5.1.13.4	Test power source - general requirements.....	56
5.1.13.5	Nominal test power source.....	56
5.1.13.5.1	Mains voltage .....	56
5.1.13.5.2	Regulated lead acid battery power sources.....	56
5.1.13.5.3	Nickel cadmium battery.....	56
5.1.13.5.4	Other power sources .....	56
5.1.13.6	Extreme test power source .....	56
5.1.13.6.1	Mains voltage .....	56
5.1.13.6.2	Regulated lead acid battery power sources.....	56
5.1.13.6.3	Nickel cadmium battery.....	56
5.1.13.6.4	Other power sources .....	57
5.1.13.7	Testing of host connected equipment and plug-in cards .....	57
5.1.13.7.1	Approaches .....	57
5.1.13.7.2	Alternative A: composite equipment.....	57
5.1.13.7.3	Alternative B: use of a test jig and three hosts .....	57
5.2	Interpretation of the measurement results .....	58
5.3	Radio test suites.....	58
5.3.1	General.....	58
5.3.2	Accuracy and stability of RF carriers .....	58
5.3.2.1	Test environment.....	58
5.3.2.2	Method of measurement.....	59
5.3.2.3	Verdict criteria when the EUT is a RFP.....	59
5.3.2.4	Verdict criteria when the EUT is a PP .....	59
5.3.3	Accuracy and stability of timing parameters .....	60
5.3.3.1	Measurement of packet timing jitter .....	60
5.3.3.1.1	Test environment.....	60
5.3.3.1.2	Method of measurement .....	60
5.3.3.1.3	Verdict criteria.....	60
5.3.3.2	Measurement of the reference timing accuracy of a RFP .....	60

5.3.3.2.1	Test environment .....	60
5.3.3.2.2	Method of measurement .....	61
5.3.3.2.3	Verdict criteria .....	61
5.3.3.3	Measurement of packet transmission accuracy of a PP .....	61
5.3.3.3.1	Test environment .....	61
5.3.3.3.2	Method of measurement .....	61
5.3.3.3.3	Verdict criteria .....	62
5.3.4	Transmission burst .....	62
5.3.4.1	Test environment .....	62
5.3.4.2	Method of measurement .....	62
5.3.4.3	Verdict criteria .....	63
5.3.5	Transmitted power .....	63
5.3.5.1	PP and RFP with an integral antenna .....	63
5.3.5.1.1	Test environment .....	63
5.3.5.1.2	Method of measurement .....	63
5.3.5.1.3	Verdict criteria for all EUTs .....	64
5.3.5.2	PP and RFP with external antenna connection(s) .....	65
5.3.5.2.1	Test environment .....	65
5.3.5.2.2	Method of measurement .....	65
5.3.5.2.3	Verdict criteria for all EUTs .....	65
5.3.6	RF carrier modulation .....	65
5.3.6.1	Test environment .....	65
5.3.6.2	Method of measurement, parts 1 and 2 .....	66
5.3.6.2.1	Introduction .....	66
5.3.6.2.2	Part 1 .....	66
5.3.6.2.3	Part 2 .....	66
5.3.6.3	Method of measurement, Parts 3 and 4 .....	67
5.3.6.3.1	General .....	67
5.3.6.3.2	Part 3 .....	67
5.3.6.3.3	Part 4 .....	67
5.3.6.4	Verdict criteria for Part 1 .....	67
5.3.6.5	Verdict criteria for Part 2 .....	68
5.3.6.6	Verdict criteria for Part 3 .....	68
5.3.6.7	Verdict criteria for Part 4 .....	68
5.3.7	Unwanted RF power radiation .....	69
5.3.7.1	General test conditions .....	69
5.3.7.2	Emissions due to modulation .....	69
5.3.7.2.1	Test environment .....	69
5.3.7.2.2	Method of measurement .....	70
5.3.7.2.3	Verdict criteria .....	71
5.3.7.3	Emissions due to transmitter transients .....	71
5.3.7.3.1	Test environment .....	71
5.3.7.3.2	Method of measurement .....	71
5.3.7.3.3	Verdict criteria .....	72
5.3.7.4	Emissions due to intermodulation .....	72
5.3.7.4.1	Test environment .....	72
5.3.7.4.2	Method of measurement .....	72
5.3.7.4.3	Verdict criteria .....	73
5.3.7.5	Spurious emissions when allocated a transmit channel .....	73
5.3.7.5.1	Radiated emissions .....	73
5.3.7.5.2	Conducted spurious emissions when the EUT has a permanent external antenna connector .....	75
5.3.8	Radio receiver testing .....	75
5.3.8.1	Radio receiver sensitivity .....	75
5.3.8.1.1	Test environment .....	75
5.3.8.1.2	Method of measurement .....	75
5.3.8.1.3	Verdict criteria .....	76
5.3.8.2	Radio receiver reference BER and FER .....	76
5.3.8.2.1	Test environment .....	76
5.3.8.2.2	Method of measurement .....	76
5.3.8.2.3	Verdict criteria .....	76
5.3.8.3	Radio receiver interference performance .....	76
5.3.8.3.1	Test environment .....	76

5.3.8.3.2	Method of measurement .....	76
5.3.8.3.3	Verdict criteria.....	77
5.3.8.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies .....	77
5.3.8.4.1	Test environment.....	77
5.3.8.4.2	Method of measurement .....	77
5.3.8.4.3	Verdict criteria.....	78
5.3.8.5	Radio receiver blocking case 2: owing to signals occurring at a different time.....	79
5.3.8.5.1	Test environment.....	79
5.3.8.5.2	Method of measurement .....	79
5.3.8.5.3	Verdict criteria.....	79
5.3.8.6	Receiver intermodulation performance .....	80
5.3.8.6.1	Test environment.....	80
5.3.8.6.2	Method of measurement .....	80
5.3.8.6.3	Verdict criteria.....	80
5.3.8.7	Spurious emissions when the PP has no allocated transmit channel .....	80
5.3.8.7.1	Test environment.....	80
5.3.8.7.2	Method of measurement .....	81
5.3.8.7.3	Verdict criteria (outside the DECT band).....	81
5.3.8.7.4	Verdict criteria (inside the DECT band).....	81
5.3.9	Channel access.....	81
5.3.10	WRS testing.....	81
5.3.10.1	General .....	81
5.3.10.2	Testing as a PP .....	82
5.3.10.3	Testing as an RFP .....	82
5.3.10.4	Additional requirements.....	82
5.3.11	Requirements for PPs with direct PP to PP communication mode .....	83
5.3.11.1	General .....	83
5.3.11.2	Setting the EUT in direct communications mode.....	83
5.3.11.3	When the EUT has not initiated a call.....	83
5.3.11.4	When the EUT initiates a call .....	83
5.3.11.5	Applicants declarations .....	84
5.3.12	Distributed Communications .....	84
5.3.12.1	General .....	84
5.3.12.2	Testing as a PP .....	84
5.3.12.3	Testing as an RFP .....	84
5.3.12.4	Applicants declaration.....	85
5.3.13	Higher level modulation options.....	85
5.3.13.1	General .....	85
5.3.13.2	Activation of higher level modulations when EUT is in Test Standby Mode.....	86
5.3.13.3	Applicants declaration.....	86
<b>Annex A (normative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>87</b>
<b>Annex B (normative):</b>	<b>Procedures for test fixture calibration.....</b>	<b>89</b>
B.1	Calibration of test fixture for receiver measurements .....	89
B.1.1	Procedure.....	89
B.1.2	Method of measurement.....	89
<b>Annex C (normative):</b>	<b>Measurement of BER and FER.....</b>	<b>91</b>
<b>Annex D (informative):</b>	<b>Procedures for the measurement of synchronization loss at the EUT by the LT .....</b>	<b>92</b>
D.1	Description .....	92
D.2	Method .....	92
<b>Annex E (informative):</b>	<b>DECT carrier numbers and carrier positions in the range 1 880 MHz to 2 025 MHz .....</b>	<b>93</b>



E.1	Introduction .....	93
E.2	1 880 MHz to 1 978 MHz and 2 010 MHz to 2 025 MHz RF band 00001.....	94
E.3	1 880 MHz to 1 925 MHz and 2 010 MHz to 2 025 MHz RF band 00010.....	95
<b>Annex F (informative):</b>	<b>Bibliography.....</b>	<b>96</b>
<b>Annex G (informative):</b>	<b>Change History .....</b>	<b>97</b>
History .....		98

---

# Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.18].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 10 of a multi-part deliverable covering the Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks, as identified below:

- Part 1: "Harmonized EN for IMT-2000, introduction and common requirements, covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 2: "Harmonised EN for IMT-2000, CDMA Direct Spread (UTRA FDD) User Equipment (UE) covering essential requirements of article 3.2 of the Directive 2014/53/EU";
- Part 3: "Harmonised EN for IMT-2000, CDMA Direct Spread (UTRA FDD) (BS) covering essential requirements of article 3.2 of the Directive 2014/53/EU";
- Part 4: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 5: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 6: "Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 7: "Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 8: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 9: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 10: "Harmonised Standard for IMT-2000, FDMA/TDMA (DECT) covering the essential requirements of article 3.2 of the Directive 2014/53/EU";**
- Part 11: "Harmonised EN for IMT-2000, CDMA Direct Spread (UTRA FDD) (Repeaters) covering essential requirements of article 3.2 of the Directive 2014/53/EU";

- Part 12: "Harmonised EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (Repeaters) covering essential requirements of article 3.2 of the Directive 2014/53/EU";
- Part 13: "Harmonised EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (UE) covering essential requirements of article 3.2 of the Directive 2014/53/EU";
- Part 14: "Harmonised EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (BS) covering essential requirements of article 3.2 of the Directive 2014/53/EU";
- Part 15: "Harmonised EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (Repeater) covering essential requirements of article 3.2 of the Directive 2014/53/EU";
- Part 16: "Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 17: "Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (BS) covering essential requirements of article 3.2 of the R&TTE Directive".
- Part 18: "Harmonised EN for IMT-2000, E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS), covering the essential requirements of article 3.2 of the Directive 2014/53/EU";
- Part 19: "Harmonised EN for IMT-2000, OFDMA TDD WMAN (Mobile WiMAX) TDD User Equipment (UE), covering the essential requirements of article 3.2 of the Directive 2014/53/EU";
- Part 20: "Harmonised EN for IMT-2000, OFDMA TDD WMAN (Mobile WiMAX) TDD Base Stations (BS), covering the essential requirements of article 3.2 of the Directive 2014/53/EU";
- Part 21: "Harmonised EN for IMT-2000, OFDMA TDD WMAN (Mobile WiMAX) FDD User Equipment (UE), covering the essential requirements of article 3.2 of the Directive 2014/53/EU";
- Part 22: "Harmonised EN for IMT-2000, OFDMA TDD WMAN (Mobile WiMAX) FDD Base Stations (BS), covering the essential requirements of article 3.2 of the Directive 2014/53/EU".

<b>National transposition dates</b>	
Date of latest announcement of this EN (doa):	28 February 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2017
Date of withdrawal of any conflicting National Standard (dow):	31 August 2018

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# 1 Scope

The present document applies to the following equipment types for IMT-FT. IMT-FT is the Digital Enhanced Cordless Telecommunications (DECT) system being a member of the ITU IMT-2000 family:

- a) Fixed Part (FP).
- b) Portable Part (PP).
- c) Cordless Terminal Adapter (CTA).
- d) Wireless Relay Station (WRS) (FP and PP combined).
- e) Hybrid Part (HyP) (a PP with capability to act as a FP to provide PP to PP communication).

These radio equipment types are capable of operating in all or any part of the frequency bands given in table 1.

**Table 1: Radiocommunications service frequency bands**

	<b>Radiocommunications service frequency bands</b>
Transmit	1 900 MHz to 1 980 MHz
Receive	1 900 MHz to 1 980 MHz
Transmit	2 010 MHz to 2 025 MHz
Receive	2 010 MHz to 2 025 MHz

The IMT-FT (DECT) service frequency bands for transmitting and receiving for all elements are the parts of the European UMTS spectrum applicable for TDD operation, 1 900 MHz to 1 980 MHz and 2 010 MHz to 2 025 MHz, (see ERC/DEC(99)25 [8] and ERC/DEC(00)01 [9]).

NOTE: IMT-FT equipment may have a second mode for providing operation also in the DECT band 1 880 MHz to 1 900 MHz. Application of DECT in the band 1 880 MHz to 1 900 MHz is covered by ETSI EN 301 406 [i.7].

Details of the DECT Common Interface may be found in ETSI EN 300 175-1 [i.12], ETSI EN 300 175 parts 2 [1] to 3 [2], ETSI EN 300 175-4 [i.13], ETSI EN 300 175 parts 5 [3] to 6 [4] and ETSI EN 300 175 parts 7 [i.14] to 8 [i.15]. Further details of the DECT system may be found in ETSI TR 101 178 [i.1] and ETSI ETR 043 [i.2]. Information about ULE may be found in ETSI TS 102 939-1 [i.16] and ETSI TS 102 939-2 [i.17].

The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-2 (V2.6.1) (07-2015): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical layer (PHL)".