

# ETSI TS 123 682 V13.8.0 (2017-01)



**Digital cellular telecommunications system (Phase 2+) (GSM);  
Universal Mobile Telecommunications System (UMTS);  
LTE;**

**Architecture enhancements to facilitate communications with  
packet data networks and applications  
(3GPP TS 23.682 version 13.8.0 Release 13)**



---

Reference

RTS/TSGS-0223682vd80

---

Keywords

GSM,LTE,UMTS

***ETSI***

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

***Important notice***

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

***Copyright Notification***

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.  
All rights reserved.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under  
<http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	7
1 Scope .....	8
2 References .....	8
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.2 Abbreviations .....	9
4 Architecture Model and Concepts.....	10
4.1 General Concept.....	10
4.2 Architectural Reference Model .....	11
4.3 Reference points.....	15
4.3.1 General.....	15
4.3.2 List of Reference Points.....	15
4.3.3 Reference Point Requirements.....	16
4.3.3.1 Tsp Reference Point Requirements .....	16
4.3.3.2 T4 Reference Point Requirements.....	16
4.3.3.3 Void.....	16
4.3.3.4 S6m Reference Point Requirements.....	16
4.3.3.5 S6n Reference Point Requirements.....	17
4.3.3.6 T6a/T6b Reference Point Requirements .....	17
4.3.3.7 S6t Reference Point Requirements.....	17
4.3.3.8 T6ai/T6bi Reference Point Requirements .....	17
4.3.3.9 T7 Reference Point Requirements.....	18
4.3.3.10 Ns Reference Point Requirements.....	18
4.4 Network Elements .....	18
4.4.1 General.....	18
4.4.2 MTC-IWF .....	18
4.4.3 HSS/HLR.....	19
4.4.4 GGSN/P-GW .....	20
4.4.5 SGSN/MME/MSC.....	20
4.4.7 MTC AAA .....	20
4.4.8 Service Capability Exposure Function.....	21
4.4.9 Interworking SCEF.....	22
4.4.10 RAN Congestion Awareness Function .....	22
4.5 High Level Function.....	22
4.5.1 Device Triggering Function.....	22
4.5.2 PS-only Service Provision .....	23
4.5.3 Core Network assisted RAN parameters tuning .....	23
4.5.4 UE Power Saving Mode .....	23
4.5.5 Group Message Delivery .....	24
4.5.6 Monitoring Events .....	25
4.5.6.1 General .....	25
4.5.6.2 Monitoring Events via HSS and MME/SGSN .....	25
4.5.6.3 Monitoring Events via PCRF .....	25
4.5.6.4 Charging Principles .....	26
4.5.7 High latency communication .....	26
4.5.8 Support of informing about potential network issues .....	27
4.5.9 Resource management of background data transfer .....	27
4.5.10 E-UTRAN network resource optimizations based on communication patterns provided to the MME .....	27
4.5.11 Support of setting up an AS session with required QoS .....	28
4.5.12 Change the chargeable party at session set-up or during the session.....	28

4.5.13	Extended idle mode DRX .....	28
4.5.13.1	General .....	28
4.5.13.2	Paging for extended idle mode DRX in UTRAN .....	29
4.5.13.3	Paging for extended idle mode DRX in E-UTRAN .....	30
4.5.13.3.0	General .....	30
4.5.13.3.1	Hyper SFN, Paging Hyperframe and Paging Time Window length .....	30
4.5.13.3.2	Loose Hyper SFN synchronization .....	30
4.5.13.3.3	MME paging and paging retransmission strategy .....	31
4.5.14	Non-IP Data Delivery (NIDD) .....	31
4.6	Identifiers .....	32
4.6.1	General .....	32
4.6.2	External Identifier .....	32
4.7	Addressing .....	32
4.8	Security Aspects .....	32
4.8.1	Security Requirements .....	32
4.8.1.0	General .....	32
4.8.1.1	Void .....	32
4.8.1.2	Void .....	32
5	Functional Description and Information Flow .....	33
5.1	Control and user plane .....	33
5.1.1	Control Plane .....	33
5.1.1.1	HSS – MTC-IWF .....	33
5.2	Device triggering procedures .....	34
5.2.1	Device triggering procedure over Tsp .....	34
5.2.2	Trigger Delivery using T4 .....	35
5.2.3	Device triggering recall/replace procedures .....	36
5.2.3.1	Device trigger recall/replace procedure over Tsp .....	36
5.2.3.2	Replace procedure for trigger delivery using T4 .....	38
5.2.3.3	Recall procedure for trigger delivery using T4 .....	39
5.3	Information Storage .....	40
5.3.0	General .....	40
5.3.1	Trigger Information in SMS-SC (Triggering with T4) .....	40
5.3.2	SCEF .....	40
5.4	Security Procedures .....	41
5.4.0	General .....	41
5.4.1	Void .....	41
5.4.2	Void .....	41
5.5	Group message delivery procedures .....	42
5.5.1	Group message delivery using MBMS .....	42
5.6	Monitoring Procedures .....	44
5.6.1	Monitoring Event configuration and deletion via HSS .....	44
5.6.1.1	Configuration Procedure .....	44
5.6.1.2	Common Parameters of the Configuration Procedure .....	46
5.6.1.3	Specific Parameters for Monitoring Event: Loss of connectivity .....	46
5.6.1.4	Specific Parameters for Monitoring Event: UE reachability .....	47
5.6.1.5	Specific Parameters for Monitoring Event: Location Reporting .....	48
5.6.1.6	Specific Parameters for Monitoring Event: Change of IMSI-IMEI(SV) Association .....	49
5.6.1.7	Specific Parameters for Monitoring Event: Roaming Status .....	49
5.6.1.8	Specific Parameters for Monitoring Event: Communication failure .....	50
5.6.1.9	Specific Parameters for Monitoring Event: Availability after DDN Failure .....	50
5.6.2	Monitoring Events configuration and deletion directly at the MME/SGSN .....	50
5.6.2.1	Configuration Procedure .....	50
5.6.2.2	Common Parameters of the Configuration Procedure .....	51
5.6.2.3	Specific Steps for Monitoring Event: Number of UEs present in a geographic area .....	51
5.6.3	Reporting of Monitoring Events from the HSS or the MME/SGSN .....	52
5.6.3.1	Reporting Procedure .....	52
5.6.3.2	Reporting Event: Loss of connectivity .....	53
5.6.3.3	Reporting Event: UE reachability .....	53
5.6.3.4	Reporting Event: Location Reporting .....	53
5.6.3.5	Reporting Event: Change of IMSI-IMEI(SV) association .....	54
5.6.3.6	Reporting Event: Roaming Status .....	54

5.6.3.7	Reporting Event: Communication failure .....	54
5.6.3.8	Reporting Event: Availability after DDN failure .....	54
5.6.4	Monitoring events configuration and reporting via PCRF.....	54
5.6.4.1	Request of monitoring event reporting.....	54
5.6.4.2	Common Parameters of the request reporting procedure .....	55
5.6.4.3	Specific Parameters for Monitoring Event: Location Reporting .....	55
5.6.4.4	Specific Parameters for Monitoring Event: Communication Failure .....	56
5.6.5	Reporting of Monitoring Events from the PCRF .....	56
5.6.6	Monitoring Event configuration and deletion via HSS for roaming scenarios using an IWK-SCEF .....	57
5.6.6.1	Configuration Procedure .....	57
5.6.6.2	Common Parameters of the Configuration Procedure.....	59
5.6.6.3	Specific Parameters for Monitoring Event: Loss of connectivity .....	59
5.6.6.4	Specific Parameters for Monitoring Event: UE reachability .....	59
5.6.6.5	Specific Parameters for Monitoring Event: Location Reporting .....	59
5.6.6.6	Specific Parameters for Monitoring Event: Change of IMSI-IMEI(SV) Association.....	60
5.6.6.7	Specific Parameters for Monitoring Event: Roaming Status.....	60
5.6.6.8	Specific Parameters for Monitoring Event: Communication failure .....	60
5.6.6.9	Specific Parameters for Monitoring Event: Availability after DDN Failure.....	61
5.6.7	Monitoring Events configuration and deletion directly at the MME/SGSN for roaming scenarios .....	61
5.6.8	Reporting of Monitoring Events from the HSS or the MME/SGSN for roaming scenarios .....	61
5.6.8.1	Reporting Procedure.....	61
5.6.8.2	Reporting Event: Loss of connectivity .....	62
5.6.8.3	Reporting Event: UE reachability .....	62
5.6.8.4	Reporting Event: Location Reporting .....	62
5.6.8.5	Reporting Event: Change of IMSI-IMEI(SV) association .....	62
5.6.8.6	Reporting Event: Roaming Status .....	62
5.6.8.7	Reporting Event: Communication failure .....	62
5.6.8.8	Reporting Event: Availability after DDN failure .....	63
5.7	High latency communications procedures.....	63
5.7.1	Availability Notification after DDN Failure .....	63
5.7.1.1	General .....	63
5.7.1.2	Event Configuration .....	63
5.7.1.3	Notification .....	64
5.7.2	Notification using Monitoring Event "UE Reachability" .....	66
5.8	Procedure for Informing about Potential Network Issues .....	66
5.8.1	General.....	66
5.8.2	Request procedure for one-time or continuous reporting of network status .....	67
5.8.3	Report procedure for continuous reporting of network status.....	68
5.8.4	Removal procedure for continuous reporting of network status .....	69
5.9	Procedure for resource management of background data transfer.....	70
5.10	Communication Pattern parameters provisioning procedure.....	71
5.10.1	Communication Pattern parameters .....	71
5.10.2	Communication Pattern parameters provisioning to the MME .....	72
5.11	Setting up an AS session with required QoS procedure .....	74
5.12	Change the chargeable party at session set-up or during the session procedure.....	75
5.12.1	Set the chargeable party at session set-up.....	75
5.12.2	Change the chargeable party during the session .....	76
5.13	Non-IP Data Delivery procedures .....	77
5.13.1	T6a Connection Establishment .....	77
5.13.1.1	General .....	77
5.13.1.2	T6a Connection Establishment Procedure .....	77
5.13.2	NIDD Configuration .....	78
5.13.3	Mobile Terminated NIDD procedure.....	79
5.13.4	Mobile Originated NIDD procedure .....	81
5.13.5	T6a Connection Release .....	82
5.13.5.1	General .....	82
5.13.5.2	T6a Connection Release procedure.....	82
5.13.6	Serving node relocation procedure over T6a .....	82
5.13.6.1	General .....	82
5.13.6.2	Successful TAU procedure with T6a .....	83
5.13.7	Charging Principles.....	83

<b>Annex A (Informative):</b>	<b>MTC Deployment Scenarios .....</b>	<b>85</b>
<b>Annex B (Informative):</b>	<b>Void .....</b>	<b>87</b>
<b>Annex C (Informative):</b>	<b>Triggering with OMA Push .....</b>	<b>88</b>
C.1	General .....	88
C.2	Triggering flow using Service Loading.....	88
<b>Annex D (Informative):</b>	<b>Device triggering using direct model over user plane .....</b>	<b>90</b>
<b>Annex E (Informative):</b>	<b>Change history .....</b>	<b>91</b>
History .....		94

---

## Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## 1 Scope

The present document specifies architecture enhancements to facilitate communications with packet data networks and applications (e.g. Machine Type Communication (MTC) applications on the (external) network/MTC servers) according to the use cases and service requirements defined in TS 22.368 [2], TS 22.101 [3], and related 3GPP requirements specifications. Both roaming and non-roaming scenarios are covered.

The present document also specifies transmission of non-IP data via SCEF for the CIoT EPS Optimization.

---

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 22.368: "Service Requirements for Machine-Type Communications (MTC)".
- [3] 3GPP TS 22.101: "Service Aspects; Service Principles".
- [4] 3GPP TS 23.003: "Numbering, addressing and identification".
- [5] 3GPP TS 23.002: "Network architecture".
- [6] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2".
- [7] 3GPP TS 23.401: "General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access".
- [8] 3GPP TS 29.061: "Interworking between the Public Land Mobile Network (PLMN) supporting Packet Based services and Packet Data Networks (PDN)".
- [9] 3GPP TS 29.303: "Domain Name System Procedures; Stage 3".
- [10] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS); Stage 2".
- [11] 3GPP TS 23.272: "Circuit Switched (CS) fallback in Evolved Packet System (EPS); Stage 2".
- [12] 3GPP TS 23.040: "Technical realization of the Short Message Service (SMS)".
- [13] 3GPP TS 23.204: "Support of Short Message Service (SMS) over generic 3GPP Internet Protocol (IP) access; Stage 2".
- [14] 3GPP TR 23.039: "Interface Protocols for the Connection of Short Message Service Centers (SMSCs) to Short Message Entities (SMEs)".
- [15] IETF RFC 3588: "Diameter Base Protocol".
- [16] IETF RFC 4960: "Stream Control Transmission Protocol".
- [17] [WAP-168-ServiceLoad-20010731-a](#): "Service Loading".
- [18] [OMA-TS-Push\\_MO-V1\\_0-20110809-A](#): "OMA Push Management Object".