

ETSI TS 129 214 V14.4.0 (2017-07)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Policy and charging control over Rx reference point
(3GPP TS 29.214 version 14.4.0 Release 14)**



Reference

RTS/TSGC-0329214ve40

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.

All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	6
1 Scope	7
2 References	7
3 Definitions and abbreviations.....	9
3.1 Definitions	9
3.2 Abbreviations	10
4 Rx reference point	10
4.1 Overview	10
4.2 Rx reference model	11
4.3 Functional elements.....	11
4.3.1 AF	11
4.3.2 PCRF	11
4.4 PCC procedures over Rx reference point	12
4.4.1 Initial Provisioning of Session Information	12
4.4.2 Modification of Session Information	16
4.4.3 Gate Related Procedures	19
4.4.4 AF Session Termination	19
4.4.5 Subscription to Notification of Signalling Path Status	20
4.4.5a Provisioning of AF Signalling Flow Information	20
4.4.6 Traffic Plane Events.....	21
4.4.6.1 IP-CAN Session Termination.....	21
4.4.6.2 Service Data Flow Deactivation.....	21
4.4.6.3 Notification of Signalling Path Status	22
4.4.6.4 IP-CAN type change Notification	22
4.4.6.5 Access Network Charging Information Notification.....	22
4.4.6.6 Reporting Usage for Sponsored Data Connectivity	23
4.4.6.7 Reporting Access Network Information.....	23
4.4.6.8 Temporary Network Failure handling	24
4.4.6.9 PLMN information change Notification	24
4.4.7 P-CSCF Restoration Enhancement Support	25
4.4.8 Priority Sharing Request.....	25
4.4.9 Support for media component versioning	26
5 Rx protocol.....	26
5.1 Protocol support	26
5.2 Initialization, maintenance and termination of connection and session.....	27
5.3 Rx specific AVPs	27
5.3.0 General.....	27
5.3.1 Abort-Cause AVP.....	30
5.3.2 Access-Network-Charging-Address AVP	30
5.3.3 Access-Network-Charging-Identifier AVP.....	30
5.3.4 Access-Network-Charging-Identifier-Value AVP	31
5.3.5 AF-Application-Identifier AVP	31
5.3.6 AF-Charging-Identifier AVP	31
5.3.7 Codec-Data AVP	31
5.3.8 Flow-Description AVP	32
5.3.9 Flow-Number AVP.....	32
5.3.10 Flows AVP.....	32
5.3.11 Flow-Status AVP	33
5.3.12 Flow-Usage AVP.....	33
5.3.13 Specific-Action AVP	33

5.3.14	Max-Requested-Bandwidth-DL AVP	36
5.3.15	Max-Requested-Bandwidth-UL AVP	36
5.3.16	Media-Component-Description AVP	37
5.3.17	Media-Component-Number AVP	38
5.3.18	Media-Sub-Component AVP	38
5.3.19	Media-Type AVP	39
5.3.20	RR-Bandwidth AVP	39
5.3.21	RS-Bandwidth AVP	39
5.3.22	SIP-Forking-Indication AVP	39
5.3.23	Service-URN AVP	39
5.3.24	Acceptable-Service-Info AVP	40
5.3.25	Service-Info-Status-AVP	40
5.3.26	AF-Signalling-Protocol-AVP	40
5.3.27	Sponsored-Connectivity-Data AVP	40
5.3.28	Sponsor-Identity AVP	41
5.3.29	Application-Service-Provider-Identity AVP	41
5.3.30	MPS-Identifier AVP	41
5.3.31	Rx-Request-Type AVP	41
5.3.32	Min-Requested-Bandwidth-DL AVP	41
5.3.33	Min-Requested-Bandwidth-UL AVP	42
5.3.34	Required-Access-Info AVP	42
5.3.35	IP-Domain-Id AVP	42
5.3.36	GCS-Identifier AVP	42
5.3.37	Sharing-Key-DL AVP	42
5.3.38	Sharing-Key-UL AVP	42
5.3.39	Retry-Interval AVP	43
5.3.40	Sponsoring-Action AVP	43
5.3.41	Max-Supported-Bandwidth-DL AVP	43
5.3.42	Max-Supported-Bandwidth-UL AVP	43
5.3.43	Min-Desired-Bandwidth-DL AVP	43
5.3.44	Min-Desired-Bandwidth-UL AVP	43
5.3.45	MCPTT-Identifier AVP	43
5.3.46	Service-Authorization-Info AVP	44
5.3.47	Priority-Sharing-Indicator AVP	44
5.3.48	Media-Component-Status AVP	44
5.3.49	Content-Version AVP	44
5.3.50	AF-Requested-Data AVP	45
5.3.51	Pre-emption-Control-Info AVP	45
5.4	Rx re-used AVPs	45
5.4.0	General	45
5.4.1	Use of the Supported-Features AVP on the Rx reference point	49
5.5	Rx specific Experimental-Result-Code AVP values	52
5.5.1	Permanent Failures	52
5.5.2	Transient Failures	53
5.6	Rx messages	53
5.6.0	General	53
5.6.1	AA-Request (AAR) command	53
5.6.2	AA-Answer (AAA) command	54
5.6.3	Re-Auth-Request (RAR) command	54
5.6.4	Re-Auth-Answer (RAA) command	55
5.6.5	Session-Termination-Request (STR) command	55
5.6.6	Session-Termination-Answer (STA) command	56
5.6.7	Abort-Session-Request (ASR) command	56
5.6.8	Abort-Session-Answer (ASA) command	57
Annex A (normative): IMS Related P-CSCF Procedures over Rx		58
A.1	Provision of Service Information at P-CSCF	58
A.2	Enabling of IP Flows	60
A.2.0	General	60
A.2.1	Gate control procedures considering the P-Early-Media header field	60
A.2.2	Gate control procedures based on the configuration in the P-CSCF	62

A.3	Support for SIP forking	62
A.3.1	PCC rule provisioning for early media for forked responses	62
A.3.2	Updating the provisioned PCC rules at the final answer	63
A.4	Notification of AF Signalling Transmission Path Status	63
A.5	Indication of Emergency Registration and Session Establishment	64
A.6	Notification IP-CAN Type Change	64
A.7	Support for Early Session disposition SDP	65
A.7.1	General	65
A.7.2	Service Information Provisioning for Early Media	65
A.7.3	Updating the Provisioned Service Information when Dialogue is established	66
A.8	Provision of Signalling Flow Information at P-CSCF	66
A.9	Handling of MPS Session	67
A.10	Retrieval of network provided location information	67
A.10.1	General	67
A.10.2	Retrieval of network provided location information at originating P-CSCF for inclusion in SIP Request	67
A.10.3	Retrieval of network provided location information at originating P-CSCF for inclusion in SIP response confirmation	68
A.10.4	Retrieval of network provided location information at terminating P-CSCF	68
A.11	Handling of RAN/NAS release cause values	69
A.12	Resource Sharing	69
A.13	Handling of MCPTT priority call	70
A.13.1	General	70
A.13.2	Determination of MCPTT priority parameter values	70
A.14	Notification of PLMN Change	70
Annex B (normative): Flow identifiers: Format definition and examples		72
B.1	Format of a flow identifier	72
B.1.1	General	72
B.1.2	Derivation of Flow Identifiers from SDP	73
B.1.2.1	Standard Procedure	73
B.1.2.2	SDP with "early session" disposition type	73
B.2	Example 1	73
B.3	Example 2	74
B.4	Example 3 without media components	75
B.5	Example 4	76
Annex C (informative): Void		78
Annex D (normative): Monitoring Related SCEF Procedures over Rx		79
D.1	Monitoring events support, using SCEF procedures over Rx	79
Annex E (informative): Change history		80
History		83

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- Y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document provides the stage 3 specification of the Rx reference point for the present release. The functional requirements and the stage 2 specifications of the Rx reference point are contained in 3GPP TS 23.203 [2]. The Rx reference point lies between the Application Function and the Policy and Charging Rule Function. The Rx interface which is based on RESTful HTTP and XML is specified in 3GPP TS 29.201 [37].

Whenever it is possible the present document specifies the requirements for the protocol by reference to specifications produced by the IETF within the scope of Diameter. Where this is not possible, extensions to Diameter are defined within the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.203: "Policy and Charging Control architecture".
- [3] Void.
- [4] Void.
- [5] 3GPP TS 29.209: "Policy control over Gq interface", latest Rel-6 version.
- [6] Void.
- [7] 3GPP TS 29.211: "Rx Interface and Rx/Gx signalling flows", latest Rel-6 version.
- [8] 3GPP TS 29.212: "Policy and Charging Control (PCC); Reference points".
- [9] 3GPP TS 29.213: "Policy and Charging Control signalling flows and Quality of Service (QoS) parameter mapping".
- [10] Void.
- [11] IETF RFC 3556: "Session Description Protocol (SDP) Bandwidth Modifiers for RTP Control Protocol (RTCP) Bandwidth".
- [12] IETF RFC 4005: "Diameter Network Access Server Application".
- [13] IETF RFC 4566: "SDP: Session Description Protocol".
- [14] IETF RFC 4006: "Diameter Credit Control Application".
- [15] ETSI TS 183 017 v3.2.1: "Telecommunications and Internet Converged Services and Protocols for Advanced Networking (TISPAN); Resource and Admission Control: DIAMETER protocol for session based policy set-up information exchange between the Application Function (AF) and the Service Policy Decision Function (SPDF); Protocol specification".
- [16] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS); Stage 2".
- [17] 3GPP TS 24.229: "IP Multimedia Call Control Protocol based on SIP and SDP; Stage 3".