Manual of Petroleum Measurement Standards Chapter 3—Tank Gauging

Section 3—Standard Practice for Level Measurement of Liquid Hydrocarbons in Stationary Pressurized Storage Tanks by Automatic Tank Gauging

FIRST EDITION, JUNE 1996

REAFFIRMED, DECEMBER 2022



Manual of Petroleum Measurement Standards Chapter 3—Tank Gauging

Section 3—Standard Practice for Level Measurement of Liquid Hydrocarbons in Stationary Pressurized Storage Tanks by Automatic Tank Gauging

Measurement Coordination

FIRST EDITION, JUNE 1996

REAFFIRMED, MARCH 2017



SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations under local, state, or federal laws.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. Sometimes a one-time extension of up to two years will be added to this review cycle. This publication will no longer be in effect five years after its publication date as an operative API standard or, where an extension has been granted, upon republication. Status of the publication can be ascertained from the API Authoring Department [telephone (202) 682-8000]. A catalog of API publications and materials is published annually and updated quarterly by API, 200 Massachusetts Avenue, NW, Washington, DC 20001.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this standard or comments and questions concerning the procedures under which this standard was developed should be directed in writing to the director of the Authoring Department (shown on the title page of this document), American Petroleum Institute, 200 Massachusetts Avenue, NW, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

API standards are published to facilitate the broad availability of proven, sound engineering and operating practices. These standards are not intended to obviate the need for applying sound engineering judgment regarding when and where these standards should be utilized. The formulation and publication of API standards is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Washington, DC 20001.

FOREWORD

This publication covers standard practice for level measurement of liquid hydrocarbons on stationary pressurized storage tanks by automatic tank gauging, and supersedes all applicable sections of API Standard 2545, *Method of Gaging Petroleum and Petroleum Products* (October 1965).

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

Suggested revisions are invited and should be submitted to the director of the Exploration and Production Department, Measurement Coordination, American Petroleum Institute, 200 Massachusetts Avenue, NW, Washington, DC 20001.

CONTENTS

SECTION 3—STANDARD PRACTICE FOR LEVEL MEASUREMENT OF LIQUID HYDROCARBONS IN STATIONARY PRESSURIZED STORAGE TANKS BY AUTOMATIC TANK GAUGING	
1 SCOPE	1
2 REFERENCES	1
2.1 Standards	1
2.2 Safety Precautions	1
3 ACCURACY REQUIREMENT.	2
3.1 Inherent Error of ATGs	2
3.2 Calibration Prior to Installation	2
3.3 Error Caused by Installation and Operating Conditions	2
3.4 Use of AIGs in Custody Transfer Service	3
4 INCTALLATION OF ATC.	2
4 INSTALLATION OF AIGS	3 3
4.2 Mounting Location	3
4.3 Manufacturer's Requirements	3
4.4 Installation of ATGs	3
4.5 Still Pipe Design	5
5 INITIAL ADJUSTMENT AND FIELD VERIFICATION OF ATGs	7
5.1 Preparation	7
5.2 Initial Adjustment	7
5.3 Initial Field Verification	8 8
	0
0 OPERATION OF ATGS	8
7 MAINTENANCE OF ATGs	9
8 SUBSEQUENT VERIFICATION OF ATGs	9
8.1 General	9
8.2 Frequency of Subsequent Verification	9
8.4 Tolerance for Subsequent Verification of ATGs in Custody Transfer	9
8.5 Comparison of the ATG Readings From Current	-
and Previous Verifications	9
8.6 Adjustment in Subsequent Verification	9
9 DATA COMMUNICATION AND RECEIVING	9
Figures	
1—Installation of Intrusive ATG in a Pressurized Storage Sphere	
With Still Pipe	4
2—Installation of Intrusive ATG in a Pressurized Storage Sphere	
Using Guide Wires	5
3—Installation of Nonintrusive ATG in a Pressurized Storage Sphere	~
win Sull Pipe	0

(This page left intentionally blank)

Chapter 3—Tank Gauging

SECTION 3—STANDARD PRACTICE FOR LEVEL MEASUREMENT OF LIQUID HYDROCARBONS IN STATIONARY PRESSURIZED STORAGE TANKS BY AUTOMATIC TANK GAUGING

1 Scope

This standard provides guidance on the installation, calibration, and verification of automatic tank gauges (ATGs) used in custody transfer for measuring the level of liquid hydrocarbons having a Reid vapor pressure of 15 psi (103 kilopascals) or greater, stored in stationary, pressurized storage tanks. The standard also provides guidance on the requirements for data collection, transmission, and receiving.

This standard is not applicable to the following:

a. Conversion of tank level to liquid volume.

b. Measurement of free water or sediment lying under the liquid hydrocarbon.

c. Measurement of temperature, density, or sediment and water (S & W). These measurements are discussed in the API *Manual of Petroleum Measurement Standards* (MPMS), Chapters 7, 9, and 10.

d. Sampling for determination of the properties of the liquid hydrocarbon. This is discussed in API MPMS Chapter 8.

e. Detection of tank leaks.

f. ATGs used for inventory control and plant operations.

Note: Converting net vapor space volumes to equivalent liquid volumes or mass is described in API MPMS Chapter 12. (The section covering calculation of vapor to liquid equivalent was in preparation at the time this standard was written.)

This standard may involve hazardous materials, operations, and equipment. This standard does not purport to address all of the safety problems associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

2 References

This section is applicable to all types of ATGs for pressurized storage tanks. Safety precautions are listed separately from general precautions that affect accuracy or performance.

2.1 STANDARDS

Unless otherwise specified, the most recent editions or revisions of the following standards, codes, and specifications shall, to the extent specified herein, form a part of this standard.

API

Manual of Petroleum Measurement Standards Chapter 1, "Vocabulary" Chapter 2, "Tank Calibration"

- Chapter 3, "Tank Gauging"
- Chapter 7, "Temperature Determination"
- Chapter 8, "Sampling"
- Chapter 9, "Density Determination"
- Chapter 10, "Sediment and Water"
- Chapter 12, "Calculation of Petroleum Quantities"
- RP 500 Recommended Practice for Classification of Locations for Electrical Installations at Petroleum Facilities
- RP 2003 Protection Against Ignition Arising Out of Static, Lightning, and Stray Currents
- Std 2610 Design, Construction, Operation, Maintenance, and Inspection of Terminals and Tank Facilities

GPA^1

Std 8195 Standard for Converting Net Vapor Space Volumes to Equivalent Liquid Volumes

2.2 SAFETY PRECAUTIONS

The following recommended practices and guidelines on safety should be followed:

a. API RP 500 Recommended Practice for Classification of Locations for Electrical Installations at Petroleum Facilities.
b. API RP 2003 Protection Against Ignition Arising Out of Static, Lightning, and Stray Currents.

c. ISGOTT—International Safety Guide for Oil Tankers and Terminals.²

Other applicable safety codes and regulations should be complied with.

2.2.1 Electrical Safety

All electric equipment uses in ATGs for use in electrically classified areas should be appropriate to the classification of the area and should conform to appropriate national electrical safety standards (such as UL, FM, FCC, NEC).

2.2.2 Equipment Precautions

2.2.2.1 All of the ATG equipment should be capable of withstanding the pressure, temperature, and operating and environmental conditions likely to be encountered in the service.

¹Gas Processors Association, 6526 East 60th Street, Tulsa, Oklahoma 74145.

²Available from the Oil Companies International Forum, Portland House, Stag Place, London SW1E SBH, England.