

Technical Report on Capabilities of API Integral Flanges Under Combination of Loading—Phase II

API TECHNICAL REPORT 6AF2
FIFTH EDITION, APRIL 2013



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2013 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, D.C. 20005, standards@api.org.

Contents

	Page	
1	Scope	1
2	Introduction	2
3	Three-dimensional Finite Element Analysis	3
3.1	Finite Element Modeling	3
3.2	Finite Element Results	11
4	Two-dimensional Heat Transfer Analysis	18
4.1	Finite Element Modeling	18
4.2	Temperature Analysis Results	18
5	Limiting Criteria for Combined Loading	21
5.1	Introduction	21
5.2	Leakage Criterion	21
5.3	Stress Criterion	23
5.4	Development of Load Combination Charts	25
5.5	Results	26
6	Reanalysis of Failed Flanges	31
7	Effect of Lockdown Screw Holes on Strength	31
8	Conclusion and Recommendations	38
	Annex A—Comparison Between Prac 86-21 and Prac 88-21 Results	40
	Annex B—Load Combination Charts	45
Tables		
1	Nodal Temperatures for Typical Type 6BX Flanges	20
2	Adopted Stress Criteria	23
3	Flanges That Did Not Meet Makeup-only Criterion, Makeup = 52.5 ksi.	33
4	Flange Geometry Modifications to Meet ASME Criterion for 52.5 ksi Makeup	33
5	Lockdown Screw Holes	33
6	Effect of Lockdown Screw Holes on Flange Stiffnesses	34
7	Effect of Lockdown Screw Holes on Flange Combined Load Capability	34
8	Modification Coefficients for Bending Capacity at Zero Tension and Zero Pressure	34
A.1	Comparison for Type 6B Flanges	41
A.2	Comparison for Type 6BX Flanges	42
B.1	Makeup Values for Flanges with Stress Criterion Governing at Least for Part of the Range of the Load Combination	45
Figures		
1	A Typical Finite Element Model of Flange and Bolt Superelements	4
2	Unit Load Cases	5
3	Superelemental Hierarchy	7
4	Gasket Modeling	8
5	Typical Lotus 1-2-3 Worksheet for Calculating Equivalent Stresses Due to Applied Forces.	9
6	Equivalent Stresses Due to Applied Bending Moment.	10
7	Deflected Shape Due to Unit Makeup (1.0 ksi).	11
8	Deflected Shape Due to Unit Pressure	12
9	Deflected Shape Due to Unit Tension (1.0 kip).	12
10	Deflected Shape Due to Bending Moment (1.0 K.in.)	13

11	Maximum Shear Stress Contours Due to Unit Makeup	13
12	Maximum Shear Stress Contours Due to Unit Pressure	14
13	Maximum Shear Stress Contours Due to Unit Tension	14
14	Maximum Shear Stress Contours Due to Unit Bending Moment	15
15	Von Mises's Equivalent Stress Contours for 2 1/16 in. 3,000 psi Type 6B Flange Under 52.5 ksi Makeup and 6,000 psi Test Pressure.	15
16	Bolt Stress (σ_z) Contours for Unit Makeup	16
17	Bolt Stress (σ_z) Contours for Unit Pressure	16
18	Bolt Stress (σ_z) Contours for Unit Tension	17
19	Bolt Stress (σ_z) Contours for Unit Bending Moment	17
20	Typical Heat Conduction 2-D Mesh for Type 6BX Flanges	19
21	Typical Leakage Load Combination Charts for 52.5 ksi and 40 ksi Makeup Loads	22
22	Stress Linearization.	24
23	Critical Section Locations	25
24	Comparison Between 2-D and 3-D Results for Leakage Criteria for 2 1/16 in. 3,000 psi 6B Flange	27
25	Comparison Between 2-D and 3-D Results for Leakage Criteria for 16 3/4 in. 3,000 psi 6B Flange	27
26	Stress Limiting Criteria for 2 1/16 in. 3,000 psi 6B Flange	28
27	Stress Limiting Criteria for 16 3/4 in. 3,000 psi 6B Flange	28
28	Leakage Criteria with Temperature Effect for 2 1/16 in. 3,000 psi 6B Flange	29
29	Leakage Criteria with Temperature Effect for 16 3/4 in. 3,000 psi 6B Flange	29
30	Stress Criterion with Temperature Effect for 2 1/16 in. 3,000 psi 6B Flange	30
31	Stress Criterion with Temperature Effect for 16 3/4 in. 3,000 psi 6B Flange	30
32	Bolt Stress Contours for 5 1/8 in. 10,000 psi Type 6BX Flange	32
33	Bolt Stress Contours for 11 in. 10,000 psi Type 6BX Flange	32
34	Finite Element Model of Flange with Lockdown Screw Holes	35
35	Effect of Lockdown Screw Holes on Leakage Charts	36
36	Effect of Lockdown Screw Holes on Stress Charts	37
A.1	Hopper Chart (from ASME <i>Boiler and Pressure Vessel Code</i> , Appendix 4)	44

Technical Report on Capabilities of API Integral Flanges Under Combination of Loading—Phase II

1 Scope

The evaluation of the load carrying capacity of API 6A integral flanges is the objective of this work. The applied loading includes the end tension and bending moment in addition to the conventional rated pressure and makeup forces. The effect of a temperature difference corresponding to 250 °F on the inside and 30 °F on the outside was also evaluated.

Three-dimensional finite element meshes were generated for the Type 6B, and Type 6BX flanges. The bending moment load case required a model of one quarter of the flange which was built up from the smaller segments and the half-bolt superelements. The computer program SESAM was used to obtain the stresses at selected critical flange and hub sections and to determine the gasket reaction due to each of the four unit load cases and the temperature difference load case. Leakage criterion was defined as the load combination which reduces the initial makeup compressive forces in the gasket to zero. The stresses in each defined section were linearized in accordance with the ASME *Section VIII, Division 2*, procedure to determine the membrane and membrane-plus-bending stress intensities. These stress intensities were checked against the allowables specified in API 6A, and the limiting loads were determined. A computer program LCCP was written to carry out this code check and a LOTUS 1-2-3 Release 3 worksheet was used to plot the load combination charts.

The results of the analysis carried out indicate that the leakage criterion governs the capacity of the smaller flanges in the Type 6B flanges. Leakage was governing for up to 9 in. size flanges in both the 52.5 ksi and 40 ksi makeups for the 2000 psi pressure. Leakage was governing the 5 1/8 in. for the higher pressures. Leakage was also found to be governing all Type 6BX flanges for working pressures of up to 5,000 psi. For the 10,000 psi and 15,000 psi flanges, leakage governed only in the larger size range greater than 2 9/16 in. Leakage was governing in all the 20,000 psi API 6BX flanges. The leakage model adopted in this study employs several approximations that have not yet been evaluated. Therefore, the actual leakage forces, i.e. load combinations leading to leakage, may be considerably higher than assumed herein. In reality, the gasket only leaks when its energized capacity is exceeded.

The state of stress at the stress governing hub section under the combined loading of makeup, pressure, tension and bending moment is considered to be “secondary.” However, when pressure, tension, and bending moments are applied together with the necessary makeup to resist these actions without leakage, the state of stress is rendered “primary” and, therefore, the allowable stress intensities are halved. This does not seem to be consistent, and it may by far exceed the intention of the code. However, the oversight subcommittee preferred to adopt the conservative route, which may be overly conservative pending further evaluation. Therefore, it may be concluded that when the hub stresses are treated as primary, most flanges do not possess significant reserve strength beyond the leakage condition. In fact, if the leakage condition was somewhat conservative, the stress condition may become governing for most flanges.

The temperature difference of 250 °F internal and 30 °F external leads to increases in the load-carrying capacity of the flanges. This condition is caused by the compressive forces generated in the gasket due to this temperature difference, and the increase in the allowable stresses when the self-limiting temperature load condition is included. It is recommended that a 3-D finite element, nonlinear material and geometric models of approximately eight flanges be carried out to determine the actual failure mechanism that governs the behavior of these flanges. This includes the prediction of the response of the gasket under increasing load and a more accurate definition of the leakage mechanism. The elimination of the raised face does not significantly reduce the stresses in the hub which caused six Type 6B flanges to fail to meet the ASME criterion for makeup load only (52.5 ksi for 105 ksi bolting). The stress intensities were reduced only by about 5 % when the raised face was eliminated, increasing the thickness of the flange by about 10 %. The hub thickness for these flanges had to be increased by up to about 27 % of their existing thicknesses together with the elimination of the raised face.

The bolt stresses did not govern for any of the flanges analyzed. Bolt stresses are typically within approximately 67 % of their yield strength due to makeup, pressure, tension, and bending moment loads. The bolts are expected to be made up to half their yield. The stresses in the bolts due to temperature differences increase by about 5 ksi to 7 ksi, which is

about 6 % to 8 % of the bolt yield stress. The other load conditions (pressure, tension, and bending moments) increase bolt stress by twice the increase due to the temperature difference. Therefore, it is concluded that the bolts will not approach their limiting criterion under the investigated load conditions.

2 Introduction

The original design criteria, of which API flange dimensions are based, were developed in the late 1920s and 1930s by Waters prior to the advent of the recent powerful, computer technology and associated finite-element analysis programs. The original analysis methods were used successfully in defining the flange design and pressure rating but did not address external loading capabilities. The flange designs were based on surface stress calculations, which are appropriate for uniform-axis symmetric loading conditions as used for bolt loading and pressure. Determining the limiting conditions of flanges beyond that of pressure rating, where external loading is considered, requires knowledge of stresses as they are distributed through the thickness. Methods of calculating these stresses have been developed through the use of finite element programs, and have been applied in this technical report.

The criteria for design stress allowables of API 6A body, bonnet, inlet and outlet connections were established in the Fifteenth Edition. Conformance with the API 6A criteria requires stress linearization calculations based on the methodology established by ASME *Pressure Vessel Code, Section VIII, Division 2*. These stress allowables are defined in terms of stress distributions through the thickness and necessitate a more accurate means of calculating component stresses as provided by finite element analysis.

Therefore, it was the intent of PRAC 86-21 (API 6AF) and the present work to establish a better understanding of the stress distribution in these flanges under the effect of the combined actions of pressure, bending moment, tension, and the original bolt makeup of the flange. Thus, the flange capacities which meet the design stress allowables of API 6A are determined.

The pressure/bending moment/tension charts developed in this technical report provide the critical load combination limits for either ASME/API 6A stress criteria or to leakage. These charts are extremely useful for both designers and users of API flange connections where external load capacities are critical.

The results of the work conducted in this technical report indicate increased load-carrying capacity for several flanges based on separate stress-limiting criteria. These stress limiting charts were not provided separately in the original work of API 6AF, which combined them with leakage criteria. The three-dimensional model analyses of this study provide verification that axisymmetric finite elements results of flanges, as used in API 6AF, are conservative. Additionally, this study determined a few flanges to have less loading capacity than originally defined in API 6A for makeup loading, and thus, have been reduced to meet design requirements.

The specifications for flange designs of Type 6B and Type 6BX originated in API 6A but have extensive diversification into other areas, such as surface and subsea drilling equipment and subsea production equipment. The API specifications for these applications either duplicate the design or reference back to the API 6A document. Therefore, use of the charts provided within this technical report have a broad base application where external loading conditions are critical.

It should be noted that the work presented herein has several limitations due to the defined scope and the assumptions involved in the analysis: the effects of transverse shear and/or torsion were not considered; the results are for static loading only, no dynamic, fatigue, or fretting phenomenon were accounted for; no elevated temperature effects were considered in the thermal stress analysis performed, only steady-state heat conduction was applied; the results representing the onset of leakage are based on linear behavior assumptions and are therefore only applicable to the linear range of the gasket response; and the load-combination capacity charts given are not intended to replace critical evaluation of any particular connection in an application where the charts show the flange to be marginal. These charts are intended to be used only as general guidelines for design.

Subsequent to the completion of this work, the 5¹/₈ in. 15,000 psi flange was added to API 6A. This new flange was analyzed using the same basic methodology but with the ABAQUS general-purpose finite-element system, and using a