Pumps—Shaft Sealing Systems for Centrifugal and Rotary Pumps

API STANDARD 682 FOURTH EDITION, MAY 2014



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Users of this Standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, "shall" denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

	P	Page
1	Scope	1
2	Normative References.	1
3 3.1 3.2	Terms, Definitions, and Symbols	3
4 4.1 4.2 4.3	Sealing Systems	. 13 . 15
5 5.1 5.2	General	. 23
6 6.1 6.2	Design Requirements	. 23
7 7.1 7.2 7.3	Specific Seal Configurations Arrangement 1 Seals Arrangement 2 Seals Arrangement 3 Seals	. 48 . 49
8 8.1 8.2 8.3	Accessories	. 54 . 56
	Instrumentation General Temperature-indicating Gauges Thermowells Pressure Indicators Transmitters and Switches Level Indicators Flow Instruments Relief Valves Pressure Control Valves Pressure Amplifiers.	. 72 . 73 . 73 . 73 . 74 . 74 . 75
10.2 10.3	Inspection, Testing, and Preparation for Shipment	. 75 . 75 . 76
11.2 11.3	Data Transfer	. 81 . 82

		Page
Ann	ex A (informative) Recommended Seal Selection Procedure	83
Ann	ex B (informative) Typical Materials and Material Specifications for Seal Chamber and Mechanical Seal Components	111
Ann	ex C (informative) Mechanical Seals Datasheets	
	ex D (informative) Seal Codes	
	,	
	ex E (normative) Mechanical Seals Data Requirement Forms	
Ann	ex F (informative) Technical Tutorials and Illustrative Calculations	140
Ann	ex G (normative) Standard Piping Plans and Auxiliary Hardware	183
Ann	ex H (informative) Inspectors' Checklist for All Seals	230
Ann	ex I (normative) Seal Qualification Testing Protocol	231
Ribli	iography	254
J.Q.	. С. д	
Figu		
1	Seal Configurations	
2	Arrangement 1: One Seal per Cartridge Assembly	
3	Arrangement 2: Two Seals per Cartridge Assembly with a Liquid Buffer Fluid	
4	Arrangement 2: Two Seals per Cartridge Assembly with or Without a Gas Buffer Fluid	
5	Arrangement 3: Two Seals per Cartridge Assembly with a Liquid Barrier Fluid	
6	Arrangement 3: Two Seals per Cartridge Assembly with a Gas Barrier Fluid	
7	Arrangement 1 Type A Seals	
8	Arrangement 1 Type B Seals	
9	Arrangement 1 Type C Seals	
10	Retention of Seal Components in Vacuum Services and Arrangement 3 Inner Seal	
11	Seal Chamber Types	
12	Seal Chamber Register Concentricity	
13	Section Showing Seal Gland Plate Shoulder	
14	Seal Chamber Face Runout	
15	Mechanical Seal Piping Connections	
16	Plastic Plug with Center Tab and Example of Warning Tag	
17	Seal Chamber/Gland Plate for Vertical Pumps	
18	Mating Joint Gasket	
19	Seal Sleeve Runout	
20	Auxiliary Sleeve Arrangement	
21	Seal Sleeve Attachment by Shrink Disk	
22	Seal Sleeve Attachment by Split Ring	
23	Clamped Faces	
24	Distributed Flush Systems	
25	Attachment of Key Drives to Shaft	
26	Section Showing Containment-Seal Chamber Bushing for 2CW-CS and 2NC-CS Configurations.	
27	Seal Testing Sequence	
A.1 Δ 2	Seal Selection Logic	
4	LECOUR II SUZI ATTANOMONT SOIRCTION L'NOTT	7111

		Page
A.3	Conversion of mg/m3 to ppmv at 25 °C (77 °F) and Atmospheric Pressure	
A.4	Temperature Correction Factor for Figure A.3	
B.1	Relative PV Comparisons for Seal Face Combinations	121
F.1	Estimated Gas Leakage for 50 mm Shaft at 0.7 bar, Expressed in Normal Liters per Minute	142
F.2	Estimated Liquid (Water) Leakage for 50 mm Shaft at 2.75 bar, Expressed in Cubic	
	Centimeters per Minute	
F.3	Illustration of Alternative Vapor Pressure Margin Calculation Options	
F.4	Illustration of Vapor Pressure Margin Calculation Methods as Applied to Propane	
F.5	Illustration of Balance Ratio Measurement Points	
F.6	Gland Plate Model	156
F.7	System Model	
F.8	Pipe System Friction Curves	
F.9	Tubing System Friction Curves	
	, , , , , , , , , , , , , , , , , , , ,	
	Circulating Device Performance and System Resistance in Pipe System Curves	160
F.12	Typical Required Flush Flow for Arrangement 3 CW Seals Without Heat Soak Considered and a	
	Pumped Fluid Temperature of 54 °C (130 °F)	161
F.13	Typical Required Flush Flow for Arrangement 3 CW Seals with Heat Soak Considered and a	
	Pumped Fluid Temperature of 176 °C (350 °F)	161
F.14	Typical Required Flush Flow for Arrangement 3 CW Seals with Heat Soak Considered and a	400
- 4 -	Pumped Fluid Temperature of 260 °C (500 °F)	162
F.15	Typical Required Flush Flow for Arrangement 3CW Seals with Heat Soak Considered and a	400
E 4 0	Pumped Fluid Temperature of 371 °C (700 °F)	
	Calculation Points for Piping Plan 53A Systems	
	Pressure Alarm Without Temperature Bias	
	Barrier Liquid Pressure Versus Accumulator Gas Volume	
	Barrier Liquid Pressure Against Barrier Liquid Volume	
	Drive Collar Holding Capability	
G.1 G.2	·	
G.2 G.3	Equipment Symbols	
	Standard Seal Piping Plan 01Standard Seal Piping Plan 02	
G.4	Standard Seal Piping Plan 02	
G.5	Standard Seal Piping Plan 03	
	Standard Seal Piping Plan 12	
	Standard Seal Piping Plan 13	
	Standard Seal Piping Plan 13	
	Standard Seal Piping Plan 14	
	Standard Seal Piping Plan 22	
	Standard Seal Piping Plan 22Standard Seal Piping Plan 23	
	Standard Seal Piping Plan 23Standard Seal Piping Plan 31	
	Standard Seal Piping Plan 31Standard Seal Piping Plan 32	
	Standard Seal Piping Plan 32Standard Seal Piping Plan 41	
	Standard Seal Piping Plan 41	
	Standard Seal Piping Plan 51	
J. I /	J.G.I.UG.I.U. JEGI F IDIIIU FIGII J	. ZU I

		Page
G.18	Standard Seal Piping Plan 53A	203
G.19	Standard Seal Piping Plan 53B	205
G.20	Standard Seal Piping Plan 53C	. 207
G.21	Standard Seal Piping Plan 54	209
G.22	Standard Seal Piping Plan 55	. 210
G.23	Standard Seal Piping Plan 61	. 211
G.24	Standard Seal Piping Plan 62	. 212
G.25	Standard Seal Piping Plan 65A	. 213
G.26	Standard Seal Piping Plan 65B	. 214
G.27	Standard Seal Piping Plan 66A	. 215
G.28	Standard Seal Piping Plan 66B	. 216
G.29	Standard Seal Piping Plan 71	. 217
G.30	Standard Seal Piping Plan 72	. 218
G.31	Standard Seal Piping Plan 74	. 219
G.32	Standard Seal Piping Plan 75	. 221
G.33	Standard Seal Piping Plan 76	223
G.35	Standard External Barrier/Buffer Fluid Reservoir	. 225
G.36	Alternative External Barrier/Buffer Fluid Reservoir	. 226
G.37	Typical Installation of a Piping Plan 23 Circulation System	. 227
G.38	Typical Installation of a Barrier/Buffer Fluid Reservoir	. 228
H.1	Inspectors' Checklist	230
I.1	Water Test Parameters	. 244
1.2	Propane Test Parameters	245
1.3	Caustic (NaOH) Test Parameters	. 246
I.4	Mineral Oil Test Parameters for Applications Between 5 °C and 176 °C (23 °F and 348.8 °F)	247
1.5	Mineral Oil Test Parameters for Applications Between 176 °C and 400 °C (348.8 °F and 750 °F)	248
1.6	Seal Manufacturer Qualification Test Procedure	
1.7	Seal Manufacturer Qualification Test Procedure for Containment Seals	
1.8	Seal Manufacturer Qualification Test Procedure for Gas Barrier Seals	
1.9	Mechanical Seal Qualification Test Form (1CW, 2CW-CW, 3CW-FB, 3CW-FF, and 3CW-BB)	
I.10	Mechanical Seal Qualification Test Form (2CW-CS, 2NC-CS, 3NC-FF, 3NC-BB, and 3NC-FB)	253
Table	es	
1	Clearances Between Rotary and Stationary Components	28
2	Symbols and Size for Seal Chamber and Gland Plate Connections	33
3	Minimum Sleeve Thickness in the Area of Component-drive Set Screws	37
4	Minimum Requirements for Auxiliary Piping	. 57
5	Minimum Pipe Wall Thickness	58
6	Minimum Tubing Wall Thickness	58
7	Conditions Affecting Cooling Water System Design	. 61
8	Approximate Densities of Materials Found in Process Streams	. 63
9	Sizing of Bladder Accumulators	
10	Nameplate for Bladder Accumulator	69
A .1	R-phrase Grouping Table	. 105
A.2	H Statement Grouping Table	. 106

		Page
B.1	Materials Standards	112
B.2	Miscellaneous Materials Specifications	117
B.3	Typical Temperature Limits for Seal Face Materials	
B.4	Typical Temperature Limits for Secondary Seals	122
B.5	Typical Hardness Range for Selected Secondary Seals	125
D.1	Example of an Arrangement 1 Mechanical Seal Code	132
D.2	API 610 Mechanical Seal Code (Obsolete)	
F.1	Pipe and Tube Dimensions for System Loss Calculations	157
F.2	Typical Hardness Ranges for Set Screw Materials	
F.3	Typical Hardness Ranges for Pump Shaft Materials	
F.4	Estimated Sleeve Axial Loads	
I.1	Organization of Qualification Testing	233
1.2	Qualification Test Fluid and Pumped Fluid Selection Chart	237
1.3	Seal Qualification Test Parameters	241

Pumps—Shaft Sealing Systems for Centrifugal and Rotary Pumps

1 Scope

This standard specifies requirements and gives recommendations for sealing systems for centrifugal and rotary pumps used in the petroleum, natural gas, and chemical industries. See A.1.1 and A.1.2. It is the responsibility of the purchaser or seal vendor to ensure that the selected seal and auxiliaries are suitable for the intended service condition. It is applicable mainly for hazardous, flammable, and/or toxic services where a greater degree of reliability is required for the improvement of equipment availability and the reduction of both emissions to the atmosphere and life-cycle sealing costs. It covers seals for pump shaft diameters from 20 mm (0.75 in.) to 110 mm (4.3 in.).

This standard is also applicable to seal spare parts and can be referred to for the upgrading of existing equipment. A classification system for the seal configurations covered by this standard into categories, types, arrangements, and orientations is provided.

This standard is referenced normatively in API 610. It is applicable to both new and retrofitted pumps and to pumps other than API 610 pumps (e.g. ASME B73.1, ASME B73.2, and API 676 pumps).

This standard might also be referenced by other machinery standards such as other pumps, compressors, and agitators. Users are cautioned that this standard is not specifically written to address all of the potential applications that a purchaser may specify. This is especially true for the size envelope specified for API 682 seals. The purchaser and seal vendor shall mutually agree on the features taken from this standard and used in the application.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Recommended Practice 520 (all parts), Sizing, Selection, and Installation of Pressure-relieving Devices in Refineries

API Standard 526, Flanged Steel Pressure Relief Valves

API Standard 610, Centrifugal Pumps for Petroleum, Petrochemical and Natural Gas Industries

API Standard 614 Lubrication, Shaft-sealing and Control-oil Systems and Auxiliaries for Petroleum, Chemical, and Gas Industry Services

ASME V 1, ASME Boiler and Pressure Vessel Code, Section V, Non-destructive Examination

ASME VIII, ASME Boiler and Pressure Vessel Code, Section VIII, Rules for the Construction of Pressure vessels

ASME IX, ASME Boiler and Pressure Vessel Code, Section IX, Welding and Brazing Qualifications

ASME B1.1, Unified Inch Screw Threads (UN and UNR Thread Form)

ASME B1.20.1, Pipe Threads, General Purpose, Inch.

ASME B16.11, Forged Fittings, Socket-welding and Threaded

ASME B16.20, Metallic Gaskets for Pipe Flanges—Ring Joint, Spiral-wound, and Jacketed

¹ ASME International, 3 Park Avenue, New York, New York 10016-5990, www.asme.org.