

ETSI TS 103 176 V1.2.1 (2016-05)



Digital Audio Broadcasting (DAB); Rules of implementation; Service information features

European Broadcasting Union



Union Européenne de Radio-Télévision

Reference

RTS/JTC-DAB-78

Keywords

audio, broadcasting, coding, DAB, digital

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
© European Broadcasting Union 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.2 Abbreviations	10
4 Overview of service information FIGs.....	11
5 Service following	12
5.1 Introduction	12
5.1.0 General.....	12
5.1.1 Service linking information	13
5.1.2 OE Services	14
5.1.3 Frequency information.....	14
5.2 Service linking.....	14
5.2.0 General.....	14
5.2.1 Short form - Activation state and change event indication	15
5.2.2 Long form - Database definition.....	15
5.2.3 Linkage sets	15
5.2.4 Signalling a link	17
5.2.4.0 General	17
5.2.4.1 Defining and redefining a linkage set.....	17
5.2.4.2 Maintaining the linkage set	17
5.2.4.3 Changing the activation state of linkage sets	17
5.2.5 Receiver behaviour for a link.....	18
5.2.5.0 General	18
5.2.5.1 Reaction to CEI.....	18
5.2.5.2 Reaction to definition.....	18
5.2.5.3 Reaction to activation and deactivation.....	18
5.3 OE Services	19
5.3.0 General.....	19
5.3.1 Short form - Change event indication	19
5.3.2 Long form - Database definition.....	19
5.3.3 OE Services fields.....	19
5.3.4 Signalling.....	19
5.3.4.0 General	19
5.3.4.1 Defining and redefining the database	19
5.3.4.2 Maintaining the database.....	19
5.3.5 Receiver behaviour	20
5.3.5.0 General	20
5.3.5.1 Reaction to CEI.....	20
5.3.5.2 Reaction to definition.....	20
5.4 Frequency information	20
5.4.0 General.....	20
5.4.1 Short form - Change event indication	20
5.4.2 Long form - Database definition.....	20
5.4.3 Frequency information fields.....	20
5.4.4 Signalling.....	21
5.4.4.0 General	21
5.4.4.1 Defining and redefining the database	21
5.4.4.2 Maintaining the database.....	21

5.4.5	Receiver behaviour	21
5.4.5.0	General	21
5.4.5.1	Reaction to CEI	21
5.4.5.2	Reaction to definition	22
5.5	Transmission model	22
5.5.1	DAB / DAB service following	22
5.5.2	DAB / FM-RDS service following	22
5.6	Receiver Reference Model	23
5.6.0	General	23
5.6.1	Reception Monitoring	23
5.6.2	Information base	23
5.6.3	Service Following Process	24
5.6.3.1	Overview	24
5.6.3.2	Stage 1: Find same service	25
5.6.3.3	Stage 2: Follow hard links	25
5.6.3.4	Stage 3: Follow soft links	25
5.6.3.5	Handling of bearer system transitions	26
5.6.4	Stored services ("presets")	26
5.6.5	Linkage sets	27
5.6.6	Linkage set management	27
6	Service lists	29
6.1	Introduction	29
6.2	Managing ensemble changes	29
6.2.1	Describing an ensemble	29
6.2.2	What is the service list	29
6.2.3	Establishment of the service list	30
6.2.4	Maintenance of the service list	31
6.2.5	Signalling conventions	32
6.3	Adding service elements to an ensemble	32
6.3.1	Introduction	32
6.3.2	Signalling	33
6.3.2.1	Preparation phase	33
6.3.2.2	Reconfiguration phase	33
6.3.2.3	Consolidation phase	33
6.3.3	Receiver behaviour	34
6.3.3.1	General	34
6.3.3.2	Response to signalling	34
6.4	Removing service elements from an ensemble	34
6.4.1	Introduction	34
6.4.2	Signalling	35
6.4.2.1	Preparation phase	35
6.4.2.2	Reconfiguration phase	36
6.4.2.3	Consolidation phase	36
6.4.3	Receiver behaviour	37
6.4.3.1	General	37
6.4.3.2	Response to signalling	37
6.5	Changing the identity or source of a service	38
6.5.1	Introduction	38
6.5.2	Signalling	38
6.5.2.1	Preparation phase	38
6.5.2.2	Reconfiguration phase	39
6.5.2.3	Consolidation phase	39
6.5.3	Receiver behaviour	39
6.5.3.1	General	39
6.5.3.2	Response to signalling	40
6.6	Changing the label of a service element	41
6.6.1	Introduction	41
6.6.2	Signalling	41
6.6.3	Receiver behaviour	41
Annex A (informative):	Service following - use case examples	42

A.1	DAB to DAB link in Multi-Frequency Networks	42
A.1.1	Problem Description.....	42
A.1.2	Concept	42
A.1.3	Signalling	42
A.1.3.1	FIG0/6 Service linking information.....	42
A.1.3.2	FIG0/24 OE Services.....	42
A.1.3.3	FIG0/21 Frequency Information	42
A.1.4	Receiver Behaviour	43
A.1.4.1	Single tuner device.....	43
A.1.4.2	Dual tuner device	43
A.2	Linking to the same service on different ensembles	43
A.2.1	Problem Description.....	43
A.2.2	Concept	44
A.2.3	Signalling	44
A.2.3.1	FIG0/6 Service linking information.....	44
A.2.3.2	FIG0/24 OE Services.....	44
A.2.3.3	FIG0/21 Frequency Information	45
A.2.4	Receiver Behaviour	45
A.3	Linking regional variations of a service on different ensembles.....	45
A.3.1	Problem Description.....	45
A.3.2	Concept	46
A.3.3	Signalling	46
A.3.3.1	FIG0/6 Service linking information.....	46
A.3.3.2	FIG0/24 OE Services.....	49
A.3.3.3	FIG0/21 Frequency Information	50
A.3.4	Receiver Behaviour	50
A.4	Linking technology variations of a service on different ensembles	51
A.4.1	Problem Description.....	51
A.4.2	Concept	52
A.4.3	Signalling	52
A.4.3.1	FIG0/6 Service linking information.....	52
A.4.3.2	FIG0/24 OE Services.....	52
A.4.3.3	FIG0/21 Frequency Information	53
A.4.4	Receiver Behaviour	53
A.5	Soft linking of services.....	54
A.5.1	Problem Description.....	54
A.5.2	Concept	55
A.5.3	Signalling	55
A.5.3.1	FIG0/6 Service linking information.....	55
A.5.3.2	FIG0/24 OE Services.....	56
A.5.3.3	FIG0/21 Frequency Information	56
A.5.4	Receiver Behaviour	56
A.6	Linkage of DAB and FM-RDS services.....	57
A.6.1	Problem Description.....	57
A.6.2	Concept	57
A.6.3	Signalling	58
A.6.3.1	FIG0/6 Service linking information.....	58
A.6.3.2	FIG0/24 OE Services.....	58
A.6.3.3	FIG0/21 Frequency Information	58
A.6.4	Receiver Behaviour	58
A.7	Linkage of DAB and FM-RDS services with time varying network relationships.....	59
A.7.1	Problem Description.....	59
A.7.2	Concept	60
A.7.3	Signalling	60
A.7.3.1	FIG0/6 Service linking information.....	60
A.7.3.2	FIG0/24 OE Services.....	60
A.7.3.3	FIG0/21 Frequency Information	60
A.7.4	Receiver Behaviour	60

A.8	Preventing implicit linkage to FM-RDS	60
A.8.1	Problem Description.....	60
A.8.2	Concept	60
A.8.3	Signalling	61
A.8.3.1	FIG0/6 Service linking information.....	61
A.8.3.2	FIG0/24 OE Services.....	61
A.8.3.3	FIG0/21 Frequency Information.....	61
A.8.4	Receiver Behaviour	61
Annex B (informative):	Service following - Transition from existing implementations	62
Annex C (informative):	Service lists - use case examples.....	63
C.1	New service on air.....	63
C.1.1	Use case description	63
C.1.2	Concept	63
C.1.3	Signalling	63
C.1.3.1	Preparation phase.....	63
C.1.3.2	Reconfiguration phase	63
C.1.3.3	Consolidation phase.....	64
C.1.4	Receiver behaviour.....	64
C.2	Continuous service is removed (with transfer).....	64
C.2.1	Use case description	64
C.2.2	Concept	64
C.2.3	Signalling	64
C.2.3.1	Preparation phase.....	64
C.2.3.2	Reconfiguration phase	65
C.2.3.3	Consolidation phase.....	65
C.2.4	Receiver behaviour.....	65
C.3	New Part-time service on air.....	66
C.3.1	Use case description	66
C.3.2	Concept	66
C.3.3	Signalling	66
C.3.3.1	Preparation phase.....	66
C.3.3.2	Reconfiguration phase	67
C.3.3.3	Consolidation phase.....	67
C.3.4	Receiver behaviour.....	67
C.4	Part-time service is on-air.....	67
C.4.1	Use case description	67
C.4.2	Concept	67
C.4.3	Signalling	67
C.4.3.1	Preparation phase.....	67
C.4.3.2	Reconfiguration phase	68
C.4.3.3	Consolidation phase.....	68
C.4.4	Receiver behaviour.....	68
C.5	Part-time service is off-air.....	68
C.5.1	Use case description	68
C.5.2	Concept	68
C.5.3	Signalling	69
C.5.3.1	Preparation phase.....	69
C.5.3.2	Reconfiguration phase	69
C.5.3.3	Consolidation phase.....	69
C.5.4	Receiver behaviour.....	69
C.6	SIId change within an ensemble	69
C.6.1	Use case description	69
C.6.2	Concept	70
C.6.3	Signalling	70
C.6.3.1	Preparation phase.....	70
C.6.3.2	Reconfiguration phase	70

C.6.3.3	Consolidation phase	70
C.6.4	Receiver behaviour	71
C.7	Service moves to a new ensemble with SId change	71
C.7.1	Use case description	71
C.7.2	Concept	71
C.7.3	Signalling	72
C.7.3.1	Preparation phase	72
C.7.3.2	Reconfiguration phase	73
C.7.3.3	Consolidation phase	73
C.7.4	Receiver behaviour	74
Annex D (informative): Service lists - presentation.....		75
D.1	Entries in the service list	75
D.2	Handling of part-time service components.....	75
D.3	Automatic updates to the service list.....	75
D.4	Character sets in the service list	76
D.5	Sorting of the service list.....	76
D.6	Presentation of secondary service components	77
D.7	Updating an ensemble from one frequency to another.....	77
D.8	Handling of unavailable service elements.....	77
D.9	Combined service list from multiple bearer systems	78
Annex E (informative): Service lists - expected receiver behaviour		79
E.1	Domestic receiver implementations	79
E.1.1	Introduction	79
E.1.2	Addition of service elements	79
E.1.3	Removal of service elements.....	80
E.1.4	Changed identity or ensemble	81
E.1.5	Multi-tuner domestic receiver	81
Annex F (normative): Service Component Information		82
History		85

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by Joint Technical Committee (JTC) Broadcast of the European Broadcasting Union (EBU), Comité Européen de Normalisation ELECTrotechnique (CENELEC) and the European Telecommunications Standards Institute (ETSI).

NOTE 1: The EBU/ETSI JTC Broadcast was established in 1990 to co-ordinate the drafting of standards in the specific field of broadcasting and related fields. Since 1995 the JTC Broadcast became a tripartite body by including in the Memorandum of Understanding also CENELEC, which is responsible for the standardization of radio and television receivers. The EBU is a professional association of broadcasting organizations whose work includes the co-ordination of its members' activities in the technical, legal, programme-making and programme-exchange domains. The EBU has active members in about 60 countries in the European broadcasting area; its headquarters is in Geneva.

European Broadcasting Union
CH-1218 GRAND SACONNEX (Geneva)
Switzerland
Tel: +41 22 717 21 11
Fax: +41 22 717 24 81

The Eureka Project 147 was established in 1987, with funding from the European Commission, to develop a system for the broadcasting of audio and data to fixed, portable or mobile receivers. Their work resulted in the publication of European Standard, ETSI EN 300 401 [1], for DAB (see note 2) which now has worldwide acceptance.

NOTE 2: DAB is a registered trademark owned by one of the Eureka Project 147 partners.

The DAB family of standards is supported by World DAB, an organization with members drawn from broadcasting organizations and telecommunication providers together with companies from the professional and consumer electronics industry.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document defines rules of implementation for certain service information features. These rules have been developed to provide a reliable and consistent experience for digital radio listeners; they provide implementation details for how the Fast Information Channel (FIC) signalling is used and how receivers will interpret and behave in response to receiving the FIC signalling. The rules defined in the present document supersede the informative guidance given in ETSI TR 101 496 [i.1] for the Fast Information Groups (FIGs) contained herein. In addition, some clarifications are provided for ETSI EN 300 401 [1] where a number interpretations may appear equally valid: in each case this is mentioned specifically. Future versions of ETSI EN 300 401 [1] will be modified to include these clarifications.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 401: "Radio Broadcasting Systems; Digital Audio Broadcasting (DAB) to mobile, portable and fixed receivers".
- [2] ETSI TS 101 756: "Digital Audio Broadcasting (DAB); Registered Tables".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 101 496 (all parts): "Digital Audio Broadcasting (DAB); Guidelines and rules for implementation and operation".
- [i.2] ISO 10646: "Information technology -- Universal Coded Character Set (UCS)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Change Event Indication (CEI): set of FIG fields with particular values to indicate a change of database content for certain service information features