

ETSI TS 129 165 V13.4.0 (2016-04)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
Inter-IMS Network to Network Interface (NNI)
(3GPP TS 29.165 version 13.4.0 Release 13)**



Reference

RTS/TSGC-0329165vd40

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	7
1 Scope	8
2 References	8
3 Definitions, symbols and abbreviations	16
3.1 Definitions.....	16
3.2 Symbols.....	17
3.3 Abbreviations	17
4 Overview	18
5 Reference model for interconnection between IM CN subsystems	20
5.1 General	20
5.2 Functionalities performed by entities at the edge of the network	21
5.2.1 Interconnection Border Control Function (IBCF).....	21
5.2.2 Transition Gateway (TrGW).....	22
5.3 Identifying II-NNI traversal scenario	22
5.3.1 General.....	22
5.3.2 Mapping of the "iotl" SIP URI parameter to II-NNI traversal scenario	22
6 Control plane interconnection	23
6.1 Definition of Inter-IMS Network to Network Interconnection.....	23
6.1.1 SIP methods and header fields.....	23
6.1.1.1 General.....	23
6.1.1.2 SIP methods	23
6.1.1.3 SIP header fields	24
6.1.1.3.0 General	24
6.1.1.3.1 Trust and no trust relationship	24
6.1.1.3.2 Derivation of applicable SIP header fields from 3GPP TS 24.229 [5]	26
6.1.1.3.3 Applicability of SIP header fields on a roaming II-NNI.....	26
6.1.1.3.4 Applicability of SIP header fields on a non-roaming II-NNI	27
6.1.1.4 Notations of the codes	27
6.1.1.5 Modes of signalling.....	27
6.1.2 SDP protocol.....	27
6.1.2.1 General	27
6.1.3 Major capabilities	28
6.1.4 SIP message bodies.....	33
6.2 Control Plane Transport	35
6.2.1 General.....	35
6.3 SIP timers	35
7 User plane Interconnection.....	37
7.1 Media and Codec.....	37
7.2 User Plane Transport.....	37
8 Numbering, Naming and Addressing	38
8.1 Numbering, Naming and Addressing for SIP message	38
8.2 Numbering, Naming and Addressing for SDP	39
9 IP Version.....	39
10 Security.....	39
11 Charging	39

11.1	General	39
11.2	Inter-operator accounting	39
11.3	Transfer of IP multimedia service tariff information.....	40
12	Supplementary services associated with the IMS multimedia telephony communication service.....	41
12.1	General	41
12.2	Malicious Communication IDentification (MCID)	41
12.3	Originating Identification Presentation (OIP) and Originating Identification Restriction (OIR)	41
12.4	Terminating Identification Presentation (TIP) and Terminating Identification Restriction (TIR)	42
12.5	Anonymous Communication Rejection (ACR).....	42
12.6	Communication DIVersion (CDIV)	42
12.7	Communication Waiting (CW)	43
12.8	Communication HOLD (HOLD)	43
12.9	Message Waiting Indication (MWI).....	43
12.10	Communication Barring (CB)	44
12.10.1	Incoming Communication Barring (ICB).....	44
12.10.2	Outgoing Communication Barring (OCB).....	44
12.11	Completion of Communications to Busy Subscriber (CCBS).....	44
12.12	Completion of Communications by No Reply (CCNR).....	45
12.13	Explicit Communication Transfer (ECT)	45
12.13.1	Consultative and blind transfer	45
12.13.2	Assured transfer	46
12.14	Customized Alerting Tone (CAT).....	46
12.15	Customized Ringing Signal (CRS).....	46
12.16	Closed User Group (CUG)	47
12.17	Personal Network Management (PNM)	47
12.18	Three-Party (3PTY).....	47
12.19	Conference (CONF)	47
12.20	Flexible Alerting (FA).....	48
12.21	Announcements	48
12.21.1	General.....	48
12.21.2	Providing announcements during the establishment of a communication session.....	48
12.21.3	Providing announcements during an established communication session	49
12.21.4	Providing announcements when communication request is rejected.....	49
12.22	Advice Of Charge (AOC).....	49
12.23	Completion of Communications on Not Logged-in (CCNL)	50
12.24	Unstructured Supplementary Service Data (USSD)	50
13	Interoperability of IMS Centralized Services (ICS) over II-NNI.....	51
13.1	General	51
13.2	IMS Centralized Services (ICS)	51
14	Interoperability of IMS Service Continuity over II-NNI	52
14.1	General	52
14.2	PS to CS Single Radio Voice Call Continuity (SRVCC) and Single Radio Video Call Continuity (vSRVCC)	52
14.2.1	Basic PS to CS SRVCC	52
14.2.2	PS to CS SRVCC for calls in alerting phase.....	52
14.2.3	Using the ATCF based architecture	53
14.2.4	PS to CS SRVCC for originating calls in pre-alerting phase	53
14.2.5	PS to CS SRVCC with the MSC server assisted mid-call feature	53
14.3	Inter UE Transfer (IUT)	53
14.4	MSC server assisted mid-call feature	53
14.5	CS to PS Single Radio Voice Call Continuity (SRVCC)	54
14.5.1	Basic CS to PS SRVCC	54
14.5.2	CS to PS SRVCC for calls in alerting phase.....	55
14.5.3	CS to PS SRVCC with the assisted mid-call feature	55
14.6	PS to CS dual radio voice call continuity (DRVCC).....	55
14.6.1	Basic PS to CS DRVCC	55
14.6.2	PS to CS DRVCC with the assisted mid-call feature.....	55
14.6.3	PS to CS DRVCC for calls in alerting phase	56
14.6.4	PS to CS DRVCC for originating calls in pre-alerting phase	56
14.7	CS to PS Dual Radio Voice Call Continuity (DRVCC)	56

14.7.1	Basic CS to PS DRVCC	56
14.7.2	CS to PS DRVCC with the assisted mid-call feature.....	56
14.7.3	CS to PS DRVCC for calls in alerting phase	56
14.7.4	CS to PS DRVCC for originating calls in pre-alerting phase	57
14.8	PS to PS access transfer.....	57
15	Presence service	57
15.0	General	57
15.1	Subscription of presence information.....	57
15.2	Watcher subscribing to Presence List.....	58
15.3	Subscription to Watcher Information	58
15.4	Subscription to state changes in XML documents	59
15.5	Presence enhancements specified in Open Mobile Alliance (OMA) Release 1.1	59
15.5.1	General.....	59
15.5.2	OMA subscription of presence information.....	59
15.5.3	OMA watcher subscribing to Presence List.....	59
15.5.4	OMA subscription to Watcher Information	59
15.6	Presence enhancements specified in Open Mobile Alliance (OMA) Release 2.0	59
15.6.1	General.....	59
15.6.2	OMA subscription of presence information.....	60
15.6.3	OMA watcher subscribing to Presence List.....	60
15.6.4	OMA subscription to Watcher Information	60
15.6.5	Subscription to state changes in XML documents	61
15.6.6	Void	61
15.6.7	Void	61
16	Messaging service	61
16.1	General	61
16.2	Page-mode messaging	61
16.4	Session-mode messaging.....	62
16.5	Session-mode messaging conferences.....	62
17	Optimal Media Routeing	62
17.1	General	62
17.2	OMR related SDP attributes	62
17.3	IP realm names	62
18	Inter-UE transfer (IUT)	63
18.1	General	63
18.2	IUT without establishment of a collaborative session	63
18.3	IUT using a collaborative session.....	63
18.3.1	Collaborative session of participants of the same subscription.....	63
18.3.2	Establishment of a collaborative session during session setup	64
18.3.3	Assignment and transfer of control of a collaborative session.....	64
18.3.4	Collaborative session of participants of different subscriptions	64
18.4	Session replication / media replication	65
18.4.1	Pull mode	65
18.4.2	Push mode.....	65
19	Roaming Architecture for Voice over IMS with Local Breakout	65
20	Delivery of Media Resource Broker address information.....	66
21	Overload control.....	66
21.1	General	66
21.2	Feedback based mechanism	66
21.3	The load filter mechanism.....	67
22	Delivery of original destination identity	67
23	Telepresence using IMS	67
24	Barring of premium rate numbers	67
25	P-CSCF restoration	67
25.1	General	67

25.2	PCRF based P-CSCF restoration.....	68
25.3	HSS based P-CSCF restoration	68
26	Resource sharing	68
27	Service access number translation.....	68
28	Mission Critical Push-To-Talk (MCPTT)	68
28.1	General	69
28.2	Interoperability of MCPTT communication service over II-NNI.....	69
28.2.1	MCPTT session establishment.....	69
28.2.2	MBMS transmission usage and location procedures	70
28.2.3	Affiliation procedure.....	70
Annex A (informative):	Summary of SIP header fields	71
Annex B (informative):	Dynamic view of SIP header fields within SIP messages	75
B.1	Scope	75
B.2	Methodology	75
B.3	ACK method	77
B.4	BYE method.....	78
B.5	CANCEL method.....	81
B.6	INFO method.....	82
B.7	INVITE method.....	85
B.8	MESSAGE method	90
B.9	NOTIFY method	93
B.10	OPTIONS method	96
B.11	PRACK method.....	99
B.12	PUBLISH method	102
B.13	REFER method	105
B.14	REGISTER method.....	109
B.15	SUBSCRIBE method	112
B.16	UPDATE method	115
Annex C (informative):	The list of option items for II-NNI	119
C.1	Scope	119
C.2	Format of option item table	119
C.3	Option item table.....	119
C.3.0	Supported II-NNI traversal scenarios	119
C.3.1	Option item table common to roaming, non-roaming II-NNI and loopback traversal scenario	120
C.3.2	Option item table specific to roaming II-NNI	127
C.3.3	Option item table specific to non-roaming II-NNI and loopback traversal scenario	130
Annex D:	Change history.....	133
History	135	

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The objective of this document is to address the Inter-IMS Network to Network Interface (II-NNI) consisting of Ici and Izi reference points between IMS networks in order to support end-to-end service interoperability.

The present document addresses the issues related to control plane signalling (3GPP usage of SIP and SDP protocols, required SIP header fields) as well as other interconnecting aspects like security, numbering/naming/addressing and user plane issues as transport protocol, media and codecs actually covered in a widespread set of 3GPP specifications. A profiling of the Inter-IMS Network to Network Interface (II-NNI) is also provided.

Charging aspects are addressed as far as SIP signalling is concerned.

SIP signalling traversing the NNI between a CSCF and MRB, e.g. for media control or Voice Interworking with Enterprise IP-PBX, and SIP signalling traversing the NNI on the Mr interface between the CSCF and the MRFC, or on the Mr' interface between the AS and MRFC, or on the Rc interface between AS and MRB is not considered in the present release of this specification.

SIP signalling traversing the NNI between an application server and the remaining IMS functional entities (e.g. for MCPTT interface SIP-2 in figure 7.3.1-2 in 3GPP TS 23.179 [200]) is not considered in the present release of this specification.

SIP signalling traversing the NNI between an ISC gateway and an AS in an enterprise network, e.g. for media control and voice interworking with enterprise IP-PBX, on the ISC interface between the ISC gateway and the enterprise network is not considered in the present release of this specification.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] IETF RFC 791: "Internet Protocol".
- [3] 3GPP TS 23.002: "Network architecture".
- [4] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS); Stage 2".
- [5] 3GPP TS 24.229: "Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".
- [6] 3GPP TR 24.930: "Signalling flows for the session setup in the IP Multimedia core network Subsystem (IMS) based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".
- [7] IETF RFC 2460: "Internet Protocol, Version 6 (IPv6) Specification".
- [8] 3GPP TS 29.162: "Interworking between the IM CN subsystem and IP networks".
- [9] 3GPP TS 22.228: "Service requirements for the IP multimedia core network subsystem".
- [10] 3GPP TS 33.210: "3G security; Network Domain Security (NDS); IP network layer security".