

ETSI TS 148 008 V13.0.0 (2016-01)



**Digital cellular telecommunications system (Phase 2+);
Mobile Switching Centre - Base Station system (MSC-BSS)
interface;
Layer 3 specification
(3GPP TS 48.008 version 13.0.0 Release 13)**



Reference

RTS/TSGG-0248008vd00

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope	12
1.1 References	12
1.2 Definitions and Abbreviations.....	14
2 Application to interface structures	15
2.1 The BSS Operation and Maintenance Application Part	15
2.2 The Direct Transfer Application Part	15
2.3 The BSS Management Application Part.....	16
2.4 Handling of abnormal events related to the BSSAP Header	16
3 The BSS Management Application Part	17
3.1 BSSMAP Procedures	17
3.1.1 Assignment	17
3.1.1.1 Successful Operation.....	18
3.1.1.2 Assignment Failure	21
3.1.1.3 Abnormal Conditions	22
3.1.2 Blocking and Unblocking	22
3.1.2.1 Successful Operation.....	23
3.1.2.2 Abnormal Conditions	24
3.1.2.2.1 Applying to the Single Circuit Block Procedure	24
3.1.2.2.2 Applying to the Circuit Group Block Procedure	24
3.1.3 Resource Indication	25
3.1.3.1 Successful Operation.....	26
3.1.4 Reset	27
3.1.4.1 Global Reset Procedure.....	27
3.1.4.1.1 Reset at the BSS	27
3.1.4.1.2 Reset at the MSC	27
3.1.4.1.3 Abnormal Conditions	28
3.1.4.1.3.1 Abnormal Condition at the BSS.....	28
3.1.4.1.3.2 Abnormal Condition at the MSC	28
3.1.4.2 Reset Circuit.....	28
3.1.4.2.1 Reset Circuit at the BSS	28
3.1.4.2.2 Reset Circuit at the MSC	28
3.1.4.2.3 Abnormal conditions	28
3.1.4.3 Reset IP Resource	29
3.1.4.3.1 Reset IP Resource procedure initiated by the BSS	29
3.1.4.3.2 Reset IP Resource procedure initiated by the MSC.....	29
3.1.4.3.3 Abnormal conditions	29
3.1.5 External Handover	30
3.1.5.1 Handover Required Indication	30
3.1.5.1.1 Generation of the HANOVER REQUIRED message	31
3.1.5.1.2 Abnormal conditions for DTM Handover	33
3.1.5.2 Handover Resource allocation	34
3.1.5.2.1 Operation of the procedure	34
3.1.5.2.2 Handover Resource Allocation Failure	38
3.1.5.2.3 Abnormal conditions	39
3.1.5.3 Handover execution	39
3.1.5.3.1 Operation of the procedure	40
3.1.5.3.2 Handover Failure	41
3.1.5.3.3 Abnormal Conditions	42
3.1.5a Handover from GSM to another System.....	42
3.1.5a.1 Generation of the HANOVER REQUIRED message for intersystem handover	43

3.1.5a.2	Inter-System Handover Resource Allocation Failure.....	44
3.1.5a.3	Intersystem handover Execution	45
3.1.5a.4	Inter System Handover Failure	46
3.1.5a.5	Abnormal Conditions	46
3.1.5b	Handover from another system to GSM	46
3.1.5b.1	General	46
3.1.5b.2	Inter-System Handover Resource Allocation.....	47
3.1.5c	BSS Internal Handover with MSC support.....	47
3.1.5c.1	Internal Handover Preparation	47
3.1.5c.1.1	Internal Handover Required Reject	48
3.1.5c.2	Internal Handover Execution	48
3.1.5c.2.1	Internal Handover failure.....	49
3.1.5c.2.2	Abnormal Conditions	49
3.1.5c.3	Internal Handover Enquiry	50
3.1.6	Internal Intra-Cell Handover Procedure.....	50
3.1.7	Internal Inter-Cell Handover Procedure.....	51
3.1.8	Handover Candidate Enquiry.....	51
3.1.8.1	Successful Operation.....	52
3.1.8.2	Abnormal conditions	52
3.1.9	Release of Radio Resource And Terrestrial Resource	52
3.1.9.1	Release Due To Transaction Completion.....	52
3.1.9.1a	Release of radio resources and the terrestrial resources for VGCS/VBS calls:.....	53
3.1.9.2	Release due to BSS generated reason	53
3.1.9.3	Release due to successful handover	55
3.1.9.4	Release due to uplink release	55
3.1.10	Paging	55
3.1.11	Trace Invocation	55
3.1.12	Flow Control.....	56
3.1.12.1	Philosophy.....	56
3.1.12.2	Processor Overload at the MSC	56
3.1.12.3	Processor/CCCH overload at the BSS	57
3.1.12.4	Message throughput congestion	57
3.1.13	Classmark Handling Procedures	57
3.1.13.1	Classmark request procedure	57
3.1.13.2	Classmark updating procedure	57
3.1.14	Cipher Mode Control	57
3.1.14.1	Successful Operation.....	57
3.1.14.2	Abnormal Conditions	58
3.1.15	General SCCP Abnormal Conditions	58
3.1.16	Initial MS message.....	59
3.1.17	Queuing Indication	59
3.1.17.1	Operation of the procedure in case of assignment procedure.....	59
3.1.17.2	Operation of the procedure in case of hand-over resource allocation procedure	60
3.1.18	Data Link Control SAPI not Equal to "0"	60
3.1.18.1	Data link set up across the radio interface.....	60
3.1.18.1.1	MS to MSC direction.....	60
3.1.18.1.2	MSC to MS Direction.....	60
3.1.18.2	Choice of the signalling link	60
3.1.19	BSSMAP Error Handling	61
3.1.19.1	Definitions of Types of Information Elements.....	61
3.1.19.2	Erroneous Events	62
3.1.19.3	Non-erroneous Events.....	62
3.1.19.4	Other Events.....	62
3.1.19.5	Appropriate Error Message and Cause Value	63
3.1.19.6	Unequipped Circuit Identification Code	63
3.1.19.7	Field Elements.....	64
3.1.20	Load Indication Procedure.....	64
3.1.20.1	Operation of the procedure.....	65
3.1.21	Voice group call service and voice broadcast service call set-up and resource assignment	65
3.1.21.1	Successful operation.....	66
3.1.21.2	VGCS/VBS call set-up abnormal cases	66
3.1.21.3	VGCS/VBS call set-up failure	66

3.1.22	Voice group call service and voice broadcast service Assignment procedure	66
3.1.22.1	Successful operation.....	67
3.1.22.2	VGCS/VBS Assignment abnormal cases.....	69
3.1.22.3	VGCS/VBS Assignment failure.....	70
3.1.22.4	VGCS/VBS Queuing Indication	71
3.1.23	(void)	71
3.1.24	Voice group call uplink control procedure - talker priority not supported by the network.....	71
3.1.24.1	Uplink allocation procedure.....	71
3.1.24.1.1	Successful uplink allocation operation.....	72
3.1.24.1.2	Unsuccessful uplink allocation operation.....	72
3.1.24.2	Uplink release procedure.....	72
3.1.24.3	Uplink seize procedure.....	72
3.1.24a	Voice group call uplink control procedure - talker priority supported by the network.....	72
3.1.24.a.1	General.....	72
3.1.24a.2	Uplink allocation procedure.....	73
3.1.24a.2.1	Successful uplink allocation operation	73
3.1.24a.2.1.1	Normal Priority Request	73
3.1.24a.2.1.2	Privileged or Emergency Priority Request via Uplink Access procedure.....	73
3.1.24a.2.1.3	Privileged or Emergency Priority Request via Priority Uplink Request procedure	74
3.1.24a.2.2	Unsuccessful uplink allocation operation	74
3.1.24a.2.2.1	Normal Priority Uplink Request	74
3.1.24a.2.2.2	Privileged or Emergency Uplink Request via Uplink Access procedure.....	74
3.1.24a.2.2.3	Privileged or Emergency Uplink Request via Priority Uplink Request procedure	75
3.1.24a.3	Uplink release procedure.....	75
3.1.24a.4	Uplink seize procedure.....	75
3.1.24a.5	Emergency Reset procedure via UPLINK ACCESS message	75
3.1.24a.5.1	Unsuccessful	75
3.1.24a.6	Emergency Reset procedure via PRIORITY UPLINK REQUEST message	75
3.1.24a.6.1	Unsuccessful	75
3.1.24b	Talker Information.....	76
3.1.24c	SMS to ongoing VGCS call all.....	76
3.1.24d	Distributing application-specific data to ongoing VGCS call.....	76
3.1.25	PDSS1 flow control	76
3.1.26	Circuit re-selection procedure	77
3.1.27	LSA handling.....	77
3.1.28	Location Acquisition.....	77
3.1.28.1	(void).....	78
3.1.28.2	Location request	78
3.1.28.2.1	Successful Operation.....	78
3.1.28.2.2	Unsuccessful Operation	79
3.1.28.2.3	Abnormal cases	79
3.1.28.2.4	Overload	79
3.1.29	Connectionless Information Transfer procedure	79
3.1.29.1	Unsuccessful Operation.....	79
3.1.29.2	Abnormal cases	79
3.1.29.3	Segmentation	79
3.1.30	Common ID	80
3.1.31	VGCS/VBS Cell Re-established - no A-interface link sharing	80
3.1.32	Rerouting procedure in case of MOCN configuration for network sharing	80
3.1.32.1	General	80
3.1.32.2	Reroute command	81
3.1.32.3	Reroute complete	82
3.1.32.4	Abnormal Conditions	82
3.1.32a	Rerouting procedure in case of GWCN configuration for network sharing	83
3.1.32a.1	General	83
3.1.33	Local Call Local Switch	85
3.1.33.1	General	85
3.1.33.2	Local switch establishment	85
3.1.33.2.1	Call Leg Correlation	85
3.1.33.2.2	Successful Operation	85
3.1.33.2.3	Unsuccessful Operation	86
3.1.33.3	Local switch break	86

3.1.33.3.1	Local switching break request from MSC	86
3.1.33.3.2	Local switching break initiated by BSS.....	86
3.1.33.3.3	Local Switching break at Handover	87
3.1.33.4	Local switch prevention	87
3.1.33.5	LCLS Notification.....	87
3.1.34	MS Registration Enquiry	87
3.1.34.1	General	87
3.1.34.2	Registration enquiry.....	88
3.1.34.3	Registration response	88
3.2	Message Formats and Coding	88
3.2.1	Message Contents	91
3.2.1.1	ASSIGNMENT REQUEST	91
3.2.1.2	ASSIGNMENT COMPLETE.....	92
3.2.1.3	ASSIGNMENT FAILURE	94
3.2.1.4	BLOCK	95
3.2.1.5	BLOCKING ACKNOWLEDGE	95
3.2.1.6	UNBLOCK	95
3.2.1.7	UNBLOCKING ACKNOWLEDGE	95
3.2.1.8	HANDOVER REQUEST	96
3.2.1.9	HANDOVER REQUIRED	99
3.2.1.10	HANDOVER REQUEST ACKNOWLEDGE.....	101
3.2.1.11	HANDOVER COMMAND	102
3.2.1.12	HANDOVER COMPLETE	102
3.2.1.13	HANDOVER SUCCEEDED.....	103
3.2.1.14	HANDOVER CANDIDATE ENQUIRE	103
3.2.1.15	HANDOVER CANDIDATE RESPONSE	103
3.2.1.16	HANDOVER FAILURE	103
3.2.1.17	RESOURCE REQUEST	105
3.2.1.18	RESOURCE INDICATION	105
3.2.1.19	PAGING	106
3.2.1.20	CLEAR REQUEST	106
3.2.1.21	CLEAR COMMAND	107
3.2.1.22	CLEAR COMPLETE.....	107
3.2.1.23	RESET	107
3.2.1.24	RESET ACKNOWLEDGE	108
3.2.1.25	HANDOVER PERFORMED	109
3.2.1.26	OVERLOAD.....	110
3.2.1.27	MSC INVOKE TRACE	110
3.2.1.28	BSS INVOKE TRACE	110
3.2.1.29	CLASSMARK UPDATE.....	111
3.2.1.30	CIPHER MODE COMMAND	111
3.2.1.31	CIPHER MODE COMPLETE.....	111
3.2.1.32	COMPLETE LAYER 3 INFORMATION.....	112
3.2.1.33	QUEUEING INDICATION.....	112
3.2.1.34	SAPI "n" REJECT.....	113
3.2.1.35	(void).....	113
3.2.1.36	(void).....	113
3.2.1.37	HANDOVER REQUIRED REJECT	113
3.2.1.38	RESET CIRCUIT	114
3.2.1.39	RESET CIRCUIT ACKNOWLEDGE.....	114
3.2.1.40	HANDOVER DETECT	114
3.2.1.41	CIRCUIT GROUP BLOCK.....	114
3.2.1.42	CIRCUIT GROUP BLOCKING ACKNOWLEDGE.....	115
3.2.1.43	CIRCUIT GROUP UNBLOCK	115
3.2.1.44	CIRCUIT GROUP UNBLOCKING ACKNOWLEDGE	115
3.2.1.45	CONFUSION	115
3.2.1.46	CLASSMARK REQUEST	116
3.2.1.47	UNEQUIPPED CIRCUIT.....	116
3.2.1.48	CIPHER MODE REJECT.....	116
3.2.1.49	LOAD INDICATION	117
3.2.1.50	VGCS/VBS SETUP	117
3.2.1.51	VGCS/VBS SETUP ACK.....	117

3.2.1.52	VGCS/VBS SETUP REFUSE	118
3.2.1.53	VGCS/VBS ASSIGNMENT REQUEST	118
3.2.1.54	VGCS/VBS ASSIGNMENT RESULT	119
3.2.1.55	VGCS/VBS ASSIGNMENT FAILURE	119
3.2.1.56	VGCS/VBS QUEUING INDICATION	120
3.2.1.57	UPLINK REQUEST	120
3.2.1.58	UPLINK REQUEST ACKNOWLEDGE	121
3.2.1.59	UPLINK REQUEST CONFIRMATION	121
3.2.1.59a	UPLINK APPLICATION DATA	121
3.2.1.60	UPLINK RELEASE INDICATION	121
3.2.1.61	UPLINK REJECT COMMAND	122
3.2.1.62	UPLINK RELEASE COMMAND	122
3.2.1.63	UPLINK SEIZED COMMAND	122
3.2.1.64	SUSPEND	122
3.2.1.65	RESUME	123
3.2.1.66	CHANGE CIRCUIT	123
3.2.1.67	CHANGE CIRCUIT ACKNOWLEDGE	123
3.2.1.68	Common ID	123
3.2.1.69	LSA INFORMATION	124
3.2.1.70	(void)	124
3.2.1.71	PERFORM LOCATION REQUEST	124
3.2.1.72	PERFORM LOCATION RESPONSE	125
3.2.1.73	PERFORM LOCATION ABORT	125
3.2.1.74	CONNECTIONLESS INFORMATION	125
3.2.1.75	CHANNEL MODIFY REQUEST	125
3.2.1.76	EMERGENCY RESET INDICATION	126
3.2.1.77	EMERGENCY RESET COMMAND	126
3.2.1.78	VGCS ADDITIONAL INFORMATION	126
3.2.1.79	VGCS/VBS AREA CELL INFO	126
3.2.1.80	VGCS/VBS ASSIGNMENT STATUS	126
3.2.1.81	VGCS SMS	127
3.2.1.82	NOTIFICATION DATA	128
3.2.1.83	INTERNAL HANDOVER REQUIRED	128
3.2.1.84	INTERNAL HANDOVER REQUIRED REJECT	129
3.2.1.85	INTERNAL HANDOVER COMMAND	129
3.2.1.86	INTERNAL HANDOVER ENQUIRY	130
3.2.1.87	RESET IP RESOURCE	130
3.2.1.88	RESET IP RESOURCE ACKNOWLEDGE	130
3.2.1.89	REROUTE COMMAND	131
3.2.1.90	REROUTE COMPLETE	131
3.2.1.91	LCLS-CONNECT-CONTROL	131
3.2.1.92	LCLS-CONNECT-CONTROL-ACK	131
3.2.1.93	LCLS-NOTIFICATION	132
3.2.1.94	MS REGISTRATION ENQUIRY	132
3.2.1.95	MS REGISTRATION ENQUIRY RESPONSE	132
3.2.2	Signalling element coding	132
3.2.2.0	General	132
3.2.2.1	Message Type	137
3.2.2.2	Circuit Identity Code	138
3.2.2.3	Connection Release Requested	139
3.2.2.4	Resource Available	139
3.2.2.5	Cause	140
3.2.2.6	IMSI	142
3.2.2.7	TMSI	143
3.2.2.8	Number Of MSs	143
3.2.2.9	Layer 3 Header Information	143
3.2.2.10	Encryption Information	144
3.2.2.11	Channel Type	144
3.2.2.12	Periodicity	150
3.2.2.13	Extended Resource Indicator	151
3.2.2.14	Total Resource Accessible	151
3.2.2.15	LSA Identifier	152

3.2.2.16	LSA Identifier List	152
3.2.2.17	Cell Identifier	153
3.2.2.18	Priority	156
3.2.2.19	Classmark Information Type 2	156
3.2.2.20	Classmark Information Type 3	157
3.2.2.21	Interference Band To Be Used	157
3.2.2.22	RR Cause	157
3.2.2.23	LSA Information	158
3.2.2.24	Layer 3 Information	158
3.2.2.25	DLCI	159
3.2.2.26	Downlink DTX Flag	159
3.2.2.27	Cell Identifier List	159
3.2.2.27a	Cell Identifier List Segment	162
3.2.2.27b	Cell Identifier List Segment for established cells	165
3.2.2.27c	Cell Identifier List Segment for cells to be established	168
3.2.2.27d	(void)	169
3.2.2.27e	Cell Identifier List Segment for released cells - no user present	169
3.2.2.27f	Cell Identifier List Segment for not established cells - no establishment possible	169
3.2.2.28	Response Request	169
3.2.2.29	Resource Indication Method	170
3.2.2.30	Classmark Information Type 1	170
3.2.2.31	Circuit Identity Code List	170
3.2.2.32	Diagnostics	171
3.2.2.33	Chosen Channel	172
3.2.2.34	Cipher Response Mode	173
3.2.2.35	Layer 3 Message Contents	173
3.2.2.36	Channel Needed	174
3.2.2.37	Trace Type	174
3.2.2.38	TriggerID	174
3.2.2.39	Trace Reference	174
3.2.2.40	TransactionID	174
3.2.2.41	Mobile Identity	175
3.2.2.42	OMCID	175
3.2.2.43	Forward Indicator	175
3.2.2.44	Chosen Encryption Algorithm	175
3.2.2.45	Circuit Pool	176
3.2.2.46	Circuit Pool List	181
3.2.2.47	Time Indication	181
3.2.2.48	Resource Situation	181
3.2.2.49	Current Channel Type 1	183
3.2.2.50	Queuing Indicator	184
3.2.2.51	Speech Version	184
3.2.2.52	Assignment Requirement	184
3.2.2.53	(void)	185
3.2.2.54	Talker Flag	185
3.2.2.55	Group Call Reference	185
3.2.2.56	eMLPP Priority	185
3.2.2.57	Configuration Evolution Indication	185
3.2.2.58	Old BSS to New BSS information	186
3.2.2.59	(void)	187
3.2.2.60	LCS QoS	187
3.2.2.61	LSA Access Control Suppression	187
3.2.2.62	LCS Priority	187
3.2.2.63	Location Type	187
3.2.2.64	Location Estimate	188
3.2.2.65	Positioning Data	188
3.2.2.66	LCS Cause	188
3.2.2.67	LCS Client Type	188
3.2.2.68	APDU	189
3.2.2.69	Network Element Identity	189
3.2.2.70	GPS Assistance Data	189
3.2.2.71	Deciphering Keys	189

3.2.2.72	Return Error Request.....	190
3.2.2.73	Return Error Cause.....	190
3.2.2.74	Segmentation.....	190
3.2.2.75	Service Handover.....	191
3.2.2.76	Source RNC to target RNC transparent information (UMTS).....	191
3.2.2.77	Source RNC to target RNC transparent information (cdma2000).....	191
3.2.2.78	GERAN Classmark	192
3.2.2.79	GERAN BSC Container.....	192
3.2.2.80	New BSS to Old BSS Information.....	193
3.2.2.81	Inter-System Information	194
3.2.2.82	SNA Access Information	194
3.2.2.83	VSTK_RAND Information.....	195
3.2.2.84	VSTK information	195
3.2.2.85	Paging Information.....	196
3.2.2.86	IMEI.....	196
3.2.2.87	Velocity Estimate.....	196
3.2.2.88	VGCS Feature Flags	197
3.2.2.89	Talker Priority	198
3.2.2.90	Emergency Set Indication	198
3.2.2.91	Talker Identity.....	198
3.2.2.92	SMS to VGCS	199
3.2.2.93	VGCS talker mode	199
3.2.2.94	VGCS/VBS Cell Status.....	200
3.2.2.95	GANSS Assistance Data	200
3.2.2.96	GANSS Positioning Data.....	200
3.2.2.97	GANSS Location Type	201
3.2.2.98	Application Data	201
3.2.2.99	Data Identity.....	201
3.2.2.100	Application Data Information	201
3.2.2.101	MSISDN	202
3.2.2.102	AoIP Transport Layer Address	202
3.2.2.103	Speech Codec List.....	202
3.2.2.104	Speech Codec	206
3.2.2.105	Call Identifier	207
3.2.2.106	Call Identifier List.....	207
3.2.2.107	A-Interface Selector for RESET	207
3.2.2.108	(void).....	208
3.2.2.109	Kc ₁₂₈	208
3.2.2.110	CSG Identifier	208
3.2.2.111	Redirect Attempt Flag	208
3.2.2.112	Reroute Reject Cause	209
3.2.2.113	Send Sequence Number	209
3.2.2.114	Reroute complete outcome	209
3.2.2.115	Global Call Reference	210
3.2.2.116	LCLS-Configuration	210
3.2.2.117	LCLS-Connection-Status-Control.....	211
3.2.2.118	LCLS-Correlation-Not-Needed.....	211
3.2.2.119	LCLS-BSS-Status	211
3.2.2.120	LCLS-Break-Request.....	212
3.2.2.121	CSFB Indication.....	212
3.2.2.122	CS to PS SRVCC	212
3.2.2.123	Source eNB to target eNB transparent information (E-UTRAN)	212
3.2.2.124	CS to PS SRVCC Indication	212
3.2.2.125	CN to MS transparent information	212
3.2.2.126	Selected PLMN ID.....	213
3.2.2.127	Last used E-UTRAN PLMN ID	213
3.2.2.128	Old Location Area Identification	213
3.2.2.129	Attach Indicator.....	214
3.2.2.130	Selected Operator	214
3.2.2.131	PS Registered Operator	214
3.2.2.132	CS Registered Operator.....	214
3.2.3	Signalling Field Element Coding.....	214

3.2.3.1	Extra information	215
3.2.3.2	Current Channel type 2	216
3.2.3.3	Target cell radio information.....	216
3.2.3.4	GPRS Suspend Information	217
3.2.3.5	MultiRate configuration Information	217
3.2.3.6	Dual Transfer Mode information	217
3.2.3.7	Inter RAT Handover Info.....	218
3.2.3.8	cdma2000 Capability Information	218
3.2.3.9	Downlink Cell Load Information.....	218
3.2.3.10	Uplink Cell Load Information.....	219
3.2.3.11	Cell Load Information Group.....	219
3.2.3.12	Cell Load Information.....	219
3.2.3.13	PS Indication	220
3.2.3.14	DTM Handover Command Indication	220
3.2.3.15	D-RNTI.....	220
3.2.3.16	IRAT Measurement Configuration	221
3.2.3.17	Source Cell ID	221
3.2.3.18	IRAT Measurement Configuration (extended E-ARFCNs).....	222
3.2.4	List of Timers in the BSSMAP Procedures	223
3.3	SDL Representation Of The Procedures At The BSS	223
4	Broadcast Information Control Channel	223
5	Definitions	223
6	List of diagrams.....	225
Annex A (informative): Change History		236
History		237

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies the layer 3 procedures used on the Base Station System (BSS) to Mobile-services Switching Centre (MSC) interface for control of GSM services.

For the purposes of call control and mobility management, messages are not interpreted at the Base Station System (BSS) which acts as a relay function. These messages and procedures are documented in 3GPP TS 24.008, the only relevant issues covering these messages in the present document are those concerned with error conditions at the interface, and the headers that are required for the correct addressing of the messages. This is specified in more detail in 3GPP TS 48.002.

The functional split between MSC and BSS is defined in 3GPP TS 48.002 and states that the BSS is responsible for local radio resource allocation and in order to support this the required procedures between BSS and MSC are defined in detail in the present document.

3GPP TS 48.002 also states that the BSS is responsible for the scheduling of all CCCH/BCCH messages and therefore some procedures for providing the BSS with the necessary information to be passed on these channels for individual calls (i.e. paging) are defined in the present document, but the scheduling is not discussed.

This interface and consequently these layer 3 procedures are designed to support BSSs providing one or more cells.

1.1 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- | | |
|------|--|
| [1] | 3GPP TR 21.905: "Vocabulary for 3GPP Specifications". |
| [2] | 3GPP TS 23.003: "Numbering, addressing and identification". |
| [3] | 3GPP TS 23.009: "Handover procedures". |
| [3a] | 3GPP TS 23.032: "Universal Geographical Area Description (GAD)". |
| [4] | (void) |
| [5] | 3GPP TS 43.059: "Functional stage 2 description of Location Services (LCS) in GERAN". |
| [6] | 3GPP TS 24.008: "Mobile radio interface Layer 3 specification; Core network protocols; Stage 3". |
| [7] | (void). |
| [8] | (void). |
| [9] | (void). |
| [10] | (void). |
| [11] | (void). |
| [12] | (void). |
| [13] | (void). |