

ETSI TS 124 301 V12.11.0 (2016-01)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Non-Access-Stratum (NAS)
protocol for Evolved Packet System (EPS);
Stage 3
(3GPP TS 24.301 version 12.11.0 Release 12)**



Reference

RTS/TSGC-0124301vcb0

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	17
1 Scope	18
2 References	18
3 Definitions and abbreviations.....	20
3.1 Definitions	20
3.2 Abbreviations	25
4 General	26
4.1 Overview	26
4.2 Linkage between the protocols for EPS mobility management and EPS session management	26
4.2A Handling of NAS signalling low priority indication	27
4.3 UE mode of operation	27
4.3.1 General.....	27
4.3.2 Change of UE mode of operation	28
4.3.2.1 General.....	28
4.3.2.2 Change of UE's usage setting	30
4.3.2.3 Change of voice domain preference for E-UTRAN.....	31
4.3.2.4 Change or determination of IMS registration status.....	32
4.3.2.5 Change of configuration regarding the use of SMS.	33
4.4 NAS security	34
4.4.1 General.....	34
4.4.2 Handling of EPS security contexts	34
4.4.2.1 General	34
4.4.2.2 Establishment of a mapped EPS security context during intersystem handover	35
4.4.2.3 Establishment of secure exchange of NAS messages	36
4.4.2.4 Change of security keys	37
4.4.2.5 Derivation of keys at CS to PS SRVCC handover from A/Gb mode to S1 mode or from Iu mode to S1 mode	37
4.4.3 Handling of NAS COUNT and NAS sequence number	38
4.4.3.1 General	38
4.4.3.2 Replay protection	39
4.4.3.3 Integrity protection and verification.....	39
4.4.3.4 Cipherring and deciphering	39
4.4.3.5 NAS COUNT wrap around.....	39
4.4.4 Integrity protection of NAS signalling messages.....	40
4.4.4.1 General	40
4.4.4.2 Integrity checking of NAS signalling messages in the UE	40
4.4.4.3 Integrity checking of NAS signalling messages in the MME	41
4.4.5 Cipherring of NAS signalling messages	42
4.5 Disabling and re-enabling of UE's E-UTRA capability	43
4.6 Applicability of procedures	44
4.6.1 Relay nodes.....	44
5 Elementary procedures for EPS mobility management.....	44
5.1 Overview	44
5.1.1 General.....	44
5.1.2 Types of EMM procedures	45
5.1.3 EMM sublayer states	46
5.1.3.1 General	46
5.1.3.2 EMM sublayer states in the UE.....	46
5.1.3.2.1 General	46

5.1.3.2.2	Main states.....	46
5.1.3.2.2.1	EMM-NULL.....	46
5.1.3.2.2.2	EMM-DEREGISTERED.....	46
5.1.3.2.2.3	EMM-REGISTERED-INITIATED.....	46
5.1.3.2.2.4	EMM-REGISTERED.....	46
5.1.3.2.2.5	EMM-DEREGISTERED-INITIATED.....	46
5.1.3.2.2.6	EMM-TRACKING-AREA-UPDATING-INITIATED.....	46
5.1.3.2.2.7	EMM-SERVICE-REQUEST-INITIATED.....	47
5.1.3.2.3	Substates of state EMM-DEREGISTERED.....	47
5.1.3.2.3.1	General.....	47
5.1.3.2.3.2	EMM-DEREGISTERED.NORMAL-SERVICE.....	47
5.1.3.2.3.3	EMM-DEREGISTERED.LIMITED-SERVICE.....	47
5.1.3.2.3.4	EMM-DEREGISTERED.ATTEMPTING-TO-ATTACH.....	48
5.1.3.2.3.5	EMM-DEREGISTERED.PLMN-SEARCH.....	48
5.1.3.2.3.6	EMM-DEREGISTERED.NO-IMSI.....	48
5.1.3.2.3.7	EMM-DEREGISTERED.ATTACH-NEEDED.....	48
5.1.3.2.3.8	EMM-DEREGISTERED.NO-CELL-AVAILABLE.....	48
5.1.3.2.4	Substates of state EMM-REGISTERED.....	48
5.1.3.2.4.1	General.....	48
5.1.3.2.4.2	EMM-REGISTERED.NORMAL-SERVICE.....	48
5.1.3.2.4.3	EMM-REGISTERED.ATTEMPTING-TO-UPDATE.....	48
5.1.3.2.4.4	EMM-REGISTERED.LIMITED-SERVICE.....	48
5.1.3.2.4.5	EMM-REGISTERED.PLMN-SEARCH.....	48
5.1.3.2.4.6	EMM-REGISTERED.UPDATE-NEEDED.....	48
5.1.3.2.4.7	EMM-REGISTERED.NO-CELL-AVAILABLE.....	48
5.1.3.2.4.8	EMM-REGISTERED.ATTEMPTING-TO-UPDATE-MM.....	49
5.1.3.2.4.9	EMM-REGISTERED.IMSI-DETACH-INITIATED.....	49
5.1.3.3	EPS update status.....	49
5.1.3.4	EMM sublayer states in the MME.....	49
5.1.3.4.1	EMM-DEREGISTERED.....	49
5.1.3.4.2	EMM-COMMON-PROCEDURE-INITIATED.....	49
5.1.3.4.3	EMM-REGISTERED.....	49
5.1.3.4.4	EMM-DEREGISTERED-INITIATED.....	49
5.1.4	Coordination between EMM and GMM.....	50
5.1.5	Coordination between EMM and MM.....	50
5.2	Behaviour of the UE in state EMM-DEREGISTERED and state EMM-REGISTERED.....	51
5.2.1	General.....	51
5.2.2	UE behaviour in state EMM-DEREGISTERED.....	51
5.2.2.1	General.....	51
5.2.2.2	Primary substate selection.....	51
5.2.2.2.1	Selection of the substate after power on.....	51
5.2.2.3	Detailed description of UE behaviour in state EMM-DEREGISTERED.....	52
5.2.2.3.1	NORMAL-SERVICE.....	52
5.2.2.3.2	LIMITED-SERVICE.....	52
5.2.2.3.3	ATTEMPTING-TO-ATTACH.....	52
5.2.2.3.4	PLMN-SEARCH.....	52
5.2.2.3.5	NO-IMSI.....	52
5.2.2.3.6	ATTACH-NEEDED.....	52
5.2.2.3.7	NO-CELL-AVAILABLE.....	52
5.2.2.4	Substate when back to state EMM-DEREGISTERED from another EMM state.....	53
5.2.3	UE behaviour in state EMM-REGISTERED.....	53
5.2.3.1	General.....	53
5.2.3.2	Detailed description of UE behaviour in state EMM-REGISTERED.....	53
5.2.3.2.1	NORMAL-SERVICE.....	53
5.2.3.2.2	ATTEMPTING-TO-UPDATE.....	53
5.2.3.2.3	LIMITED-SERVICE.....	54
5.2.3.2.4	PLMN-SEARCH.....	54
5.2.3.2.5	UPDATE-NEEDED.....	54
5.2.3.2.6	NO-CELL-AVAILABLE.....	54
5.2.3.2.7	ATTEMPTING-TO-UPDATE-MM.....	54
5.2.3.2.8	IMSI-DETACH-INITIATED.....	55
5.3	General on elementary EMM procedures.....	55

5.3.1	EMM modes and NAS signalling connection.....	55
5.3.1.1	Establishment of the NAS signalling connection.....	55
5.3.1.2	Release of the NAS signalling connection.....	56
5.3.2	Lists of forbidden tracking areas.....	57
5.3.3	List of forbidden PLMNs for attach in S101 mode.....	57
5.3.3a	Forbidden PLMNs for EPS services.....	57
5.3.4	Equivalent PLMNs list.....	57
5.3.5	Handling of the periodic tracking area update timer and mobile reachable timer (S1 mode only).....	58
5.3.6	Handling of timer T3402.....	59
5.3.7	Handling of the Local Emergency Numbers List.....	59
5.3.7a	Specific requirements for UE configured to use timer T3245.....	60
5.3.8	Abnormal cases in the UE.....	60
5.3.9	Handling of NAS level mobility management congestion control.....	60
5.3.10	Access class control.....	61
5.3.11	Power saving mode.....	61
5.4	EMM common procedures.....	62
5.4.1	GUTI reallocation procedure.....	62
5.4.1.1	General.....	62
5.4.1.2	GUTI reallocation initiation by the network.....	62
5.4.1.3	GUTI reallocation completion by the UE.....	63
5.4.1.4	GUTI reallocation completion by the network.....	63
5.4.1.5	Abnormal cases in the UE.....	63
5.4.1.6	Abnormal cases on the network side.....	63
5.4.2	Authentication procedure.....	64
5.4.2.1	General.....	64
5.4.2.2	Authentication initiation by the network.....	65
5.4.2.3	Authentication response by the UE.....	65
5.4.2.4	Authentication completion by the network.....	66
5.4.2.5	Authentication not accepted by the network.....	66
5.4.2.6	Authentication not accepted by the UE.....	67
5.4.2.7	Abnormal cases.....	67
5.4.3	Security mode control procedure.....	72
5.4.3.1	General.....	72
5.4.3.2	NAS security mode control initiation by the network.....	72
5.4.3.3	NAS security mode command accepted by the UE.....	74
5.4.3.4	NAS security mode control completion by the network.....	75
5.4.3.5	NAS security mode command not accepted by the UE.....	75
5.4.3.6	Abnormal cases in the UE.....	75
5.4.3.7	Abnormal cases on the network side.....	75
5.4.4	Identification procedure.....	76
5.4.4.1	General.....	76
5.4.4.2	Identification initiation by the network.....	76
5.4.4.3	Identification response by the UE.....	77
5.4.4.4	Identification completion by the network.....	77
5.4.4.5	Abnormal cases in the UE.....	77
5.4.4.6	Abnormal cases on the network side.....	77
5.4.5	EMM information procedure.....	78
5.4.5.1	General.....	78
5.4.5.2	EMM information procedure initiation by the network.....	78
5.4.5.3	EMM information procedure in the UE.....	78
5.4.5.4	Abnormal cases on the network side.....	78
5.5	EMM specific procedures.....	79
5.5.1	Attach procedure.....	79
5.5.1.1	General.....	79
5.5.1.2	Attach procedure for EPS services.....	80
5.5.1.2.1	General.....	80
5.5.1.2.2	Attach procedure initiation.....	80
5.5.1.2.3	EMM common procedure initiation.....	82
5.5.1.2.4	Attach accepted by the network.....	82
5.5.1.2.5	Attach not accepted by the network.....	84
5.5.1.2.5A	Attach for emergency bearer services not accepted by the network.....	87

5.5.1.2.5B	Attach for initiating a PDN connection for emergency bearer services not accepted by the network.....	88
5.5.1.2.6	Abnormal cases in the UE.....	88
5.5.1.2.7	Abnormal cases on the network side.....	91
5.5.1.3	Combined attach procedure for EPS services and non-EPS services (S1 mode only).....	92
5.5.1.3.1	General.....	92
5.5.1.3.2	Combined attach procedure initiation.....	92
5.5.1.3.3	EMM common procedure initiation.....	92
5.5.1.3.4	Combined attach accepted by the network.....	93
5.5.1.3.4.1	General.....	93
5.5.1.3.4.2	Combined attach successful.....	93
5.5.1.3.4.3	Combined attach successful for EPS services only.....	94
5.5.1.3.5	Combined attach not accepted by the network.....	95
5.5.1.3.6	Abnormal cases in the UE.....	98
5.5.1.3.7	Abnormal cases on the network side.....	99
5.5.2	Detach procedure.....	99
5.5.2.1	General.....	99
5.5.2.2	UE initiated detach procedure.....	100
5.5.2.2.1	UE initiated detach procedure initiation.....	100
5.5.2.2.2	UE initiated detach procedure completion for EPS services only.....	101
5.5.2.2.3	UE initiated combined detach procedure completion.....	101
5.5.2.2.4	Abnormal cases in the UE.....	101
5.5.2.2.5	Abnormal cases on the network side.....	103
5.5.2.3	Network initiated detach procedure.....	103
5.5.2.3.1	Network initiated detach procedure initiation.....	103
5.5.2.3.2	Network initiated detach procedure completion by the UE.....	104
5.5.2.3.3	Network initiated detach procedure completion by the network.....	107
5.5.2.3.4	Abnormal cases in the UE.....	107
5.5.2.3.5	Abnormal cases on the network side.....	108
5.5.3	Tracking area updating procedure (S1 mode only).....	109
5.5.3.1	General.....	109
5.5.3.2	Normal and periodic tracking area updating procedure.....	110
5.5.3.2.1	General.....	110
5.5.3.2.2	Normal and periodic tracking area updating procedure initiation.....	110
5.5.3.2.3	EMM common procedure initiation.....	113
5.5.3.2.4	Normal and periodic tracking area updating procedure accepted by the network.....	114
5.5.3.2.5	Normal and periodic tracking area updating procedure not accepted by the network.....	119
5.5.3.2.5A	Tracking area updating procedure for initiating a PDN connection for emergency bearer services not accepted by the network.....	123
5.5.3.2.6	Abnormal cases in the UE.....	123
5.5.3.2.7	Abnormal cases on the network side.....	127
5.5.3.3	Combined tracking area updating procedure.....	128
5.5.3.3.1	General.....	128
5.5.3.3.2	Combined tracking area updating procedure initiation.....	128
5.5.3.3.3	EMM common procedure initiation.....	130
5.5.3.3.4	Combined tracking area updating procedure accepted by the network.....	130
5.5.3.3.4.1	General.....	130
5.5.3.3.4.2	Combined tracking area updating successful.....	130
5.5.3.3.4.3	Combined tracking area updating successful for EPS services only.....	131
5.5.3.3.5	Combined tracking area updating procedure not accepted by the network.....	132
5.5.3.3.6	Abnormal cases in the UE.....	137
5.5.3.3.7	Abnormal cases on the network side.....	138
5.6	EMM connection management procedures (S1 mode only).....	138
5.6.1	Service request procedure.....	138
5.6.1.1	General.....	138
5.6.1.2	Service request procedure initiation.....	141
5.6.1.3	EMM common procedure initiation.....	141
5.6.1.4	Service request procedure accepted by the network.....	141
5.6.1.5	Service request procedure not accepted by the network.....	143
5.6.1.5A	Service request procedure for initiating a PDN connection for emergency bearer services not accepted by the network.....	149
5.6.1.6	Abnormal cases in the UE.....	149

5.6.1.7	Abnormal cases on the network side	154
5.6.2	Paging procedure	155
5.6.2.1	General	155
5.6.2.2	Paging for EPS services	155
5.6.2.2.1	Paging for EPS services through E-UTRAN using S-TMSI	155
5.6.2.2.1.1	General	155
5.6.2.2.1.2	Abnormal cases on the network side	156
5.6.2.2.2	Paging for EPS services through E-UTRAN using IMSI	156
5.6.2.3	Paging for CS fallback to A/Gb or Iu mode	157
5.6.2.3.1	General	157
5.6.2.3.2	Abnormal cases in the UE	158
5.6.2.3.3	Abnormal cases on the network side	158
5.6.2.4	Paging for SMS	158
5.6.3	Transport of NAS messages procedure	158
5.6.3.1	General	158
5.6.3.2	UE initiated transport of NAS messages	159
5.6.3.3	Network initiated transport of NAS messages	159
5.6.3.4	Abnormal cases in the UE	159
5.6.3.5	Abnormal cases on the network side	159
5.6.4	Generic transport of NAS messages procedure	159
5.6.4.1	General	159
5.6.4.2	UE initiated generic transport of NAS messages	159
5.6.4.3	Network initiated transport of NAS messages	159
5.6.4.4	Abnormal cases in the UE	160
5.6.4.5	Abnormal cases on the network side	160
5.7	Reception of an EMM STATUS message by an EMM entity	160
6	Elementary procedures for EPS session management	161
6.1	Overview	161
6.1.1	General	161
6.1.2	Types of ESM procedures	161
6.1.3	ESM sublayer states	162
6.1.3.1	General	162
6.1.3.2	ESM sublayer states in the UE	162
6.1.3.2.1	BEARER CONTEXT INACTIVE	162
6.1.3.2.2	BEARER CONTEXT ACTIVE	162
6.1.3.2.3	PROCEDURE TRANSACTION INACTIVE	162
6.1.3.2.4	PROCEDURE TRANSACTION PENDING	163
6.1.3.3	ESM sublayer states in the MME	163
6.1.3.3.1	BEARER CONTEXT INACTIVE	163
6.1.3.3.2	BEARER CONTEXT ACTIVE PENDING	163
6.1.3.3.3	BEARER CONTEXT ACTIVE	163
6.1.3.3.4	BEARER CONTEXT INACTIVE PENDING	163
6.1.3.3.5	BEARER CONTEXT MODIFY PENDING	163
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE	164
6.1.3.3.7	PROCEDURE TRANSACTION PENDING	164
6.1.4	Coordination between ESM and SM	164
6.1.5	Coordination between ESM and EMM for supporting ISR	165
6.2	IP address allocation	165
6.2.1	General	165
6.2.2	IP address allocation via NAS signalling	165
6.3	General on elementary ESM procedures	167
6.3.1	Services provided by lower layers	167
6.3.2	Principles of address handling for ESM procedures	167
6.3.3	Abnormal cases in the UE	169
6.3.4	Abnormal cases in the network	169
6.3.5	Handling of APN based congestion control	170
6.3.6	Handling of network rejection not due to APN based congestion control	170
6.3.7	Handling of WLAN offload control	170
6.4	Network initiated ESM procedures	170
6.4.1	Default EPS bearer context activation procedure	170
6.4.1.1	General	170

6.4.1.2	Default EPS bearer context activation initiated by the network.....	170
6.4.1.3	Default EPS bearer context activation accepted by the UE.....	171
6.4.1.4	Default EPS bearer context activation not accepted by the UE.....	171
6.4.1.5	Abnormal cases in the UE.....	172
6.4.1.6	Abnormal cases on the network side.....	172
6.4.2	Dedicated EPS bearer context activation procedure	172
6.4.2.1	General	172
6.4.2.2	Dedicated EPS bearer context activation initiated by the network.....	172
6.4.2.3	Dedicated EPS bearer context activation accepted by the UE	173
6.4.2.4	Dedicated EPS bearer context activation not accepted by the UE	173
6.4.2.5	Abnormal cases in the UE.....	175
6.4.2.6	Abnormal cases on the network side.....	175
6.4.3	EPS bearer context modification procedure.....	175
6.4.3.1	General	175
6.4.3.2	EPS bearer context modification initiated by the network.....	176
6.4.3.3	EPS bearer context modification accepted by the UE.....	176
6.4.3.4	EPS bearer context modification not accepted by the UE.....	177
6.4.3.5	Abnormal cases in the UE.....	179
6.4.3.6	Abnormal cases on the network side.....	179
6.4.4	EPS bearer context deactivation procedure.....	179
6.4.4.1	General	179
6.4.4.2	EPS bearer context deactivation initiated by the network.....	179
6.4.4.3	EPS bearer context deactivation accepted by the UE.....	180
6.4.4.4	Abnormal cases in the UE.....	181
6.4.4.5	Abnormal cases on the network side.....	182
6.4.4.6	Local EPS bearer context deactivation without NAS signalling	182
6.5	UE requested ESM procedures.....	183
6.5.0	General.....	183
6.5.1	UE requested PDN connectivity procedure	183
6.5.1.1	General	183
6.5.1.2	UE requested PDN connectivity procedure initiation	184
6.5.1.3	UE requested PDN connectivity procedure accepted by the network.....	185
6.5.1.4	UE requested PDN connectivity procedure not accepted by the network.....	186
6.5.1.4.1	General	186
6.5.1.4.2	Handling of network rejection due to ESM cause #26	187
6.5.1.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	189
6.5.1.4A	Handling the maximum number of active EPS bearer contexts	192
6.5.1.4B	Void.....	192
6.5.1.5	Abnormal cases in the UE.....	192
6.5.1.6	Abnormal cases on the network side.....	192
6.5.1.7	Handling PDN connectivity request for UE configured for dual priority	193
6.5.2	UE requested PDN disconnect procedure.....	193
6.5.2.1	General	193
6.5.2.2	UE requested PDN disconnection procedure initiation.....	194
6.5.2.3	UE requested PDN disconnection procedure accepted by the network.....	194
6.5.2.4	UE requested PDN disconnection procedure not accepted by the network	194
6.5.2.5	Abnormal cases in the UE.....	195
6.5.2.6	Abnormal cases on the network side.....	195
6.5.3	UE requested bearer resource allocation procedure.....	195
6.5.3.1	General	195
6.5.3.2	UE requested bearer resource allocation procedure initiation.....	195
6.5.3.3	UE requested bearer resource allocation procedure accepted by the network	196
6.5.3.4	UE requested bearer resource allocation procedure not accepted by the network	196
6.5.3.4.1	General	196
6.5.3.4.2	Handling of network rejection due to ESM cause #26	198
6.5.3.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	199
6.5.3.4A	Handling the maximum number of active EPS bearer contexts	200
6.5.3.5	Abnormal cases in the UE.....	201
6.5.3.6	Abnormal cases on the network side.....	201
6.5.4	UE requested bearer resource modification procedure	201
6.5.4.1	General.....	201
6.5.4.2	UE requested bearer resource modification procedure initiation	201

6.5.4.3	UE requested bearer resource modification procedure accepted by the network	202
6.5.4.4	UE requested bearer resource modification procedure not accepted by the network	203
6.5.4.4.1	General	203
6.5.4.4.2	Handling of network rejection due to ESM cause #26	206
6.5.4.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	206
6.5.4.5	Abnormal cases in the UE	208
6.5.4.6	Abnormal cases on the network side	208
6.5.5	Handling session management request for UE configured for dual priority	208
6.6	Miscellaneous procedures	209
6.6.1	Exchange of protocol configuration options	209
6.6.1.1	General	209
6.6.1.2	ESM information request procedure	209
6.6.1.2.1	General	209
6.6.1.2.2	ESM information request initiated by the network	209
6.6.1.2.3	ESM information request completion by the UE	209
6.6.1.2.4	ESM information request completion by the network	210
6.6.1.2.5	Abnormal cases in the UE	210
6.6.1.2.6	Abnormal cases on the network side	210
6.6.1.3	Exchange of protocol configuration options in other messages	210
6.6.2	Notification procedure	210
6.6.2.1	General	210
6.6.2.2	Notification procedure initiation by the network	210
6.6.2.3	Notification procedure in the UE	211
6.6.2.4	Abnormal cases on the network side	211
6.7	Reception of an ESM STATUS message by an ESM entity	211
7	Handling of unknown, unforeseen, and erroneous protocol data	212
7.1	General	212
7.2	Message too short	212
7.3	Unknown or unforeseen procedure transaction identity or EPS bearer identity	213
7.3.1	Procedure transaction identity	213
7.3.2	EPS bearer identity	214
7.4	Unknown or unforeseen message type	215
7.5	Non-semantic mandatory information element errors	216
7.5.1	Common procedures	216
7.5.2	EPS mobility management	216
7.5.3	EPS session management	216
7.6	Unknown and unforeseen IEs in the non-imperative message part	217
7.6.1	IEs unknown in the message	217
7.6.2	Out of sequence IEs	217
7.6.3	Repeated IEs	217
7.7	Non-imperative message part errors	217
7.7.1	Syntactically incorrect optional IEs	217
7.7.2	Conditional IE errors	217
7.8	Messages with semantically incorrect contents	218
8	Message functional definitions and contents	218
8.1	Overview	218
8.2	EPS mobility management messages	219
8.2.1	Attach accept	219
8.2.1.1	Message definition	219
8.2.1.2	GUTI	220
8.2.1.3	Location area identification	220
8.2.1.4	MS identity	220
8.2.1.5	EMM cause	220
8.2.1.6	T3402 value	220
8.2.1.7	T3423 value	221
8.2.1.8	Equivalent PLMNs	221
8.2.1.9	Emergency number list	221
8.2.1.10	EPS network feature support	221
8.2.1.11	Additional update result	221
8.2.1.12	T3412 extended value	221

8.2.1.13	T3324 value.....	221
8.2.2	Attach complete	221
8.2.3	Attach reject.....	222
8.2.3.1	Message definition	222
8.2.3.2	ESM message container	222
8.2.3.3	T3346 value.....	222
8.2.3.4	T3402 value.....	222
8.2.3.5	Extended EMM cause	222
8.2.4	Attach request	222
8.2.4.1	Message definition	222
8.2.4.2	Old P-TMSI signature	223
8.2.4.3	Additional GUTI	224
8.2.4.4	Last visited registered TAI.....	224
8.2.4.5	DRX parameter	224
8.2.4.6	MS network capability	224
8.2.4.7	Old location area identification	224
8.2.4.8	TMSI status	224
8.2.4.9	Mobile station classmark 2.....	224
8.2.4.10	Mobile station classmark 3.....	224
8.2.4.11	Supported Codecs	224
8.2.4.12	Additional update type	224
8.2.4.13	Voice domain preference and UE's usage setting.....	224
8.2.4.14	Device properties	224
8.2.4.15	Old GUTI type	224
8.2.4.16	MS network feature support.....	224
8.2.4.17	TMSI based NRI container	224
8.2.4.18	T3324 value.....	225
8.2.4.19	T3412 extended value	225
8.2.5	Authentication failure	225
8.2.5.1	Message definition	225
8.2.5.2	Authentication failure parameter.....	225
8.2.6	Authentication reject.....	225
8.2.7	Authentication request	226
8.2.8	Authentication response.....	226
8.2.9	CS service notification.....	226
8.2.9.1	Message definition	226
8.2.9.2	CLI	227
8.2.9.3	SS Code.....	227
8.2.9.4	LCS indicator	227
8.2.9.5	LCS client identity	227
8.2.10	Detach accept.....	227
8.2.10.1	Detach accept (UE originating detach)	227
8.2.10.2	Detach accept (UE terminated detach).....	228
8.2.11	Detach request	228
8.2.11.1	Detach request (UE originating detach).....	228
8.2.11.2	Detach request (UE terminated detach).....	228
8.2.11.2.1	Message definition.....	228
8.2.11.2.2	EMM cause.....	229
8.2.12	Downlink NAS Transport.....	229
8.2.13	EMM information	229
8.2.13.1	Message definition	229
8.2.13.2	Full name for network.....	230
8.2.13.3	Short name for network.....	230
8.2.13.4	Local time zone	230
8.2.13.5	Universal time and local time zone	230
8.2.13.6	Network daylight saving time	230
8.2.14	EMM status.....	230
8.2.15	Extended service request	231
8.2.15.1	Message definition	231
8.2.15.2	CSFB response	231
8.2.15.3	EPS bearer context status	232
8.2.15.4	Device properties	232

8.2.16	GUTI reallocation command	232
8.2.16.1	Message definition	232
8.2.16.2	TAI list	232
8.2.17	GUTI reallocation complete	232
8.2.18	Identity request	233
8.2.19	Identity response	233
8.2.20	Security mode command	233
8.2.20.1	Message definition	233
8.2.20.2	IMEISV request	234
8.2.20.3	Replayed nonce _{UE}	234
8.2.20.4	Nonce _{MME}	234
8.2.21	Security mode complete	234
8.2.21.1	Message definition	234
8.2.21.2	IMEISV	235
8.2.22	Security mode reject	235
8.2.23	Security protected NAS message	235
8.2.24	Service reject	235
8.2.24.1	Message definition	235
8.2.24.2	T3442 value	236
8.2.24.3	T3346 value	236
8.2.25	Service request	236
8.2.26	Tracking area update accept	236
8.2.26.1	Message definition	236
8.2.26.2	T3412 value	237
8.2.26.3	GUTI	237
8.2.26.4	TAI list	237
8.2.26.5	EPS bearer context status	237
8.2.26.6	Location area identification	238
8.2.26.7	MS identity	238
8.2.26.8	EMM cause	238
8.2.26.9	T3402 value	238
8.2.26.10	T3423 value	238
8.2.26.11	Equivalent PLMNs	238
8.2.26.12	Emergency number list	238
8.2.26.13	EPS network feature support	238
8.2.26.14	Additional update result	238
8.2.26.15	T3412 extended value	238
8.2.26.16	T3324 value	238
8.2.27	Tracking area update complete	238
8.2.28	Tracking area update reject	239
8.2.28.1	Message definition	239
8.2.28.2	T3346 value	239
8.2.28.3	Extended EMM cause	239
8.2.29	Tracking area update request	239
8.2.29.1	Message definition	239
8.2.29.2	Non-current native NAS key set identifier	242
8.2.29.3	GPRS ciphering key sequence number	242
8.2.29.4	Old P-TMSI signature	242
8.2.29.5	Additional GUTI	242
8.2.29.6	Nonce _{UE}	242
8.2.29.7	UE network capability	242
8.2.29.8	Last visited registered TAI	242
8.2.29.9	DRX parameter	242
8.2.29.10	UE radio capability information update needed	242
8.2.29.11	EPS bearer context status	242
8.2.29.12	MS network capability	242
8.2.29.13	Old location area identification	242
8.2.29.14	TMSI status	242
8.2.29.15	Mobile station classmark 2	242
8.2.29.16	Mobile station classmark 3	243
8.2.29.17	Supported Codecs	243
8.2.29.18	Additional update type	243

8.2.29.19	Voice domain preference and UE's usage setting.....	243
8.2.29.20	Old GUTI type	243
8.2.29.21	Device properties	243
8.2.29.22	MS network feature support.....	243
8.2.29.23	TMSI based NRI container	243
8.2.29.24	T3324 value.....	243
8.2.29.25	T3412 extended value	243
8.2.30	Uplink NAS Transport.....	243
8.2.31	Downlink generic NAS transport.....	244
8.2.31.1	Message definition	244
8.2.31.2	Additional information.....	244
8.2.32	Uplink generic NAS transport	244
8.2.32.1	Message definition	244
8.2.32.2	Additional information.....	245
8.3	EPS session management messages	245
8.3.1	Activate dedicated EPS bearer context accept.....	245
8.3.1.1	Message definition	245
8.3.1.2	Protocol configuration options	245
8.3.2	Activate dedicated EPS bearer context reject	245
8.3.2.1	Message definition	245
8.3.2.2	Protocol configuration options	246
8.3.3	Activate dedicated EPS bearer context request.....	246
8.3.3.1	Message definition	246
8.3.3.2	Transaction identifier	247
8.3.3.3	Negotiated QoS	247
8.3.3.4	Negotiated LLC SAPI.....	247
8.3.3.5	Radio priority	247
8.3.3.6	Packet flow identifier	247
8.3.3.7	Protocol configuration options	247
8.3.3.8	WLAN offload indication	248
8.3.4	Activate default EPS bearer context accept.....	248
8.3.4.1	Message definition	248
8.3.4.2	Protocol configuration options	248
8.3.5	Activate default EPS bearer context reject	248
8.3.5.1	Message definition	248
8.3.5.2	Protocol configuration options	249
8.3.6	Activate default EPS bearer context request.....	249
8.3.6.1	Message definition	249
8.3.6.2	Transaction identifier	249
8.3.6.3	Negotiated QoS	249
8.3.6.4	Negotiated LLC SAPI.....	250
8.3.6.5	Radio priority	250
8.3.6.6	Packet flow identifier	250
8.3.6.7	APN-AMBR.....	250
8.3.6.8	ESM cause.....	250
8.3.6.9	Protocol configuration options	250
8.3.6.10	Connectivity type	250
8.3.6.11	WLAN offload indication	250
8.3.7	Bearer resource allocation reject.....	250
8.3.7.1	Message definition	250
8.3.7.2	Protocol configuration options	251
8.3.7.3	Back-off timer value	251
8.3.7.4	Re-attempt indicator.....	251
8.3.8	Bearer resource allocation request.....	251
8.3.8.1	Message definition	251
8.3.8.2	Protocol configuration options	252
8.3.8.3	Device properties	252
8.3.9	Bearer resource modification reject.....	252
8.3.9.1	Message definition	252
8.3.9.2	Protocol configuration options	253
8.3.9.3	Back-off timer value	253
8.3.9.4	Re-attempt indicator.....	253

8.3.10	Bearer resource modification request	253
8.3.10.1	Message definition	253
8.3.10.2	Required traffic flow QoS	254
8.3.10.3	ESM cause.....	254
8.3.10.4	Protocol configuration options	254
8.3.10.5	Device properties	254
8.3.11	Deactivate EPS bearer context accept.....	254
8.3.11.1	Message definition	254
8.3.11.2	Protocol configuration options	255
8.3.12	Deactivate EPS bearer context request	255
8.3.12.1	Message definition	255
8.3.12.2	Protocol configuration options	255
8.3.12.3	T3396 value.....	255
8.3.12.4	WLAN offload indication	256
8.3.13	ESM information request.....	256
8.3.14	ESM information response	256
8.3.14.1	Message definition	256
8.3.14.2	Access point name.....	256
8.3.14.3	Protocol configuration options	257
8.3.15	ESM status	257
8.3.16	Modify EPS bearer context accept.....	257
8.3.16.1	Message definition	257
8.3.16.2	Protocol configuration options	257
8.3.17	Modify EPS bearer context reject	258
8.3.17.1	Message definition	258
8.3.17.2	Protocol configuration options	258
8.3.18	Modify EPS bearer context request	258
8.3.18.1	Message definition	258
8.3.18.2	New EPS QoS	259
8.3.18.3	TFT	259
8.3.18.4	New QoS	259
8.3.18.5	Negotiated LLC SAPI.....	259
8.3.18.6	Radio priority	259
8.3.18.7	Packet flow identifier	259
8.3.18.8	APN-AMBR.....	259
8.3.18.9	Protocol configuration options	260
8.3.18.10	WLAN offload indication	260
8.3.18A	Notification	260
8.3.19	PDN connectivity reject.....	260
8.3.19.1	Message definition	260
8.3.19.2	Protocol configuration options	261
8.3.19.3	Back-off timer value	261
8.3.19.4	Re-attempt indicator.....	261
8.3.20	PDN connectivity request	261
8.3.20.1	Message definition	261
8.3.20.2	ESM information transfer flag	262
8.3.20.3	Access point name.....	262
8.3.20.4	Protocol configuration options	262
8.3.20.5	Device properties	262
8.3.21	PDN disconnect reject	262
8.3.21.1	Message definition	262
8.3.21.2	Protocol configuration options	263
8.3.22	PDN disconnect request	263
8.3.22.1	Message definition	263
8.3.22.2	Protocol configuration options	263
9	General message format and information elements coding.....	264
9.1	Overview	264
9.2	Protocol discriminator	265
9.3	Security header type and EPS bearer identity.....	265
9.3.1	Security header type.....	265
9.3.2	EPS bearer identity	265

9.4	Procedure transaction identity	266
9.5	Message authentication code	266
9.6	Sequence number	266
9.7	NAS message	266
9.8	Message type	266
9.9	Other information elements	268
9.9.1	General	268
9.9.2	Common information elements	269
9.9.2.0	Additional information	269
9.9.2.0A	Device properties	269
9.9.2.1	EPS bearer context status	269
9.9.2.2	Location area identification	270
9.9.2.3	Mobile identity	270
9.9.2.4	Mobile station classmark 2	270
9.9.2.5	Mobile station classmark 3	270
9.9.2.6	NAS security parameters from E-UTRA	270
9.9.2.7	NAS security parameters to E-UTRA	270
9.9.2.8	PLMN list	271
9.9.2.9	Spare half octet	271
9.9.2.10	Supported codec list	271
9.9.3	EPS Mobility Management (EMM) information elements	271
9.9.3.0A	Additional update result	271
9.9.3.0B	Additional update type	272
9.9.3.1	Authentication failure parameter	272
9.9.3.2	Authentication parameter AUTN	272
9.9.3.3	Authentication parameter RAND	272
9.9.3.4	Authentication response parameter	273
9.9.3.4A	Ciphering key sequence number	273
9.9.3.5	CSFB response	273
9.9.3.6	Daylight saving time	274
9.9.3.7	Detach type	274
9.9.3.8	DRX parameter	274
9.9.3.9	EMM cause	274
9.9.3.10	EPS attach result	275
9.9.3.11	EPS attach type	276
9.9.3.12	EPS mobile identity	276
9.9.3.12A	EPS network feature support	278
9.9.3.13	EPS update result	279
9.9.3.14	EPS update type	280
9.9.3.15	ESM message container	280
9.9.3.16	GPRS timer	281
9.9.3.16A	GPRS timer 2	281
9.9.3.16B	GPRS timer 3	281
9.9.3.17	Identity type 2	281
9.9.3.18	IMEISV request	281
9.9.3.19	KSI and sequence number	281
9.9.3.20	MS network capability	282
9.9.3.20A	MS network feature support	282
9.9.3.21	NAS key set identifier	282
9.9.3.22	NAS message container	282
9.9.3.23	NAS security algorithms	283
9.9.3.24	Network name	284
9.9.3.24A	Network resource identifier container	284
9.9.3.25	Nonce	284
9.9.3.25A	Paging identity	285
9.9.3.26	P-TMSI signature	285
9.9.3.26A	Extended EMM cause	285
9.9.3.27	Service type	285
9.9.3.28	Short MAC	286
9.9.3.29	Time zone	287
9.9.3.30	Time zone and time	287
9.9.3.31	TMSI status	287

9.9.3.32	Tracking area identity	287
9.9.3.33	Tracking area identity list.....	288
9.9.3.34	UE network capability.....	293
9.9.3.35	UE radio capability information update needed.....	297
9.9.3.36	UE security capability.....	298
9.9.3.37	Emergency Number List	302
9.9.3.38	CLI	302
9.9.3.39	SS Code.....	303
9.9.3.40	LCS indicator	303
9.9.3.41	LCS client identity	303
9.9.3.42	Generic message container type.....	304
9.9.3.43	Generic message container.....	304
9.9.3.44	Voice domain preference and UE's usage setting.....	305
9.9.3.45	GUTI type	305
9.9.4	EPS Session Management (ESM) information elements.....	305
9.9.4.1	Access point name.....	305
9.9.4.2	APN aggregate maximum bit rate	305
9.9.4.2A	Connectivity type	309
9.9.4.3	EPS quality of service	309
9.9.4.4	ESM cause.....	315
9.9.4.5	ESM information transfer flag	317
9.9.4.6	Linked EPS bearer identity	317
9.9.4.7	LLC service access point identifier.....	318
9.9.4.7A	Notification indicator	318
9.9.4.8	Packet flow identifier	318
9.9.4.9	PDN address.....	319
9.9.4.10	PDN type.....	319
9.9.4.11	Protocol configuration options	320
9.9.4.12	Quality of service	320
9.9.4.13	Radio priority	320
9.9.4.13A	Re-attempt indicator.....	320
9.9.4.14	Request type	321
9.9.4.15	Traffic flow aggregate description	321
9.9.4.16	Traffic flow template.....	321
9.9.4.17	Transaction identifier	321
9.9.4.18	WLAN offload acceptability.....	321
10	List of system parameters.....	321
10.1	General	321
10.2	Timers of EPS mobility management.....	322
10.3	Timers of EPS session management.....	328
Annex A (informative): Cause values for EPS mobility management.....		330
A.1	Causes related to UE identification	330
A.2	Cause related to subscription options.....	330
A.3	Causes related to PLMN specific network failures and congestion/authentication failures.....	331
A.4	Causes related to nature of request.....	332
A.5	Causes related to invalid messages	332
Annex B (informative): Cause values for EPS session management		334
B.1	Causes related to nature of request.....	334
B.2	Protocol errors (e.g., unknown message) class.....	336
Annex C (normative): Storage of EMM information		338
Annex D (normative): Establishment cause (S1 mode only)		339
D.1	Mapping of NAS procedure to RRC establishment cause (S1 mode only).....	339

Annex E (informative): Guidelines for enhancements to MS network capability IE and UE network capability IE345

Annex F (informative): Change history346

History366

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies the procedures used by the protocols for mobility management and session management between User Equipment (UE) and Mobility Management Entity (MME) in the Evolved Packet System (EPS). These protocols belong to the non-access stratum (NAS).

The EPS Mobility Management (EMM) protocol defined in the present document provides procedures for the control of mobility when the User Equipment (UE) is using the Evolved UMTS Terrestrial Radio Access Network (E-UTRAN). The EMM protocol also provides control of security for the NAS protocols.

The EPS Session Management (ESM) protocol defined in the present document provides procedures for the handling of EPS bearer contexts. Together with the bearer control provided by the access stratum, this protocol is used for the control of user plane bearers.

For both NAS protocols the present document specifies procedures for the support of inter-system mobility between E-UTRAN and other 3GPP or non-3GPP access networks:

- For inter-system mobility between E-UTRAN and GERAN or UTRAN, this includes rules for a mapping between parameters and procedures used by the NAS protocols defined in the present document and the NAS protocols specified in 3GPP TS 24.008 [13].
- For inter-system mobility between E-UTRAN and generic non-3GPP access networks, this includes specific NAS procedures to maintain IP connectivity to the PDN Gateway and to provide parameters needed by the UE when using mobility management based on Dual-Stack Mobile IPv6 (see 3GPP TS 24.303 [14]) or MIPv4 (see 3GPP TS 24.304 [15]).

The present document is applicable to the UE and to the Mobility Management Entity (MME) in the EPS.

The present document is also applicable to the relay node in the EPS (see 3GPP TS 23.401 [10]).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [1A] 3GPP TS 22.011: "Service accessibility".
- [1B] Void.
- [1C] 3GPP TS 22.278: "Service requirements for the Evolved Packet System (EPS)".
- [2] 3GPP TS 23.003: "Numbering, addressing and identification".
- [3] 3GPP TS 23.038: "Alphabets and language-specific information".
- [4] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service Description; Stage 2".
- [5] 3GPP TS 23.107: "Quality of Service (QoS) concept and architecture".
- [6] 3GPP TS 23.122: "Non-Access-Stratum functions related to Mobile Station (MS) in idle mode".