

# ETSI TS 102 490 V1.8.1 (2014-06)



Technical Specification

**Electromagnetic compatibility  
and Radio spectrum Matters (ERM);  
Peer-to-Peer Digital Private Mobile Radio using FDMA  
with a channel spacing of 6,25 kHz with e.r.p. of up to 500 mW**

---

Reference

RTS/ERM-TGDMM-320

---

Keywords

air interface, digital, FDMA, PMR, protocol, radio

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
1 Scope .....	7
2 References .....	7
2.1 Normative references .....	7
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations .....	8
3.1 Definitions.....	8
3.2 Symbols.....	9
3.3 Abbreviations .....	9
4 Overview .....	10
4.1 Protocol architecture.....	11
4.1.1 Air Interface Physical Layer (layer 1).....	12
4.1.2 Air Interface Data Link Layer (layer 2).....	12
4.1.3 Air Interface Call Control Layer (layer 3) .....	12
4.2 FDMA Structure.....	13
4.2.1 Overview of the transmission structure .....	13
4.2.2 Transmission format .....	13
4.2.3 Transmission sequences.....	14
5 Frame coding.....	16
5.1 Superframe .....	16
5.2 Header frame .....	17
5.3 End frame .....	17
5.4 Packet data header .....	18
5.5 ACK frame .....	18
5.6 Frame numbering .....	19
5.7 Communication mode .....	19
5.8 Communication format.....	19
5.9 SLD format.....	19
5.9.1 Slow data in the voice superframe .....	19
5.9.2 Slow data field use with Type 1 or 2 data.....	20
5.10 Call information .....	21
5.10.1 Call Information for powersave .....	21
5.10.2 Call Information for Types 1 and 2 data.....	21
5.10.3 Call Information for Type 3 (packet) data .....	22
5.10.4 Call Information for system transactions .....	23
5.10.5 Call Information for acknowledgements.....	23
5.11 Header type .....	23
5.12 End type .....	24
5.13 ARQ .....	24
5.14 Tx Wait.....	24
5.15 Status .....	25
5.16 Version [V].....	25
6 Synchronization.....	25
6.1 Frame synchronization .....	25
6.1.1 FS1.....	25
6.1.2 FS2.....	25
6.1.3 FS3.....	26
6.1.4 FS4.....	26
6.1.5 Channel code .....	26
6.1.6 Preamble .....	27
7 Interleaving and FEC coding.....	28

7.1	Di-bit coding .....	28
7.2	CRC addition.....	28
7.3	Hamming code .....	28
7.4	Scrambling .....	28
7.5	Interleaving.....	29
7.6	FEC coding of CCH (superframe).....	30
7.7	FEC coding of HI (header information) .....	30
7.8	FEC coding of END information .....	31
8	Bearer services, tele-services and supplementary services .....	31
8.1	Initial mode .....	31
8.1.1	Initial addressing.....	31
8.1.1.1	Common ID.....	31
8.1.1.2	Fixed part of address .....	32
8.1.2	ISF channel codes .....	32
8.2	Configured mode.....	32
8.2.1	Call types .....	33
8.2.1.1	Individual call .....	33
8.2.1.2	Group call.....	33
8.2.2	Addressing .....	33
8.2.3	CSF channel codes.....	33
8.3	Packet data.....	33
8.3.1	Format.....	33
8.3.2	Receiving party .....	34
8.3.3	Packet frame coding.....	34
8.3.4	Data frame size .....	35
8.3.5	Valid data length.....	35
8.3.6	Data checksum.....	35
9	Channel coding process.....	37
9.1	Voice superframe .....	38
9.2	Type 1 data superframe .....	41
9.3	Type 2 Data superframe .....	43
9.4	Type 3 (Packet) Data frame.....	44
9.5	Headers.....	46
9.6	End frames.....	47
10	Channel access .....	48
10.1	Listen Before Transmit (LBT).....	48
10.2	Hang time messages and timers .....	49
10.2.1	Definition.....	49
10.2.2	Action by receiving stations.....	49
10.2.3	Break-in requests .....	49
10.3	Call duration timers .....	49
10.4	Transmit admit criteria .....	49
10.4.1	General admit criteria .....	49
10.4.2	ISF admit criteria .....	50
10.4.3	CSF admit criteria.....	50
10.5	Transmission re-tries .....	50
10.6	Channel access timers and constants .....	50
10.6.1	Timers.....	50
10.6.2	Constants .....	51
11	Powersave.....	51
11.1	Transmitted format .....	51
11.2	Receive format .....	52
12	Physical Layer .....	52
12.1	General parameters.....	52
12.1.1	Frequency range.....	52
12.1.2	RF carrier bandwidth .....	52
12.1.3	Transmit frequency error .....	52
12.1.4	Time base clock drift error.....	52
12.2	Modulation .....	52

12.2.1	Symbols .....	52
12.2.2	4FSK generation .....	53
12.2.2.1	Deviation index .....	53
12.2.2.2	Square root raised cosine filter .....	54
12.2.2.3	4FSK Modulator .....	55
<b>Annex A (normative): Standard User Interface for CSF radios.....</b>		<b>56</b>
A.1	Numbering and dialling plan .....	56
A.1.1	Introduction to the numbering and dialling plan .....	56
A.2	Subscriber mapping .....	57
A.2.1	User Interface - Air Interface .....	57
A.2.1.1	Mapping for MS address space .....	58
A.2.1.1.1	The concept of the wildcard character .....	58
A.2.1.1.2	The concept of stored parameters .....	58
A.2.1.1.3	The concept of ad-hoc arrangement .....	58
A.2.1.1.4	The rules for the sender .....	58
A.2.1.1.5	The rules for the recipient .....	59
A.2.1.1.6	Mapping of dialled strings to the AI address space .....	59
A.2.1.1.6.1	Mapping of numeric dialled strings to the AI address space .....	59
A.2.2	Addresses .....	60
A.2.3	Conversion rules .....	60
A.2.3.1	MS addresses .....	60
A.2.3.2	Limiting the length of the destination address .....	61
A.2.3.3	All talkgroup address .....	61
A.3	User dialling plan .....	61
A.3.1	User numbering .....	61
A.3.1.1	Dialling method .....	61
A.3.1.2	Call Type determination .....	61
A.3.1.3	Call modifier strings .....	62
A.3.2	Dialled digits to address mapping .....	62
A.3.3	Storage requirements .....	62
A.3.3.1	MS individual address .....	62
A.3.3.2	Dialled Talkgroups .....	63
A.3.3.3	All MSs .....	63
A.3.3.4	Non-dialable numbers .....	63
A.3.3.5	Talkgroup recognition .....	63
A.3.3.5.1	All numeric talkgroups .....	63
A.3.3.5.2	Talkgroups defined by wildcards .....	64
A.3.3.5.3	MS receives a talkgroup call .....	64
A.3.4	Dialling procedures .....	64
A.3.4.1	MS calls .....	64
A.3.4.1.1	Seven digit dialling .....	64
A.3.4.1.2	Abbreviated dialling .....	64
A.3.4.1.3	Masked dialling .....	65
A.3.4.1.4	Dialling with numbers and wildcards .....	65
A.3.4.2	Call modifiers .....	66
A.3.4.2.1	Broadcast call .....	66
A.3.4.2.2	Status call .....	66
A.3.4.2.3	Force talkgroup service .....	66
A.3.4.3	Call set-up abandon or call complete .....	66
History .....		67

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

---

# 1 Scope

The present document covers digital private mobile radio equipment operating in peer-to-peer mode only.

The equipment is based on FDMA with channel spacing of 6,25 kHz supporting voice and data applications.

It covers only hand portable equipment complying with EN 301 166-2 [1] and having an integral antenna.

This equipment is for use:

- i) In accordance with ECC/DEC/(05)12 [i.1] on harmonized frequencies, technical characteristics, exemption from individual licensing and free carriage and use of digital PMR 446 applications operating in the frequency band 446,100 MHz to 446,200 MHz.

NOTE 1: The technical requirements for Digital PMR 446 included in ECC/DEC/(05)12 [i.1] are: operation in the frequency range 446,100 MHz to 446,200 MHz, maximum e.r.p. of 500 mW, and a maximum transmitter time-out-time of 180 seconds.

- ii) In the frequency band 149,01875 MHz to 149,11875 MHz under exemption from individual licensing.

NOTE 2: These requirements are: maximum e.r.p. of 500 mW, and a maximum transmitter time-out-time of 180 seconds.

---

# 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

## 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 166-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment for analogue and/or digital communication (speech and/or data) and operating on narrow band channels and having an antenna connector; Part 2: Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive".
- [2] Void.
- [3] ETSI ETS 300 230: "Radio Equipment and Systems (RES); Land mobile service; Binary Interchange of Information and Signalling (BIIS) at 1200 bit/s (BIIS 1 200)".
- [4] MPT 1327 (June 1997): "A Signalling Standard for Trunked Private Land Mobile Radio Systems".

## 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CEPT ECC/DEC/(05)12: "ECC Decision of 28 October 2005 on harmonized frequencies, technical characteristics, exemption from individual licensing and free carriage and use of digital PMR 446 applications operating in the frequency band 446.1-446.2 MHz".