

ETSI EN 301 127 V1.3.1 (2002-07)

European Standard (Telecommunications series)

**Fixed Radio Systems;
Point-to-point equipment;
High capacity digital radio systems carrying
SDH signals (up to 2 x STM-1) in frequency bands
with about 30 MHz channel spacing and using
co-polar arrangements or Co-Channel Dual Polarized
(CCDP) operation**



Reference

REN/TM-04149-5

Keywords

architecture, DRRS, PDH, point-to-point, SDH,
STM, transmission

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

DECT™, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	6
2 References	7
3 Symbols and abbreviations.....	9
3.1 Symbols.....	9
3.2 Abbreviations	9
4 General characteristics	10
4.1 Frequency bands and channel arrangements	10
4.2 Modes of operation.....	10
4.3 Compatibility requirements between systems	11
4.4 Performance and availability requirements	11
4.5 Environmental Conditions.....	11
4.5.1 Equipment within weather protected locations (indoor locations).....	11
4.5.2 Equipment for non-weather protected locations (outdoor locations).....	11
4.6 Mechanical dimensions	11
4.7 Power supply	11
4.8 Electro Magnetic Compatibility (EMC).....	12
4.9 TMN interfaces	12
4.10 Block diagram	12
4.11 Intermediate frequency.....	12
4.12 Branching/feeder/antenna requirements	12
5 Baseband characteristics.....	13
5.1 Plesiochronous digital hierarchy	13
5.2 Synchronous Digital Hierarchy (SDH).....	13
6 Transmitter characteristics	13
6.1 Output power.....	13
6.2 Automatic Transmit Power Control (ATPC).....	14
6.3 RF spectrum masks	14
6.4 Discrete CW components exceeding the spectrum mask limit.....	15
6.4.1 Spectral lines at the symbol rate	15
6.4.2 Additional CW components.....	15
6.5 Spurious emissions	16
6.5.1 Spurious emissions-External.....	16
6.5.2 Spurious emissions-Internal.....	16
6.6 Radio frequency tolerance.....	16
6.7 Return loss at point C'	17
7 Receiver characteristics	17
7.1 Rx local oscillator frequency arrangements	17
7.2 Receiver image rejection.....	17
7.3 Spurious emissions	17
7.3.1 Spurious emissions-External.....	17
7.3.2 Spurious emissions-Internal.....	17
7.4 Input level range.....	18
7.5 Overall receiver selectivity.....	18
7.6 Return loss at point C	18
8 System characteristics without diversity	18
8.1 Equipment background BER.....	18
8.2 BER as a function of receive input level (dBm).....	18
8.3 Interference sensitivity	19
8.3.1 Co-channel "external" interference sensitivity.....	19

8.3.2	Adjacent channel interference sensitivity	19
8.4	Distortion sensitivity	20
9	System characteristics with diversity	20
9.1	Differential delay compensation.....	20
9.2	BER performance	20
10	Cross polar interference sensitivity	20
10.1	Co-channel "internal" interference sensitivity in flat fading conditions.....	20
10.2	Co-channel "internal" interference sensitivity in dispersive fading conditions	21
Annex A (normative): Requirements and measurement test set.....		26
A.1	Branching, feeder and antenna requirements	26
A.1.1	Antenna radiation pattern envelopes	26
A.1.2	Cross-Polar Discrimination (XPD).....	26
A.1.3	Intermodulation products	26
A.1.4	Interport isolation	26
A.1.5	Return loss.....	26
A.1.6	Antenna/equipment/feeder flanges	26
A.2	Measurement test set for XPI characteristics	27
Annex B (informative): Typical behaviours of interference sensitivity.....		28
History		31