

ETSI EN 300 219 v2.1.1 (2016-08)



**Land Mobile Service;
Radio equipment transmitting signals to initiate
a specific response in the receiver;
Harmonised Standard covering the essential requirements
of article 3.2 of the Directive 2014/53/EU**

Reference
REN/ERM-TGDMR-349

Keywords
analogue, mobile, PMR, radio, signalling

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.
The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions.....	10
3.2 Symbols.....	10
3.3 Abbreviations	10
4 Speech equipment with signalling.....	11
4.1 Applicability.....	11
4.1.1 General.....	11
4.1.2 Equipment with speech and signalling functions.....	11
4.1.3 Equipment with an add-on signalling unit	11
5 General and operational requirements.....	12
5.1 General	12
5.1.1 Environmental profile	12
5.1.2 Choice of model for testing	12
5.2 Mechanical and electrical design.....	12
5.2.1 General.....	12
5.2.2 Controls	12
5.2.3 Transmitter shut-off facility (time-out).....	12
6 Test conditions, power sources and ambient temperatures	12
6.1 Normal and extreme test conditions	12
6.2 Test power source.....	12
6.3 Normal test conditions.....	13
6.3.1 Normal temperature and humidity	13
6.3.2 Normal test power source	13
6.3.2.1 Mains voltage	13
6.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	13
6.3.2.3 Other power sources.....	13
6.4 Extreme test conditions	13
6.4.1 Extreme temperatures	13
6.4.2 Extreme test source voltages.....	14
6.4.2.1 Mains voltage.....	14
6.4.2.2 Regulated lead-acid battery power sources used on vehicles.....	14
6.4.2.3 Power sources using other types of batteries.....	14
6.4.2.4 Other power sources.....	14
6.5 Procedure for tests at extreme temperatures.....	14
6.5.0 Thermal balance.....	14
6.5.1 Procedure for equipment designed for continuous transmission.....	15
6.5.2 Procedure for equipment designed for intermittent transmission	15
7 General conditions of measurement	15
7.1 Arrangements for test signals at the input of the receiver	15
7.2 Receiver mute or squelch facility	15
7.3 Normal test signals, (wanted and unwanted signals).....	15
7.4 Encoder for receiver measurements	16
7.5 Test Load (artificial antenna)	16
7.6 Test sites and general arrangements for radiated measurements	16
7.7 Transmitter automatic shut-off facility (time-out).....	16

7.8	Modes of operation of the transmitter	16
7.9	Facilities for access between the receiver demodulator output and its decoder	16
7.10	Calling indicator	17
7.11	Reset	17
7.12	Reset time	17
7.13	Test of equipment with a duplex filter.....	17
8	Technical characteristic of the transmitter	17
8.1	Frequency error	17
8.1.0	Applicability	17
8.1.1	Definition.....	17
8.1.2	Method of measurement	17
8.1.3	Limits.....	18
8.2	Carrier power (conducted).....	18
8.2.0	Applicability	18
8.2.1	Definitions	18
8.2.2	Method of measurement	19
8.2.3	Limits.....	19
8.3	Effective radiated power (field strength).....	19
8.3.0	Applicability	19
8.3.1	Definition.....	19
8.3.2	Method of measurement	19
8.3.3	Limits.....	21
8.4	Adjacent and alternate channel power.....	22
8.4.0	Applicability	22
8.4.1	Definition.....	22
8.4.2	Method of measurement	22
8.4.3	Limits.....	24
8.5	Transmitter spurious emissions	24
8.5.0	Applicability	24
8.5.1	Definition.....	24
8.5.2	Method of measuring the power level	24
8.5.3	Method of measuring the effective radiated power.....	25
8.5.4	Transmitter spurious emissions.....	26
8.6	Intermodulation attenuation.....	27
8.6.0	Applicability	27
8.6.1	Definition.....	27
8.6.2	Method of measurement	28
8.6.3	Limits.....	29
8.7	Transmitter Attack Time	29
8.7.0	Applicability	29
8.7.1	Definition.....	29
8.7.2	Method of measurement	29
8.7.3	Limits.....	30
8.8	Transmitter release time	30
8.8.0	Applicability	30
8.8.1	Definition.....	30
8.8.2	Method of measurement	30
8.8.3	Limits.....	31
8.9	Transient frequency behaviour of the transmitter.....	31
8.9.0	Applicability	31
8.9.1	Definitions	31
8.9.2	Method of measurement	31
8.9.3	Limits.....	35
9	Technical characteristics of the receiver	35
9.1	Reference sensitivity (responses)	35
9.1.1	Definition.....	35
9.1.2	Reference sensitivity (response)	35
9.2	Maximum usable sensitivity (responses, conducted)	35
9.2.0	Applicability	35
9.2.1	Definition.....	35

9.2.2	Method of measurement ("up-down method")	36
9.2.3	Limits	36
9.3	Average usable sensitivity (field strength, responses).....	36
9.3.0	Applicability	36
9.3.1	Definition	37
9.3.2	Method of measurement under normal test conditions	37
9.3.3	Method of measurement of the average usable sensitivities under extreme test conditions.....	38
9.3.4	References for degradation measurements	39
9.3.4.1	Definition.....	39
9.3.4.2	Procedures for measurements using the test fixture	39
9.3.4.3	Procedures for measurements using the test site	40
9.3.5	Limits	40
9.4	Co-channel rejection.....	41
9.4.0	Applicability	41
9.4.1	Definition.....	41
9.4.2	Method of measurement	41
9.4.3	Limits	42
9.5	Adjacent channel selectivity.....	42
9.5.0	Applicability	42
9.5.1	Definition.....	42
9.5.2	Method of measurement	43
9.5.3	Limits	44
9.6	Spurious response rejection.....	44
9.6.0	Applicability	44
9.6.1	Definition.....	44
9.6.2	Introduction to the method of measurement	44
9.6.3	Method of search over the "limited frequency range"	45
9.6.4	Method of measurement	46
9.6.5	Limits	47
9.7	Intermodulation response	47
9.7.0	Applicability	47
9.7.1	Definition.....	47
9.7.2	Method of measurement	47
9.7.3	Limits	48
9.8	Blocking or desensitization	48
9.8.0	Applicability	48
9.8.1	Definition.....	48
9.8.2	Method of measurement	49
9.8.3	Limits.....	50
9.9	Receiver spurious radiations.....	50
9.9.0	Applicability	50
9.9.1	Definition.....	50
9.9.2	Method of measuring the power level	50
9.9.3	Method of measuring the effective radiated power.....	51
9.9.4	Limits	52
10	Duplex operation	52
10.0	Applicability	52
10.1	Receiver desensitization (with simultaneous transmission and reception).....	52
10.1.1	Definition.....	52
10.1.2	Method of measurement when the equipment operates with a duplex filter.....	53
10.1.3	Method of measurement when the equipment operates with separate Tx and Rx antennas	54
10.1.4	Limits.....	54
10.2	Receiver spurious response rejection (with simultaneous transmission and reception)	55
10.2.1	Definition.....	55
10.2.2	Method of measurement	55
10.2.3	Limits.....	56
11	Testing for compliance with technical requirements.....	56
11.1	Test conditions, power supply and ambient temperatures	56
11.2	Interpretation of the measurement results	56
	Annex A (normative): Radiated measurement	58

A.1	Test sites and general arrangements for measurements involving the use of radiated fields	58
A.1.0	General	58
A.1.1	Anechoic chamber	58
A.1.2	Anechoic chamber with a conductive ground plane	59
A.1.3	Open Area Test Site (OATS)	60
A.1.4	Test antenna	61
A.1.5	Substitution antenna	61
A.1.6	Measuring antenna	62
A.2	Guidance on the use of radiation test sites	62
A.2.0	General	62
A.2.1	Verification of the test site	62
A.2.2	Preparation of the EUT	62
A.2.3	Power supplies to the EUT	62
A.2.4	Volume control setting for analogue speech tests	62
A.2.5	Range length	63
A.2.6	Site preparation	63
A.3	Coupling of signals	64
A.3.1	General	64
A.3.2	Data signals	64
A.3.3	Speech and analogue signals	64
A.3.3.0	General	64
A.3.3.1	Acoustic coupler description	64
A.3.3.2	Calibration	65
A.4	Test fixture	65
A.4.1	Description	65
A.4.2	Calibration	65
A.4.3	Mode of use	66
Annex B (normative): Specification for some particular measurement arrangements	67	
B.1	Power measuring receiver specification	67
B.1.0	General	67
B.1.1	IF filter	67
B.1.2	Attenuation indicator	69
B.1.3	RMS value indicator	69
B.1.4	Oscillator and amplifier	69
B.2	Spectrum analyser specification	69
B.2.1	Adjacent and alternate channel power measurement	69
B.2.2	Unwanted emissions measurement	70
B.3	Integrating and power summing device	70
Annex C (normative): Relationship between the present document and the essential requirements of Directive 2014/53/EU	71	
History	73	

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.7] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.5].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table C.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	21 March 2016
Date of latest announcement of this EN (doa):	30 June 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 2016
Date of withdrawal of any conflicting National Standard (dow):	31 December 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document applies to constant envelope angle modulation systems for use in the land mobile service, using the available bandwidth, operating on radio frequencies between 30 MHz and 1 GHz, with channel separations of 12,5 kHz, 20 kHz and 25 kHz intended for transmission and/or reception of signals used to initiate a specific response in the receiver.

Table 1: Radiocommunications service frequency bands

Radiocommunications service frequency bands	
Transmit	30 MHz to 1 000 MHz
Receive	30 MHz to 1 000 MHz

The present document applies to non-speech and to the non-speech part of combined speech/non-speech analogue equipment. In the present document, non-speech radio equipment is defined as a radio equipment transmitting a signal to initiate a specific response in the receiver. The equipment shall comprise a transmitter and associated encoder and/or a receiver and associated decoder. The encoder and/or decoder may be a separate piece of equipment, in which case compliance to the present document covers the encoder and/or decoder in connection with the transmitter and/or receiver equipment.

In the present document different requirements are given for the different radio frequency bands, channel separations, environmental conditions and types of equipment, where appropriate.

The types of equipment covered by the present document are as follows:

- Base Station: equipment fitted with an antenna socket;
- Mobile Station: equipment fitted with an antenna socket;
- Handportable stations:
 - a) fitted with an antenna socket; or
 - b) without an external antenna socket (integral antenna equipment) but fitted with a permanent internal or a temporary internal 50 Ω Radio Frequency (RF) connector which allows access to the transmitter output and the receiver input.

Handportable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50 Ω RF connector is not covered by the present document. Integral antenna equipment is covered by ETSI EN 300 341 [i.1] (see the corresponding scope).

The present document contains requirements to demonstrate that "... *Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference*" and that "...*radio equipment supports certain features ensuring access to emergency services*" [i.5].

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Radio Equipment Directive [i.5] may apply to equipment within the scope of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.