

ETSI TS 129 272 V13.7.0 (2016-10)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Evolved Packet System (EPS);
Mobility Management Entity (MME)
and Serving GPRS Support Node (SGSN)
related interfaces based on Diameter protocol
(3GPP TS 29.272 version 13.7.0 Release 13)**



Reference

RTS/TSGC-0429272vd70

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	10
1 Scope	11
2 References	11
3 Definitions and abbreviations.....	13
3.1 Definitions	13
3.2 Abbreviations	14
4 General Description.....	14
5 MME – HSS (S6a) and SGSN – HSS (S6d)	14
5.1 Introduction	14
5.2 Mobility Services	15
5.2.1 Location Management Procedures.....	15
5.2.1.1 Update Location.....	15
5.2.1.1.1 General	15
5.2.1.1.2 Detailed behaviour of the MME and the SGSN	18
5.2.1.1.3 Detailed behaviour of the HSS	22
5.2.1.2 Cancel Location	25
5.2.1.2.1 General	25
5.2.1.2.2 Detailed behaviour of the MME and the SGSN	26
5.2.1.2.3 Detailed behaviour of the HSS	26
5.2.1.3 Purge UE.....	27
5.2.1.3.1 General	27
5.2.1.3.2 Detailed behaviour of the MME and the SGSN	27
5.2.1.3.3 Detailed behaviour of HSS	28
5.2.2 Subscriber Data Handling Procedures	28
5.2.2.1 Insert Subscriber Data	28
5.2.2.1.1 General	28
5.2.2.1.2 Detailed behaviour of the MME and the SGSN	31
5.2.2.1.3 Detailed behaviour of HSS	34
5.2.2.2 Delete Subscriber Data.....	36
5.2.2.2.1 General	36
5.2.2.2.2 Detailed behaviour of the MME and the SGSN	38
5.2.2.2.3 Detailed behaviour of the HSS	38
5.2.3 Authentication Procedures.....	39
5.2.3.1 Authentication Information Retrieval	39
5.2.3.1.1 General	39
5.2.3.1.2 Detailed behaviour of the MME and the SGSN	40
5.2.3.1.3 Detailed behaviour of the HSS	41
5.2.4 Fault Recovery Procedures	42
5.2.4.1 Reset.....	42
5.2.4.1.1 General	42
5.2.4.1.2 Detailed behaviour of the MME and the SGSN	43
5.2.4.1.3 Detailed behaviour of the HSS	43
5.2.5 Notification Procedures	44
5.2.5.1 Notification	44
5.2.5.1.1 General	44
5.2.5.1.2 Detailed behaviour of the MME and the SGSN	46
5.2.5.1.3 Detailed behaviour of the HSS	47
5A MME – CSS (S7a) and SGSN – CSS (S7d).....	48

5A.1	Introduction	48
5A.2	Mobility Services	48
5A.2.1	Location Management Procedures	48
5A.2.1.1	Update VCSG Location	48
5A.2.1.1.1	General	48
5A.2.1.1.2	Detailed behaviour of the MME and the SGSN	49
5A.2.1.1.3	Detailed behaviour of the CSS	50
5A.2.1.2	Cancel VCSG Location	50
5A.2.1.2.1	General	50
5A.2.1.2.2	Detailed behaviour of the MME and the SGSN	51
5A.2.1.2.3	Detailed behaviour of the CSS	51
5A.2.2	Subscriber Data Handling Procedures	51
5A.2.2.1	Insert VCSG Subscriber Data	51
5A.2.2.1.1	General	51
5A.2.2.1.2	Detailed behaviour of the MME and the SGSN	52
5A.2.2.1.3	Detailed behaviour of CSS	53
5A.2.2.2	Delete VCSG Subscriber Data	53
5A.2.2.2.1	General	53
5A.2.2.2.2	Detailed behaviour of the MME and the SGSN	54
5A.2.2.2.3	Detailed behaviour of the CSS	54
5A.2.3	Fault Recovery Procedures	54
5A.2.3.1	VCSG Reset	54
5A.2.3.1.1	General	54
5A.2.3.1.2	Detailed behaviour of the MME and the SGSN	55
5A.2.3.1.3	Detailed behaviour of the CSS	55
6	MME – EIR (S13) and SGSN – EIR (S13')	56
6.1	Introduction	56
6.2	ME Identity Check Procedures	56
6.2.1	ME Identity Check	56
6.2.1.1	General	56
6.2.1.2	Detailed behaviour of the MME and the SGSN	57
6.2.1.3	Detailed behaviour of the EIR	57
7	Protocol Specification and Implementation	58
7.1	Introduction	58
7.1.1	Use of Diameter base protocol	58
7.1.2	Securing Diameter Messages	58
7.1.3	Accounting functionality	58
7.1.4	Use of sessions	58
7.1.5	Transport protocol	58
7.1.6	Routing considerations	58
7.1.7	Advertising Application Support	59
7.1.8	Diameter Application Identifier	59
7.1.9	Use of the Supported-Features AVP	60
7.2	Commands	61
7.2.1	Introduction	61
7.2.2	Command-Code values	61
7.2.3	Update-Location-Request (ULR) Command	62
7.2.4	Update-Location-Answer (ULA) Command	63
7.2.5	Authentication-Information-Request (AIR) Command	63
7.2.6	Authentication-Information-Answer (AIA) Command	64
7.2.7	Cancel-Location-Request (CLR) Command	64
7.2.8	Cancel-Location-Answer (CLA) Command	64
7.2.9	Insert-Subscriber-Data-Request (IDR) Command	65
7.2.10	Insert-Subscriber-Data-Answer (IDA) Command	65
7.2.11	Delete-Subscriber-Data-Request (DSR) Command	66
7.2.12	Delete-Subscriber-Data-Answer (DSA) Command	67
7.2.13	Purge-UE-Request (PUR) Command	68
7.2.14	Purge-UE-Answer (PUA) Command	68
7.2.15	Reset-Request (RSR) Command	68
7.2.16	Reset-Answer (RSA) Command	69

7.2.17	Notify-Request (NOR) Command	70
7.2.18	Notify-Answer (NOA) Command	70
7.2.19	ME-Identity-Check-Request (ECR) Command	71
7.2.20	ME-Identity-Check-Answer (ECA) Command	71
7.2.21	Update-VCSG-Location-Request (UVR) Command.....	71
7.2.22	Update-VCSG-Location-Answer (UVA) Command.....	72
7.2.23	Cancel-VCSG-Location-Request (CVR) Command	72
7.2.24	Cancel-VCSG-Location-Answer (CVA) Command.....	73
7.3	Information Elements	74
7.3.1	General.....	74
7.3.2	Subscription-Data	82
7.3.3	Terminal-Information	83
7.3.4	IMEI.....	83
7.3.5	Software-Version	83
7.3.6	3GPP2-MEID	83
7.3.7	ULR-Flags	83
7.3.8	ULA-Flags	84
7.3.9	Visited-PLMN-Id.....	85
7.3.10	Feature-List AVP.....	85
7.3.10.1	Feature-List AVP for the S6a/S6d application.....	85
7.3.10.2	Feature-List AVP for the S7a/S7d application.....	95
7.3.11	Requested-EUTRAN-Authentication-Info	95
7.3.12	Requested-UTRAN- GERAN-Authentication-Info.....	95
7.3.13	RAT-Type.....	96
7.3.14	Number-Of-Requested-Vectors	96
7.3.15	Re-Synchronization-Info	96
7.3.16	Immediate-Response-Preferred.....	96
7.3.17	Authentication-Info.....	96
7.3.18	E-UTRAN-Vector.....	96
7.3.19	UTRAN-Vector	97
7.3.20	GERAN-Vector	97
7.3.21	Network-Access-Mode	97
7.3.22	HPLMN-ODB.....	97
7.3.23	Item-Number.....	98
7.3.24	Cancellation-Type.....	98
7.3.25	DSR-Flags.....	98
7.3.26	DSA-Flags	100
7.3.27	Context-Identifier	100
7.3.28	Void.....	100
7.3.29	Subscriber-Status	100
7.3.30	Operator-Determined-Barring.....	100
7.3.31	Access-Restriction-Data	101
7.3.32	APN-OI-Replacement.....	101
7.3.33	All-APN-Configurations-Included-Indicator.....	101
7.3.34	APN-Configuration-Profile	102
7.3.35	APN-Configuration.....	102
7.3.36	Service-Selection	103
7.3.37	EPS-Subscribed-QoS-Profile.....	104
7.3.38	VPLMN-Dynamic-Address-Allowed	104
7.3.39	STN-SR	104
7.3.40	Allocation-Retention-Priority	104
7.3.41	AMBR	105
7.3.42	MIP-Home-Agent-Address.....	105
7.3.43	MIP-Home-Agent-Host	105
7.3.44	PDN-GW-Allocation-Type.....	105
7.3.45	MIP6-Agent-Info	105
7.3.46	RAT-Frequency-Selection-Priority-ID	106
7.3.47	IDA-Flags	106
7.3.48	PUA-Flags	106
7.3.49	NOR-Flags.....	106
7.3.50	User-Id.....	107
7.3.51	Equipment-Status.....	107

7.3.52	Regional-Subscription-Zone-Code	108
7.3.53	RAND	108
7.3.54	XRES	108
7.3.55	AUTN	108
7.3.56	KASME	108
7.3.57	Confidentiality-Key AVP	108
7.3.58	Integrity-Key AVP	108
7.3.59	Kc AVP	108
7.3.60	SRES	108
7.3.61	Void	108
7.3.62	PDN-Type	108
7.3.63	Trace-Data AVP	109
7.3.64	Trace-Reference AVP	109
7.3.65	Void	110
7.3.66	Void	110
7.3.67	Trace-Depth AVP	110
7.3.68	Trace-NE-Type-List AVP	110
7.3.69	Trace-Interface-List AVP	110
7.3.70	Trace-Event-List AVP	110
7.3.71	OMC-Id AVP	110
7.3.72	GPRS-Subscription-Data	110
7.3.73	Complete-Data-List-Included-Indicator	111
7.3.74	PDP-Context	111
7.3.75	PDP-Type	111
7.3.75A	Ext-PDP-Type	112
7.3.76	Void	112
7.3.77	QoS-Subscribed	112
7.3.78	CSG-Subscription-Data	112
7.3.79	CSG-Id	112
7.3.80	Expiration-Date	112
7.3.81	Roaming-Restricted-Due-To-Unsupported-Feature	112
7.3.82	Specific-APN-Info AVP	112
7.3.83	Alert-Reason AVP	113
7.3.84	LCS-Info	113
7.3.85	GMLC-Number	113
7.3.86	LCS-PrivacyException	113
7.3.87	SS-Code	114
7.3.88	SS-Status	114
7.3.89	Notification-To-UE-User	114
7.3.90	External-Client	114
7.3.91	Client-Identity	114
7.3.92	GMLC-Restriction	114
7.3.93	PLMN-Client	115
7.3.94	Service-Type	115
7.3.95	ServiceTypeIdentity	115
7.3.96	MO-LR	115
7.3.97	Void	115
7.3.98	Trace-Collection-Entity AVP	115
7.3.99	Teleservice-List	115
7.3.100	TS-Code	116
7.3.101	Call-Barring-Info	116
7.3.102	SGSN-Number	116
7.3.103	IDR-Flags	116
7.3.104	ICS-Indicator	117
7.3.105	Visited-Network-Identifier	117
7.3.107	Homogeneous-Support-of-IMS-Voice-Over-PS-Sessions	118
7.3.108	Last-UE-Activity-Time	118
7.3.109	GMLC-Address	118
7.3.110	EPS-User-State	118
7.3.111	EPS-Location-Information	118
7.3.112	MME-User-State	119
7.3.113	SGSN-User-State	119

7.3.114	User-State	119
7.3.115	MME-Location-Information	120
7.3.116	SGSN-Location-Information	120
7.3.117	E-UTRAN-Cell-Global-Identity	121
7.3.118	Tracking-Area-Identity	121
7.3.119	Cell-Global-Identity	121
7.3.120	Routing-Area-Identity	121
7.3.121	Location-Area-Identity	121
7.3.122	Service-Area-Identity.....	121
7.3.123	Geographical-Information	121
7.3.124	Geodetic-Information.....	121
7.3.125	Current-Location-Retrieved.....	121
7.3.126	Age-Of-Location-Information	122
7.3.127	Active-APN	122
7.3.128	Error-Diagnostic	122
7.3.129	Ext-PDP-Address AVP.....	122
7.3.130	UE-SRVCC-Capability.....	123
7.3.131	MPS-Priority.....	123
7.3.132	VPLMN-LIPA-Allowed	123
7.3.133	LIPA-Permission	123
7.3.134	Subscribed-Periodic-RAU-TAU-Timer.....	123
7.3.135	SIPTO-Permission	124
7.3.136	MDT-Configuration.....	124
7.3.137	Job-Type	124
7.3.138	Area-Scope	125
7.3.139	List-Of-Measurements	125
7.3.140	Reporting-Trigger	125
7.3.141	Report-Interval.....	125
7.3.142	Report-Amount	125
7.3.143	Event-Threshold-RSRP	125
7.3.144	Event-Threshold-RSRQ.....	125
7.3.145	Logging-Interval	125
7.3.146	Logging-Duration	125
7.3.147	Relay-Node-Indicator	126
7.3.148	MDT-User-Consent	126
7.3.149	PUR-Flags.....	126
7.3.150	Subscribed-VSRVCC	126
7.3.151	Equivalent-PLMN-List	126
7.3.152	CLR-Flags.....	127
7.3.153	UVR-Flags.....	127
7.3.154	UVA-Flags.....	127
7.3.155	VPLMN-CSG-Subscription-Data.....	128
7.3.156	Local-Time-Zone	128
7.3.157	A-MSISDN	128
7.3.158	Void	128
7.3.159	MME-Number-for-MT-SMS.....	128
7.3.160	Void	129
7.3.161	Void	129
7.3.162	SMS-Register-Request.....	129
7.3.163	Time-Zone	129
7.3.164	Daylight-Saving-Time	129
7.3.165	Subscription-Data-Flags	129
7.3.166	Measurement-Period-LTE	130
7.3.167	Measurement-Period-UMTS.....	130
7.3.168	Collection-Period-RRM-LTE	130
7.3.169	Collection-Period-RRM-UMTS	130
7.3.170	Positioning-Method	130
7.3.171	Measurement-Quantity	130
7.3.172	Event-Threshold-Event-1F	130
7.3.173	Event-Threshold-Event-1I	130
7.3.174	Restoration-Priority	131
7.3.175	SGs-MME-Identity.....	131

7.3.176	SIPTO-Local-Network-Permission.....	131
7.3.177	Coupled-Node-Diameter-ID.....	131
7.3.178	OC-Supported-Features	131
7.3.179	OC-OLR	131
7.3.180	ProSe-Subscription-Data	131
7.3.181	WLAN-offloadability	131
7.3.182	WLAN-offloadability-EUTRAN	132
7.3.183	WLAN-offloadability-UTRAN	132
7.3.184	Reset-ID.....	132
7.3.185	MDT-Allowed-PLMN-Id	132
7.3.186	Adjacent-PLMNs	133
7.3.187	Adjacent-Access-Restriction-Data.....	133
7.3.188	DL-Buffering-Suggested-Packet-Count.....	133
7.3.189	IMSI-Group-Id.....	133
7.3.190	Group-Service-Id	134
7.3.191	Group-PLMN-Id.....	134
7.3.192	Local-Group-Id	134
7.3.193	AESE-Communication-Pattern.....	134
7.3.194	Communication-Pattern-Set.....	135
7.3.195	Monitoring-Event-Configuration	135
7.3.196	Monitoring-Event-Report	136
7.3.197	UE-Reachability-Configuration	136
7.3.198	eNodeB-ID.....	136
7.3.199	Supported-Services	136
7.3.200	Supported-Monitoring-Events	136
7.3.201	AIR-Flags	137
7.3.202	UE-Usage-Type	137
7.3.203	DRMP	137
7.3.204	Non-IP-PDN-Type-Indicator	137
7.3.205	Non-IP-Data-Delivery-Mechanism.....	138
7.3.206	Additional-Context-Identifier	138
7.3.207	SCEF-Realm.....	138
7.3.208	Void.....	138
7.3.209	Preferred-Data-Mode.....	138
7.4	Result-Code and Experimental-Result Values	139
7.4.1	General.....	139
7.4.2	Success.....	139
7.4.3	Permanent Failures	139
7.4.3.1	DIAMETER_ERROR_USER_UNKNOWN (5001).....	139
7.4.3.2	DIAMETER_ERROR_UNKNOWN_EPS_SUBSCRIPTION (5420).....	139
7.4.3.3	DIAMETER_ERROR_RAT_NOT_ALLOWED (5421).....	139
7.4.3.4	DIAMETER_ERROR_ROAMING_NOT_ALLOWED (5004)	139
7.4.3.5	DIAMETER_ERROR_EQUIPMENT_UNKNOWN (5422)	140
7.4.3.6	DIAMETER_ERROR_UNKOWN_SERVING_NODE (5423).....	140
7.4.4	Transient Failures	140
7.4.4.1	DIAMETER_AUTHENTICATION_DATA_UNAVAILABLE (4181).....	140
7.4.4.2	DIAMETER_ERROR_CAMEL_SUBSCRIPTION_PRESENT (4182).....	140
8	User identity to HSS resolution.....	140
Annex A (normative):	MME mapping table for S6a and NAS Cause Code values	142
Annex B(normative):	SGSN mapping table for S6d and NAS Cause Code values.....	145
Annex C (normative):	Diameter overload control mechanism	147
C.1	General	147
C.2	S6a/S6d interfaces	147
C.2.1	General.....	147
C.2.2	HSS behaviour	147
C.2.3	MME/SGSN behaviour.....	147
Annex D (Informative):	Diameter overload control node behaviour	148
D.1	Message prioritisation over S6a/d	148

Annex E (normative): Diameter message priority mechanism.....149

E.1 General 149

E.2 S6a/S6d interfaces 149

E.2.1 General..... 149

E.2.2 HSS, CSS, EIR behaviour..... 149

E.2.3 MME/SGSN behaviour..... 149

Annex F (informative): Change history150

History 156

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document describes the Mobility Management Entity (MME) and Serving GPRS Support Node (SGSN) related diameter-based interfaces towards the Home Subscriber Server (HSS) or the CSG Subscriber Server (CSS), and the MME and the SGSN related diameter-based interface towards the Equipment Identity Register (EIR).

This specification defines the Diameter application for the MME-HSS, S6a reference point, for the MME-CSS, S7a reference point, for the SGSN-HSS, S6d reference point, and for the SGSN-CSS, S7d reference point. The interactions between the HSS/CSS and the MME/SGSN are specified, including the signalling flows.

This specification defines the Diameter application for the MME-EIR, S13 reference point, and for the SGSN-EIR, S13' reference point. The interactions between the MME/SGSN and the EIR are specified, including the signalling flows.

In this specification, if there is no specific indication, the following principles apply:

- "SGSN" refers to an SGSN which at least supports the S4 interface and may support Gn and Gp interfaces.
- "S4-SGSN" refers to an SGSN which supports the S4 interface and does not support Gn and Gp interfaces.
- Gn/Gp-SGSN refers to an SGSN which supports the Gn and Gp interfaces and does not support S4 interface.
- "GPRS subscription data" refers to the parameters in the HLR column in Table 5.2. in 3GPP TS 23.008 [30].
- "EPS subscription data" refers to the parameters in the HSS column in Table 5.2A-1 in 3GPP TS 23.008 [30].

The Evolved Packet System stage 2 description (architecture and functional solutions) is specified in 3GPP TS 23.401 [2] and in 3GPP TS 23.060 [12].

SGSN CAMEL Subscription Data are not supported over S6d interface.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.401: "GPRS enhancements for E-UTRAN access".
- [3] 3GPP TS 23.003: "Numbering, addressing and identification".
- [4] IETF RFC 3588: "Diameter Base Protocol".
- [5] 3GPP TS 33.401: "3GPP System Architecture Evolution: Security Architecture".
- [6] IETF RFC 4005: "Diameter Network Access Server Application".
- [7] IETF RFC 2234: "Augmented BNF for syntax specifications".
- [8] 3GPP TS 32.299: "Charging management; Diameter charging applications".
- [9] 3GPP TS 29.229: "Cx and Dx interfaces based on the Diameter protocol".
- [10] 3GPP TS 29.212: "Policy and Charging Control (PCC); Reference points".