

ETSI TS 125 105 V14.0.0 (2017-04)



**Universal Mobile Telecommunications System (UMTS);
Base Station (BS) radio transmission and reception (TDD)
(3GPP TS 25.105 version 14.0.0 Release 14)**



Reference

RTS/TSGR-0425105ve00

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
oneM2M logo is protected for the benefit of its Members
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 8 |
| 1 Scope | 9 |
| 2 References | 9 |
| 3 Definitions, symbols and abbreviations | 9 |
| 3.1 Definitions..... | 9 |
| 3.2 (void)..... | 11 |
| 3.3 Abbreviations | 11 |
| 4 General | 12 |
| 4.1 Relationship between Minimum Requirements and Test Requirements | 12 |
| 4.2 Base station classes | 12 |
| 4.3 Regional requirements..... | 12 |
| 4.4 Environmental requirements for the BS equipment | 13 |
| 4.5 MBSFN-only operation..... | 13 |
| 4.6 Requirements for BS capable of multi-band operation | 14 |
| 5 Frequency bands and channel arrangement..... | 14 |
| 5.1 General | 14 |
| 5.2 Frequency bands..... | 14 |
| 5.3 TX-RX frequency separation | 14 |
| 5.3.1 3,84 Mcps TDD Option | 14 |
| 5.3.2 1,28 Mcps TDD Option | 15 |
| 5.3.3 7.68 Mcps TDD Option | 15 |
| 5.4 Channel arrangement..... | 15 |
| 5.4.1 Channel spacing..... | 15 |
| 5.4.1.1 3,84 Mcps TDD Option..... | 15 |
| 5.4.1.2 1,28 Mcps TDD Option..... | 15 |
| 5.4.1.3 7.68 Mcps TDD Option..... | 15 |
| 5.4.2 Channel raster | 15 |
| 5.4.2.1 3.84 Mcps TDD Option..... | 15 |
| 5.4.2.2 7.68 Mcps TDD Option..... | 15 |
| 5.4.3 Channel number..... | 15 |
| 6 Transmitter characteristics | 16 |
| 6.1 General | 16 |
| 6.2 Base station output power | 16 |
| 6.2.1 Base station maximum output power..... | 17 |
| 6.2.1.1 Minimum Requirement | 17 |
| 6.3 Frequency stability | 17 |
| 6.3.1 Minimum Requirement..... | 17 |
| 6.3.1.1 3,84 Mcps TDD Option..... | 17 |
| 6.3.1.2 1,28 Mcps TDD Option..... | 17 |
| 6.3.1.3 7,68 Mcps TDD Option..... | 17 |
| 6.4 Output power dynamics..... | 18 |
| 6.4.1 Inner loop power control..... | 18 |
| 6.4.2 Power control steps..... | 18 |
| 6.4.2.1 Minimum Requirement | 18 |
| 6.4.3 Power control dynamic range | 18 |
| 6.4.3.1 Minimum Requirement | 18 |
| 6.4.4 Minimum output power | 18 |
| 6.4.4.1 Minimum Requirement | 18 |
| 6.4.5 Primary CCPCH power | 19 |

| | | |
|-----------|---|----|
| 6.4.6 | Differential accuracy of Primary CCPCH power..... | 19 |
| 6.4.6.1 | Minimum Requirement for Differential accuracy of PCCPCH power | 19 |
| 6.5 | Transmit ON/OFF power | 19 |
| 6.5.1 | Transmit OFF power..... | 19 |
| 6.5.1.1 | Minimum Requirement | 19 |
| 6.5.1.1.1 | 3,84 Mcps TDD Option..... | 19 |
| 6.5.1.1.2 | 1,28 Mcps TDD Option..... | 19 |
| 6.5.1.1.3 | 7,68 Mcps TDD Option..... | 19 |
| 6.5.2 | Transmit ON/OFF Time mask | 19 |
| 6.5.2.1 | Minimum Requirement | 20 |
| 6.5.2.1.1 | 3,84 Mcps TDD Option..... | 20 |
| 6.5.2.1.2 | 1,28 Mcps TDD Option..... | 20 |
| 6.5.2.1.3 | 7,68 Mcps TDD Option..... | 20 |
| 6.6 | Output RF spectrum emissions..... | 21 |
| 6.6.1 | Occupied bandwidth | 21 |
| 6.6.1.1 | 3,84 Mcps TDD Option..... | 21 |
| 6.6.1.2 | 1,28 Mcps TDD Option..... | 21 |
| 6.6.1.3 | 7,68 Mcps TDD Option..... | 21 |
| 6.6.2 | Out of band emission | 21 |
| 6.6.2.1 | Spectrum emission mask..... | 21 |
| 6.6.2.1.1 | 3,84 Mcps TDD Option..... | 21 |
| 6.6.2.1.2 | 1,28 Mcps TDD Option..... | 23 |
| 6.6.2.1.3 | 7,68 Mcps TDD Option..... | 25 |
| 6.6.2.2 | Adjacent Channel Leakage power Ratio (ACLR)..... | 27 |
| 6.6.2.2.1 | Minimum Requirement | 28 |
| 6.6.2.2.2 | Void..... | 29 |
| 6.6.2.2.3 | Void..... | 29 |
| 6.6.3 | Spurious emissions | 29 |
| 6.6.3.1 | Mandatory Requirements | 30 |
| 6.6.3.1.1 | Spurious emissions (Category A) | 30 |
| 6.6.3.1.2 | Spurious emissions (Category B) | 31 |
| 6.6.3.2 | Co-existence with GSM, DCS, UTRA and/or E-UTRA | 32 |
| 6.6.3.2.1 | Operation in the same geographic area..... | 32 |
| 6.6.3.2.2 | Co-located base stations | 36 |
| 6.6.3.3 | Void..... | 37 |
| 6.6.3.3.1 | Void..... | 37 |
| 6.6.3.3.2 | Void..... | 37 |
| 6.6.3.4 | Void..... | 38 |
| 6.6.3.4.1 | Void..... | 38 |
| 6.6.3.4.2 | Void..... | 38 |
| 6.6.3.5 | Co-existence with unsynchronised UTRA TDD and/or E-UTRA TDD | 38 |
| 6.6.3.5.1 | Operation in the same geographic area..... | 38 |
| 6.6.3.5.2 | Co-located base stations | 40 |
| 6.6.3.6 | Co-existence with PHS | 43 |
| 6.6.3.6.1 | Minimum Requirement | 44 |
| 6.7 | Transmitter intermodulation | 44 |
| 6.7.1 | Minimum Requirement | 44 |
| 6.7.1.1 | 3,84 Mcps TDD Option..... | 44 |
| 6.7.1.2 | 1,28 Mcps TDD Option: | 44 |
| 6.7.1.3 | 7,68 Mcps TDD Option..... | 45 |
| 6.8 | Transmit modulation | 45 |
| 6.8.1 | Transmit pulse shape filter..... | 45 |
| 6.8.2 | Modulation Accuracy | 45 |
| 6.8.2.1 | Minimum Requirement | 46 |
| 6.8.3 | Peak Code Domain Error | 46 |
| 6.8.3.1 | Minimum Requirement | 46 |
| 6.8.4 | Relative Code Domain Error for 64QAM modulation..... | 46 |
| 6.8.4.1 | Minimum requirement | 46 |
| 6.8.5 | Time alignment error in MIMO transmission | 46 |
| 6.8.5.1 | Minimum Requirement | 46 |
| 7 | Receiver characteristics | 46 |

| | | |
|-----------|---|----|
| 7.1 | General | 46 |
| 7.2 | Reference sensitivity level..... | 47 |
| 7.2.1 | Minimum Requirement..... | 47 |
| 7.2.1.1 | 3,84 Mcps TDD Option..... | 47 |
| 7.2.1.2 | 1,28 Mcps TDD Option..... | 47 |
| 7.2.1.3 | 7,68 Mcps TDD Option..... | 48 |
| 7.3 | Dynamic range | 48 |
| 7.3.1 | Minimum requirement | 48 |
| 7.3.1.1 | 3,84 Mcps TDD Option..... | 48 |
| 7.3.1.2 | 1,28 Mcps TDD Option: | 48 |
| 7.3.1.3 | 7,68 Mcps TDD Option..... | 48 |
| 7.4 | Adjacent Channel Selectivity (ACS)..... | 49 |
| 7.4.1 | Minimum Requirement..... | 49 |
| 7.4.1.1 | 3,84 Mcps TDD Option..... | 49 |
| 7.4.1.2 | 1,28 Mcps TDD Option..... | 49 |
| 7.4.1.3 | 7,68 Mcps TDD Option..... | 49 |
| 7.5 | Blocking characteristics | 50 |
| 7.5.0 | Minimum requirement | 50 |
| 7.5.0.1 | 3,84 Mcps TDD Option..... | 50 |
| 7.5.0.2 | 1,28 Mcps TDD Option..... | 52 |
| 7.5.0.3 | 7,68 Mcps TDD Option..... | 56 |
| 7.5.1 | Co-location with GSM, DCS, UTRA FDD and/or E-UTRA FDD, UTRA TDD and/or E-UTRA TDD | 58 |
| 7.5.1.1 | 3,84 Mcps TDD Option..... | 58 |
| 7.5.1.2 | 1,28 Mcps TDD Option..... | 59 |
| 7.5.1.3 | 7,68 Mcps TDD Option..... | 61 |
| 7.5.2 | Void | 62 |
| 7.5.2.1 | Void..... | 62 |
| 7.5.2.2 | Void..... | 62 |
| 7.5.2.3 | Void..... | 62 |
| 7.6 | Intermodulation characteristics | 62 |
| 7.6.1 | Minimum requirement | 62 |
| 7.6.1.1 | 3,84 Mcps TDD Option..... | 62 |
| 7.6.1.2 | 1,28 Mcps TDD Option..... | 62 |
| 7.6.1.3 | 7,68 Mcps TDD Option..... | 63 |
| 7.7 | Spurious emissions | 63 |
| 7.7.1 | Minimum Requirement | 63 |
| 7.7.1.1 | 3,84 Mcps TDD Option..... | 63 |
| 7.7.1.2 | 1,28 Mcps TDD Option..... | 64 |
| 7.7.1.3 | 7,68 Mcps TDD Option..... | 65 |
| 8 | Performance requirement | 65 |
| 8.1 | General | 65 |
| 8.2 | Demodulation in static propagation conditions | 66 |
| 8.2.1 | Demodulation of DCH..... | 66 |
| 8.2.1.1 | Minimum requirement | 66 |
| 8.2.1.1.1 | 3,84 Mcps TDD Option..... | 66 |
| 8.2.1.1.2 | 1,28 Mcps TDD Option..... | 67 |
| 8.2.1.1.3 | 7,68 Mcps TDD Option..... | 67 |
| 8.3 | Demodulation of DCH in multipath fading conditions | 68 |
| 8.3.1 | Multipath fading Case 1 | 68 |
| 8.3.1.1 | Minimum requirement | 68 |
| 8.3.1.1.1 | 3,84 Mcps TDD Option..... | 68 |
| 8.3.1.1.2 | 1,28 Mcps TDD Option..... | 68 |
| 8.3.1.1.3 | 7,68 Mcps TDD Option..... | 69 |
| 8.3.2 | Multipath fading Case 2..... | 70 |
| 8.3.2.1 | Minimum requirement | 70 |
| 8.3.2.1.1 | 3,84 Mcps TDD Option..... | 70 |
| 8.3.2.1.2 | 1,28 Mcps TDD Option..... | 70 |
| 8.3.2.1.3 | 7,68 Mcps TDD Option..... | 71 |
| 8.3.3 | Multipath fading Case 3..... | 72 |
| 8.3.3.1 | Minimum requirement | 72 |

| | | |
|-----------|--|----|
| 8.3.3.1.1 | 3,84 Mcps TDD Option..... | 72 |
| 8.3.3.1.2 | 1,28 Mcps TDD Option..... | 72 |
| 8.3.3.1.3 | 7,68 Mcps TDD Option..... | 73 |
| 8.3A | Demodulation of DCH in High speed train conditions..... | 74 |
| 8.3A.1 | General..... | 74 |
| 8.3A.2 | Minimum requirement | 74 |
| 8.3A.2.1 | 3,84 Mcps TDD Option..... | 74 |
| 8.3A.2.2 | 1,28 Mcps TDD Option..... | 74 |
| 8.3A.2.3 | 7,68 Mcps TDD Option..... | 75 |
| 8.4 | Demodulation of E-DCH FRC in multipath fading conditions | 75 |
| 8.4.1 | Minimum requirement | 75 |
| 8.4.1.1 | 3.84 Mcps TDD Option..... | 75 |
| 8.4.1.2 | 1.28 Mcps TDD Option..... | 76 |
| 8.4.1.3 | 7.68 Mcps TDD Option..... | 77 |
| 8.5 | Performance of ACK detection for HS-SICH | 79 |
| 8.5.1 | Minimum requirement..... | 79 |
| 8.5.1.1 | 3.84 Mcps TDD Option..... | 79 |
| 8.5.1.2 | 1.28 Mcps TDD Option..... | 79 |

Annex A (normative): Measurement Channels..... **81**

| | | |
|-----------|--|-----|
| A.1 | (void) | 81 |
| A.2 | Reference measurement channel | 81 |
| A.2.1 | UL reference measurement channel (12.2 kbps)..... | 81 |
| A.2.1.1 | 3,84 Mcps TDD Option | 81 |
| A.2.1.2 | 1,28 Mcps TDD Option | 82 |
| A.2.1.3 | 7,68 Mcps TDD Option | 83 |
| A.2.2 | UL reference measurement channel (64 kbps) | 84 |
| A.2.2.1 | 3,84 Mcps TDD Option | 84 |
| A.2.2.2 | 1,28 Mcps TDD Option | 86 |
| A.2.2.3 | 7,68 Mcps TDD Option | 87 |
| A.2.3 | UL reference measurement channel (144 kbps) | 88 |
| A.2.3.1 | 3,84 Mcps TDD Option | 88 |
| A.2.3.2 | 1,28 Mcps TDD Option | 90 |
| A.2.3.3 | 7,68 Mcps TDD Option | 91 |
| A.2.4 | UL reference measurement channel (384 kbps) | 92 |
| A.2.4.1 | 3,84 Mcps TDD Option | 92 |
| A.2.4.2 | 1,28 Mcps TDD Option | 94 |
| A.2.4.3 | 7,68 Mcps TDD Option | 95 |
| A.2.5 | RACH reference measurement channel | 96 |
| A.2.5.0 | General..... | 96 |
| A.2.5.0.1 | 3,84 Mcps TDD Option..... | 96 |
| A.2.5.0.2 | 1,28 Mcps TDD Option..... | 96 |
| A.2.5.0.3 | 7,68 Mcps TDD Option..... | 97 |
| A.2.5.1 | RACH mapped to 1 code SF16..... | 98 |
| A.2.5.1.1 | 3,84 Mcps TDD Option..... | 98 |
| A.2.5.1.2 | 1,28 Mcps TDD Option..... | 98 |
| A.2.5.1.3 | 7,68 Mcps TDD Option..... | 99 |
| A.2.5.2 | RACH mapped to 1 code SF8..... | 99 |
| A.2.5.2.1 | 3,84 Mcps TDD Option..... | 99 |
| A.2.5.2.2 | 1,28 Mcps TDD Option..... | 100 |
| A.2.5.3 | RACH mapped to 1 code SF4 (1,28 Mcps option only) | 100 |
| A.2.5.4 | RACH mapped to 1 code SF32 (7,68 Mcps option only) | 101 |
| A.3 | E-DCH Reference measurement channels | 101 |
| A.3.1 | E-DCH Fixed Reference Channels..... | 101 |
| A.3.1.1 | 3,84 Mcps TDD Option | 101 |
| A.3.1.1.1 | Fixed Reference Channel 1 (FRC1) | 101 |
| A.3.1.1.2 | Fixed Reference Channel 2 (FRC2) | 102 |
| A.3.1.1.3 | Fixed Reference Channel 3 (FRC3) | 103 |
| A.3.1.2 | 1.28Mcps TDD Option | 104 |
| A3.1.2.1 | Fixed reference channel 1 (FRC1) | 104 |

| | | |
|-------------------------------|--|------------|
| A3.1.2.2 | Fixed reference channel 2(FRC2) | 105 |
| A3.1.2.3 | Fixed reference channel 3(FRC3) | 106 |
| A3.1.2.4 | Fixed reference channel 4(FRC4)..... | 107 |
| A.3.1.3 | 7,68 Mcps TDD Option | 108 |
| A.3.1.3.1 | Fixed Reference Channel 1 (FRC1) | 108 |
| A.3.1.3.2 | Fixed Reference Channel 2 (FRC2) | 109 |
| A.3.1.3.3 | Fixed Reference Channel 3 (FRC3) | 110 |
| A.4 | HS-SICH Reference measurement channels | 111 |
| A.4.1 | 3.84 Mcps TDD Option..... | 111 |
| A.4.2 | 1.28 Mcps TDD Option..... | 111 |
| Annex B (normative): | Propagation conditions..... | 113 |
| B.1 | Static propagation condition..... | 113 |
| B.2 | Multi-path fading propagation conditions | 113 |
| B.2.1 | 3,84 Mcps TDD Option..... | 113 |
| B.2.2 | 1,28 Mcps TDD Option..... | 113 |
| B.2.3 | 7,68 Mcps TDD Option..... | 114 |
| B.3 | High speed train conditions | 115 |
| Annex C (informative): | Change history | 117 |
| History | | 122 |

Foreword

This Technical Specification has been produced by the 3GPP.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of this TS, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version 3.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 Indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the specification.

1 Scope

This document establishes the minimum RF characteristics of all three options of the TDD mode of UTRA. The three options are the 3.84 Mcps, 1.28 Mcps and 7.68 Mcps options respectively. The requirements are listed in different subsections only if the parameters deviate.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] ITU-R Recommendation SM.329: "Unwanted emissions in the spurious domain".
- [2] ETSI ETR 273-1-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement of radiated methods of measurement (using test sites) and evaluation of the corresponding measurement uncertainties; Part 1: Uncertainties in the measurement of mobile radio equipment characteristics; Sub-part 2: Examples and annexes".
- [3] IEC 60721-3-3 (1994): "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 3: Stationary use at weather protected locations".
- [4] IEC 60721-3-4 (1995): "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 4: Stationary use at non-weather protected locations".
- [5] 3GPP TS 25.142: "Base station conformance testing (TDD)".
- [6] 3GPP TS 25.346: "Introduction of the Multimedia Broadcast/Multicast Service (MBMS) in the Radio Access Network (RAN)".
- [7] 3GPP TS 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
- [8] 3GPP TR 25.942 "Radio Frequency RF System Scenarios".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following definitions apply.

Base Station RF bandwidth: The bandwidth in which a Base Station simultaneously transmits and simultaneously receives multiple carriers within each supported operating band.

Base Station RF bandwidth edge: The frequency of one of the edges of the Base Station RF bandwidth.

Power Spectral Density: The units of Power Spectral Density (PSD) are extensively used in this document. PSD is a function of power versus frequency and when integrated across a given bandwidth, the function represents the mean power in such a bandwidth. When the mean power is normalised to (divided by) the chip-rate it represents the mean