
**Fire fighting — Wheeled fire
extinguishers — Performance and
construction**

*Lutte contre l'incendie — Extincteurs sur roues — Performances et
construction*





COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

| | Page |
|---|-----------|
| Foreword | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Types of wheeled fire extinguishers | 3 |
| 5 Extinguishing media, propellants and fill densities | 4 |
| 5.1 Extinguishing media..... | 4 |
| 5.1.1 Carbon dioxide..... | 4 |
| 5.1.2 Clean agents..... | 4 |
| 5.1.3 Powder..... | 4 |
| 5.1.4 Foam concentrates..... | 4 |
| 5.2 Propellants..... | 4 |
| 5.3 Fill density..... | 4 |
| 5.4 Filling tolerance..... | 4 |
| 5.5 Charges..... | 5 |
| 5.5.1 Nominal charge..... | 5 |
| 5.5.2 Gross weight..... | 5 |
| 6 Performance | 5 |
| 6.1 Operating temperatures..... | 5 |
| 6.2 Effective discharge time and bulk range of discharge..... | 5 |
| 6.2.1 Effective discharge time..... | 5 |
| 6.2.2 Bulk range..... | 5 |
| 6.3 Resistance to temperature changes..... | 6 |
| 6.3.1 Requirements..... | 6 |
| 6.3.2 Test procedure..... | 6 |
| 6.4 Retention of charge..... | 7 |
| 6.4.1 Checking..... | 7 |
| 6.5 Intermittent discharge test..... | 7 |
| 6.6 Resistance to corrosion..... | 7 |
| 6.6.1 External corrosion test..... | 7 |
| 6.6.2 Internal corrosion test for water and foam extinguishers..... | 8 |
| 6.7 Durability test..... | 8 |
| 6.8 Electrical conductivity of extinguisher discharge..... | 9 |
| 6.8.1 Requirement..... | 9 |
| 6.8.2 Procedure used to test for electrical conductivity..... | 9 |
| 7 Fire performance tests | 9 |
| 7.1 Suitability for the various classes of fire..... | 9 |
| 7.2 Class A fire tests..... | 10 |
| 7.3 Class B fire tests..... | 10 |
| 7.4 Class D fire tests..... | 10 |
| 8 Construction requirements | 10 |
| 8.1 General requirements..... | 10 |
| 8.2 High-pressure cylinders..... | 11 |
| 8.3 Low-pressure cylinders..... | 11 |
| 8.3.1 General..... | 11 |
| 8.4 Steel cylinders..... | 11 |
| 8.4.1 Welded low-carbon steel..... | 11 |
| 8.4.2 Stainless steel cylinders..... | 12 |
| 8.5 Aluminium cylinders..... | 12 |
| 8.6 Minimum wall thickness..... | 12 |
| 8.7 Caps, valves and closures..... | 12 |
| 8.8 Safety and anti-overfill devices..... | 13 |

| | | |
|---|--|-----------|
| 8.8.1 | Safety devices | 13 |
| 8.8.2 | Anti-overfill devices | 13 |
| 8.9 | Manufacturing tests | 13 |
| 8.9.1 | Low-pressure cylinders | 13 |
| 8.9.2 | Leakage tests | 13 |
| 8.10 | Requirements for plastic components | 14 |
| 8.10.1 | General requirements | 14 |
| 8.10.2 | Requirements for normally pressurized components | 14 |
| 8.10.3 | Ultraviolet light exposure | 14 |
| 8.10.4 | Normally non-pressurized components | 15 |
| 8.10.5 | Exposure to extinguishing agent test | 15 |
| 8.11 | Discharge assembly | 15 |
| 8.12 | Control valve | 16 |
| 8.13 | Horn for carbon dioxide extinguisher | 16 |
| 8.14 | Method of operation | 17 |
| 8.15 | Safety locking devices | 17 |
| 8.16 | Pressure gauges for low-pressure extinguishers | 17 |
| 8.16.1 | General | 17 |
| 8.16.2 | Pressure gauge calibration test | 18 |
| 8.16.3 | Pressure gauge burst strength test | 18 |
| 8.16.4 | Pressure gauge overpressure test | 19 |
| 8.16.5 | Pressure gauge impulse test | 19 |
| 8.16.6 | Pressure gauge relief test | 19 |
| 8.16.7 | Pressure gauge water resistance test | 19 |
| 8.16.8 | Pressure gauge leakage test | 19 |
| 8.16.9 | Pressure gauge plastics components | 20 |
| 8.17 | Siphon tubes and filters for water-based extinguishers | 20 |
| 8.18 | Carriage assembly | 20 |
| 8.18.1 | Carriage | 20 |
| 8.18.2 | Mobility | 20 |
| 8.18.3 | Hose retaining unit | 20 |
| 8.19 | Gasket and O-rings | 21 |
| 8.19.1 | Tensile strength, elongation, maximum set and hardness | 21 |
| 8.19.2 | Compression set | 21 |
| 9 | Colour and marking | 21 |
| 9.1 | Colour | 21 |
| 9.2 | Marking | 21 |
| 9.3 | Operating instructions | 22 |
| 9.4 | Warning markings | 23 |
| 9.5 | Use-code symbols | 23 |
| 9.6 | Recharging instructions | 23 |
| 9.7 | Inspection instructions | 24 |
| 10 | Manuals | 24 |
| 10.1 | User manual | 24 |
| 10.2 | Service manual | 25 |
| Annex A (normative) Clean agent FK-5-1-12 — Extinguishing agent physical properties | | 26 |
| Annex B (normative) Clean agent HCFC Blend B — Extinguishing agent physical properties | | 29 |
| Annex C (normative) Clean agent HFC-227ea — Extinguishing agent physical properties | | 32 |
| Annex D (normative) Clean agent HFC-236fa — Extinguishing agent physical properties | | 35 |
| Bibliography | | 38 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 21, *Equipment for fire protection and fire fighting*, Subcommittee SC 2, *Manually transportable fire extinguishers*.

This third edition cancels and replaces the second edition (ISO 11601:2008), which has been technically revised.

The main changes compared to the previous editions are as follows:

- new requirements for four clean agents have been added;
- marking requirements for water-based extinguishers found suitable for use on polar solvents has been added.

Fire fighting — Wheeled fire extinguishers — Performance and construction

1 Scope

This document specifies the principal requirements intended to ensure the safety, reliability and performance of wheeled fire extinguishers.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 37, *Rubber, vulcanized or thermoplastic — Determination of tensile stress-strain properties*

ISO 5923, *Equipment for fire protection and fire fighting — Fire extinguishing media — Carbon dioxide*

ISO 7165:2017, *Fire fighting — Portable fire extinguishers — Performance and construction*

ISO 7202, *Fire protection — Fire extinguishing media — Powder*

ISO 7203-1, *Fire extinguishing media — Foam concentrates — Part 1: Specification for low-expansion foam concentrates for top application to water-immiscible liquids*

ISO 7203-2, *Fire extinguishing media — Foam concentrates — Part 2: Specification for medium- and high-expansion foam concentrates for top application to water-immiscible liquids*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at <http://www.electropedia.org/>

— ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

batch

group of the same products made on the same production line using the same lot of materials during one production shift

3.2

body

metal shell of an extinguisher designed to contain the extinguishing media including any skirt

3.3

bulk range

range of the extinguisher when 50 % of its media has been expelled

3.4

burst pressure

P_b

pressure at which the extinguisher cylinder ruptures