

Design and Operation of Solution-mined Salt Caverns Used for Liquid Hydrocarbon Storage

API RECOMMENDED PRACTICE 1115
SECOND EDITION, NOVEMBER 2018



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, applicable laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this Recommended Practice should consult with the appropriate authorities having jurisdiction.

Users of this Recommended Practice should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2018 American Petroleum Institute

Foreword

This document supersedes both the 2nd Edition of API Recommended Practice 1114, and the 1st edition of API Recommended Practice 1115.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Contents

	Page
1 Scope	1
1.1 Overview	1
1.2 Applicable Rules and Regulations	1
2 Normative References	2
3 Terms, Definitions, Acronyms, and Abbreviations	2
3.1 Terms and Definitions	2
3.2 Acronyms and Abbreviations	9
4 Overview of Underground Liquids Storage	10
4.1 General	10
4.2 Functional Integrity	10
4.3 Overview of Major Steps in the Development of Liquid Storage Caverns	10
5 Geological and Geomechanical Evaluation	13
5.1 General Considerations	13
5.2 Site Selection Criteria	13
5.3 Geologic Site Characterization	14
5.4 Geomechanical Site Evaluation	22
5.5 Assessment of Cavern Stability and Geomechanical Performance	27
6 Cavern and Well Design	28
6.1 General	28
6.2 Cavern Spacing Constraints	30
6.3 Hole Section Design	31
6.4 Casing Design	34
6.5 Wellhead Design	37
6.6 Storage Volume	41
6.7 Displacement-fluid Characteristics	42
6.8 Product Characteristics	42
7 Drilling	42
7.1 Preliminary Considerations	42
7.2 Rig and Equipment	43
7.3 Drilling Fluids	45
7.4 Drilling Guidelines	46
7.5 Logging	47
7.6 Casing Handling and Running	48
7.7 Cementing	48
7.8 Completion	52
8 Cavern Solution Mining	52
8.1 General	52
8.2 Cavern Solution-mining Design	52
8.3 Cavern Development Phases and Control	56
8.4 Instrumentation, Control, and Shut Down	64
8.5 Cavern Monitoring	65
8.6 Workovers During Solution Mining	67
8.7 Workover to Configure for Liquid Hydrocarbon Storage Service	68
8.8 Existing Cavern Conversions	69
8.9 Cavern Enlargement	71
9 Liquid Hydrocarbon Storage Operations	71

Contents

	Page
9.1 Facilities and Equipment	71
9.2 Minimum and Maximum Operating Limits	74
9.3 Backwash Operations	75
9.4 Equipment	75
9.5 Instrumentation, Control, and Shutdown	76
9.6 Inspection and Testing	77
9.7 Workovers	78
9.8 Site Security and Safety	79
9.9 Operating Administration	81
10 Cavern Integrity Monitoring	83
10.1 General	83
10.2 Holistic and Comprehensive Approach	86
10.3 Integrity Monitoring Program	86
10.4 Review of Integrity Monitoring Methods	86
10.5 Inactive Caverns	86
11 Cavern Abandonment	87
11.1 Objectives	87
11.2 Abandonment Design	87
11.3 Removal of Stored Product	87
11.4 Wellbore Integrity Test	87
11.5 Removal of Downhole Equipment	87
11.6 Production Casing Inspection	88
11.7 Sonar Survey	88
12 Risk Management for Liquid Hydrocarbon Storage Operations	88
12.1 General	88
12.2 Risk Management	88
12.3 Data Collection and Integration	88
12.4 Threat and Hazard Identification and Analysis	88
12.5 Preventive and Mitigative (P&M) Measures	89
12.6 Risk Assessment	94
12.7 Periodic Review and Reassessment	94
12.8 Recordkeeping	95
Annex A (informative) Open-hole Well Logs	96
Annex B (normative) Integrity Monitoring Methods	99
Annex C (informative) Brine Tables	102
Bibliography	103
Figures	
1 Simplified Salt Dome Storage Cavern Schematic	12
2 Typical Cemented Casing Program for Domal Salt	33
3 Typical Solution-mining Wellhead	38
4 Typical Liquid Hydrocarbon Storage Wellhead with Hanging String	39
5 Solution-mining Methods	55
6 Cavern Development Phases	57
Tables	
1 Integrity Monitoring Methods	84
2 Potential Threats and Consequences/Preventive and Mitigative Programs	89

Design and Operation of Solution-mined Salt Caverns Used for Liquid Hydrocarbon Storage

1 Scope

This recommended practice (RP) provides the functional recommendations for salt cavern facilities used for liquid hydrocarbon storage service and covers facility geomechanical assessments, cavern well design and drilling, and solution mining techniques and operations, including monitoring and maintenance practices. This RP is based on the accumulated knowledge and experience of geologists, engineers, and other personnel in the liquid hydrocarbon storage industry and promotes public safety by providing a set of industry accepted design and operation guidelines. This RP recognizes the nature of subsurface geological diversity and stresses the need for in-depth, site-specific geomechanical assessments, with a goal of long-term facility integrity and safety.

This RP includes the cavern well system (wellhead, wellbore, and cavern) from the emergency shutdown (ESD) valve to the cavern and facilities that have a significant impact on the safety and integrity of the cavern system. It also includes a structure for risk assessment for salt cavern facilities used for liquid hydrocarbon storage service.

This RP may be applied to existing facilities at the discretion of the user.

This RP does not apply to caverns used for the storage of gaseous products, natural gas, brine production, or waste disposal, nor to caverns that are mechanically mined, or depleted hydrocarbon or aquifer underground gas storage systems. This RP does not cover facility piping.

1.1 Overview

Storage of liquid hydrocarbons in solution-mined salt caverns has been utilized in the United States since the late 1940s. Today, storage of liquid hydrocarbons in caverns developed in both domal and bedded salt formations is utilized throughout the world.

Salt caverns can act as long-term, seasonal storage vessels; or they may serve as short-term, operational storage. Caverns can also be inserted into the production plant/pipeline systems to prevent supply interruptions when maintenance or emergency shutdowns occur, or to “float” on pipelines to optimize operations.

Storage of liquid hydrocarbons in a salt cavern may require careful review to ensure that the product is compatible with the salt. Chemical and physical properties of the salt at the cavern depth and at the pressure anticipated should be reviewed to verify that unwanted chemical or physical reactions do not occur. Incompatibility of product and salt is rarely a problem for most hydrocarbons. Examples of exceptions are storage in salt caverns where sulfides are present and storage of jet fuels with de-icing agents that absorb water.

In summary, storage of liquid hydrocarbons in salt caverns can provide an economical, safe, and environmentally sound method to store large quantities of compatible materials.

1.2 Applicable Rules and Regulations

This document was written to provide a technical reference for the development and operations of solution-mined salt caverns used for the storage of liquid hydrocarbons, and is not intended to represent or reflect any regulatory requirement. Depending on location and nature of the project, the recommended practices herein may address items that are in conflict with some regulatory requirements. If this occurs, the regulatory requirement supersedes the recommended practice unless an appropriate waiver or variance is granted from the issuing agency. A thorough review of the applicable rules and regulations is to be performed prior to the design of solution-mined liquid storage caverns to ensure ongoing compliance.