Side-pocket Mandrels

API SPECIFICATION 19G1
SECOND EDITION, FEBRUARY 2019

API MONOGRAM PROGRAM EFFECTIVE DATE: NOVEMBER 2019

ERRATA 1, JUNE 2019
ERRATA 2, JULY 2019

Date of Issue: July 2019
Affected Publication: API Specification 19G1, *Side-pocket Mandrels*, Second Edition, February 2019

Errata 2

Page 33, Table B.1, first column, ninth row, shall be replaced with the following:

Flow control—install/pull with KOT

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this specification are as follows:

— the term “shall” denotes a minimum requirement in order to conform to the standard;

— the term “should” denotes a recommendation or that which is advised but not required in order to conform to the standard;

— the term “may” is used to express permission or a provision that is optional;

— the term “can” is used to express possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

For API Monogram Program licensees and APIQR Program registrants, this standard shall become effective on the program date printed on the cover but may be used voluntarily from the date of publication.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every 5 years. A one-time extension of up to 2 years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571, standards@api.org.

Contents

Contents

Introduction

This specification has been developed by users/purchasers and suppliers/manufacturers of side-pocket mandrel products intended for use in the worldwide petroleum and natural gas industry. This specification is intended to provide requirements and information to all parties who are involved in the specification, selection, manufacture, testing and use of side-pocket mandrel products. Further, this specification addresses supplier/manufacturer requirements that set the minimum parameters with which each supplier/manufacturer shall comply, to be able to claim conformity with this specification.

This has been structured to allow different quality control grades to support quality control, design validation, design verification, and product functional testing. These variations allow the user/purchaser to select the grades that are required for a specific application. If the user/purchaser does not specify a specific grade for the following categories, the supplier/manufacturer will meet the requirements of grade 3.

This specification is not intended to inhibit a supplier/manufacturer from offering, or the user/purchaser from accepting, alternative equipment or engineering solutions. Where an alternative is offered, the supplier/manufacturer should identify any variations from this specification and provide details.

Design validation grades. There are four design validation grades for side-pocket mandrel products that provide the user/purchaser with a range of technical and performance requirements. Users of this specification should be aware that requirements in addition to those outlined herein might be needed for individual applications.

Product functional testing grades. There are four product functional testing grades for side-pocket mandrel products that provide the user/purchaser with a range of choices for validating that individual products manufactured under this specification meet the design specifications.

Quality control grades. There are four quality control grades that provide the user/purchaser with varying grades of quality control requirements to meet specific preferences or applications. Additional quality upgrades can be specified by the user/purchaser as supplemental requirements.

Annex A provides guidelines for use of API monogram, while Annexes, B, C and D of this specification are normative requirements; Annexes E and F are informative

.

Side-pocket Mandrels

1 Scope

This specification provides requirements for side-pocket mandrels used in the petroleum and natural gas industry. This specification includes specifying, selecting, designing, manufacturing, quality control, testing, and preparation for shipping of side-pocket mandrels.

This specification addresses standard side-pocket mandrel designs as well as high pressure and/or high temperature (HPHT) equipment rated greater than 103.43 MPa (15,000 psi) and/or greater than 177 °C (350 °F) wellbore conditions as proffered by API 1PER15K-1.

This specification does not address nor include requirements for end connections between the side-pocket mandrels and the well conduit. The installation and retrieval of side-pocket mandrels is outside the scope of this specification. Additionally, this specification does not include specifications for center-set mandrels, mandrels that employ or support tubing-retrievable flow control devices or side-pocket mandrels that incorporate non-metallic materials for pressure containment.

This specification does not include gas-lift or any other flow-control valves or devices, latches, and/or associated wire line equipment that can or cannot be covered in other API specifications.

The side-pocket mandrels to which this specification refers are independent devices that can accept installation of flow control or other devices down-hole.

2 Normative References

The following referenced documents are indispensable for the application of this specification. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Q1, *Specification for Quality Management System Requirements for Manufacturing Organizations for the Petroleum and Natural Gas Industry*

API 20A, *Carbon Steel, Alloy Steel, Stainless Steel, and Nickel Based Alloy Castings for Use in the Petroleum and Natural Gas Industry*

API 20H, *Heat Treatment Services—Batch Type for Equipment used in the Petroleum and Natural Gas Industry*

ANSI/NCSL Z540-1, *Calibration Laboratories and Measuring and Test Equipment General Requirements*[1]

ASME Boiler and Pressure Vessel Code, Section V, *Non-destructive Examination*[2]

ASME Boiler and Pressure Vessel Code, Section VIII, *Pressure Vessels*, Division 1, *Rules for Construction of Pressure Vessels*

ASME Boiler and Pressure Vessel Code, Section VIII, *Rules for Construction* of *Pressure Vessels*, Division 2, *Alternative Rule*ASME Boiler and Pressure Vessel Code, Section VIII, *Rules for Construction* of *Pressure Vessels*, Division 3, *Alternative Rules for Construction of High Pressure Vessels*

ASME Boiler and Pressure Vessel Code, Section IX, *Welding and Brazing Qualifications*

ASTM E10, *Standard Test Method for Brinell Hardness of Metallic Materials*

[1] NCSL International, 2995 Wilderness Place, Suite 107, Boulder, Colorado 80301-5404, USA.

[2] American Society of Mechanical Engineers, Three Park Avenue, New York, NY 10016-5990, USA.