



BSI Standards Publication

Air cargo unit load devices — Performance requirements and test parameters

National foreword

This British Standard is the UK implementation of ISO 21100:2020. It supersedes BS ISO 21100:2014, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee ACE/57, Air cargo and ground support equipment.

A list of organizations represented on this committee can be obtained on request to its committee manager.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2020
Published by BSI Standards Limited 2020

ISBN 978 0 580 93367 7

ICS 49.120; 49.100

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2020.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

ISO
21100

Second edition
2020-06

**Air cargo unit load devices —
Performance requirements and test
parameters**

*Unités de charge de fret aérien — Exigences de performances et
paramètres d'essai*



Reference number
ISO 21100:2020(E)

© ISO 2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	2
3 Terms and definitions	2
4 Classification	3
4.1 Types.....	3
4.2 Sizes.....	3
4.3 Configurations.....	4
4.4 Forms.....	4
4.5 Classification identifier.....	4
5 Performance requirements	4
5.1 Materials.....	4
5.2 Fabrication methods and workmanship.....	4
5.3 Protection.....	4
5.4 Construction.....	5
5.5 Marking.....	5
5.6 Inspection provisions.....	5
5.7 Fire protection.....	5
5.8 Rapid decompression.....	5
5.9 Dimensions and tolerances.....	5
5.10 Strength.....	6
5.10.1 Ultimate load criteria.....	6
5.10.2 Restraint criteria.....	6
5.10.3 Pallets and nets.....	6
5.10.4 Base performance.....	7
5.11 Environmental degradation.....	7
6 Tests	7
6.1 Test requirements.....	7
6.2 Test parameters.....	7
6.3 Test methods.....	7
6.4 Test results.....	8
7 Additional information	8
7.1 Intended use.....	8
7.2 Unit load device capacities.....	8
7.3 Container contours.....	8
7.4 Pallet configurations.....	8
8 Unit load device configurations	8
8.1 General.....	8
8.2 ULD CONFIGURATION A7.....	10
8.3 ULD CONFIGURATION A8.....	11
8.4 ULD CONFIGURATION B7.....	12
8.5 ULD CONFIGURATION B8.....	13
8.6 ULD CONFIGURATION G1.....	14
8.7 ULD CONFIGURATION K4.....	15
8.8 ULD CONFIGURATION L5.....	16
8.9 ULD CONFIGURATION L6.....	18
8.10 ULD CONFIGURATION M4.....	20
8.11 ULD CONFIGURATION M5.....	21
8.12 ULD CONFIGURATION N1.....	22
8.13 ULD CONFIGURATION P1.....	23

8.14	ULD CONFIGURATION Q1	24
8.15	ULD CONFIGURATION R1	25
8.16	ULD CONFIGURATION S1	27
9	Testing restraint conditions	28
9.1	General	28
9.2	RESTRAINT CONDITION (RC) A1	29
9.3	RESTRAINT CONDITION (RC) A2	30
9.4	RESTRAINT CONDITION (RC) G	32
9.5	RESTRAINT CONDITION (RC) K	33
9.6	RESTRAINT CONDITION (RC) L	35
9.7	RESTRAINT CONDITION (RC) N	37
9.8	RESTRAINT CONDITION (RC) P	39
9.9	RESTRAINT CONDITION (RC) Q	40
9.10	RESTRAINT CONDITION (RC) R	43
	Bibliography	45

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 9, *Air cargo and ground equipment*.

This second edition cancels and replaces the first edition (ISO 21100:2014), which has been technically revised.

The main changes compared to the previous edition are as follows:

- [5.10.3.5](#), addition of pallets track test to ensure compatibility with straps restraint;
- [5.10.4.3](#), addition of stiffness requirements for containers base edges;
- [Clause 8](#), ULD configurations A8, B8 and M5 use limited to lower deck containers;
- [Clause 8](#), ULD configuration Q1 change to add pallet and net applicability;
- [Clause 9](#), restraint conditions K, L, P and Q change as a result of testing experience.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document specifies the performance and testing requirements for approved (certified) cargo unit load devices (containers, pallets and nets) intended to be used for cargo restraint on board civil transport aircraft.

The civil aviation requirements referred to in this document are those concerning certification of transport aircraft and appliances to be installed aboard them, and constitute the set of design and operation requirements internationally agreed in application of International Civil Aviation Organization (ICAO) Annex 8, *Airworthiness of aircraft*, to the Convention on International Civil Aviation. This document provides one means of compliance for unit load devices.

Dimensions and tolerances are expressed in millimetres, with dimensions in inches shown between brackets. The nominal values of outer unit load device base dimensions are those expressed in inches. Forces are expressed in Newton, with forces in pound-force shown between brackets.

Air cargo unit load devices — Performance requirements and test parameters

1 Scope

This document specifies the minimum requirements for airworthiness approval of air cargo pallets, nets and containers, generally designated as air cargo unit load devices (ULD).

This document is intended to provide a uniform technical reference for air cargo unit load devices approval. As a prerequisite, it is presupposed that the applicable general civil aviation requirements and the aircraft manufacturer's approved Weight and Balance Manual are followed.

This document defines the minimum performance requirements and test parameters for air cargo unit load devices requiring approval of airworthiness for installation in an approved aircraft cargo compartment and restraint system that complies with the cargo restraint and occupant protection requirements of EASA CS-25 or 14 CFR Part 25, except for the 9,0 g forward ultimate inertia force of § 25.561(b) (3) (ii).

This document applies to airworthiness approved air cargo unit load devices intended for carriage on board civil transport category airplanes type certificated under EASA CS-25 or 14 CFR Part 25, or equivalent.

This document exclusively applies to unit load devices airworthiness approval and testing parameters. It does not apply to aircraft design or aircraft operating requirements, which are provided by the approved Weight and Balance Manual for each aircraft type.

Other aspects that do not directly pertain to air cargo unit load devices airworthiness approval and testing are not covered by this document and are defined in other International Standards (see Bibliography), e.g.:

- ULD design specifications,
- ULD in service damage limits,
- ULD restraint malfunction limitations,
- ULD test methods,
- ULD load distribution models,
- ULD maximum allowable contours,
- ULD CG (centre for gravity) location control means,
- ULD pressure equalization methods,
- ULD utilization guidelines.

Air cargo unit load devices qualified prior to publication of this document were approved in accordance with the requirements of ISO 8097:2001. This document is intended as a TSO approval reference for all new models of unit load devices in the sizes and types it covers, in replacement of ISO 8097. For air cargo unit load devices the size or type of which is not covered in this document, see the requirements of ISO 8097:2001, if their size or type is contained therein, or other equivalent criteria, if not.

NOTE 1 ISO 8097 is based on USA National Aerospace Standard NAS 3610 revision 10:1990, Specification for Cargo Unit Load Devices.