# General-purpose, Extruder, and Epicyclic Gear Units for Petroleum, Chemical, and Gas Industry Services

API STANDARD 677 FOURTH EDITION, SEPTEMBER 2021



## **Special Notes**

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API is not undertaking to meet the duties of employers, manufacturers, or vendors to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations under local, state, or federal laws. Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or vendor of that material, or the safety data sheet.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

#### **Foreword**

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, "shall" denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, "may" denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, "can" denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

## Contents

1	Scope	1
2	Normative References	1
3	Terms, Definitions, Acronyms, and Abbreviations	5
3.1	Terms and Definitions	5
3.2	Acronyms and Abbreviations	
4	General	
4.1	Unit Responsibility	
4.2 4.3	Unit ConversionStandards and Codes	
5	Requirements	
5.1 5.2	Units of MeasureStatutory Requirements	
5.2 5.3	Hierarchy of Requirements	
	Basic Design	
6 6.1	General	
6.2	Shaft Assembly Designation	
6.3	Shaft Rotation	
6.4	Rating	<b>2</b> 1
6.5	Casings	
6.6 6.7	Casing Connections	_
6. <i>7</i> 6.8	Gear Elements	
6.9	Bearings and Bearing Housings	
6.10	Lubrication	
6.11	Materials	
6.12	Nameplates and Rotation Arrows	62
7	Accessories	
7.2	Couplings and Guards	
7.3 7.4	Belt Drives	
7. <del>4</del> 7.5	Controls and Instrumentation	
7.6	Piping and Appurtenances	
7.7	Special Tools	
8	Inspection, Testing, and Preparation for Shipment	70
8.1	General	
8.2	Inspection	
8.3	Testing	
8.4	Preparation for Shipment	
9	Low-speed/High-torque Applications, Extruder Gears	
9.1	General	
9.2	Basic Design	
9.3 9.4	Materials Controls and Instrumentation	
9. <del>4</del> 9.5	Inspection	
9.6	Testing	87
9.7	Preparation for Shipment	89
10	Epicyclic Gear Units	89
10.1	Scope	
10.2	General	
10.3	Definition of Terms	90

10.4	Configurations and Shaft Arrangements	
10.5	Rating	93
10.6	Casings	
10.7	Casing Connections	
10.8	Gear Elements	
10.9	Balancing	
10.10	Bearings	
10.11	Lubrication	
10.12	Materials	
10.13 10.14	Nameplates and Rotation Arrows  Controls and Instrumentation	
10.14	Testing	
11	Vendor's Data	
	K A (informative) Data Sheets	
	R A (Informative) Data Sheets	
	( C (normative) Material Specifications for General-purpose, Extruder, and Epicyclic Gea	
Annex	c D (informative) Proposal and Contract Documents and Engineering Design Data	134
Annex	c E (normative) Vendor Drawing and Data Requirements	140
Annex	F (normative) Procedure for the Verification of Residual Unbalance	147
Annex	G (informative) Inspector's Checklist	153
Annex	κ Η (informative) Nomenclature for General-purpose, Extruder, and Epicyclic Gears	157
Annex	(I (informative) Toothing Configuration—Applicable to Epicyclic Gear Applications	161
Annex	c J (informative) Installation and Commissioning	163
Biblio	graphy	176
Figure	es	
1	Apex	
2	Lead	
3	Shaft Assembly Designations	
4	Shaft Rotation Designations	
5	Gear Mesh	
6	Material Index Number, Through Hardened	
7	Material Index Number, Carburized	
8 9	Allowable Bending Stress Number, Through Hardened	
10	Undamped Lateral Critical Speed Map	
11	Unbalance Placement	
12	Rotor Response Plot	
13	Plot of Applicable Speed Range of Vibration Limit	
14	Star Gearing Configuration	
15	Planetary Gearing Configurations	91
16	Compound Gearing Configuration	92
17	Solar Gearing Configurations	
18	Single Stage Epicyclic Rotor Pitch Diameters	
19	Compound Epicyclic Rotor Pitch Diameters	
20	Face Width-to-Diameter Ratio ( $b/d_{WS}$ ) Limits	
B.1	Typical Circulating Lube Oil System for Gear Units	
B.2	Schematic Symbols for a Pressurized Lube Oil System	
B.3	Typical Pressurized Lube Oil System for Hydrodynamic Bearings in Gear Units	
F.1	Residual Unbalance Worksheet	150

F.2	Sample Residual Unbalance Worksheet for Left Plane (Metric)	151
F.3	Sample Residual Unbalance Worksheet for Right Plane (USC)	
H.1	Parallel Shaft Gearbox	
H.2	Co-rotating Twin Screw Extruder	158
H.3	Epicyclic Gearbox—Planetary Configuration	
H.4	Epicyclic Gearbox—Star Configuration	160
Tabl		
1	Corresponding DN and NPS Pipe Sizes	
2	Pipe Sizes and Number of Threads per Inch (ASME B.1.20.1 Table 2)	
3	Driver Trip Speeds	
4	Shaft Assembly Combinations	
5	Minimum Gear Tooth Service Factors	
6	Allowable Material Index Numbers, I <sub>m</sub>	24
7	Allowable Bending Stress Number, Sall	27
8	Overhung Load Factors Applied to Parallel Shaft Gears	29
9	Minimum Tubing Wall Thickness	31
10	Drain Pipe Sizes	
11	Bearing Cap Vibration Limits	
12	Maximum $d_m N$ Numbers for Rolling Element Bearings	
13	Cage Types	
14	Minimum Requirements for Piping System Components	
15	ASME Materials Inspection Standards	
16	Maximum Severity of Defects in Castings	
17	Mesh Load Factor, $K_{\nu}$	
18	Material Index Number, $I_{m}$	
	· III	
19	Allowable Bending Stress Number, Sa	100
20	Guideline for Maximum Ratio for Simple Star and Planetary Epicyclics with Different Numbers of Planets	105
B.1	Lube Oil System Schematic	
C.1	Gear Unit Housings	
C.2	Shafts, Pinions, and Gear Wheels	131
C.3	Fabricated Gears	
F.1	Trial Weight Multiplier vs $N_{\rm mc}$	
	9 1 1110	
I.1 J.1	Differentiating Characteristics of Spur, Single Helical, and Double Helical Gearing Storage Preservative Types	
J. I	Sidiaue rieseivalive ivdes	מסו

#### Introduction

Users of this standard should be aware that further or differing requirements may be needed for individual applications. This standard is not intended to inhibit a vendor from offering, or the purchaser from accepting, alternative equipment or engineering solutions for the individual application. This may be particularly applicable where there is innovative or developing technology. Where an alternative is offered, the vendor should identify any variations from this standard and provide details.

A bullet (•) at the beginning of a section or subsection indicates that either a decision is required or the purchaser is required to provide further information. It is necessary that this information be indicated on data sheets or stated in the enquiry or purchase order (see examples in Annex A).

This standard requires the purchaser to specify certain details and features. Although it is recognized that the purchaser may desire to modify, delete, or amplify sections of this standard, it is strongly recommended that such modifications, deletions, and amplifications be made by supplementing this standard, rather than by rewriting or incorporating sections thereof into another standard.

For effective use of this standard and ease of reference to the text, the use of the data sheets in Annex A is recommended.

# General-purpose, Extruder, and Epicyclic Gear Units for Petroleum, Chemical, and Gas Industry Services

### 1 Scope

This standard covers the minimum requirements for general-purpose, enclosed single and multistage gear units incorporating parallel shaft spur, and helical gears for use in the petroleum, chemical, and gas industry services. General-purpose and extruder gears manufactured according to this standard are limited to pitch line velocities that do not exceed 60 m/s (12,000 ft/min).

The requirements for parallel shaft helical gears applied to extruder services are included in Section 9 of this standard.

The requirements for epicyclic gears driving equipment, such as electrical generators, centrifugal compressors, and pumps, are included in Section 10 of this standard.

This standard does not apply to gears in special-purpose service, which are covered in API 613, to gears integral with other equipment, or gears with noninvolute tooth forms.

NOTE General-purpose gears are applied in equipment trains that are usually spared, or are in noncritical service. Typical applications for which this standard is intended are cooling tower water pump systems, forced and induced draft fan systems, and other general-purpose equipment trains.

#### 2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Specification 5L, Line Pipe

API Standard 670, Machinery Protection Systems

API Standard 671, Special-purpose Couplings for Petroleum, Chemical, and Gas Industry Services

API Recommended Practice 686, Recommended Practice for Machinery Installation and Installation Design

API Recommended Practice 691, Risk-based Machinery Management

API Manual of Petroleum Measurement Standards (MPMS) Chapter 15, Guidelines for the Use of Petroleum Industry-specific International System (SI) Units

AGMA 925-A03 1, Effect of Lubrication on Gear Surface Distress

ANSI <sup>2</sup>/API Standard 614, *Lubrication, Shaft-sealing and Oil-control Systems and Auxiliaries*, Fifth Edition, April 2008

ANSI/ABMA Standard 7 <sup>3</sup>, Shaft and Housing Fits for Metric Radial Ball and Roller Bearings (Except Tapered Roller Bearings) Conforming to Basic Boundary Plan

<sup>&</sup>lt;sup>1</sup> American Gear Manufacturers Association, 1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314, www.agma.org.

American National Standards Institute, 1899 L. Street, NW, 11th Floor, Washington, DC 20036, www.ansi.org.

<sup>&</sup>lt;sup>3</sup> American Bearing Manufacturers Association, 1001 N. Fairfax Street, Suite 500, Alexandria, Virginia 22314, www.americanbearings.org.