



BSI Standards Publication

Maritime navigation and radiocommunication equipment and systems — Digital interfaces

Part 1: Single talker and multiple listeners

National foreword

This British Standard is the UK implementation of EN IEC 61162-1:2024. It is identical to IEC 61162-1:2024. It supersedes BS EN 61162-1:2016, which will be withdrawn on 9 May 2027.

The UK participation in its preparation was entrusted to Technical Committee EPL/80, Maritime navigation and radiocommunication equipment and systems.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2024
Published by BSI Standards Limited 2024

ISBN 978 0 539 20600 5

ICS 47.020.70

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2024.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

EUROPEAN STANDARD

EN IEC 61162-1

NORME EUROPÉENNE

EUROPÄISCHE NORM

May 2024

ICS 47.020.70

Supersedes EN 61162-1:2016

English Version

**Maritime navigation and radiocommunication equipment and
systems - Digital interfaces - Part 1: Single talker and multiple
listeners
(IEC 61162-1:2024)**

Matériels et systèmes de navigation et de
radiocommunication maritimes - Interfaces numériques -
Partie 1: Émetteur unique et récepteurs multiples
(IEC 61162-1:2024)

Navigations- und Funkkommunikationsgeräte und -systeme
für die Seeschifffahrt - Digitale Schnittstellen - Teil 1: Ein
Datensender und mehrere Datenempfänger
(IEC 61162-1:2024)

This European Standard was approved by CENELEC on 2024-05-09. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 80/1093/FDIS, future edition 6 of IEC 61162-1, prepared by IEC/TC 80 "Maritime navigation and radiocommunication equipment and systems" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61162-1:2024.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2025-02-09
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2027-05-09

This document supersedes EN 61162-1:2016 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 61162-1:2024 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standard indicated:

IEC 61023	NOTE Approved as EN 61023
IEC 61108-1	NOTE Approved as EN 61108-1
IEC 61108-2	NOTE Approved as EN 61108-2
IEC 61108-3	NOTE Approved as EN 61108-3
IEC 61108-4	NOTE Approved as EN 61108-4
IEC 61108-5	NOTE Approved as EN IEC 61108-5
IEC 61162-2	NOTE Approved as EN 61162-2
IEC 61162-450	NOTE Approved as EN IEC 61162-450
IEC 61174	NOTE Approved as EN 61174
IEC 61924-2	NOTE Approved as EN IEC 61924-2
IEC 61993-2	NOTE Approved as EN IEC 61993-2
IEC 61996-1	NOTE Approved as EN 61996-1
IEC 61996-2	NOTE Approved as EN 61996-2

IEC 62065	NOTE Approved as EN 62065
IEC 62287-2	NOTE Approved as EN 62287-2
IEC 62288	NOTE Approved as EN IEC 62288
IEC 62320 (series)	NOTE Approved as EN 62320 (series)
IEC 62320-1	NOTE Approved as EN 62320-1
IEC 62320-2	NOTE Approved as EN 62320-2
IEC 62320-3	NOTE Approved as EN 62320-3
IEC 62388	NOTE Approved as EN 62388
IEC 62616	NOTE Approved as EN 62616
IEC 62923-1	NOTE Approved as EN IEC 62923-1

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cencenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60945	-	Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results	EN 60945	-
ISO/IEC 8859-1	1998	Information technology - 8-bit single-byte coded graphic character sets - Part 1: Latin alphabet No.1	-	-
ITU-T Recommendation X.27/V.11	1996	Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s	-	-

CONTENTS

FOREWORD.....	8
INTRODUCTION.....	10
1 Scope.....	11
2 Normative references	11
3 Terms and definitions	11
4 Manufacturer's documentation	12
5 Hardware specification	12
5.1 General.....	12
5.2 Interconnecting wire.....	12
5.3 Conductor definitions	12
5.4 Electrical connections/shield requirements.....	13
5.5 Connector	13
5.6 Electrical signal characteristics	13
5.6.1 General	13
5.6.2 Signal state definitions	13
5.6.3 Talker drive circuits	13
5.6.4 Listener receive circuits	13
5.6.5 Electrical isolation	14
5.6.6 Maximum voltage on bus	14
6 Data transmission.....	14
7 Data format protocol.....	15
7.1 Characters	15
7.1.1 General	15
7.1.2 Reserved characters.....	15
7.1.3 Valid characters.....	15
7.1.4 Undefined characters.....	15
7.1.5 Character symbols.....	15
7.1.6 Manufacturer's mnemonic code	15
7.2 Fields.....	16
7.2.1 String	16
7.2.2 Address field	16
7.2.3 Data fields	17
7.2.4 Checksum field.....	18
7.2.5 Sequential message identifier field	18
7.3 Sentences.....	18
7.3.1 General structure.....	18
7.3.2 Description of approved sentences	18
7.3.3 Parametric sentences	19
7.3.4 Encapsulation sentences	20
7.3.5 Query sentences	22
7.3.6 Proprietary sentences.....	23
7.3.7 Command sentences	23
7.3.8 Valid sentences	24
7.3.9 Multi-sentence messages	24
7.3.10 Sentence transmission timing	24
7.3.11 Additions to approved sentences	25

7.3.12	Message reception timeout for multi-sentence method.....	25
7.4	Error detection and handling	25
7.5	Handling of deprecated sentences	25
8	Data content.....	25
8.1	Character definitions	25
8.2	Field definitions	28
8.3	Approved sentences	31
8.3.1	General format	31
8.3.2	AAM – Waypoint arrival alarm.....	31
8.3.3	ABK – AIS addressed and binary broadcast acknowledgement.....	32
8.3.4	ABM – AIS addressed binary and safety related message	33
8.3.5	ACA – AIS channel assignment message	34
8.3.6	ACK – Acknowledge alarm.....	35
8.3.7	ACN – Alert command	35
8.3.8	ACS – AIS channel management information source	36
8.3.9	AGL – Alert group list	37
8.3.10	AIR – AIS interrogation request	37
8.3.11	AKD – Acknowledge detail alarm condition	39
8.3.12	ALA – Report detailed alarm condition	39
8.3.13	ALC – Cyclic alert list	40
8.3.14	ALF – Alert sentence	41
8.3.15	ALR – Set alarm state.....	44
8.3.16	APB – Heading/track controller (autopilot) sentence B	44
8.3.17	ARC – Alert command refused.....	45
8.3.18	BBM – AIS broadcast binary message	45
8.3.19	BEC – Bearing and distance to waypoint – Dead reckoning	46
8.3.20	BOD – Bearing origin to destination	47
8.3.21	BWC – Bearing and distance to waypoint – Great circle.....	47
8.3.22	BWR – Bearing and distance to waypoint – Rhumb line	47
8.3.23	BWW – Bearing waypoint to waypoint.....	47
8.3.24	CUR – Water current layer – Multi-layer water current data	48
8.3.25	DBT – Depth below transducer	48
8.3.26	DDC – Display dimming control	48
8.3.27	DOR – Door status detection	51
8.3.28	DPT – Depth.....	53
8.3.29	DSC – Digital selective calling information.....	53
8.3.30	DSE – Expanded digital selective calling	54
8.3.31	DTM – Datum reference.....	54
8.3.32	EPM – Command or report long equipment property value.....	55
8.3.33	EPV – Command or report equipment property value.....	56
8.3.34	ETL – Engine telegraph operation status	58
8.3.35	EVE – General event message	59
8.3.36	FIR – Fire detection	59
8.3.37	FSI – Frequency set information	60
8.3.38	GBS – GNSS satellite fault detection	61
8.3.39	GDC – GNSS differential correction	64
8.3.40	GEN – Generic binary information	67
8.3.41	GFA – GNSS fix accuracy and integrity	68
8.3.42	GGA – Global positioning system (GPS) fix data.....	69

8.3.43	GLL – Geographic position – Latitude/longitude	69
8.3.44	GNS – GNSS fix data	70
8.3.45	GRS – GNSS range residuals	72
8.3.46	GSA – GNSS DOP and active satellites	75
8.3.47	GST – GNSS pseudorange error statistics	78
8.3.48	GSV – GNSS satellites in view	78
8.3.49	HBT – Heartbeat supervision sentence	81
8.3.50	HCR – Heading correction report	81
8.3.51	HDG – Heading, deviation and variation	82
8.3.52	HDT – Heading true	82
8.3.53	HMR – Heading monitor receive	82
8.3.54	HMS – Heading monitor set	83
8.3.55	HRM – Heel angle, roll period and roll amplitude measurement device	83
8.3.56	HSC – Heading steering command	85
8.3.57	HSS – Hull stress surveillance systems	85
8.3.58	HTC – Heading/track control command; HTD – Heading /track control data	85
8.3.59	LR1 – AIS long-range reply sentence 1	87
8.3.60	LR2 – AIS long-range reply sentence 2	87
8.3.61	LR3 – AIS long-range reply sentence 3	88
8.3.62	LRF – AIS long-range function	88
8.3.63	LRI – AIS long-range interrogation	89
8.3.64	MOB – Man over board notification	90
8.3.65	MSK – MSK receiver interface	91
8.3.66	MSS – MSK receiver signal status	92
8.3.67	MTW – Water temperature	92
8.3.68	MWD – Wind direction and speed	92
8.3.69	MWV – Wind speed and angle	92
8.3.70	NAK – Negative acknowledgement	93
8.3.71	NLS – Navigation light status	94
8.3.72	NRM – NAVTEX receiver mask	95
8.3.73	NRX – MSI received message	96
8.3.74	NSR – Navigation status report	98
8.3.75	OSD – Own ship data	99
8.3.76	POS – Device position and ship dimensions report or configuration command	100
8.3.77	PRC – Propulsion remote control status	101
8.3.78	RLM – Return link message	102
8.3.79	RMA – Recommended minimum specific LORAN-C data	103
8.3.80	RMB – Recommended minimum navigation information	103
8.3.81	RMC – Recommended minimum specific GNSS data	104
8.3.82	ROR – Rudder order status	106
8.3.83	ROT – Rate of turn	106
8.3.84	RPM – Revolutions	106
8.3.85	RRT – Report route transfer	106
8.3.86	RSA – Rudder sensor angle	108
8.3.87	RSD – Radar system data	108
8.3.88	RTE – Routes	109
8.3.89	SEL – Selection report	109

8.3.90	SFI – Scanning frequency information	110
8.3.91	SLM – Steering location/mode	111
8.3.92	SM1 – SafetyNET Message, All Ships/NavArea	112
8.3.93	SM2 – SafetyNET Message, Coastal Warning Area	114
8.3.94	SM3 – SafetyNET Message, Circular Area address	116
8.3.95	SM4 – SafetyNET Message, Rectangular Area Address	118
8.3.96	SMB – IMO SafetyNET Message Body	121
8.3.97	SMV – SafetyNET Message, Vessel in distress information	122
8.3.98	SPW – Security password sentence.....	124
8.3.99	SSD – AIS ship static data.....	125
8.3.100	STN – Multiple data ID.....	126
8.3.101	THS – True heading and status	126
8.3.102	TLB – Target label	126
8.3.103	TLL – Target latitude and longitude	127
8.3.104	TRC – Thruster control data	127
8.3.105	TRD – Thruster response data.....	128
8.3.106	TRL – AIS transmitter-non-functioning log	128
8.3.107	TTD – Tracked target data.....	129
8.3.108	TTM – Tracked target message	132
8.3.109	TUT – Transmission of multi-language text.....	132
8.3.110	TXT – Text transmission	133
8.3.111	UID – User identification code transmission.....	134
8.3.112	VBC – Water-referenced and ground-referenced docking speed data	134
8.3.113	VBW – Dual ground/water speed	135
8.3.114	VDM – AIS VHF data-link message.....	135
8.3.115	VDO – AIS VHF data-link own-vessel report	136
8.3.116	VDR – Set and drift.....	137
8.3.117	VER – Version	137
8.3.118	VHW – Water speed and heading	138
8.3.119	VLW – Dual ground/water distance	138
8.3.120	VPW – Speed measured parallel to wind	138
8.3.121	VSD – AIS voyage static data.....	138
8.3.122	VTG – Course over ground and ground speed	140
8.3.123	WAT – Water level detection.....	140
8.3.124	WCV – Waypoint closure velocity	141
8.3.125	WNC – Distance waypoint to waypoint.....	142
8.3.126	WPL – Waypoint location	142
8.3.127	XDR – Transducer measurements	142
8.3.128	XTE – Cross-track error, measured.....	145
8.3.129	XTR – Cross-track error, dead reckoning.....	145
8.3.130	ZDA – Time and date.....	146
8.3.131	ZDL – Time and distance to variable point.....	146
8.3.132	ZFO – UTC and time from origin waypoint	146
8.3.133	ZTG – UTC and time to destination waypoint.....	146
9	Applications.....	147
9.1	Example parametric sentences	147
9.1.1	General	147
9.1.2	Example 1 – LORAN-C latitude/longitude	147
9.1.3	Example 2 – LORAN-C arrival alarm.....	147

9.1.4	Example 3 – Proprietary sentence	148
9.1.5	Example 4 – RMA examples	148
9.1.6	Example 5 – FSI examples	149
9.1.7	Example 6 – MSK/MSS examples	149
9.1.8	Example 7 – DSC and DSE sentences	150
9.1.9	Example 8 – FIR, DOR and WAT sentences	150
9.2	Example encapsulation sentences	151
9.3	Examples of receiver diagrams	151
Annex A (informative)	Example encapsulation sentence	152
A.1	Example encapsulation sentence	152
A.2	AIS VHF data-link message VDM sentence encapsulation example	152
A.3	Background discussion – Encapsulation coding	152
A.4	Decoding the encapsulated string	156
A.5	Conversion from symbols to binary bits	156
A.6	Organising the binary message data	157
A.7	Interpreting the decoded binary strings	157
Annex B (normative)	Guidelines for methods of testing and required test results	158
B.1	General.....	158
B.2	Definition of environmental conditions for the tests	158
B.3	Examination of the manufacturer's documentation	158
B.4	Test of hardware.....	159
B.4.1	Interface units.....	159
B.4.2	Input circuit test.....	159
B.4.3	Check of electrical isolation	159
B.4.4	Maximum input voltage test	159
B.4.5	Test arrangement for performance tests according to IEC 60945.....	159
B.4.6	Test under maximum interface workload	159
B.4.7	Test for correct parsing of sentences	160
B.4.8	Test under long term conditions	161
B.4.9	Protocol test of the interface of the EUT	161
Annex C (normative)	Six-bit binary field conversion	167
Annex D (normative)	Alarm system fields.....	170
Annex E (informative)	Example of use of FIR, DOR and WAT sentences	178
E.1	Example of the use of system status messages	178
E.2	Use of system division codes	178
E.3	Send complete status.....	179
E.4	Change measurement point status	180
E.5	Point status change during a status update.....	180
E.6	Failure in a sub-system	180
E.7	Status updates when a sub-system is in fault	181
E.8	Signal a correction of a sub-system fault.....	181
Bibliography	182
Figure 1	– Listener receive circuit	14
Figure 2	– Data transmission format	14
Figure 3	– Example 1, J-FET, N channel, opto-isolator based listener circuit	151
Figure 4	– Example 2, NPN opto-isolator based listener circuit	151

Figure A.1 – Message data format	154
Figure A.2 – Work sheet for decoding and interpreting encapsulated string.....	155
Figure C.1 – 6-bit binary code converted to valid IEC 61162-1 character	168
Figure C.2 – Valid IEC 61162-1 character converted to 6-bit binary code.....	169
Figure E.1 – Example system diagram	179
Table 1 – Reserved characters	26
Table 2 – Valid characters	26
Table 3 – Character symbol	27
Table 4 – Talker identifier mnemonics.....	28
Table 5 – Field type summary	30
Table A.1 – Example message from ITU-R M.1371	153
Table B.1 – Example – Special characters	160
Table B.2 – Example – Parsing	160
Table B.3 – Example – Future extensions	161
Table B.4 – Example – Data string GGA sent by the EUT to the test receiver (listener).....	162
Table B.5 – Example – Checksum data sent	163
Table B.6 – Example – Data string GNS received by the EUT	164
Table B.7 – Example – Checksum data received.....	165
Table B.8 – Example – Break of data line	166
Table B.9 – Example – Receiving interval	166
Table B.10 – Example – Talker ID.....	166
Table C.1 – Six-bit binary field conversion table.....	167
Table D.1 – System alarm fields	170

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS – DIGITAL INTERFACES –****Part 1: Single talker and multiple listeners**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61162-1 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems. It is an International Standard.

This sixth edition cancels and replaces the fifth edition published in 2016. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) alternative hardware is given in 5.1 which may now be as specified in this document or as specified in IEC 61162-2;
- b) the data transmission rate given in Clause 6 is now configurable. The default remains as 4 800 (bits/s) but higher rates may be provided;

- c) new identifiers have been added to Table 4;
- d) new sentences AGL, EPM, GDC, NLS, SEL, SLM, SMV and VBC have been added;
- e) revisions have been made to ABK, ABM, ACN, ALC, ALF, ARC, BBM, DDC, DTM, EPV, FIR, GBS, GFA, GLL, GNS, GRS, GSA, GST, GSV, HRM, NRX, POS, RLM, ROR, RSA, TLB, TTD, VSD and XDR;
- f) the previous Annex A, Glossary, has been deleted as being of historical interest.

The text of this International Standard is based on the following documents:

Draft	Report on voting
80/1093/FDIS	80/1097/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61162 series, published under the general title *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The IEC 61162 series consists of 5 parts which specify digital interfaces for application in marine navigation, radiocommunication and system integration, as follows:

IEC 61162-1: Single talker and multiple listeners;

IEC 61162-2: Single talker and multiple listeners, high speed transmission;

IEC 61162-3: Serial data instrument network;

IEC 61162-450: Multiple talkers and multiple listeners – Ethernet interconnection;

IEC 61162-460: Multiple talkers and multiple listeners – Ethernet interconnection – Safety and security

IEC technical committee 80 interface standards are developed with input from manufacturers, private and government organisations and equipment operators. The information is intended to meet the needs of users at the time of publication, but users should recognise that as applications and technology change, interface standards should change as well. Users of this document are advised to immediately inform the IEC of any perceived inadequacies therein.

The first edition of IEC 61162-1 was published in 1995. The second edition published in 2000 removed some sentences which were no longer in use, added some new sentences and included details of the ship equipment defined in IMO resolutions together with appropriate sentences for communication between them. This information was subsequently removed from the third edition when it became the practice to specify the sentence formatters in the individual standards for equipment.

The third edition published in 2007 introduced a re-arrangement of the text and new sentences particularly to support the automatic identification system and the voyage data recorder. The third edition also introduced a further type of start of sentence delimiter. The conventional delimiter "\$" was retained for the conventional sentences which are now called "parametric sentences". The new delimiter "!" identifies sentences that conform to special purpose encapsulation.

The fourth edition removed some sentences which were not in use, added some new sentences for new applications and made some corrections and additions. In particular, the sentences of relevance to satellite navigation receivers were expanded to facilitate the description of new satellite systems.

The fifth edition also removed some sentences which were no longer in use, added some new sentences for new applications and made some corrections and additions.

This sixth edition adds some new sentences for new applications and makes some corrections and additions.

This edition has been aligned where appropriate and possible with NMEA 0183 version 4.10.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – DIGITAL INTERFACES –

Part 1: Single talker and multiple listeners

1 Scope

This part of IEC 61162 contains the requirements for data communication between maritime electronic instruments, navigation and radiocommunication equipment when interconnected via an appropriate system.

This document is intended to support one-way serial data transmission from a single talker to one or more listeners. These data are in printable ASCII form and can include information such as position, speed, depth, frequency allocation, etc. Typical messages can be from about 11 to a maximum of 79 characters in length and generally require transmission no more rapidly than one message per second.

The electrical definitions in this document are not intended to accommodate high-bandwidth applications such as radar or video imagery, or intensive database or file transfer applications. Since there is no provision for guaranteed delivery of messages and only limited error checking capability, it is important this document is used with caution in all safety applications.

For applications where a faster transmission rate is necessary, IEC 61162-2 applies.

For applications to shore based equipment of the automatic identification system (AIS) the IEC 62320 series applies.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements - Methods of testing and required test results*

ISO/IEC 8859-1:1998, *Information technology - 8-bit single-byte coded graphic character sets - Part 1: Latin alphabet No. 1*

ITU-T Recommendation X.27/V.11:1996, *Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>