



**ASA/ANSI S12.10-2010/Part 1
(Revision of ANSI/ASA S12.10-2002/
ISO 7779:1999)**

Reaffirmed by ANSI June 19, 2020

AMERICAN NATIONAL STANDARD

**Acoustics – Measurement of Airborne Noise
Emitted by Information Technology and
Telecommunications Equipment – Part 1:
Determination of Sound Power Level and
Emission Sound Pressure Level**

Secretariat:

Acoustical Society of America

Approved on October 15, 2010:

American National Standards Institute, Inc.

Abstract

This Standard specifies methods for the measurement of airborne noise emitted by information technology and telecommunications equipment. Hitherto, a wide variety of methods have been applied by individual manufacturers and users to satisfy particular equipment or application needs. These diverse practices have, in many cases, made comparison of noise emission difficult. This Standard simplifies such comparisons and is the basis for the declaration of the noise emission levels of information technology and telecommunications equipment.

This Standard is technically identical to parts of ECMA-74.

ANSI/ASA S12.10-2010/Part 1
(Revision of ANSI/ASA S12.10-2002/ISO 7779:1999)

Reaffirmed by ANSI June 19, 2020

AMERICAN NATIONAL STANDARD

Acoustics – Measurement of Airborne Noise Emitted by Information Technology and Telecommunications Equipment – Part 1: Determination of Sound Power Level and Emission Sound Pressure Level

ANSI/ASA S12.10-2010/Part 1

Accredited Standards Committee S12, Noise

Standards Secretariat
Acoustical Society of America
35 Pinelawn Road, Suite 114 E
Melville, NY 11747-3177

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



ANSI/ASA S12.10-2010/Part 1
(Revision of ANSI/ASA S12.10-2002/ISO 7779-1999 (R2007))

AMERICAN NATIONAL STANDARD

**Acoustics - Measurement of Airborne
Noise Emitted by Information Technology and
Telecommunications Equipment -
Part 1: Determination of Sound Power Level and
Emission Sound Pressure Level**

Secretariat:

Acoustical Society of America

Approved October 6, 2010 by:

American National Standards Institute, Inc.

Abstract

This Standard specifies methods for the measurement of airborne noise emitted by information technology and telecommunications equipment. Hitherto, a wide variety of methods have been applied by individual manufacturers and users to satisfy particular equipment or application needs. These diverse practices have, in many cases, made comparison of noise emission difficult. This Standard simplifies such comparisons and is the basis for the declaration of the noise emission levels of information technology and telecommunications equipment.

This Standard is technically identical to parts of ECMA-74.

AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, S3/SC 1 on Animal Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute (ANSI).


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America
ASA Secretariat
35 Pinelawn Road, Suite 114E
Melville, New York 11747-3177
Telephone: 1 (631) 390-0215
Fax: 1 (631) 390-0217
E-mail: asastds@aip.org

© 2010 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

Contents

1	Scope	1
2	Normative references	2
3	Terms and definitions	3
3.1	General definitions	3
3.2	Acoustical definitions.....	5
4	Conformance requirements.....	6
5	Installation and operating conditions.....	6
5.1	Equipment installation.....	6
5.2	Input voltage and frequency.....	8
5.3	Equipment operation.....	9
6	Method for determining sound power levels of equipment in reverberation test rooms	10
6.1	General	10
6.2	Measurement uncertainty	10
6.3	Test environment	11
6.4	Instrumentation	11
6.5	Installation and operation of equipment: General requirements.....	12
6.6	Microphone positions and source locations.....	12
6.7	Measurement of sound pressure level.....	13
6.8	Measurement of the sound pressure level of the reference sound source.....	13
6.9	Calculation of mean time-averaged band sound pressure level.....	14
6.10	Determination of sound power level.....	14
7	Method for determining sound power levels of equipment under essentially free-field conditions over a reflecting plane	16
7.1	General	16
7.2	Measurement uncertainty	17
7.3	Test environment	17
7.4	Instrumentation	18
7.5	Installation and operation of equipment: General requirements.....	19
7.6	Measurement surface and microphone positions.....	19
7.7	Measurement of sound pressure levels.....	20
7.8	Calculation of surface sound pressure level.....	21
7.9	Determination of sound power levels.....	21
8	Method for determining emission sound pressure levels at defined operator and bystander positions.....	22
8.1	General	22
8.2	Measurement uncertainty	22
8.3	Test environment	23
8.4	Instrumentation	24
8.5	Installation and operation of equipment.....	24
8.6	Microphone positions	24
8.7	Measurement of sound pressure levels.....	26
8.8	Determination of emission sound pressure levels	27

9	Information to be recorded and reported	29
9.1	Information to be recorded.....	29
9.2	Test report.....	34
Annex A (normative)	Test accessories.....	36
A.1	Standard test table.....	36
A.2	Typing robot.....	37
Annex B (normative)	Measurement surfaces.....	40
B.1	Hemispherical measurement surface	40
B.2	Cylindrical measurement surface	41
Annex C (normative)	Installation and operating conditions for specific equipment categories.....	45
C.1	General	45
Annex D (informative)	Identification and evaluation of prominent discrete tones	46
D.1	Field of application	46
D.2	Background.....	46
D.3	Microphone position(s).....	47
D.4	Instrumentation	47
D.5	Initial screening tests	48
D.6	Discrete tones and noise emissions near the threshold of hearing.....	49
D.7	Critical bandwidths.....	51
D.8	Tone-to-noise ratio method.....	52
D.9	Prominence ratio method.....	57
D.10	Information to be recorded for prominent discrete tones.....	62
Annex E (informative)	Detection of impulsive sound.....	64
E.1	General	64
E.2	Instruments	64
E.3	Microphone position.....	64
E.4	Measurement procedure.....	65
E.5	Test record for impulsive sound pressure levels	65
Bibliography.....		66

Figures

Figure 1 —	Examples of microphone positions for standing and seated operators	25
Figure A.1 —	Standard test table	36
Figure A.2 —	Solenoid characteristics for a plunger stroke of 4 mm.....	38
Figure A.3 —	Solenoid cross section	38
Figure A.4 —	Individual steps of the solenoid operation.....	39
Figure B.1 —	Example 1: Illustration of the cylindrical measurement surface and cylindrical microphone array showing the arrangement using 6 side microphones and 3 top microphones .	42

Figure B.2 — Example 2: Illustration of the cylindrical measurement surface and microphone array showing an arrangement using 5 side microphones and 4 top microphones.....	44
Figure D.1 — The Lower Threshold of Hearing (LTH) and the LTH + 10 dB curves illustrated for the analysis of low-level tones.....	50
Figure D.2 — Tone-to-noise ratio method applied to a single tone in a critical band	56
Figure D.3 — Tone-to-noise ratio method applied to multiple tones in a critical band.....	57
Figure D.4 — Illustration of the prominence ratio method for prominent discrete tone identification ...	62
Figure D.5 — Criteria for prominence for both tone-to-noise ratio (D.8.5) and prominence ratio (D.9.6) as a function of frequency	63

Tables

Table 1 — Uncertainty in determining sound power levels in a reverberation test room according to Clause 6 of this Standard	10
Table 2 — Identification number k for octave bands.....	15
Table 3 — Values of A-weighting, A_j , for one-third-octave bands	15
Table 4 — Type of noise and determination of sound power levels	16
Table 5 — Uncertainty in determining sound power levels in a free field over a reflecting plane according to Clause 7 of this Standard	17
Table 6 — Uncertainty in determining emission sound pressure level at the operator and bystander positions in an essentially free field over a reflecting plane according to Clause 8 of this Standard	23
Table B.1 — Coordinates of microphone positions for equipment emitting discrete tones	40
Table D.1 — Parameters for calculation of P_1	50
Table D.2 — Parameters for calculation of $f_{1,L}$	59
Table D.3 — Parameters for calculation of $f_{2,U}$	60

Foreword

[This Foreword is for information only and is not a part of the American National Standard ANSI/ASA S12.10-2010/Part 1 American National Standard Acoustics – Measurement of airborne noise emitted by information technology and telecommunications equipment - Part 1: Determination of Sound Power Level and Emission Sound Pressure Level.]

This standard comprises a part of a group of definitions, standards, and specifications for use in noise. It was developed and approved by Accredited Standards Committee S12 Noise, under its approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI). The Scope of Accredited Standards Committee S12 is as follows:

Standards, specifications, and terminology in the field of acoustical noise pertaining to methods of measurement, evaluation, and control, including biological safety, tolerance, and comfort, and physical acoustics as related to environmental and occupational noise.

This standard revises and replaces ANSI/ASA S12.10-2002/ISO 7779:1999. This document adopts, with permission, parts of the 10th Edition of ECMA-74 (2008). ECMA-74 is also the underlying document for ISO 7779 and it is anticipated that the next edition of ISO 7779 will be essentially identical to the 10th Edition of ECMA-74 (2008).

Changes from ANSI/ASA S12.10-2002/ISO 7779:1999 include the following:

Changes were made to the main body of this Standard to be consistent with ECMA-74, which was revised to correspond with upcoming changes in the underlying standards: ANSI/ASA S12.51 / ISO 3741, ANSI/ASA S12.54 / ISO 3744, ANSI/ASA S12.55 / ISO 3745 and ISO 11201.

A revised Annex B includes a provision allowing the use of a 0.5 m radius hemispherical surface for measuring the sound power emitted by small noise sources such as disk drives. Annex B also allows the use of a cylindrical measurement surface and follows wording in ANSI/ASA S12.54 / ISO 3744.

Annex C was modified to reference the latest version of ECMA-74 for details of modes of operation and installation of specific product types, which is contained in Annex C of the 10th Edition of ECMA-74 (2008).

A revised Annex D includes prominence ratio in addition to tone-to-noise ratio, provides improved figures illustrating the tone-to-noise and prominence ratio calculations, and contains new criteria for prominent discrete tones. The new criteria are a result of a 3-year study by ECMA TC26 and ITI TC6. Changes were also made in part to better define the critical band edges, including changing from geometric critical bands to arithmetic critical bands for frequencies below 500 Hz. Also, curves were fitted to the band edges for the lower and upper critical bands when calculating prominence ratio, thus eliminating the need to use iteration for the calculations. Clarifications were added on frequency range of interest and elsewhere. Annex D was also revised to give clearer direction on determining the prominence of tones as well as introducing the concept of threshold of hearing when analyzing very low-noise equipment.

At the time this Standard was submitted to Accredited Standards Committee S12, Noise, for approval, the membership was as follows:

W.J. Murphy, *Chair*
 R.D. Hellweg, *Vice-Chair*

S.B. Blaeser, *Secretary*

3M Occupational Health and Environmental Safety Division	E.H. Berger
Acoustical Society of America	R.D. Hellweg
.....	D. Lubman (Alt.)
Air-Conditioning, Heating and Refrigeration Institute	S. Lind
.....	D. Abbate (Alt.)
Air Movement and Control Association, Inc.	J.A. Brooks
.....	M. Stevens (Alt.)
Alcoa Inc.	W.D. Gallagher
American Academy of Audiology	D. Ostergren
.....	S. Gordon-Salant (Alt.)
American Academy of Otolaryngology – Head and Neck Surgery	R.A. Dobie
.....	L.A. Michael (Alt.)
American Industrial Hygiene Association	D. Driscoll
.....	S.N. Hacker (Alt.)
American Speech-Language-Hearing Association	L.A. Wilber
.....	V. Gladstone (Alt.)
Caterpillar, Inc.	K.G. Meitl
Compressed Air and Gas Institute	R.C. Johnson
.....	D.R. Bookshar (Alt.)
Council for Accreditation in Occupational Hearing Conservation	Vacant
.....	L.D. Hager (Alt.)
Emerson Electric – Copeland Corporation	A.T. Herfat
.....	G. Williamson (Alt.)
ETS–Lindgren Acoustic Systems	D. Winker
.....	M. Black (Alt.)
ExxonMobil	B. Moulton
.....	A. Ratliff (Alt.)
G.R.A.S. Sound & Vibration	B. Schustrich
General Motors	D.B. Moore
Information Technology Industry Council	W.M. Beltman
.....	J. Rosenberg (Alt.)
Institute of Noise Control Engineering	B. Tinianov
.....	M.J. Lucas (Alt.)

International Safety Equipment Association	J. Birkner
.....	C.Z. Fargo (Alt.)
John Deere	K.B. Washburn
.....	K. Cone (Alt.)
NASA Glenn Research Center	B. Cooper
National Council of Acoustical Consultants	J. Erdreich
.....	G.E. Winzer (Alt.)
National Hearing Conservation Association	J. Cissna
National Institute for Occupational Safety and Health	W.J. Murphy
.....	E. Zechmann (Alt.)
National Park Service	G.R. Stanley
.....	K. Fristrup (Alt.)
Noise Control Engineering, Inc.	M.A. Bahtiarian
.....	R. Fischer (Alt.)
Noise Pollution Clearinghouse	L. Blomberg
North American Insulation Manufacturers Association	H. Alter
PCB Group	K. Cox
.....	L. Harbaugh (Alt.)
Power Tool Institute, Inc.	W.D. Spencer
.....	M. Hickok (Alt.)
Quest Technologies, Inc.	M. Wurm
.....	P.J. Battenberg (Alt.)
Schomer and Associates, Inc.	P.D. Schomer
Siebein Associates, Inc.	G.W. Siebein
.....	R.M. Lilkendey (Alt.)
Sierra Club National Parks and Monument Committee	D.J. Hingson
Sperian Hearing Protection, LLC	B. Witt
.....	T. Schulz (Alt.)
U.S. Access Board	L. Thibault
U.S. Air Force	R.L. McKinley
.....	F. Mobley (Alt.)
U.S. Army Aeromedical Research Lab	W. Ahroon
U.S. Army Center for Health Promotion and Preventive Medicine	W.D. Whiteford
.....	C. Stewart (Alt.)
U.S. Army Construction Engineering Research Laboratory	M.J. White
.....	M. Swearingen (Alt.)
U.S. Army Research Laboratory, Human Research and Engineering Directorate	M.S. Binseel
U.S. Department of Transportation	A. Konheim

U.S. Naval Surface Warfare Center – CarderockM. Craun

Individual Experts of Accredited Standards Committee S12, Noise, were:

P.K. Baade	R.D. Hellweg	R.J. Peppin
L.L. Beranek	W.W. Lang	J. Schmitt
E.H. Berger	D. Lubman	P.D. Schomer
B.M. Brooks	D. Michaud	L.C. Sutherland
A.J. Campanella	N.P. Miller	W.R. Thornton
K.M. Eldred	W.J. Murphy	L.A. Wilber
L.S. Finegold	M.A. Nobile	G.E. Winzer
R.D. Godfrey		

Working Group S12/WG 3, Measurement of Noise from Information Technology and Telecommunications Equipment, which assisted Accredited Standards Committee S12, Noise, in the development of this standard, had the following membership.

K.X.C. Man, Chair

D. Ali	R.D. Hellweg	C. Saunder
B.A. Bard	A. Nava	J. Schmitt
E. Baugh	M.A. Nobile	R. Underwood
W.M. Beltman	V. Ojeda	L. Wittig
J. DeMoss	R.J. Peppin	J. Wong
E. Dunens	D. Quinlan	Y. Xu

Suggestions for improvements of this standard will be welcomed. They should be sent to Accredited Standards Committee S12, Noise, in care of the Standards Secretariat of the Acoustical Society of America, 35 Pinelawn Road, Suite 114E, Melville, New York 11747-3177. Telephone: 631-390-0215; FAX: 631-390-0217; E-mail: asastds@aip.org.

Introduction

ANSI/ASA S12.10-2010/Part 1 specifies methods for the measurement of airborne noise emitted by information technology and telecommunications equipment. Hitherto, a wide variety of methods have been applied by individual manufacturers and users to satisfy particular equipment or application needs. These diverse practices have, in many cases, made comparison of noise emission difficult. This Standard simplifies such comparisons and is the basis for declaration of the noise emission level of information technology and telecommunications equipment.

In order to ensure accuracy, validity and acceptability, this Standard is based on the basic Standards for determining the sound power level and for determining the emission sound pressure level at the operator position(s) and bystander position(s). Furthermore, implementation is simplified by conformance with these International Standards.

In many cases free-field conditions over a reflecting plane are realized by hemi-anechoic rooms. These rooms may be particularly useful during product design to locate and to improve individual contributing noise sources. Reverberation test rooms may be more economical for production control and for obtaining sound power levels for noise emission declaration purposes.

The method for measuring the emission sound pressure level at the operator or bystander positions (based on ISO 11201) is specified in a separate clause, as this level is not considered to be primary noise emission declaration information. The measurements can, however, be carried out in conjunction with those for sound power determination in a free field over a reflecting plane.

For comparison of similar equipment it is essential that the installation conditions and mode of operation are the same. In Annex C these parameters are standardized for many categories of equipment by referring to the latest edition of ECMA-74, which is the world-wide test code for the IT industry.

American National Standard

Measurement of Airborne Noise Emitted by Information Technology and Telecommunications Equipment - Part 1: Determination of Sound Power Level and Emission Sound Pressure Level

1 Scope

This American National Standard specifies procedures for measuring and reporting the noise emission of information technology and telecommunications equipment. This Standard is considered part of a noise test code for this type of equipment and is based on basic noise emission standards ANSI/ASA S12.51 / ISO 3741, ANSI/ASA S12.54 / ISO 3744, ANSI/ASA S12.55 / ISO 3745 and ISO 11201. The basic emission quantity is the A-weighted sound power level which may be used for comparing equipment of the same type but from different manufacturers, or for comparing different equipment.

Three basic noise emission standards for determining the sound power levels are specified in this American National Standard in order to avoid undue restriction on existing facilities and experience. The first basic standard (ANSI/ASA S12.51 / ISO 3741) specifies comparison measurements in a reverberation test room; the other two (ANSI/ASA S12.54 / ISO 3744 and ANSI/ASA S12.55 / ISO 3745) specify measurements in an essentially free field over a reflecting plane. Any one of these three basic noise emission standards may be selected and shall then be used exclusively according to this Standard when determining sound power levels of a machine.

The A-weighted sound power level is supplemented by the A-weighted emission sound pressure level determined at the operator position(s) or the bystander positions, based on the basic noise emission standard ISO 11201. This sound pressure level is not a worker's immission rating level, but it may assist in identifying any potential problems that could cause annoyance, activity interference, or hearing damage to operators and bystanders.

Methods for determining whether the noise emission includes prominent discrete tones or is impulsive in character are specified in Annexes D and E, respectively.

This Standard is suitable for type tests and provides methods for manufacturers and testing laboratories to obtain comparable results.

The methods specified in this Standard allow the determination of noise emission levels for a unit tested individually.

The procedures may be applied to equipment which emits broad-band noise, narrow-band noise and noise which contains discrete-frequency components, or impulsive noise.

The sound power and emission sound pressure levels obtained may serve noise emission declaration and comparison purposes (see ECMA-109). They are not to be considered as installation noise immission levels; however, they may be used for installation planning (see ECMA TR/27).

If sound power levels obtained are determined for a number of units of the same production series, they can be used to determine a statistical value for that production series (see ECMA-109).