

ETSI TS 136 104 V12.11.0 (2016-04)



LTE;
**Evolved Universal Terrestrial Radio Access (E-UTRA);
Base Station (BS) radio transmission and reception
(3GPP TS 36.104 version 12.11.0 Release 12)**



Reference

RTS/TSGR-0436104vcb0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	7
1 Scope	8
2 References	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Symbols.....	11
3.3 Abbreviations	12
4 General	14
4.1 Relationship between minimum requirements and test requirements	14
4.2 Base station classes	14
4.3 Regional requirements.....	14
4.4 Applicability of requirements.....	15
4.5 Requirements for BS capable of multi-band operation	16
5 Operating bands and channel arrangement.....	16
5.1 General	16
5.2 Void.....	17
5.3 Void.....	17
5.4 Void.....	17
5.5 Operating bands.....	17
5.6 Channel bandwidth.....	26
5.7 Channel arrangement.....	28
5.7.1 Channel spacing.....	28
5.7.1A CA Channel spacing	29
5.7.2 Channel raster	29
5.7.3 Carrier frequency and EARFCN.....	29
5.8 Requirements for contiguous and non-contiguous spectrum.....	30
6 Transmitter characteristics	31
6.1 General	31
6.2 Base station output power	31
6.2.1 Minimum requirement	32
6.2.2 Additional requirement (regional)	32
6.2.3 Home BS output power for adjacent UTRA channel protection.....	32
6.2.4 Home BS output power for adjacent E-UTRA channel protection.....	33
6.2.5 Home BS Output Power for co-channel E-UTRA protection	34
6.3 Output power dynamics.....	35
6.3.1 RE Power control dynamic range	35
6.3.1.1 Minimum requirements	35
6.3.2 Total power dynamic range	36
6.3.2.1 Minimum requirements	36
6.4 Transmit ON/OFF power	36
6.4.1 Transmitter OFF power	36
6.4.1.1 Minimum Requirement	36
6.4.2 Transmitter transient period.....	37
6.4.2.1 Minimum requirements	37
6.5 Transmitted signal quality	37
6.5.1 Frequency error.....	37
6.5.1.1 Minimum requirement	37
6.5.2 Error Vector Magnitude.....	38
6.5.3 Time alignment error	38
6.5.3.1 Minimum Requirement	38

6.5.4	DL RS power	38
6.5.4.1	Minimum requirements	39
6.6	Unwanted emissions	39
6.6.1	Occupied bandwidth	39
6.6.1.1	Minimum requirement	39
6.6.2	Adjacent Channel Leakage power Ratio (ACLR)	39
6.6.2.1	Minimum requirement	40
6.6.2.2	Cumulative ACLR requirement in non-contiguous spectrum	42
6.6.3	Operating band unwanted emissions	43
6.6.3.1	Minimum requirements for Wide Area BS (Category A)	44
6.6.3.2	Minimum requirements for Wide Area BS (Category B)	47
6.6.3.2.1	Category B requirements (Option 1)	47
6.6.3.2.2	Category B (Option 2)	50
6.6.3.2A	Minimum requirements for Local Area BS (Category A and B)	52
6.6.3.2B	Minimum requirements for Home BS (Category A and B)	53
6.6.3.2C	Minimum requirements for Medium Range BS (Category A and B)	54
6.6.3.3	Additional requirements	56
6.6.4	Transmitter spurious emissions	59
6.6.4.1	Mandatory Requirements	59
6.6.4.1.1	Spurious emissions (Category A)	59
6.6.4.1.2	Spurious emissions (Category B)	60
6.6.4.2	Protection of the BS receiver of own or different BS	60
6.6.4.2.1	Minimum Requirement	60
6.6.4.3	Additional spurious emissions requirements	60
6.6.4.3.1	Minimum Requirement	60
6.6.4.4	Co-location with other base stations	72
6.6.4.4.1	Minimum Requirement	72
6.7	Transmitter intermodulation	82
6.7.1	Minimum requirement	82
6.7.2	Additional requirement for Band 41	82
7	Receiver characteristics	83
7.1	General	83
7.2	Reference sensitivity level	83
7.2.1	Minimum requirement	84
7.3	Dynamic range	85
7.3.1	Minimum requirement	85
7.4	In-channel selectivity	87
7.4.1	Minimum requirement	87
7.5	Adjacent Channel Selectivity (ACS) and narrow-band blocking	89
7.5.1	Minimum requirement	89
7.6	Blocking	91
7.6.1	General blocking requirement	91
7.6.1.1	Minimum requirement	91
7.6.2	Co-location with other base stations	96
7.6.2.1	Minimum requirement	96
7.7	Receiver spurious emissions	105
7.7.1	Minimum requirement	105
7.8	Receiver intermodulation	106
7.8.1	Minimum requirement	106
8	Performance requirement	110
8.1	General	110
8.2	Performance requirements for PUSCH	111
8.2.1	Requirements in multipath fading propagation conditions	111
8.2.1.1	Minimum requirements	111
8.2.2	Requirements for UL timing adjustment	124
8.2.2.1	Minimum requirements	124
8.2.3	Requirements for high speed train	125
8.2.3.1	Minimum requirements	125
8.2.4	Requirements for HARQ-ACK multiplexed on PUSCH	126
8.2.4.1	Minimum requirement	126

8.2.5	Requirements for PUSCH with TTI bundling and enhanced HARQ pattern	127
8.2.5.1	Minimum requirements	128
8.3	Performance requirements for PUCCH	128
8.3.1	DTX to ACK performance	128
8.3.1.1	Minimum requirement	128
8.3.2	ACK missed detection requirements for single user PUCCH format 1a	128
8.3.2.1	Minimum requirements	128
8.3.3	CQI performance requirements for PUCCH format 2	129
8.3.3.1	Minimum requirements	129
8.3.4	ACK missed detection requirements for multi user PUCCH format 1a	130
8.3.4.1	Minimum requirement	130
8.3.5	ACK missed detection requirements for PUCCH format 1b with Channel Selection	130
8.3.5.1	Minimum requirements	131
8.3.6	ACK missed detection requirements for PUCCH format 3	131
8.3.6.1	Minimum requirements	131
8.3.7	NACK to ACK requirements for PUCCH format 3	132
8.3.7.1	Minimum requirement	132
8.3.8	CQI performance requirements for PUCCH format 2 with DTX detection	132
8.3.8.1	Minimum requirements	133
8.4	Performance requirements for PRACH	133
8.4.1	PRACH False alarm probability	133
8.4.1.1	Minimum requirement	133
8.4.2	PRACH detection requirements.....	133
8.4.2.1	Minimum requirements	133

Annex A (normative): Reference measurement channels135

A.1	Fixed Reference Channels for reference sensitivity and in-channel selectivity (QPSK, R=1/3)	135
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3).....	136
A.3	Fixed Reference Channels for performance requirements (QPSK 1/3)	136
A.4	Fixed Reference Channels for performance requirements (16QAM 3/4)	137
A.5	Fixed Reference Channels for performance requirements (64QAM 5/6)	137
A.6	PRACH Test preambles	137
A.7	Fixed Reference Channels for UL timing adjustment (Scenario 1)	138
A.8	Fixed Reference Channels for UL timing adjustment (Scenario 2)	138
A.9	Multi user PUCCH test.....	138
A.10	PUCCH transmission on two antenna ports test.....	139
A.11	Fixed Reference Channel for PUSCH with TTI bundling and enhanced HARQ pattern	139

Annex B (normative): Propagation conditions.....140

B.1	Static propagation condition.....	140
B.2	Multi-path fading propagation conditions	140
B.3	High speed train condition	141
B.4	Moving propagation conditions.....	142
B.5	Multi-Antenna channel models	143
B.5.1	Definition of MIMO Correlation Matrices	143
B.5.2	MIMO Correlation Matrices at High, Medium and Low Level.....	144

B.5A Multi-Antenna channel models using cross polarized antennas.....146

B.5A.1	Definition of MIMO Correlation Matrices using cross polarized antennas	147
B.5A.2	Spatial Correlation Matrices at UE and eNB sides.....	147
B.5A.3	MIMO Correlation Matrices using cross polarized antennas.....	148

Annex C (normative):	Characteristics of the interfering signals.....	149
Annex D (normative):	Environmental requirements for the BS equipment	150
Annex E (normative):	Error Vector Magnitude	151
E.1	Reference point for measurement.....	151
E.2	Basic unit of measurement	151
E.3	Modified signal under test.....	152
E.4	Estimation of frequency offset	152
E.5	Estimation of time offset	152
E.5.1	Window length	153
E.6	Estimation of TX chain amplitude and frequency response parameters	153
E.7	Averaged EVM	154
Annex F (Informative):	Unwanted emission requirements for multi-carrier BS	156
F.1	General	156
F.2	Multi-carrier BS of different E-UTRA channel bandwidths	156
F.3	Multi-carrier BS of E-UTRA and UTRA.....	156
Annex G (Informative):	Regional requirement for protection of DTT	157
G.1	Regional requirement for protection of DTT	157
Annex H (Informative):	Calculation of EIRP based on manufacturer declarations and site specific conditions	158
H.1	Calculation of EIRP based on manufacturer declarations and site specific conditions.....	158
Annex I (Informative):	Change history	159
	History	168

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document establishes the minimum RF characteristics and minimum performance requirements of E-UTRA Base Station (BS).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] ITU-R Recommendation SM.329: "Unwanted emissions in the spurious domain".
- [3] ITU-R Recommendation M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [4] 3GPP TS 36.141: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) conformance testing".
- [5] ITU-R recommendation SM.328: "Spectra and bandwidth of emissions".
- [6] 3GPP TS 25.104: "Base Station (BS) radio transmission and reception (FDD)".
- [7] 3GPP TS 25.105: "Base Station (BS) radio transmission and reception (TDD)".
- [8] 3GPP TR 25.942: "RF system scenarios".
- [9] 3GPP TR 36.942: "E-UTRA RF system scenarios".
- [10] 3GPP TS 36.211: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Channels and Modulation".
- [11] 3GPP TS 36.213: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures".
- [12] ECC/DEC/(09)03 "Harmonised conditions for MFCN in the band 790-862 MHz", 30 Oct. 2009

- [13] IEC 60721-3-3 (2002): "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 3: Stationary use at weather protected locations".
- [14] IEC 60721-3-4 (1995): "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 4: Stationary use at non-weather protected locations".
- [15] 3GPP TS 37.104: "E-UTRA, UTRA and GSM/EDGE; Multi-Standard Radio (MSR) Base Station (BS) radio transmission and reception".
- [16] CEPT ECC Decision (13)03, "The harmonised use of the frequency band 1452-1492 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".