

# ETSI TS 136 104 V13.2.0 (2016-01)



**LTE;  
Evolved Universal Terrestrial Radio Access (E-UTRA);  
Base Station  
(BS) radio transmission and reception  
(3GPP TS 36.104 version 13.2.0 Release 13)**



Reference

---

RTS/TSGR-0436104vd20

Keywords

---

LTE

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**Important notice**

---

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	7
1 Scope .....	8
2 References .....	8
3 Definitions, symbols and abbreviations .....	9
3.1 Definitions .....	9
3.2 Symbols.....	11
3.3 Abbreviations .....	12
4 General .....	14
4.1 Relationship between minimum requirements and test requirements .....	14
4.2 Base station classes .....	14
4.3 Regional requirements.....	14
4.4 Applicability of requirements.....	15
4.5 Requirements for BS capable of multi-band operation .....	16
5 Operating bands and channel arrangement.....	16
5.1 General .....	16
5.2 Void.....	17
5.3 Void.....	17
5.4 Void.....	17
5.5 Operating bands.....	17
5.6 Channel bandwidth.....	31
5.7 Channel arrangement.....	33
5.7.1 Channel spacing.....	33
5.7.1A CA Channel spacing .....	33
5.7.2 Channel raster .....	33
5.7.3 Carrier frequency and EARFCN.....	33
5.8 Requirements for contiguous and non-contiguous spectrum.....	37
6 Transmitter characteristics .....	37
6.1 General .....	37
6.2 Base station output power .....	38
6.2.1 Minimum requirement .....	38
6.2.2 Additional requirement (regional) .....	38
6.2.3 Home BS output power for adjacent UTRA channel protection.....	39
6.2.4 Home BS output power for adjacent E-UTRA channel protection.....	40
6.2.5 Home BS Output Power for co-channel E-UTRA protection.....	41
6.3 Output power dynamics.....	42
6.3.1 RE Power control dynamic range .....	42
6.3.1.1 Minimum requirements .....	42
6.3.2 Total power dynamic range .....	42
6.3.2.1 Minimum requirements .....	42
6.4 Transmit ON/OFF power .....	43
6.4.1 Transmitter OFF power .....	43
6.4.1.1 Minimum Requirement .....	43
6.4.2 Transmitter transient period.....	43
6.4.2.1 Minimum requirements.....	44
6.5 Transmitted signal quality .....	44
6.5.1 Frequency error.....	44
6.5.1.1 Minimum requirement .....	44
6.5.2 Error Vector Magnitude.....	44
6.5.3 Time alignment error .....	45
6.5.3.1 Minimum Requirement .....	45

6.5.4	DL RS power .....	45
6.5.4.1	Minimum requirements .....	45
6.6	Unwanted emissions .....	45
6.6.1	Occupied bandwidth .....	45
6.6.1.1	Minimum requirement .....	46
6.6.2	Adjacent Channel Leakage power Ratio (ACLR) .....	46
6.6.2.1	Minimum requirement .....	46
6.6.2.2	Cumulative ACLR requirement in non-contiguous spectrum .....	48
6.6.3	Operating band unwanted emissions .....	50
6.6.3.1	Minimum requirements for Wide Area BS (Category A) .....	51
6.6.3.2	Minimum requirements for Wide Area BS (Category B) .....	54
6.6.3.2.1	Category B requirements (Option 1) .....	54
6.6.3.2.2	Category B (Option 2) .....	58
6.6.3.2A	Minimum requirements for Local Area BS (Category A and B) .....	60
6.6.3.2B	Minimum requirements for Home BS (Category A and B) .....	61
6.6.3.2C	Minimum requirements for Medium Range BS (Category A and B) .....	62
6.6.3.2D	Minimum requirements for Local Area and Medium Range BS in Band 46 (Category A and B) .....	64
6.6.3.3	Additional requirements .....	64
6.6.4	Transmitter spurious emissions .....	68
6.6.4.1	Mandatory Requirements .....	68
6.6.4.1.1	Spurious emissions (Category A) .....	68
6.6.4.1.2	Spurious emissions (Category B) .....	69
6.6.4.2	Protection of the BS receiver of own or different BS .....	69
6.6.4.2.1	Minimum Requirement .....	69
6.6.4.3	Additional spurious emissions requirements .....	69
6.6.4.3.1	Minimum Requirement .....	69
6.6.4.4	Co-location with other base stations .....	82
6.6.4.4.1	Minimum Requirement .....	82
6.7	Transmitter intermodulation .....	91
6.7.1	Minimum requirement .....	92
6.7.2	Additional requirement for Band 41 .....	92
7	Receiver characteristics .....	93
7.1	General .....	93
7.2	Reference sensitivity level .....	93
7.2.1	Minimum requirement .....	93
7.3	Dynamic range .....	95
7.3.1	Minimum requirement .....	95
7.4	In-channel selectivity .....	97
7.4.1	Minimum requirement .....	97
7.5	Adjacent Channel Selectivity (ACS) and narrow-band blocking .....	99
7.5.1	Minimum requirement .....	99
7.6	Blocking .....	101
7.6.1	General blocking requirement .....	101
7.6.1.1	Minimum requirement .....	101
7.6.2	Co-location with other base stations .....	107
7.6.2.1	Minimum requirement .....	107
7.7	Receiver spurious emissions .....	116
7.7.1	Minimum requirement .....	116
7.8	Receiver intermodulation .....	117
7.8.1	Minimum requirement .....	117
8	Performance requirement .....	122
8.1	General .....	122
8.2	Performance requirements for PUSCH .....	123
8.2.1	Requirements in multipath fading propagation conditions .....	123
8.2.1.1	Minimum requirements .....	123
8.2.2	Requirements for UL timing adjustment .....	137
8.2.2.1	Minimum requirements .....	137
8.2.3	Requirements for high speed train .....	138
8.2.3.1	Minimum requirements .....	138
8.2.4	Requirements for HARQ-ACK multiplexed on PUSCH .....	139

8.2.4.1	Minimum requirement .....	139
8.2.5	Requirements for PUSCH with TTI bundling and enhanced HARQ pattern .....	140
8.2.5.1	Minimum requirements .....	141
8.3	Performance requirements for PUCCH .....	141
8.3.1	DTX to ACK performance .....	141
8.3.1.1	Minimum requirement .....	141
8.3.2	ACK missed detection requirements for single user PUCCH format 1a .....	141
8.3.2.1	Minimum requirements .....	141
8.3.3	CQI performance requirements for PUCCH format 2 .....	142
8.3.3.1	Minimum requirements .....	142
8.3.4	ACK missed detection requirements for multi user PUCCH format 1a .....	143
8.3.4.1	Minimum requirement .....	143
8.3.5	ACK missed detection requirements for PUCCH format 1b with Channel Selection .....	143
8.3.5.1	Minimum requirements .....	144
8.3.6	ACK missed detection requirements for PUCCH format 3 .....	144
8.3.6.1	Minimum requirements .....	144
8.3.7	NACK to ACK requirements for PUCCH format 3 .....	145
8.3.7.1	Minimum requirement .....	145
8.3.8	CQI performance requirements for PUCCH format 2 with DTX detection .....	145
8.3.8.1	Minimum requirements .....	146
8.4	Performance requirements for PRACH .....	146
8.4.1	PRACH False alarm probability .....	146
8.4.1.1	Minimum requirement .....	146
8.4.2	PRACH detection requirements .....	146
8.4.2.1	Minimum requirements .....	146
9	Channel access procedures .....	148
9.1	Downlink channel access procedure .....	148
9.1.1	Channel access parameters .....	148
9.1.2	Minimum requirement .....	148
<b>Annex A (normative): Reference measurement channels .....</b>		<b>149</b>
A.1	Fixed Reference Channels for reference sensitivity and in-channel selectivity (QPSK, R=1/3) .....	149
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3) .....	150
A.3	Fixed Reference Channels for performance requirements (QPSK 1/3) .....	150
A.4	Fixed Reference Channels for performance requirements (16QAM 3/4) .....	151
A.5	Fixed Reference Channels for performance requirements (64QAM 5/6) .....	151
A.6	PRACH Test preambles .....	151
A.7	Fixed Reference Channels for UL timing adjustment (Scenario 1) .....	152
A.8	Fixed Reference Channels for UL timing adjustment (Scenario 2) .....	152
A.9	Multi user PUCCH test .....	152
A.10	PUCCH transmission on two antenna ports test .....	153
A.11	Fixed Reference Channel for PUSCH with TTI bundling and enhanced HARQ pattern .....	153
<b>Annex B (normative): Propagation conditions .....</b>		<b>154</b>
B.1	Static propagation condition .....	154
B.2	Multi-path fading propagation conditions .....	154
B.3	High speed train condition .....	155
B.4	Moving propagation conditions .....	156
B.5	Multi-Antenna channel models .....	157
B.5.1	Definition of MIMO Correlation Matrices .....	157
B.5.2	MIMO Correlation Matrices at High, Medium and Low Level .....	158

<b>B.5A Multi-Antenna channel models using cross polarized antennas</b> .....	160
<b>B.5A.1 Definition of MIMO Correlation Matrices using cross polarized antennas</b> .....	161
<b>B.5A.2 Spatial Correlation Matrices at UE and eNB sides</b> .....	161
<b>B.5A.3 MIMO Correlation Matrices using cross polarized antennas</b> .....	162
<b>Annex C (normative): Characteristics of the interfering signals</b> .....	163
<b>Annex D (normative): Environmental requirements for the BS equipment</b> .....	164
<b>Annex E (normative): Error Vector Magnitude</b> .....	165
E.1 Reference point for measurement .....	165
E.2 Basic unit of measurement .....	165
E.3 Modified signal under test .....	166
E.4 Estimation of frequency offset .....	166
E.5 Estimation of time offset .....	166
E.5.1 Window length .....	167
E.6 Estimation of TX chain amplitude and frequency response parameters .....	167
E.7 Averaged EVM .....	168
<b>Annex F (Informative): Unwanted emission requirements for multi-carrier BS</b> .....	170
F.1 General .....	170
F.2 Multi-carrier BS of different E-UTRA channel bandwidths .....	170
F.3 Multi-carrier BS of E-UTRA and UTRA .....	170
<b>Annex G (Informative): Regional requirement for protection of DTT</b> .....	171
G.1 Regional requirement for protection of DTT .....	171
<b>Annex H (Informative): Calculation of EIRP based on manufacturer declarations and site specific conditions</b> .....	172
H.1 Calculation of EIRP based on manufacturer declarations and site specific conditions .....	172
<b>Annex I (Informative): Change history</b> .....	173
History .....	182

---

# Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.



---

# 1 Scope

The present document establishes the minimum RF characteristics and minimum performance requirements of E-UTRA Base Station (BS).

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] ITU-R Recommendation SM.329: "Unwanted emissions in the spurious domain".
- [3] ITU-R Recommendation M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [4] 3GPP TS 36.141: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) conformance testing".
- [5] ITU-R recommendation SM.328: "Spectra and bandwidth of emissions".
- [6] 3GPP TS 25.104: "Base Station (BS) radio transmission and reception (FDD)".
- [7] 3GPP TS 25.105: "Base Station (BS) radio transmission and reception (TDD)".
- [8] 3GPP TR 25.942: "RF system scenarios".
- [9] 3GPP TR 36.942: "E-UTRA RF system scenarios".
- [10] 3GPP TS 36.211: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Channels and Modulation".
- [11] 3GPP TS 36.213: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures".
- [12] ECC/DEC/(09)03 "Harmonised conditions for MFCN in the band 790-862 MHz", 30 Oct. 2009
- [13] IEC 60721-3-3 (2002): "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 3: Stationary use at weather protected locations".
- [14] IEC 60721-3-4 (1995): "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 4: Stationary use at non-weather protected locations".
- [15] 3GPP TS 37.104: "E-UTRA, UTRA and GSM/EDGE; Multi-Standard Radio (MSR) Base Station (BS) radio transmission and reception".
- [16] CEPT ECC Decision (13)03, "The harmonised use of the frequency band 1452-1492 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".