

ETSI TS 127 002 V13.0.0 (2016-01)



**Digital cellular telecommunications system (Phase 2+);
Universal Mobile Telecommunications System (UMTS);
Terminal Adaptation Functions (TAF) for services using
asynchronous bearer capabilities
(3GPP TS 27.002 version 13.0.0 Release 13)**



Reference

RTS/TSGC-0327002vd00

Keywords

GSM,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope	6
1.1 References	6
1.2 Abbreviations	8
1.3 Definitions	8
2 Reference Configuration	8
2.1 Customer Access Configuration.....	8
2.2 Terminal Adaptation Function (TAF)	8
3 Terminal Adaptation Functions for transparent services.....	9
3.1 Rate Adaptation in A/Gb mode	9
3.1.1 Rate Adaptation - R interface	9
3.1.2 Rate Adaptation - S Interface (ITU-T I.420 [14]).....	9
3.2 Interchange Circuit Signalling Mapping - ITU-T V-series interface.....	9
3.2.1 Mapping of V.24 [19] circuits to status bits.....	9
3.2.2 Single slot configurations (TCH/F9.6 or TCH/F4.8).....	10
3.2.3 Multislot configurations (TCH/F9.6 or TCH/F4.8)	10
3.2.4 Channel codings TCH/F14.4, TCH/F28.8	10
3.3 Interface Signal Levels - R interface	10
3.4 Call Establishment and Clearing Signalling Mapping.....	11
3.4.1 V-series interface Autocalling/answering	11
3.4.2 S Interface (I.420) Signalling Mapping	11
3.4.3 Call Establishment Manual Operation - Utilizing the Unrestricted Digital Capability.....	11
3.4.4 V-series interface Call Clearing.....	11
4 Terminal Adaptation Functions for non-transparent services	11
4.1 Data Structure.....	11
4.1.1 Data Structure on S Interface	11
4.1.2 Data Structure on R Interface	12
4.1.3 Data Structure Provided by the L2R Function to the RLP Function.....	12
4.2 Signalling Mapping	12
4.2.1 Interchange Circuit Signalling Mapping - ITU-T V-series interface	12
4.2.2 Call Establishment and Clearing Signalling Mapping	13
4.3 Flow Control	13
4.3.1 Conditions Requiring Flow Control towards the Network	13
4.3.2 Conditions Requiring Flow Control towards TE2	13
4.3.3 Local Flow Control.....	13
4.3.4 Character Orientated Protocol with No Flow Control	14
4.4 Buffers	14
4.4.1 TX Buffers.....	14
4.4.2 RX Buffers.....	14
4.5 Bit Transparency	14
4.6 Transportation of "BREAK" condition	14
4.7 Data Compression	14
5 Terminal interfacing to 3GPP TS 24.008 [8] Mapping.....	15
5.1 Mobile Originated Calls	16
5.2 Mobile Terminated Calls.....	16
5.3 Call Clearing	17
5.3.1 Mobile initiated.....	17
5.3.2 Network initiated	17

Annex A (normative):	L2R Functionality	18
A.1	Introduction	18
A.2	The L2RCOP.....	18
A.3	Use of the L2RCOP.....	21
A.3.1	Radio Link Connection Control	21
A.3.2	Data Transfer.....	21
A.3.3	Status Transfer.....	21
A.3.4	Flow Control	21
A.3.5	Break	21
A.3.5.1	Normal Realization.....	21
A.3.5.2	Realization in case of Data Compression is used.....	22
Annex B (informative):	Use of a 9 pin connector as an MT2 type interface.....	23
Annex C (informative):	General mapping of ITU-T V.24 [19] circuits to channel status bits	24
Annex D (informative):	Change history	25
History		26

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document defines the interfaces and Terminal Adaptation Functions (TAF) integral to a Mobile Termination (MT) which enable the use of asynchronous bearer services in the PLMN and the attachment of asynchronous terminals to a MT (see 3GPP TS 24.002 [3] and 3GPP TS 23.101 [6]).

The general aspects of Terminal Adaptation Functions are contained in 3GPP TS 27.001 [10].

The present document covers support of these services for the following interfaces and procedures:

- (i) ITU-T V.14 [16] procedures.
- (ii) ITU-T V.21 [17] DTE/DCE interface.
- (iii) ITU-T V.22bis [18] DTE/DCE interface.
- (iv) ITU-T V.32 [24] DTE/DCE procedures.
- (v) ITU-T I.420 [14] S interface.
- (vi) ITU-T V.250 [22] signalling procedures.

The asynchronous data rates between the MT and the IWF are defined in 3GPP TS 22.002 [5].

NOTE: From GSM R99 onwards the following services are no longer required in a PLMN:

- the dual Bearer Services "alternate speech/data" and "speech followed by data";
- the dedicated services for PAD and Packet access;
- the BS 21 ... 26 and BS 31 ... 34.

The support of these services is still optional. The specification of these services is not within the scope of the present document. For that, the reader is referred to GSM Release 98.

NOTE: Please note that the Gb interface does not play any role in the scope of the present document although the term 'A/Gb mode' is used. GERAN Iu mode is for further study.

1.1 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] Void.
- [2] 3GPP TS 43.010: "GSM Public Land Mobile Network (PLMN) connection types".
- [3] 3GPP TS 24.002: "GSM-UMTS Public Land Mobile Network (PLMN) access reference configuration".
- [4] 3GPP TS 44.021: "Rate adaption on the Mobile Station - Base Station System (MS - BSS) interface".
- [5] 3GPP TS 22.002: "Circuit Bearer Services (BS) supported by a Public Land Mobile Network (PLMN)".
- [6] 3GPP TS 23.101: "General UMTS Architecture".
- [7] 3GPP TR 23.910: "Circuit Switched Data Bearer Services".