

ETSI EN 300 392-12-4 V1.4.1 (2016-07)



**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 12: Supplementary services stage 3;
Sub-part 4: Call Forwarding (CF)**

Reference

REN/TETRA-03229

Keywords

CF, late entry, radio, stage 3,
supplementary service, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	9
Foreword.....	9
Modal verbs terminology.....	10
Introduction	11
1 Scope	12
2 References	12
2.1 Normative references	12
2.2 Informative references.....	13
3 Definitions, symbols and abbreviations	14
3.1 Definitions	14
3.2 Symbols.....	16
3.3 Abbreviations	16
4 Signalling protocol for the support of SS-CF.....	18
4.1 SS-CF description	18
4.2 SS-CF services offered over the TNSS-SAP.....	18
4.2.0 General.....	18
4.2.1 ACTIVATE request.....	19
4.2.2 ACTIVATE ACK indication.....	20
4.2.3 DELETE request.....	20
4.2.4 DELETE ACK indication.....	20
4.2.5 DISABLE request.....	21
4.2.6 DISABLE ACK indication.....	21
4.2.7 ENABLE request.....	21
4.2.8 ENABLE ACK indication.....	22
4.2.9 INFORM2 indication.....	22
4.2.10 INFORM5 indication.....	22
4.2.11 INFORM8 indication.....	23
4.2.12 INFORM9 indication.....	23
4.2.13 INTERROGATE request.....	23
4.2.14 INTERROGATE ACK indication.....	23
4.2.15 INTERROGATE2 request.....	24
4.2.16 INTERROGATE2 ACK indication.....	24
4.2.17 CHANGE ACTIVATION request.....	24
4.2.18 CHANGE ACTIVATION ACK indication.....	25
4.2.19 PARAMETERISE request.....	25
4.2.20 PARAMETERISE ACK indication.....	26
4.2.21 INTERROGATE STATUS request.....	26
4.2.22 INTERROGATE STATUS ACK indication.....	26
4.3 Parameter description	27
5 Signalling procedures for the support of SS-CF.....	29
5.1 SS-CF operational requirements.....	29
5.1.1 Requirements on the originating SwMI.....	29
5.1.2 Requirements on the served user SwMI	30
5.1.3 Requirements on the forwarded-to SwMI.....	30
5.1.4 Requirements on the re-routeing SwMI.....	30
5.1.5 Requirements on a forward switching SwMI	30
5.1.6 Requirements on the served or authorized user visited SwMI.....	30
5.2 SS-CF Coding requirements.....	31
5.2.1 SS-CF PDUs	31
5.2.1.0 General	31
5.2.1.1 ACTIVATE PDU.....	31
5.2.1.2 ACTIVATE ACK PDU	31
5.2.1.3 DELETE PDU.....	32

5.2.1.4	DELETE ACK PDU	33
5.2.1.5	DISABLE PDU	33
5.2.1.6	DISABLE ACK PDU	34
5.2.1.7	ENABLE PDU	35
5.2.1.8	ENABLE ACK	35
5.2.1.9	INFORM2 PDU	36
5.2.1.10	INFORM4 PDU	36
5.2.1.11	INFORM5 PDU	37
5.2.1.12	INFORM8 PDU	38
5.2.1.13	INFORM9 PDU	38
5.2.1.14	INTERROGATE PDU	39
5.2.1.15	INTERROGATE ACK PDU	40
5.2.1.16	INTERROGATE2 PDU	40
5.2.1.17	INTERROGATE2 ACK PDU	41
5.2.1.18	REPORT PDU	41
5.2.1.19	CHANGE ACTIVATION PDU	42
5.2.1.20	CHANGE ACTIVATION ACK PDU	42
5.2.1.21	PARAMETERISE PDU	43
5.2.1.22	PARAMETERISE ACK PDU	44
5.2.1.23	INTERROGATE STATUS PDU	44
5.2.1.24	INTERROGATE STATUS ACK PDU	45
5.2.2	TETRA PDU information element coding	45
5.2.2.1	Accept/reject	45
5.2.2.1a	Activated forwarding types and basic services	46
5.2.2.2	Activating/activation changing/deleting/parameterising user type	46
5.2.2.2a	Activation/deactivation	46
5.2.2.3	Activation by served user	46
5.2.2.4	Addressing information elements	46
5.2.2.4.1	General on addresses	46
5.2.2.4.2	Address type of the authorized user	47
5.2.2.4.3	Address type of the forwarded-to user	47
5.2.2.4.4	Address type of the last forwarding user	47
5.2.2.4.5	Address type of the originally called user	47
5.2.2.4.6	Address type of the served user	47
5.2.2.5	Basic service information	48
5.2.2.6	CF-PDU type	49
5.2.2.7	Enabled authorized user definition	50
5.2.2.8	External subscriber number	50
5.2.2.9	External subscriber number digit	50
5.2.2.10	Forwarded-to definition	50
5.2.2.10a	Forwarded-to user address	51
5.2.2.10b	Forwarding types and basic services	52
5.2.2.10c	Forwarding types and basic services present	52
5.2.2.11	Forwarding types	52
5.2.2.11a	Interrogating user type	53
5.2.2.12	Invoked call forwarding type	53
5.2.2.13	Last forwarding type	53
5.2.2.14	Number of external subscriber number digits	53
5.2.2.15	Original forwarding type	53
5.2.2.15a	Parameters addition/removal	53
5.2.2.16	Reject cause	54
5.2.2.17	Served user definition	54
5.2.2.18	SS-CF invocation counter	55
5.2.2.19	SS type	55
5.2.3	Additional coding requirements over the ISI	55
5.3	SS-CF State Definitions	57
5.3.1	General on state definitions	57
5.3.2	States at the calling user MS	57
5.3.3	States at the originating SwMI	57
5.3.4	States at the Served User MS	57
5.3.5	States at the served user SwMI	57
5.3.6	States at the forwarded-to user MS	57

5.3.7	States at the forwarded-to SwMI	57
5.3.8	States at the re-routeing SwMI	58
5.3.9	States at the authorized user MS	58
5.3.10	States at the Activating SwMI	58
5.3.11	States at the deactivating user MS	58
5.3.12	States at the deactivating SwMI.....	58
5.3.13	States at the interrogating user MS	58
5.3.14	States at the interrogating SwMI.....	58
5.4	SS-CF signalling procedures	58
5.4.1	Actions at MSs.....	58
5.4.1.1	Activation requesting user MS	58
5.4.1.1.1	Normal operation.....	58
5.4.1.1.2	Exceptional procedures.....	59
5.4.1.2	Deletion requesting user MS	59
5.4.1.2.1	Normal operation for served or authorized user MS	59
5.4.1.2.2	Exceptional procedures for served or authorized user MS	59
5.4.1.2.3	Normal operation for forwarded-to user MS	59
5.4.1.2.4	Exceptional procedures for forwarded-to user MS	59
5.4.1.3	Interrogation requesting user MS	60
5.4.1.3.1	Normal operation of interrogation.....	60
5.4.1.3.2	Exceptional procedures for interrogation services.....	60
5.4.1.4	Interrogation requesting forwarded-to user MS	60
5.4.1.4.1	Normal operation of interrogation.....	60
5.4.1.4.2	Exceptional procedures for interrogation	60
5.4.1.5	Unsolicited indication to the served user	60
5.4.1.6	Invocation and operation at MS	60
5.4.1.6.1	General on SS-CF invocation indications.....	60
5.4.1.6.2	Notification to the calling user	61
5.4.1.6.3	Additional indication to the calling user.....	61
5.4.1.6.4	Notification to the forwarded-to user	61
5.4.1.6.5	Additional indication to the forwarded-to user.....	61
5.4.1.6.6	Identification of the forwarded-to user to the calling user.....	61
5.4.1.7	Reminder notification to the served user.....	61
5.4.1.7.1	Normal operation.....	61
5.4.1.7.2	Exceptional procedures.....	61
5.4.1.8	Parameterise requesting user MS	61
5.4.1.8.1	Normal operation.....	61
5.4.1.8.2	Exceptional procedures.....	62
5.4.1.9	Change activation requesting user MS	62
5.4.1.9.1	Normal operation.....	62
5.4.1.9.2	Exceptional procedures.....	63
5.4.1.10	Disable requesting user MS	63
5.4.1.10.1	Normal operation.....	63
5.4.1.10.2	Exceptional procedures.....	63
5.4.1.11	Enable requesting user MS.....	63
5.4.1.11.1	Normal operation.....	63
5.4.1.11.2	Exceptional procedures.....	63
5.4.2	Actions at the originating SwMI.....	64
5.4.2.1	General requirements	64
5.4.2.2	Normal Procedure	64
5.4.2.3	Exceptional Procedures.....	64
5.4.3	Actions at the served user home SwMI	64
5.4.3.1	Normal Procedure	64
5.4.3.1.1	Activation	64
5.4.3.1.2	Deletion	65
5.4.3.1.3	Interrogation	65
5.4.3.1.4	Invocation and operation	65
5.4.3.1.5	Reminder notification to the served user	67
5.4.3.1.6	Parameterise	67
5.4.3.1.7	Change activation	67
5.4.3.1.8	Disabling	67
5.4.3.1.9	Enabling.....	68

5.4.3.2	Exceptional Procedures	68
5.4.3.2.1	Activation	68
5.4.3.2.2	Deletion	68
5.4.3.2.3	Interrogation	68
5.4.3.2.4	Invocation	68
5.4.3.2.5	Parameterise	68
5.4.3.2.6	Change activation	69
5.4.3.2.7	Disabling	69
5.4.3.2.8	Enabling	69
5.4.4	Actions at the Forwarding SwMI	69
5.4.4.1	Functionalities in the case of call forwarding by re-routeing	69
5.4.4.2	Functionalities in the case of call forwarding by forward switching	69
5.4.4.3	Normal procedure	69
5.4.4.4	Exceptional procedures	69
5.4.5	Procedures at the forwarded-to SwMI	69
5.4.5.1	Normal procedure on invocation	69
5.4.5.2	Exceptional Procedures	70
5.4.6	Procedures at the served or authorized user visited SwMI	70
5.4.6.1	Normal Procedure	70
5.4.6.2	Exceptional Procedures	70
5.4.7	Protocol for SS-CF invocation counter	70
5.5	Interworking	70
5.6	Protocol Interactions between SS-CF and other SSs and ANFs	70
5.6.1	Interactions with Ambience Listening (SS-AL)	70
5.6.2	Interactions with Call Authorized by Dispatcher (SS-CAD)	71
5.6.3	Other protocol interactions of SS-CFU	71
5.6.3.1	Interaction with Completion of Call to Busy Subscriber (SS-CCBS)	71
5.6.3.1.0	General	71
5.6.3.1.1	Originating SwMI procedures for invoking CCBS at a CFU forwarded-to user	71
5.6.3.1.2	Originating SwMI procedures if CFU is activated by SS-CCBS user A	71
5.6.3.1.3	Terminating SwMI procedures if CFU is activated by user B after CCBS has been invoked	71
5.6.3.2	Interaction with Completion of Calls on No Reply (SS-CCNR)	72
5.6.3.2.0	General	72
5.6.3.2.1	Originating SwMI procedures for invoking CCNR at a CFU diverted-to user	72
5.6.3.2.2	Originating SwMI procedures if CFU is activated by SS-CCNR user A	72
5.6.3.2.3	Terminating PINX procedures if CFU is activated by user B after CCNR has been invoked	72
5.6.3.3	Interaction with Call Forwarding Busy (SS-CFB)	72
5.6.3.4	Interaction with Call Forwarding No Reply (SS-CFNR)	72
5.6.4	Protocol interactions of SS-CFB	72
5.6.4.1	Interaction with Completion of Calls to Busy Subscriber (SS-CCBS)	72
5.6.4.1.0	General	72
5.6.4.1.1	Originating SwMI procedures for invoking CCBS at a CFB diverted-to user	73
5.6.4.1.2	Originating SwMI procedures if CFB is activated by SS-CCBS user A	73
5.6.4.1.3	Terminating SwMI procedures if CFB is activated by user B after CCBS has been invoked	73
5.6.4.2	Interaction with Completion of Calls on No Reply (SS-CCNR)	73
5.6.4.2.0	General	73
5.6.4.2.1	Originating SwMI procedures for invoking CCNR at a CFB diverted-to user	73
5.6.4.2.2	Originating SwMI procedures if CFB is activated by SS-CCNR user A	73
5.6.4.2.3	Terminating SwMI procedures if CFB is activated by user B after CCNR has been invoked	73
5.6.4.3	Interaction with Call Forwarding Unconditional (SS-CFU)	73
5.6.4.4	Interaction with Call Forwarding No Reply (SS-CFNry)	73
5.6.4.5	Interaction with Call Waiting (SS-CW)	73
5.6.5	Protocol interactions of SS-CFNry	73
5.6.5.1	Interaction with Completion of Calls to Busy Subscriber (SS-CCBS)	73
5.6.5.2	Interaction with Completion of Calls on No Reply (SS-CCNR)	74
5.6.5.2.0	General	74
5.6.5.2.1	Originating SwMI procedures for invoking CCNR at a CFNR diverted-to user	74
5.6.5.2.2	Originating SwMI procedures if CFNR is activated by SS-CCNR user A	74
5.6.5.2.3	Terminating SwMI procedures if CFNR is activated by user B after CCNR has been invoked	74
5.6.5.3	Interaction with Call Forwarding Unconditional (SS-CFU)	74
5.6.5.4	Interaction with Call Forwarding Busy (SS-CFB)	74
5.6.6	Other protocol interactions of SS-CFNrc	74

5.6.6.0	General	74
5.6.6.1	Protocol interactions of SS-CFNRC in the case of early CFNRC	74
5.6.6.2	Protocol interactions of SS-CFNRC in the case of late CFNRC	74
5.6.7	Protocol interactions of SS-CF with ANF-Inter-System-Interface Individual Call (ANF-ISIIC)	75
5.6.7.1	General on interactions	75
5.6.7.2	Interactions of SS-CFU with ANF-ISIIC.....	75
5.6.7.3	Interactions of SS-CFNRC with ANF-ISIIC	75
5.6.7.4	Interactions of SS-CFB and SS-CFNRY with ANF-ISIIC	75
5.6.8	Protocol Interactions of SS-CF with ANF Group Call	75
5.6.8.0	General	75
5.6.8.1	Protocol interactions of SS-CFU with ANF-ISIGC	75
5.6.8.2	Protocol interactions of SS-CFB with ANF-ISIGC	76
5.6.9	Protocol Interactions of SS-CF with ANF-SDS	76
5.6.10	Protocol interactions of SS-CF with ANF Mobility Management.....	77
5.6.10.0	General	77
5.6.10.1	Protocol interactions of SS-CFU, early SS-CFB and early SS-CFNRC with ANF-MM.....	79
5.6.10.2	Protocol interactions of late SS-CFB, SS-CFNRY and SS-CFNRC with ANF-MM	79
5.6.10.2.1	Protocol interactions affecting the calling user.....	79
5.6.10.2.2	Protocol interactions affecting the called/served user	79
5.6.10.2.3	Protocol interactions affecting the forwarded-to user.....	80
5.6.10.3	Interaction with SS-CF at call restoration	80
5.7	SS-CF parameter values (timers).....	81
5.8	Support of SDS and STATUS	81
Annex A (informative): Interactions of SS-CFB and SS-CFNRY with ANF-ISIIC.....		82
A.1	Interactions of SS-CFB and SS-CFNRY with ANF-ISIIC	82
A.2	Interactions	82
A.2.1	Interactions of late SS-CFB and SS-CFNRY with ANF-ISIIC.....	82
A.2.2	Protocol interactions in cases 1, 10 and 11.....	85
A.2.2.1	General on cases 1, 10 and 11.....	85
A.2.2.2	Case 1	85
A.2.2.3	Case 10	86
A.2.2.4	Case 11	87
A.2.3	Protocol interactions affecting the called/served user	89
A.2.3.1	General.....	89
A.2.3.2	Case 2	89
A.2.3.3	Case 4	91
A.2.3.4	Case 5	92
A.2.3.5	Case 7	94
A.2.4	Protocol interactions affecting the forwarded-to user.....	95
A.2.4.1	General.....	95
A.2.4.2	Case 3	96
A.2.4.3	Case 6	96
A.2.4.4	Case 8	98
A.2.4.5	Case 9	100
A.2.4.6	Case 12	102
Annex B (normative): Interworking with other networks		103
B.1	Procedures for interworking with public ISDNs	103
B.1.1	Actions at an incoming gateway SwMI.....	103
B.1.2	Actions at an outgoing gateway SwMI.....	103
B.1.3	Procedures where a call from the public ISDN is forwarded within or beyond TETRA	103
B.1.3.1	Normal operation	103
B.1.3.2	Exceptional procedures	104
B.1.3.3	Presentation of a forwarded call from a public ISDN to the TETRA network	104
B.1.3.3.1	Normal operation	104
B.1.3.3.2	Exceptional procedures	104
B.1.4	Procedures where a call from the TETRA network is forwarded within or beyond the public ISDN.....	105
B.1.5	Presentation of a forwarded call from a TETRA network to the public ISDN.....	105
B.1.5.1	Normal operation	105

B.1.5.2	Exceptional procedures.....	105
B.1.6	Procedures where a call from the public ISDN is forwarded within or beyond the TETRA network and partial re-routeing takes place in the public ISDN	106
B.1.6.1	Normal operation.....	106
B.1.6.2	Exceptional procedures.....	108
B.1.7	Procedures where a call from the public ISDN to the TETRA network is forwarded by the public ISDN....	108
B.2	SS-CF Impact of interworking with non-ISDNs.....	109
B.2.1	Impact of interworking on incoming calls.....	109
B.2.2	Impact of interworking on outgoing calls.....	109
Annex C (normative): SS-CF profile for mobility management.....		110
C.1	Profile exchange.....	110
C.2	Profile definitions	110
C.2.1	General on SS-CF profiles	110
C.2.2	PDU definitions.....	110
C.2.2.1	SS-PROFILE REJECT PDU	110
C.2.2.2	SS-PROFILE UPDATE PDU.....	110
C.2.2.3	SS-PROFILE UPDATE RESPONSE PDU.....	111
C.2.3	Information element definitions	111
C.2.3.1	Basic migration profile info	111
C.2.3.2	Individual basic migration profile (original and temporary).....	112
C.2.3.3	Profile type.....	113
C.2.3.4	Profile status	113
C.2.3.5	SS-information.....	113
C.2.3.6	SS-information response.....	113
C.2.3.7	SS-migration profile (original)	114
C.2.3.8	SS-migration profile response (temporary).....	114
C.2.3.9	SS-profile response status.....	114
C.2.3.10	SS-profile update indicator	114
C.2.3.11	SS-response status	115
C.2.3.12	SS-status	115
C.2.3.13	SS-type.....	115
C.2.3.14	SS-CF profiles	115
C.2.3.14.1	SS-CF migration original profile.....	115
C.2.3.14.2	SS-CF served user migration information PDU	116
C.2.3.14.3	Number of Call forwarding types information element content.....	117
Annex D (informative): Specification and Description Language (SDL) representation of procedures		118
Annex E (informative): Bibliography.....		119
Annex F (informative): Change Requests.....		120
History		122

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee TETRA and Critical Communications Evolution (TCCE).

The present document is part 12, sub-part 4 of a multi-part deliverable covering Voice plus Data (V+D), as identified below:

- ETSI EN 300 392-1: "General network design";
- ETSI EN 300 392-2: "Air Interface (AI)";
- ETSI EN 300 392-3: "Interworking at the Inter-System Interface (ISI)";
- ETSI ETS 300 392-4: "Gateways basic operation";
- ETSI EN 300 392-5: "Peripheral Equipment Interface (PEI)";
- ETSI EN 300 392-7: "Security";
- ETSI EN 300 392-9: "General requirements for supplementary services";
- ETSI EN 300 392-10: "Supplementary services stage 1";
- ETSI EN 300 392-11: "Supplementary services stage 2";
- ETSI EN 300 392-12: "Supplementary services stage 3";**
 - ETSI EN 300 392-12-1: "Call Identification (CI)";
 - ETSI ETS 300 392-12-2: "Call Report (CR)";
 - ETSI EN 300 392-12-3: "Talking Party Identification (TPI)";
 - ETSI EN 300 392-12-4: "Call Forwarding (CF)";**
 - ETSI ETS 300 392-12-5: "List Search Call (LSC)";
 - ETSI EN 300 392-12-6: "Call Authorized by Dispatcher (CAD)";
 - ETSI ETS 300 392-12-7: "Short Number Addressing (SNA)";
 - ETSI EN 300 392-12-8: "Area Selection (AS)";
 - ETSI ETS 300 392-12-9: "Access Priority (AP)";
 - ETSI EN 300 392-12-10: "Priority Call (PC)";
 - ETSI ETS 300 392-12-11: "Call Waiting (CW)";
 - ETSI EN 300 392-12-12: "Call Hold (HOLD)";

ETSI EN 300 392-12-13: "Call Completion to Busy Subscriber (CCBS)";
 ETSI EN 300 392-12-14: "Late Entry (LE)";
 ETSI EN 300 392-12-16: "Pre-emptive Priority Call (PPC)";
 ETSI EN 300 392-12-17: "Include Call (IC)";
 ETSI EN 300 392-12-18: "Barring of Outgoing Calls (BOC)";
 ETSI EN 300 392-12-19: "Barring of Incoming Calls (BIC)";
 ETSI EN 300 392-12-20: "Discreet Listening (DL)";
 ETSI EN 300 392-12-21: "Ambience Listening (AL)";
 ETSI EN 300 392-12-22: "Dynamic Group Number Assignment (DGNA)";
 ETSI EN 300 392-12-23: "Call Completion on No Reply (CCNR)";
 ETSI EN 300 392-12-24: "Call Retention (CRT)";

ETSI EN 300 392-13: "SDL model of the Air Interface (AI)";

ETSI EN 300 392-14: "Protocol Implementation Conformance Statement (PICS) proforma specification";

ETSI TS 100 392-15: "TETRA frequency bands, duplex spacings and channel numbering";

ETSI TS 100 392-16: "Network Performance Metrics";

ETSI TR 100 392-17: "TETRA V+D and DMO specifications";

ETSI TS 100 392-18: "Air interface optimized applications".

NOTE 1: Part 3, sub-parts 6 and 7 (Speech format implementation), part 4, sub-part 3 (Data networks gateway), part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

NOTE 2: Some parts are also published as Technical Specifications such as TS 100 392-2 and those may be the latest version of the document.

National transposition dates

Date of adoption of this EN:	12 July 2016
Date of latest announcement of this EN (doa):	31 October 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2017
Date of withdrawal of any conflicting National Standard (dow):	30 April 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The supplementary service stage 3 description is preceded by the stage 1 [2] and the stage 2 [3] description of the service, according to the method described in Recommendation ITU-T I.130 [i.4]. The stage 1 description specifies the service from the user's point of view. The stage 2 description identifies the functional capabilities of each SS and the information flows needed to support the supplementary service as specified in its stage 1 description. The present stage 3 description specifies the protocols at the air interface and at the various Inter-System Interfaces (ISI) to support each Supplementary Service.

NOTE: According to Recommendation ITU-T I.130 [i.4], the stage 3 description of any telecommunication service addresses the network implementation aspects. Consequently it comprises two steps: the specifications of all protocols at the various reference points involved in any of the service procedures (notably the service operation) are the first step of the stage 3 description, and the specifications of the functions of the corresponding network entities are its second step. The latter have not been provided since they can be derived from the specification of the functional entity actions in the stage 2 description.

The present document adds parameterisation functionality for a later activation.

1 Scope

The present document specifies the stage 3 description of the Supplementary Services CFU Call Forwarding Unconditional, CFB Call Forwarding on Busy, CFNRy Call Forwarding on No Reply and CFNRc Call Forwarding on Not Reachable for the Terrestrial Trunked Radio (TETRA).

SS-CFU, SS-CFB, SS-CFNRy and SS-CFNRc are supplementary services which allow a served user to have a TETRA network send all or specific incoming calls addressed to the served user's TETRA number to another number.

Man-Machine Interface and charging principles are outside the scope of the present document.

The present document is applicable to Voice plus Data individual call or group call; some parts of the present document are applicable to SDS (Short Data Service); more specifically to the following entities:

- the MS of either the calling user or the called user during an individual call or a group call;
- the originating Switching and Management Infrastructure (SwMI) in an individual call or a group call;
- the group controlling SwMI for a group call;
- the terminating SwMI in an individual call;
- the interworking SwMI for an individual call.

The present document is based on the latest version of ECMA-174 [i.1]. Contrary to ECMA-174 [i.1], the present document does not define Call Deflection supplementary service and the present document distinguishes between the case of No Reply and the case of Not Reachable. Moreover, the present document defines the protocol in cases of group calls and of mobility not covered by ECMA-174 [i.1].

The present document also specifies additional signalling protocol requirements for the support of interactions at the ISI reference point, other supplementary services and ANFs. The present document is applicable to SwMIs that can interconnect to form a TETRA network.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [2] ETSI EN 300 392-10-4: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 4: Call Forwarding (CF)".
- [3] ETSI EN 300 392-11-4: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 11: Supplementary services stage 2; Sub-part 4: Call Forwarding (CF)".
- [4] ETSI EN 300 392-9: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".