

ETSI TS 123 228 V13.7.0 (2016-10)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
IP Multimedia Subsystem (IMS);
Stage 2
(3GPP TS 23.228 version 13.7.0 Release 13)**



Reference

RTS/TSGS-0223228vd70

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	14
1 Scope	15
2 References	15
3 Definitions, symbols and abbreviations	19
3.1 Definitions	19
3.2 Symbols	21
3.3 Abbreviations	22
4 IP multimedia subsystem concepts.....	23
4.0 General	23
4.1 Relationship to CS domain and the IP-Connectivity Access Network.....	24
4.2 IMS services concepts	25
4.2.1 Home-network based services	25
4.2.1.1 Support of CAMEL or IN	25
4.2.1.2 Support of OSA.....	25
4.2.1.3 Dynamic services interactions handling	25
4.2.1.3.1 Service information exchanged between Application Servers	25
4.2.1.3.2 Handling by the Application Server	25
4.2.1.3.3 Deletion of services interaction information	25
4.2.2 Support of numbers in non-international format in the IMS	26
4.2.3 Support of roaming users	26
4.2.4 IP multimedia Subsystem Service Control Interface (ISC)	28
4.2.4.a HSS to service platform Interface	30
4.2.4.b S-CSCF Service Control Model.....	32
4.2.4.c I-CSCF to AS reference point (Ma).....	33
4.2.5 The QoS requirements for an IM CN subsystem session.....	34
4.2.6 QoS Requirements for IM CN subsystem signalling.....	35
4.2.7 Support of SIP forking.....	36
4.2.7.1 SIP Forking	36
4.2.7.2 Forking within and outside the IM CN Subsystem	36
4.2.7.3 Support for forked requests	37
4.3 Naming and addressing concepts	37
4.3.1 Address management.....	37
4.3.2 Void	37
4.3.3 Identification of users	37
4.3.3.0 General.....	37
4.3.3.1 Private User Identities	37
4.3.3.2 Public User Identities	38
4.3.3.2.a Globally Routable User Agent URI (GRUU)	39
4.3.3.2.a.1 Architecture Requirements	39
4.3.3.2.b Wildcarded Public User Identity	40
4.3.3.3 Routing of SIP signalling within the IP multimedia subsystem	40
4.3.3.3.a Handling of dialled number formats	41
4.3.3.3.b Termination of session with the TEL URI format Public User Identity.....	41
4.3.3.4 Relationship of Private and Public User Identities.....	41
4.3.3.5 Relationship of Public User Identities, GRUUs, and UEs	42
4.3.4 Identification of network nodes	43
4.3.5 E.164 address to SIP URI resolution in an IM CN subsystem.....	43
4.3.5.1 ENUM/DNS translation mechanism.....	43
4.3.5.2 Handling of Tel URIs.....	43
4.3.5.3 Handling of SIP URIs representing a telephone number	44

4.3.6	Public Service Identities	44
4.4	Signalling concepts.....	44
4.5	Mobility related concepts	45
4.6	Roles of Session Control Functions	46
4.6.0	General.....	46
4.6.1	Proxy-CSCF.....	46
4.6.2	Interrogating-CSCF	47
4.6.2.0	General.....	47
4.6.2.1	Void.....	47
4.6.3	Serving-CSCF.....	47
4.6.4	Breakout Gateway Control Function	49
4.6.5	Void	50
4.7	Multimedia Resource Function	50
4.7a	Media Resource Broker.....	51
4.8	Security Concepts.....	51
4.9	Charging Concepts	51
4.10	IMS group management concepts	52
4.10.0	General.....	52
4.10.1	IMS group administration	52
4.10.2	Group identifiers	52
4.11	Relationship to 3GPP Generic User Profile (GUP).....	52
4.12	Network Address Translation traversal in access network	52
4.13	Identification of IMS communication Services.....	52
4.13.1	General.....	52
4.13.2	Identification of IMS communication Services	52
4.13.3	Identification of IMS applications	54
4.14	Border Control concepts.....	55
4.15	IMS in transit network scenarios	56
4.15.1	General concepts.....	56
4.15.2	IMS transit network configurations	56
4.15.3	Providing IMS application services in transit network scenarios	57
4.15a	Roaming Architecture for Voice over IMS with Local Breakout.....	57
4.16	Support of multimedia telephony	58
4.16.1	Telephony Application Server	58
4.16.2	Identification of multimedia telephony	58
4.16.3	Session setup principles.....	58
4.17	Support of short message service	59
4.17.1	IP Short Message Gateway (IP-SM-GW).....	59
4.18	Support of Number portability	59
4.18.1	Number portability.....	59
4.19	Support of Preferred Circuit Carrier Access and Per Call Circuit Carrier Selection	60
4.19.1	Preferred Circuit Carrier Access and Per Call Circuit Carrier Selection	60
4.20	Support of IMS Service Centralization and Continuity.....	60
4.21	Support of Overlap Signalling.....	60
4.22	Support of Explicit Congestion Notification (ECN)	60
4.22.1	General.....	60
4.22.2	CS GERAN/UTRAN Interworking at MGCF/IM-MGW	61
4.22.3	Interworking with non-ECN IP network and/or terminal at IBCF/TrGW	61
4.22.4	Interworking with non-3GPP ECN IP terminal at IBCF/TrGW	62
4.22.5	ECN support at IMS-ALG/IMS-AGW	62
4.22.6	ECN support at MRFC/MRFP	63
4.22.7	CS GERAN/UTRAN Interworking at the MSC Server enhanced for ICS/MSC Server enhanced for SRVCC with SIP/CS-MGW	63
4.23	Support of Load Balancing.....	63
4.23.1	General.....	63
4.23.2	Registration-based load balancing of S-CSCFs	63
4.23.3	Registration independent load balancing of Transit Functions	64
4.24	Support of Restoration Procedures	64
4.25	Support of Overload Control	64
4.25.1	General.....	64
4.25.2	Next-hop monitoring of overload	64
4.25.3	Filter based Overload Control.....	65

4.26	Support for Business Trunking	65
5	IP multimedia subsystem procedures	65
5.0	General	65
5.0a	Session-unrelated procedures	66
5.1	CSCF related procedures	66
5.1.0	Establishing IP-Connectivity Access Network bearer for IM CN Subsystem Related Signalling	66
5.1.1	Procedures related to Proxy-CSCF discovery	66
5.1.1.0	General	66
5.1.1.1	DHCP/DNS procedure for P-CSCF discovery	66
5.1.1.2	Void	67
5.1.2	Procedures related to Serving-CSCF assignment	67
5.1.2.1	Assigning a Serving-CSCF for a user	67
5.1.2.2	Cancelling the Serving-CSCF assignment	68
5.1.2.3	Void	68
5.1.3	Procedures related to Interrogating-CSCF	68
5.1.4	Procedures related to Proxy-CSCF	69
5.1.5	Subscription Updating Procedures	69
5.1.5.0	General	69
5.1.5.1	Subscription updating information flow	69
5.2	Application level registration procedures	69
5.2.0	General	69
5.2.1	Requirements considered for registration	69
5.2.1a	Implicit Registration	70
5.2.1a.0	General	70
5.2.1a.1	Implicit Registration for UE without ISIM or IMC	72
5.2.2	Registration flows	72
5.2.2.1	Requirements to consider for registration	72
5.2.2.2	Assumptions	72
5.2.2.3	Registration information flow – User not registered	73
5.2.2.4	Re-Registration information flow – User currently registered	74
5.2.2.5	Stored information	76
5.3	Application level de-registration procedures	77
5.3.1	Mobile initiated de-registration	77
5.3.2	Network initiated de-registration	78
5.3.2.0	General	78
5.3.2.1	Network Initiated Application (SIP) De-registration, Registration Timeout	79
5.3.2.2	Network Initiated Application (SIP) De-registration, Administrative	79
5.3.2.2.0	General	79
5.3.2.2.1	Network Initiated De-registration by HSS, administrative	80
5.3.2.2.2	Network Initiated De-registration by Service Platform	80
5.4	Procedures for IP multi-media sessions	82
5.4.0	General	82
5.4.1	Bearer interworking concepts	82
5.4.2	Interworking with Internet	82
5.4.2a	IP version interworking	82
5.4.3	Interworking with PSTN	83
5.4.4	Requirements for IP multi-media session control	84
5.4.5	Session Path Information	84
5.4.5.1	Session Path Information during Registration and Session Initiation	84
5.4.5.2	P-CSCF in the Session Path	84
5.4.5.3	S-CSCF in the Session Path	85
5.4.6	End-user preferences and terminal capabilities	85
5.4.6.0	General	85
5.4.6.1	Objectives	85
5.4.6.2	End-user expectations	85
5.4.6.3	Mechanism for bearer establishment	86
5.4.6.4	Session progress indication to the originating UE	88
5.4.7	Interaction between QoS and session signalling	88
5.4.7.0	General	88
5.4.7.1	Authorize QoS Resources	89
5.4.7.1a	Resource Reservation with Policy and Charging Control	89

5.4.7.2	Enabling of Media Flows	89
5.4.7.3	Disabling of Media Flows	90
5.4.7.4	Revoke Authorization for IP-Connectivity Access Network and IP Resources.....	90
5.4.7.5	Indication of IP-Connectivity Access Network bearer release.....	90
5.4.7.6	Authorization of IP-Connectivity Access Network bearer modification.....	90
5.4.7.7	Indication of IP-Connectivity Access Network bearer modification	91
5.4.7.8	Sharing of Resources for Network Detected Concurrent Sessions	91
5.4.7.8.1	Network Detected Concurrent Sessions	91
5.4.7.8.2	Initiating Resource Sharing For Network Detected Concurrent Sessions	91
5.4.7.8.3	Void.....	91
5.4.7.9	Priority sharing for concurrent sessions	92
5.4.8	QoS-Assured Preconditions	92
5.4.9	Event and information distribution	93
5.4.9.0	General	93
5.4.9.1	Subscription to event notifications	94
5.4.10	Void	96
5.4.11	Signalling Transport Interworking.....	96
5.4.12	Configuration and Routing principles for Public Service Identities	96
5.4.12.0	General	96
5.4.12.1	PSIs on the originating side.....	96
5.4.12.2	PSIs on the terminating side.....	96
5.4.12.3	Subdomain based PSIs	97
5.4.12.4	PSI configuration in the HSS	97
5.4.12.5	Requests originated by the AS hosting the PSI.....	97
5.4.13	Transcoding concepts	98
5.4a	Overview of session flow procedures.....	98
5.4a.1	End-to-End session flow procedures	98
5.4a.2	Transit network session flow procedures.....	101
5.5	Serving-CSCF/MGCF to serving-CSCF/MGCF procedures	103
5.5.0	General.....	103
5.5.1	(S-S#1) Different network operators performing origination and termination	103
5.5.2	(S-S#2) Single network operator performing origination and termination	105
5.5.3	(S-S#3) Session origination with PSTN termination in the same network as the S-CSCF	108
5.5.4	(S-S#4) Session origination with PSTN termination in a different network from the S-CSCF	110
5.6	Origination procedures	112
5.6.0	General.....	112
5.6.1	(MO#1) Mobile origination, roaming	112
5.6.2	(MO#2) Mobile origination, home	115
5.6.3	(PSTN-O) PSTN origination.....	117
5.6.4	(NI-O) Non-IMS Origination procedure from an external SIP client.....	118
5.6.5	Application Server Origination Procedure.....	120
5.6.5.1	(AS-O) Origination at Application Server	120
5.6.5.2	Void.....	122
5.6.5.3	S-CSCF selection by I-CSCF for AS Originating call procedures.....	122
5.7	Termination procedures.....	124
5.7.0	General.....	124
5.7.1	(MT#1) Mobile termination, roaming.....	124
5.7.2	(MT#2) Mobile termination, home	127
5.7.2a	(MT#3) Mobile termination, CS Domain roaming	129
5.7.3	(PSTN-T) PSTN termination	129
5.7.4	(NI-T) Non-IMS Termination to an external SIP client.....	131
5.7.5	(AS-T#1) PSI based Application Server termination – direct.....	133
5.7.6	(AS-T#2) PSI based Application Server termination – indirect.....	133
5.7.7	(AS-T#3) PSI based Application Server termination – DNS routing	134
5.7.8	(AS-T#4) Termination at Application Server based on service logic	135
5.7a	Procedures for the establishment of sessions without preconditions.....	136
5.7a.1	General.....	136
5.7a.2	Procedures for the establishment of sessions without preconditions - no resource reservation required before session becomes active	138
5.7a.3	Void	140
5.8	Procedures related to routing information interrogation.....	140
5.8.0	General.....	140

5.8.1	User identity to HSS resolution	140
5.8.2	SLF on register	141
5.8.3	SLF on UE invite	142
5.8.4	SLF on AS access to HSS	143
5.9	Routing of mid-session signalling	143
5.10	Session release procedures	144
5.10.0	General.....	144
5.10.1	Terminal initiated session release	144
5.10.2	PSTN initiated session release	146
5.10.3	Network initiated session release.....	147
5.10.3.0	Removal of IP-CAN bearers used to transport IMS SIP signalling	147
5.10.3.1	Network initiated session release - P-CSCF initiated.....	147
5.10.3.1.0	General	147
5.10.3.1.1	Network initiated session release - P-CSCF initiated – after removal of IP-Connectivity Access Network bearer	148
5.10.3.1.2	Void.....	149
5.10.3.2	Network initiated session release - S-CSCF Initiated	149
5.11	Procedures to enable enhanced multimedia services	150
5.11.1	Session Hold and Resume Procedures	150
5.11.1.0	General	150
5.11.1.1	Mobile-to-Mobile Session Hold and Resume Procedures.....	150
5.11.1.2	Mobile-initiated Hold and Resume of a Mobile-PSTN Session.....	152
5.11.1.3	PSTN-initiated Hold and Resume of a Mobile-PSTN Session	154
5.11.2	Procedures for anonymous session establishment	156
5.11.2.0	General	156
5.11.2.1	Signalling requirements for anonymous session establishment	156
5.11.2.2	Bearer path requirements for anonymous session establishment	156
5.11.3	Procedures for codec and media characteristics flow negotiations	156
5.11.3.0	General	156
5.11.3.1	Codec and media characteristics flow negotiation during initial session establishment	157
5.11.3.2	Codec or media characteristics flow change within the existing reservation	160
5.11.3.3	Codec or media characteristics flow change requiring new resources and/or authorization	161
5.11.3.4	Sample MM session flow - addition of another media.....	164
5.11.4	Procedures for providing or blocking identity	167
5.11.4.0	General	167
5.11.4.1	Procedures for providing the authenticated identity of the originating party	167
5.11.4.2	Procedures for blocking the identity of the originating party.....	169
5.11.4.3	Procedures for providing the authenticated identity of the originating party (PSTN origination)	170
5.11.4.4	Procedures for providing the authenticated identity of the originating party (PSTN termination)	170
5.11.5	Session Redirection Procedures	170
5.11.5.0	General	170
5.11.5.1	Session Redirection initiated by S-CSCF to IMS.....	170
5.11.5.2	Session Redirection to PSTN Termination (S-CSCF #2 forwards INVITE)	171
5.11.5.2a	Session Redirection to PSTN Termination (REDIRECT to originating UE#1).....	172
5.11.5.3	Session Redirection initiated by S-CSCF to general endpoint (REDIRECT to originating UE#1)....	174
5.11.5.4	Session Redirection initiated by P-CSCF.....	175
5.11.5.5	Session Redirection initiated by UE.....	176
5.11.5.6	Session Redirection initiated by originating UE#1 after Bearer Establishment (REDIRECT to originating UE#1)	177
5.11.6	Session Transfer Procedures	178
5.11.6.0	General	178
5.11.6.1	Refer operation.....	178
5.11.6.2	Application to Session Transfer Services	180
5.11.6.2.0	General	180
5.11.6.2.1	Blind Transfer and Assured Transfer	180
5.11.6.2.2	Consultative Transfer	181
5.11.6.2.3	Three-way Session.....	181
5.12	Mobile Terminating call procedures to unregistered Public User Identities	182
5.12.0	General.....	182
5.12.1	Mobile Terminating call procedures to unregistered Public User Identity that has services related to unregistered state	182

5.12.2	Mobile Terminating call procedures to unregistered Public User Identity that has no services related to unregistered state	184
5.13	IMS Emergency Sessions	184
5.14	Interactions involving the MRFC/MRFP	184
5.14.0	General.....	184
5.14.1	Interactions between the UE and the MRFC.....	184
5.14.2	Service control based interactions between the MRFC and the AS	185
5.14.3	Interactions for services using both the Ut interface and MRFC capabilities.....	185
5.14.4	Transcoding services involving the MRFC/MRFP	185
5.15	Mobile Terminating session procedure for unknown user	186
5.15.0	General.....	186
5.15.1	Unknown user determined in the HSS	186
5.15.2	Unknown user determined in the SLF	187
5.16	IMS messaging concepts and procedures.....	187
5.16.0	General.....	187
5.16.1	Immediate Messaging	187
5.16.1.0	General	187
5.16.1.1	Procedures to enable Immediate Messaging	188
5.16.1.1.0	General	188
5.16.1.1.1	Immediate messaging procedure to registered Public User Identity.....	188
5.16.1.1.2	Immediate messaging procedure to unregistered Public User Identity.....	189
5.16.1.2	Immediate messages with multiple recipients	190
5.16.2	Session-based Messaging	190
5.16.2.0	General	190
5.16.2.1	Architectural principles	190
5.16.2.2	Procedures to enable Session based Messaging	191
5.16.2.2.0	General	191
5.16.2.2.1	Session based messaging procedure to registered Public User Identity	191
5.16.2.2.2	Session based messaging procedure using multiple UEs	192
5.16.2.2.3	Session based messaging procedure with an intermediate node.....	195
5.16.2.2.4	Session based messaging release procedure	196
5.16.2.2.5	Session based messaging release procedure with an intermediate node.....	197
5.17	Refreshing sessions	197
5.18	Void.....	198
5.19	Support for Transit scenarios in IMS	198
5.19.1	General.....	198
5.19.2	Providing IMS application services in transit network scenarios	201
5.20	Procedures for Assigning, Using, and Processing GRUUs	201
5.20.1	UE.....	201
5.20.1.1	Obtaining a GRUU during registration	201
5.20.1.2	Using a GRUU	202
5.20.1.3	Using a GRUU while requesting Privacy.....	202
5.20.2	Serving-CSCF.....	202
5.20.2.1	Allocating a GRUU during registration	202
5.20.2.2	Using a GRUU	202
5.20.3	Interrogating-CSCF	203
5.20.3a	HSS	203
5.20.4	Elements other than UE acting as a UA.....	203
5.20.4.1	Using a GRUU	203
5.20.4.2	Assigning a GRUU	203
5.21	IMS Multimedia Priority Services Procedures	203
5.22	Support of Overload Control	204
5.22.1	Next-hop monitoring of overload	204
5.22.2	Filter based Overload Control.....	205
Annex A (Informative):	Information flow template	206
Annex B (Informative):	Void	208
Annex C (Informative):	Void	209
Annex D (Informative):	Void	210

Annex E (Normative):	IP-Connectivity Access Network specific concepts when using GPRS and/or EPS to access IMS	211
E.0	General	211
E.1	Mobility related concepts	211
E.1.0	General	211
E.1.1	Procedures for P-CSCF discovery	211
E.1.1.0	General.....	211
E.1.1.1	GPRS/EPS procedure for P-CSCF discovery	212
E.2	QoS related concepts	213
E.2.1	Application Level Signalling for IMS	213
E.2.1.0	General.....	213
E.2.1.1	QoS Requirements for Application Level Signalling	213
E.2.1.2	Requirements for IM CN subsystem signalling flag	214
E.2.1.3	Application Level Signalling support for IMS services	214
E.2.1a	PDP context/EPS Bearer procedures for IMS	215
E.2.1a.1	Establishing PDP Context/EPS bearer for IM CN Subsystem Related Signalling	215
E.2.1a.2	Deletion of PDP Context/EPS bearer used to transport IMS SIP signalling.....	216
E.2.2	The QoS requirements for an IM CN subsystem session	216
E.2.2.0	General.....	216
E.2.2.1	Relation of IMS media components and PDP contexts/EPS bearers carrying IMS media	217
E.2.3	Interaction between GPRS/EPS QoS and session signalling.....	217
E.2.3.0	General.....	217
E.2.3.1	Resource Reservation with Policy and Charging Control.....	217
E.2.4	Network initiated session release - P-CSCF initiated	218
E.2.4.0	General.....	218
E.2.4.1	Network initiated session release - P-CSCF initiated after loss of radio coverage	219
E.3	Address and identity management concepts.....	220
E.3.1	Deriving IMS identifiers from the USIM	220
E.4	Void.....	221
E.5	IP version interworking in IMS	221
E.6	Usage of NAT in GPRS/EPS	221
E.7	Retrieval of Network Provided Location Information in GPRS/EPS	221
E.8	Geographical Identifier.....	222
E.9	Support for Paging policy differentiation for IMS services	222
Annex F (Informative):	Routing subsequent requests through the S-CSCF	223
Annex G (Normative):	Reference Architecture and procedures when the NAT is invoked between the UE and the IMS domain	224
G.1	General	224
G.1.1	General requirements	224
G.2	Reference models	224
G.2.1	IMS-ALG and IMS Access Gateway model.....	225
G.2.2	ICE and Outbound reference model.....	225
G.3	Network elements for employing the IMS-ALG and IMS Access Gateway	226
G.3.1	Required functions of the P-CSCF	226
G.3.2	Required functions of the IMS Access Gateway	226
G.3.3	Iq reference point.....	227
G.4	Procedures for employing the IMS-ALG and IMS Access Gateway.....	227
G.4.1	General	227
G.4.2	NAT detection in P-CSCF.....	227
G.4.3	Session establishment procedure	227
G.4.4	Session release procedure.....	229

G.4.5	Session modification	229
G.4.6	Media forwarding in the IMS Access Gateway.....	229
G.5	Network elements for employing NAT Traversal for ICE and Outbound.....	230
G.5.1	General requirements	230
G.5.2	ICE	230
G.5.2.1	Overview	230
G.5.2.2	Required functions of the UE	231
G.5.2.3	Required functions of the STUN relay server.....	231
G.5.2.4	Required functions of the STUN server.....	231
G.5.3	Outbound.....	232
G.5.3.1	Overview	232
G.5.3.2	Required functions of the P-CSCF	232
G.5.3.3	Required functions of the S-CSCF	232
G.5.3.4	Required functions of the UE	232
G.6	Procedures for employing ICE and Outbound	233
G.6.1	Flow establishment procedures	233
G.6.2	Session establishment procedures	234
G.6.3	Session release procedures	236
G.6.4	Session modification procedures	237
G.6.5	Policy and Charging Control procedures.....	237
G.6.6	Detection of NAT Traversal support.....	238
G.6.7	Procedures at other IMS entities processing SDP	238
Annex H (Informative):	Example HSS deployment.....	239
Annex I (Normative):	Border Control Functions	240
I.1	General	240
I.2	Overall architecture	240
I.3	Border Control Functions.....	241
I.3.1	IP version interworking	241
I.3.1.1	Originating Session Flows towards IPv4 SIP network	241
I.3.1.2	Terminating Session Flows from IPv4 SIP network.....	243
I.3.2	Configuration independence between operator networks.....	244
I.3.3	Transcoding Support for Interworking	244
I.3.3.1	General.....	244
I.3.3.2	Session Flows	245
I.3.3.2.1	Proactive transcoding support.....	245
I.3.3.2.2	Reactive transcoding support	247
Annex J (Informative):	Dynamic User Allocation to the Application Servers	250
J.1	General	250
J.2	Representative AS	250
J.2.1	Concept of Representative AS.....	250
J.2.2	Procedures related to Representative AS.....	251
J.3	Dynamic assignment of AS by S-CSCF caching	251
J.3.1	Concept of Dynamic assignment of AS by S-CSCF caching	251
J.3.2	Procedures related to Dynamic assignment of AS by S-CSCF caching	252
Annex K (Normative):	Inter-IMS Network to Network Interface between two IM CN subsystem networks	253
K.1	General	253
K.2	Overall architecture	253
Annex L (Normative):	Aspects for use of Common IMS in 3GPP2 systems.....	254
L.1	General	254

L.2	Definitions	254
L.2.1	HSS	254
L.3	Mobility related concepts when using 3GPP2 Packet Data Subsystem	254
L.3.1	General	254
L.3.2	Procedures for P-CSCF discovery	255
L.4	QoS related concepts when using 3GPP2 Packet Data Subsystem	255
L.5	IP version support in IMS when using 3GPP2 Packet Data Subsystem	255
L.6	Address and identity management concepts.....	255
L.6.1	Deriving IMS identifiers	255
L.7	Relationship to 3GPP Generic User Profile (GUP).....	256
Annex M (Informative):	IMS Local Breakout	257
M.1	P-CSCF located in visited network	257
M.1.1	Description	257
M.1.1.0	General.....	257
M.1.1.1	Architecture	257
M.1.1.2	Flow for originating session	257
M.2	P-CSCF located in home network	259
M.2.1	Description	259
M.2.1.0	General.....	259
M.2.1.1	Architecture	259
M.2.1.2	Flow for originating session	259
M.2.2	Address assignment.....	261
M.2.3	IPv4 - IPv6 interworking.....	261
M.2.4	NAT traversal.....	261
M.3	P-CSCF located in visited network and with VPLMN loopback possibility	261
M.3.1	Description	261
M.3.1.1	General.....	261
M.3.1.2	Architecture	261
M.3.1.3	Flow for originating session with VPLMN routing	262
M.3.1.4	Flow for originating session with Home routing	263
M.3.2	Interaction with SRVCC and ICS.....	264
Annex N (Normative):	Aspects for use of Common IMS in Fixed xDSL, Fiber and Ethernet based systems	265
N.1	Origination procedures	265
N.1.1	(FO#1) Fixed xDSL origination, home	265
N.2	Termination procedures.....	267
N.2.1	(FT#1) Fixed xDSL termination, home	267
N.3	Geographical Identifier.....	268
Annex P (Informative):	Transcoding Support involving the MRFC/MRFP	269
P.1	General	269
P.1.1	Scope	269
P.1.2	Description	269
P.1.3	Session flows	269
P.1.3.1	General.....	269
P.1.3.2	Proactive transcoding invocation	270
P.1.3.3	Reactive transcoding invocation	271
Annex Q (Normative):	Optimal media routing	274
Q.1	General	274
Q.2	Procedures and flows.....	275

Q.2.1	SDP extension	275
Q.2.2	General IMS-ALG procedures	275
Q.2.3	Common flows	277
Q.2.3.1	IMS-ALG allocates a TrGW	277
Q.2.3.2	IMS-ALG does not allocate a TrGW	277
Q.2.3.3	IMS-ALG bypasses its TrGW and one or more prior TrGWs	277
Q.2.3.4	IMS-ALG bypasses its TrGW using secondary realm from prior IMS-ALG	279
Q.2.3.5	IMS-ALG bypasses one or more prior TrGWs using a secondary realm	280
Q.2.3.6	IMS-ALG bypasses TrGWs performing NAT traversal	281
Q.2.5	Flows with transcoding	282
Q.2.5.1	Proactive transcoding where transcoding is required	282
Q.2.5.2	Proactive transcoding where transcoding not required	282
Q.2.5.3	IMS-ALG bypasses prior unrequired proactive transcoder	284
Q.2.5.4	IMS-ALG bypasses its TrGW and prior unrequired proactive transcoder	285
Q.2.5.5	IMS-ALG replaces prior proactive transcoder	287
Q.2.5.6	Proactive transcoding without resource reservation	288
Q.2.5.7	Reactive transcoding	288
Q.3	Charging	288

Annex R (Informative): Distribution of Network Provided Location Information within IMS....289

R.1	General	289
R.2	Session Establishment/Modification at Mobile Origination - Location Info in Request	289
R.3	Session Establishment/Modification at Mobile Origination - Location Info in Response	291
R.4	Session Establishment/Modification at Mobile Termination	292
R.5	Session Establishment/Modification - Location Information Distributed by IMS AS	293
R.6	Session Release	294

Annex S (Normative): Business Trunking295

S.1	General	295
S.2	IP-PBXs using static mode Business Trunking	295
S.2.1	High level architecture	295
S.2.2	High level Flows	296
S.2.2.1	General	296
S.2.2.2	Originating procedures	296
S.2.2.2.1	Originating procedures using the S-CSCF	296
S.2.2.2.2	Originating procedures using the Transit Function	297
S.2.2.3	Terminating Procedures	298
S.2.2.3.1	Terminating procedures using the S-CSCF	298
S.2.2.3.2	Terminating procedures using the Transit Function	300

Annex T (Normative): IP-Connectivity Access Network specific concepts when using Trusted WLAN (TWAN) to access IMS301

T.0	General	301
T.1	Retrieval of Network Provided Location Information in TWAN access	301

Annex U (Normative): WebRTC access to IMS - network-based architecture302

U.1	Overview	302
U.1.0	General	302
U.1.1	Assumptions	302
U.1.2	Architecture and reference model	303
U.1.3	Functional entities	303
U.1.3.1	WIC (WebRTC IMS Client)	303
U.1.3.2	WWSF (WebRTC Web Server Function)	303
U.1.3.3	eP-CSCF (P-CSCF enhanced for WebRTC)	304
U.1.3.4	eIMS-AGW (IMS Access GateWay enhanced for WebRTC)	304

U.1.3.5	WAF (WebRTC Authorisation Function).....	305
U.1.4	Reference points	305
U.1.4.1	W1 (UE to WWSF).....	305
U.1.4.2	W2 (UE to eP-CSCF)	305
U.1.4.3	Iq (eP-CSCF to eIMS-AGW).....	305
U.1.4.4	W3 (UE to eIMS-AGW).....	305
U.1.4.5	W4 (WWSF to WAF)	306
U.1.5	Media plane protocol architecture	306
U.1.5.0	General.....	306
U.1.5.1	Protocol architecture for MSRP	306
U.1.5.2	Protocol architecture for BFCP.....	306
U.1.5.3	Protocol architecture for T.140	307
U.1.5.4	Protocol architecture for Voice and Video	307
U.2	Procedures	308
U.2.1	Registration	308
U.2.1.1	Introduction.....	308
U.2.1.2	WIC registration of individual Public User Identity using IMS authentication	308
U.2.1.3	WIC registration of individual Public User Identity based on web authentication	309
U.2.1.4	WIC registration of individual Public User Identity from a pool of Public User Identities.....	310
U.2.2	Session management related procedures	310
U.2.3	De-Registration procedures	310
U.2.4	Media plane Optimization	310
Annex V (Normative):	IP-Connectivity Access Network specific concepts when using Untrusted WLAN to access IMS	313
V.1	General	313
V.2	UE Provided Access Information in Untrusted WLAN access	313
Annex V (Informative):	Change history	314
	History	315

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

This document defines the stage-2 service description for the IP Multimedia Core Network Subsystem (IMS), which includes the elements necessary to support IP Multimedia (IM) services. ITU-T Recommendation I.130 [4] describes a three-stage method for characterisation of telecommunication services, and ITU-T Recommendation Q.65 [3] defines stage 2 of the method.

This document does not cover the Access Network functionality except as they relate to provision of IM services, these aspects are covered in the normative Annex E.

This document identifies the mechanisms to enable support for IP multimedia applications. In order to align IP multimedia applications wherever possible with non-3GPP IP applications, the general approach is to adopt non-3GPP specific IP based solutions.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 23.002: "Network Architecture".
- [2] CCITT Recommendation E.164: "Numbering plan for the ISDN era".
- [3] CCITT Recommendation Q.65: "Methodology – Stage 2 of the method for the characterisation of services supported by an ISDN".
- [4] ITU Recommendation I.130: "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [5] Void.
- [6] Void.
- [7] 3GPP TS 23.221: "Architectural Requirements".
- [8] 3GPP TS 22.228: "Service requirements for the IP multimedia core network subsystem".
- [9] 3GPP TS 23.207: "End-to-end QoS concept and architecture".
- [10] Void.
- [10a] 3GPP TS 24.229: "IP Multimedia Call Control based on SIP and SDP; Stage 3".
- [11] Void.
- [11a] 3GPP TS 29.207: "Policy control over Go interface".
- [12] IETF RFC 3261: "SIP: Session Initiation Protocol".
- [13] IETF RFC 3986: "Uniform Resource Identifiers (URI): Generic Syntax".
- [14] IETF RFC 4282: "The Network Access Identifier".
- [15] IETF RFC 3966: "The tel URI for Telephone Numbers".