

ETSI TS 129 213 V13.6.0 (2016-08)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
Policy and charging control signalling flows and Quality of
Service (QoS) parameter mapping
(3GPP TS 29.213 version 13.6.0 Release 13)**



Reference

RTS/TSGC-0329213vd60

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	9
1 Scope	10
2 References	10
3 Definitions and abbreviations.....	12
3.1 Definitions	12
3.2 Abbreviations	13
3a Reference architecture.....	13
4 Signalling Flows over Gx, Gxx, Rx, Sd, Sy, Np, Nt, St and S9.....	17
4.0 General	17
4.1 IP-CAN Session Establishment.....	18
4.2 IP-CAN Session Termination.....	22
4.2.1 UE-Initiated	22
4.2.1.1 AF located in the HPLMN	22
4.2.1.2 AF located in the VPLMN	25
4.2.2 PCEF-Initiated	27
4.2.2.1 AF located in the HPLMN	27
4.2.2.2 AF located in the VPLMN	29
4.2.3 PCRF-Initiated.....	30
4.2.3.1 AF located in the HPLMN	30
4.2.3.2 AF located in the VPLMN	32
4.3 IP-CAN Session Modification.....	34
4.3.1 Network-Initiated IP-CAN Session Modification.....	34
4.3.1.1 Interactions between BBERF, PCEF, TDF, OCS, TSSF and PCRF(PCC/QoS/ADC Rule Provisioning in PUSH mode).....	34
4.3.1.2 Interactions between PCRF, AF and SPR	39
4.3.1.2.1 AF Session Establishment	39
4.3.1.2.1.1 AF located in HPLMN	39
4.3.1.2.1.2 AF located in VPLMN	40
4.3.1.2.2 AF session modification	42
4.3.1.2.2.1 AF located in the VPLMN.....	43
4.3.1.2.3 AF session termination	45
4.3.2 PCEF –Initiated IP-CAN Session Modification (PCC Rule Provisioning in PULL Mode)	47
4.3.2.1 PCEF-initiated IP-CAN Session Modification. AF located in HPLMN	47
4.3.2.2 PCEF-initiated IP-CAN Session Modification, AF located in the VPLMN	52
4.4 Gateway Control Session Procedures.....	53
4.4.1 Gateway Control Session Establishment	54
4.4.2 Gateway Control and QoS Rules Request	58
4.4.2.1 Non-Roaming and Home Routed cases.....	58
4.4.2.2 Visited access cases.....	60
4.4.3 Gateway Control and QoS Rules Provision	61
4.4.4 Gateway Control Session Termination	62
4.4.4.1 BBERF-Initiated Gateway Control Session Termination	62
4.4.4.2 PCRF-Initiated Gateway Control Session Termination	64
4.5 Multiple BBERF Signalling Flows	65
4.5.1 Non-Roaming and Home Routed cases	65
4.5.1.1 New Gateway Control Session Establishment	65
4.5.1.2 PCEF IP-CAN session modification – Handover	68
4.5.1.3 PCEF IP-CAN session modification – S2c-based IP flow mobility	69
4.5.1.4 Gateway Control Session Establishment and PCEF IP-CAN session modification – S2c-based IP flow mobility	71

4.5.2	Visited access case.....	72
4.5.2.1	New Gateway Control Session Establishment	72
4.5.2.2	PCEF-Initiated IP-CAN session modification-Handover.....	74
4.5.2.3	PCEF-Initiated IP-CAN session modification - S2c-based IP flow mobility.....	76
4.5.2.4	Gateway Control Session Establishment and PCEF IP-CAN session modification – S2c-based IP flow mobility.....	78
4.6	Application Detection and Enforcement Procedures.....	80
4.6.1	TDF Session Establishment in case of solicited reporting.....	80
4.6.1A	TDF Session Establishment in case of unsolicited reporting.....	81
4.6.2	TDF Session termination	81
4.6.3	TDF Session modification	83
4.6.3.1	Application Detection, Reporting and Control Rules Request.....	83
4.6.3.2	Application Detection and Control Rules Provision	84
4.7	Spending limits Procedures over Sy reference point	85
4.7.1	Initial Spending Limit Report Request	85
4.7.2	Intermediate Spending Limit Report Request.....	85
4.7.3	Final Spending Limit Report.....	86
4.7.4	Spending Limit Report.....	87
4.8	Call flows for User Plane Congestion Management.....	87
4.8.1	General.....	87
4.8.2	RUCI reporting	88
4.8.2.1	Non-aggregated RUCI report procedure	88
4.8.2.2	Aggregated RUCI report procedure	88
4.8.3	Np reporting restriction provisioning.....	89
4.8.4	UE mobility between RCAFs	89
4.8.5	Removal of UE context.....	90
4.9	Traffic Steering Control Procedures over St reference point	90
4.9.1	St Session Establishment	90
4.9.2	St Session Modification	91
4.9.3	St Session Termination	92
4.9.4	St notification initiated by the TSSF.....	92
4.10	Negotiation for future background data transfer procedure over Nt reference point.....	93
5	Binding Mechanism	93
5.1	Overview	93
5.2	Session Binding.....	94
5.3	PCC Rule Authorization and QoS Rule Generation.....	95
5.4	Bearer Binding	96
6	QoS Parameters Mapping.....	97
6.1	Overview	97
6.1.1	UE-Initiated IP-CAN bearers.....	98
6.1.2	Network-Initiated IP-CAN bearers	100
6.2	QoS parameter mapping Functions at AF	101
6.3	QoS parameter mapping Functions at PCRF.....	108
6.4	QoS parameter mapping Functions at PCEF	115
6.4.1	GPRS	115
6.4.1.1	Authorized IP QoS parameters per PDP Context to Authorized UMTS QoS parameters mapping in GGSN.....	115
6.4.1.2	Comparing UMTS QoS Parameters against the Authorized UMTS QoS parameters in GGSN for UE initiated PDP context	117
6.4.2	3GPP- EPS.....	117
6.4.2.1	Authorized IP QoS parameters per PDP Context to Authorized UMTS QoS parameters mapping in P-GW	117
6.4.2.2	Comparing UMTS QoS Parameters against the Authorized UMTS QoS parameters in P-GW for UE initiated PDP context	119
6.5	QoS parameter mapping Functions at UE for a UE-initiated GPRS PDP Context	119
6.5.1	SDP to UMTS QoS parameter mapping in UE.....	121
6.5.2	SDP parameters to Authorized UMTS QoS parameters mapping in UE.....	121
7	PCRF addressing	125
7.1	General	125
7.2	DRA Definition	125

7.3	DRA Procedures.....	125
7.3.1	General.....	125
7.3.2	DRA Information Storage.....	125
7.3.3	Capabilities Exchange.....	126
7.3.4	Redirect DRA	126
7.3.4.1	Redirecting Diameter Requests.....	126
7.3.4.2	DRA binding removal	127
7.3.5	Proxy DRA	127
7.3.6	PCRF selection by BBERF/PCEF (non-roaming case)	127
7.3.7	PCRF selection by AF	128
7.3.8	PCRF selection in a roaming scenario	128
7.3.9	PCRF selection by TDF for unsolicited application reporting.....	129
7.3.10	PCRF selection by RCAF	129
7.4	DRA flows.....	129
7.4.1	Proxy DRA	129
7.4.1.1	Establishment of Diameter Sessions	129
7.4.1.1.1	Non-roaming cases	129
7.4.1.1.2	Roaming cases	130
7.4.1.2	Modification of Diameter Sessions	131
7.4.1.2.1	Non-roaming cases	131
7.4.1.2.1.1	Client-initiated.....	131
7.4.1.2.1.2	PCRF-initiated.....	132
7.4.1.2.2	Roaming cases	133
7.4.1.2.2.1	V-PCRF initiated.....	133
7.4.1.2.2.2	H-PCRF initiated	134
7.4.1.3	Termination of Diameter Sessions	135
7.4.1.3.1	Non-roaming cases	135
7.4.1.3.2	Roaming cases	136
7.4.2	Redirect DRA	137
7.4.2.1	Establishment of Diameter Sessions	137
7.4.2.1.1	Non-roaming cases	137
7.4.2.1.2	Roaming cases	138
7.4.2.2	Modification of Diameter sessions.....	139
7.4.2.3	Termination of Diameter Sessions	139
7.4.2.3.1	Non-roaming cases	139
7.4.2.3.2	Roaming cases	140
8	Diameter race condition handling	142
8.1	Overview	142
8.2	Procedures for Gx, Gxx, Sd and S9.....	142

Annex A (informative):	Examples of deriving the Maximum Authorized parameters from the SDP parameters	144
-------------------------------	---------------------------------------------------------------------------------------------	------------

Annex B (normative):	Signalling Flows for IMS.....	145
B.0	General	145
B.1	Subscription to Notification of Signalling Path Status at IMS Registration	145
B.1a	Subscription to Notification of Change of IP-CAN Type at IMS Registration.....	146
B.1b	Provisioning of SIP signalling flow information at IMS Registration	147
B.2	IMS Session Establishment.....	148
B.2.1	Provisioning of service information at Originating P-CSCF and PCRF	148
B.2.2	Provisioning of service information at terminating P-CSCF and PCRF	151
B.3	IMS Session Modification.....	155
B.3.1	Provisioning of service information	155
B.3.2	Enabling of IP Flows.....	159
B.3.3	Disabling of IP Flows.....	160
B.3.4	Media Component Removal.....	161
B.4	IMS Session Termination.....	162

B.4.1	Mobile initiated session release / Network initiated session release	162
B.4.2	IP-CAN Bearer Release/Loss	164
B.5	P-CSCF Restoration	165

Annex C (normative): NAT Related Procedures.....167

C.1	Support for media traversal of NATs using ICE	167
C.2	P-CSCF procedures	167
C.2.1	General	167
C.2.2	Deriving the Ues IP address	168
C.2.3	Deriving flow descriptions	168
C.2.4	Gating control.....	168
C.2.5	Bandwidth impacts	168
C.3	PCRF procedures.....	169
C.3.1	General	169
C.3.2	Deriving additional flow descriptions	169
C.3.3	Gating control.....	169
C.3.4	Bandwidth impacts	169
C.4	P_CSCF procedures to support media traversal through hosted NAT without ICE	169

Annex D (normative): Access specific procedures for GPRS.....171

D.1	General	171
D.2	Binding Mechanisms.....	171
D.3	PCC Procedures.....	172
D.3.1	IP-CAN Session Modification.....	172
D.3.1.1	Network-initiated IP-CAN Session Modification.....	172
D.3.1.2	PCEF-initiated IP-CAN Session Modification	172
D.3.1.2.1	UE-initiated IP-CAN Bearer Establishment or IP-CAN Bearer Modification.....	172
D.3.1.2.2	UE-initiated IP-CAN Bearer Termination	175

Annex E (normative): Fixed Broadband Access Interworking with EPC.....178

E.1	General	178
E.2	Definitions and abbreviations.....	178
E.2.1	Definitions	178
E.2.2	Abbreviations	178
E.3	Binding Mechanisms.....	178
E.3.1	EPC-routed traffic	178
E.3.2	NSWO traffic	178
E.4	PCC Procedures.....	179
E.4.1	Introduction	179
E.4.2	IP-CAN Session Establishment.....	180
E.4.2.1	IP-CAN Session Establishment for EPC- routed traffic	180
E.4.2.2	IP-CAN Session Establishment for NSWO traffic	184
E.4.3	IP-CAN Session Termination.....	186
E.4.3.1	IP-CAN Session Termination for EPC- routed traffic	186
E.4.3.2	IP-CAN Session Termination for NSWO traffic	190
E.4.3.2.1	BPCF-initiated IP-CAN Session Termination for NSWO traffic	190
E.4.3.2.2	PCRF-initiated IP-CAN Session Termination for NSWO traffic	192
E.4.4	IP-CAN Session Modification.....	193
E.4.4.1	IP-CAN Session Modification for EPC-routed traffic	193
E.4.4.1.1	PCRF-initiated IP-CAN Session Modification	193
E.4.4.1.2	BPCF-initiated IP-CAN Session Modification	194
E.4.4.1.3	PCEF-initiated IP-CAN Session Modification.....	196
E.4.4.1.4	BBERF-initiated IP-CAN Session Modification.....	197
E.4.4.2	IP-CAN Session Modification for NSWO traffic	199
E.4.4.2.1	PCRF-initiated IP-CAN Session Modification	199

E.4.4.2.2	BPCF-initiated IP-CAN Session Modification	201
E.5	3GPP HNB Procedures – CS Support.....	203
E.5.1	S9a CS Session Establishment	203
E.5.2	PCRF initiated S9a CS Session Modification	204
E.5.2a	BPCF initiated S9a CS Session Modification	205
E.5.3	S9a CS Session Termination	205
E.6	PCRF Addressing	206
E.6.1	General	206
E.6.2	DRA Definition	207
E.6.3	DRA Procedure	207
E.6.3.1	DRA Information Storage	207
E.6.3.2	Capabilities Exchange.....	207
E.6.3.3	Redirect DRA	208
E.6.3.4	Proxy DRA	208
E.6.3.5	PCRF selection by BPCF.....	208
E.6.3.6	PCRF selection by AF and TDF in Unsolicited application reporting mode for NSWO traffic	209
E.6.3.7	PCRF selection in a roaming scenario	209
E.6.3.8	PCRF selection for the HNB CS Service	209
E.6.4	DRA flows.....	210
E.6.4.1	General.....	210
E.6.4.2	Proxy DRA	210
E.6.4.2.1	S9 session establishment trigger	210
E.6.4.2.2	S9 session termination notification	211
E.6.4.3	Redirect DRA	212
E.6.4.3.1	S9 session establishment trigger	212
E.6.4.3.2	S9 session termination notification	212
E.7	BPCF Addressing	213
E.7.1	General	213
E.8	Session Linking Function.....	213

Annex F (normative): Access specific aspects, Fixed Broadband Access network convergence **214**

F.1	General	214
F.2	Definitions and abbreviations.....	214
F.2.1	Definitions	214
F.2.2	Abbreviations.....	214
F.3	Binding Mechanisms.....	214
F.3.1	NSWO traffic	214
F.3.2	Traffic from fixed devices	215
F.4	PCC procedures.....	215
F.4.1	Introduction	215
F.4.2	IP-CAN Session Establishment.....	215
F.4.3	IP-CAN Session Termination.....	215
F.4.3.1	UE-Initiated	215
F.4.3.2	PCEF-Initiated	216
F.4.3.3	PCRF-Initiated.....	216
F.4.4	IP-CAN Session Modification.....	216
F.4.4.1	PCRF-Initiated IP-CAN Session Modification.....	216
F.4.4.2	PCEF-Initiated IP-CAN Session Modification	216
F.5	PCRF Addressing	216
F.5.1	General	216
F.5.2	DRA Definition	216
F.5.3	DRA Procedure	216
F.5.3.1	Redirect DRA	216
F.5.3.2	Proxy DRA	216
F.5.3.3	PCRF selection by AF and TDF in unsolicited application reporting mode.....	217

F.5.3.4	PCRF selection in a roaming scenario	217
F.5.4	DRA flows.....	217
Annex G (normative):	Diameter overload control mechanism.....	218
G.1	General	218
G.2	Reporting Node	218
G.3	Reacting Node	218
G.4	DRA Diameter Overload Behavior	218
G.4.1	DRA reacting to Host Reports.....	218
Annex H (normative):	Access specific procedures for 3GPP EPS.....	220
H.1	General	220
H.2	Binding Mechanisms.....	220
Annex I (normative):	APN matching procedures	221
Annex J (normative):	Diameter message priority mechanism.....	222
J.1	General	222
J.2	PCC functional element behaviour.....	222
J.3	Interactions	222
Annex K (informative):	Change history	223
History		225

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present specification adds detailed flows of Policy and Charging Control (PCC) over the Diameter-based Rx, Gx, Gxx, Sd, Sy, S9, Nt, Diameter-based St and Np reference points and their relationship with the bearer level signalling flows over the Gn/Gp, S4, S5/S8, S2a and S2c interfaces.

The calls flows depicted in this Technical Specification represent usual cases, i.e. not all situations are covered. Detailed information provided in 3GPP TS 29.212 [9], 3GPP TS 29.214 [10], 3GPP TS 29.215 [22], 3GPP TS 29.217 [36], 3GPP TS 29.154 [56] and 3GPP TS 29.219 [28] shall be taken into consideration.

The present specification also describes the binding and the mapping of QoS parameters among SDP, UM3GPP TS QoS parameters, and QoS authorization parameters.

The present specification also describes the PCRF addressing using DRA.

The present specification also describes Diameter race condition handling for Gx based applications, i.e Gx, Gxx, Sd and S9.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: 'Vocabulary for 3GPP Specifications'.
- [2] 3GPP TS 23.203: 'Policy Control and charging architecture'.
- [3] 3GPP TS 23.060: 'General Packet Radio Service (GPRS); Service description; Stage 2'.
- [4] 3GPP TS 23.107: 'Quality of Service (QoS) concept and architecture'.
- [5] 3GPP TS 24.229: 'IP Multimedia Call Control Protocol based on SIP and SDP; Stage 3'.
- [6] 3GPP TS 26.234: 'End-to-end transparent streaming service; Protocols and codecs'.
- [7] Void.
- [8] Void
- [9] 3GPP TS 29.212: 'Policy and Charging Control (PCC); Reference points'.
- [10] 3GPP TS 29.214: 'Policy and Charging Control over Rx reference point'.
- [11] IETF RFC 2327: 'SDP: Session Description Protocol'.
- [12] IETF RFC 3264: 'An Offer/Answer model with the Session Description Protocol (SDP)'.
- [13] IETF RFC 3556: 'Session Description Protocol (SDP) Bandwidth Modifiers for RTP Control Protocol (RTCP) Bandwidth'.
- [14] IETF RFC 3588: 'Diameter Base Protocol'.