

ETSI TS 129 213 V14.3.0 (2017-04)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
Policy and charging control signalling flows and
Quality of Service (QoS) parameter mapping
(3GPP TS 29.213 version 14.3.0 Release 14)**



Reference

RTS/TSGC-0329213ve30

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	9
1 Scope	10
2 References	10
3 Definitions and abbreviations.....	12
3.1 Definitions	12
3.2 Abbreviations	13
3a Reference architecture.....	14
4 Signalling Flows over Gx, Gxx, Rx, Sd, Sy, Np, Nt, St and S9.....	17
4.0 General	17
4.1 IP-CAN Session Establishment.....	18
4.2 IP-CAN Session Termination.....	22
4.2.1 UE-Initiated	22
4.2.1.1 AF located in the HPLMN	22
4.2.1.2 AF located in the VPLMN	25
4.2.2 PCEF-Initiated	27
4.2.2.1 AF located in the HPLMN	27
4.2.2.2 AF located in the VPLMN	29
4.2.3 PCRF-Initiated.....	30
4.2.3.1 AF located in the HPLMN	30
4.2.3.2 AF located in the VPLMN	32
4.3 IP-CAN Session Modification.....	34
4.3.1 Network-Initiated IP-CAN Session Modification.....	34
4.3.1.1 Interactions between BBERF, PCEF, TDF, OCS, TSSF and PCRF(PCC/QoS/ADC Rule Provisioning in PUSH mode).....	34
4.3.1.2 Interactions between PCRF, AF and SPR	39
4.3.1.2.1 AF Session Establishment	39
4.3.1.2.1.1 AF located in HPLMN	39
4.3.1.2.1.2 AF located in VPLMN	41
4.3.1.2.2 AF session modification	42
4.3.1.2.2.2 AF located in the VPLMN.....	44
4.3.1.2.3 AF session termination	45
4.3.2 PCEF –Initiated IP-CAN Session Modification (PCC Rule Provisioning in PULL Mode)	48
4.3.2.1 PCEF-initiated IP-CAN Session Modification. AF located in HPLMN.	48
4.3.2.2 PCEF-initiated IP-CAN Session Modification, AF located in the VPLMN	53
4.4 Gateway Control Session Procedures.....	54
4.4.1 Gateway Control Session Establishment	55
4.4.2 Gateway Control and QoS Rules Request	59
4.4.2.1 Non-Roaming and Home Routed cases.....	59
4.4.2.2 Visited access cases.....	61
4.4.3 Gateway Control and QoS Rules Provision.....	62
4.4.4 Gateway Control Session Termination	63
4.4.4.1 BBERF-Initiated Gateway Control Session Termination	63
4.4.4.2 PCRF-Initiated Gateway Control Session Termination	65
4.5 Multiple BBERF Signalling Flows	66
4.5.1 Non-Roaming and Home Routed cases	66
4.5.1.1 New Gateway Control Session Establishment	66
4.5.1.2 PCEF IP-CAN session modification – Handover	69
4.5.1.3 PCEF IP-CAN session modification – S2c-based IP flow mobility	70
4.5.1.4 Gateway Control Session Establishment and PCEF IP-CAN session modification – S2c-based IP flow mobility.....	72

4.5.2	Visited access case.....	73
4.5.2.1	New Gateway Control Session Establishment	73
4.5.2.2	PCEF-Initiated IP-CAN session modification-Handover.....	75
4.5.2.3	PCEF-Initiated IP-CAN session modification - S2c-based IP flow mobility.....	77
4.5.2.4	Gateway Control Session Establishment and PCEF IP-CAN session modification – S2c-based IP flow mobility.....	79
4.6	Application Detection and Enforcement Procedures.....	81
4.6.1	TDF Session Establishment in case of solicited reporting	81
4.6.1A	TDF Session Establishment in case of unsolicited reporting	82
4.6.2	TDF Session termination	82
4.6.3	TDF Session modification	84
4.6.3.1	Application Detection, Reporting and Control Rules Request.....	84
4.6.3.2	Application Detection and Control Rules Provision	85
4.7	Spending limits Procedures over Sy reference point.....	86
4.7.1	Initial Spending Limit Report Request	86
4.7.2	Intermediate Spending Limit Report Request.....	86
4.7.3	Final Spending Limit Report Request.....	87
4.7.4	Spending Limit Report.....	88
4.8	Call flows for User Plane Congestion Management.....	88
4.8.1	General.....	88
4.8.2	RUCI reporting	89
4.8.2.1	Non-aggregated RUCI report procedure	89
4.8.2.2	Aggregated RUCI report procedure	89
4.8.3	Np reporting restriction provisioning.....	90
4.8.4	UE mobility between RCAF's	90
4.8.5	Removal of UE context.....	91
4.9	Traffic Steering Control Procedures over St reference point	91
4.9.1	St Session Establishment	91
4.9.2	St Session Modification	92
4.9.3	St Session Termination	93
4.9.4	St notification initiated by the TSSF.....	93
4.10	Negotiation for future background data transfer procedure over Nt reference point.....	94
5	Binding Mechanism	94
5.1	Overview	94
5.2	Session Binding.....	95
5.3	PCC Rule Authorization and QoS Rule Generation.....	96
5.4	Bearer Binding	97
6	QoS Parameters Mapping.....	98
6.1	Overview	98
6.1.1	UE-Initiated IP-CAN bearers.....	100
6.1.2	Network-Initiated IP-CAN bearers	101
6.2	QoS parameter mapping Functions at AF	102
6.3	QoS parameter mapping Functions at PCRF.....	112
6.4	QoS parameter mapping Functions at PCEF	120
6.4.1	GPRS	120
6.4.1.1	Authorized IP QoS parameters per PDP Context to Authorized UMTS QoS parameters mapping in GGSN.....	120
6.4.1.2	Comparing UMTS QoS Parameters against the Authorized UMTS QoS parameters in GGSN for UE initiated PDP context	122
6.4.2	3GPP- EPS.....	122
6.4.2.1	Authorized IP QoS parameters per PDP Context to Authorized UMTS QoS parameters mapping in P-GW.	122
6.4.2.2	Comparing UMTS QoS Parameters against the Authorized UMTS QoS parameters in P-GW for UE initiated PDP context	125
6.5	QoS parameter mapping Functions at UE for a UE-initiated GPRS PDP Context	125
6.5.1	SDP to UMTS QoS parameter mapping in UE.....	127
6.5.2	SDP parameters to Authorized UMTS QoS parameters mapping in UE.....	127
7	PCRF addressing	133
7.1	General	133
7.2	DRA Definition	133

7.3	DRA Procedures.....	133
7.3.1	General.....	133
7.3.2	DRA Information Storage.....	133
7.3.3	Capabilities Exchange.....	134
7.3.4	Redirect DRA	134
7.3.4.1	Redirecting Diameter Requests.....	134
7.3.4.2	DRA binding removal.....	135
7.3.5	Proxy DRA	135
7.3.6	PCRF selection by BBERF/PCEF (non-roaming case)	135
7.3.7	PCRF selection by AF	136
7.3.8	PCRF selection in a roaming scenario	136
7.3.9	PCRF selection by TDF for unsolicited application reporting.....	137
7.3.10	PCRF selection by RCAF.....	137
7.4	DRA flows.....	137
7.4.1	Proxy DRA	137
7.4.1.1	Establishment of Diameter Sessions	137
7.4.1.1.1	Non-roaming cases	137
7.4.1.1.2	Roaming cases	138
7.4.1.2	Modification of Diameter Sessions	139
7.4.1.2.1	Non-roaming cases	139
7.4.1.2.1.1	Client-initiated.....	139
7.4.1.2.1.2	PCRF-initiated.....	140
7.4.1.2.2	Roaming cases	141
7.4.1.2.2.1	V-PCRF initiated	141
7.4.1.2.2.2	H-PCRF initiated	142
7.4.1.3	Termination of Diameter Sessions	143
7.4.1.3.1	Non-roaming cases	143
7.4.1.3.2	Roaming cases	144
7.4.2	Redirect DRA	145
7.4.2.1	Establishment of Diameter Sessions	145
7.4.2.1.1	Non-roaming cases	145
7.4.2.1.2	Roaming cases	146
7.4.2.2	Modification of Diameter sessions.....	147
7.4.2.3	Termination of Diameter Sessions	147
7.4.2.3.1	Non-roaming cases	147
7.4.2.3.2	Roaming cases	148
8	Diameter race condition handling	150
8.1	Overview	150
8.2	Procedures for Gx, Gxx, Sd and S9.....	150
Annex A (informative): Examples of deriving the Maximum Authorized parameters from the SDP parameters		152
Annex B (normative): Signalling Flows for IMS.....		153
B.0	General	153
B.1	Subscription to Notification of Signalling Path Status at IMS Registration	153
B.1a	Subscription to Notification of Change of IP-CAN Type at IMS Registration.....	154
B.1b	Provisioning of SIP signalling flow information at IMS Registration	155
B.1c	Subscription to Notification of Change of PLMN Identifier at IMS Registration	156
B.2	IMS Session Establishment	158
B.2.1	Provisioning of service information at Originating P-CSCF and PCRF	158
B.2.2	Provisioning of service information at terminating P-CSCF and PCRF	161
B.3	IMS Session Modification.....	165
B.3.1	Provisioning of service information	165
B.3.2	Enabling of IP Flows	169
B.3.3	Disabling of IP Flows.....	170
B.3.4	Media Component Removal.....	171

B.4	IMS Session Termination	172
B.4.1	Mobile initiated session release / Network initiated session release	172
B.4.2	IP-CAN Bearer Release/Loss	174
B.5	P-CSCF Restoration	175
Annex C (normative): NAT Related Procedures.....		177
C.1	Support for media traversal of NATs using ICE	177
C.2	P-CSCF procedures	177
C.2.1	General	177
C.2.2	Deriving the Ues IP address	178
C.2.3	Deriving flow descriptions	178
C.2.4	Gating control.....	178
C.2.5	Bandwidth impacts	178
C.3	PCRF procedures.....	179
C.3.1	General	179
C.3.2	Deriving additional flow descriptions	179
C.3.3	Gating control.....	179
C.3.4	Bandwidth impacts	179
C.4	P_CSCF procedures to support media traversal through hosted NAT without ICE	179
Annex D (normative): Access specific procedures for GPRS.....		181
D.1	General	181
D.2	Binding Mechanisms	181
D.3	PCC Procedures.....	182
D.3.1	IP-CAN Session Modification.....	182
D.3.1.1	Network-initiated IP-CAN Session Modification	182
D.3.1.2	PCEF-initiated IP-CAN Session Modification	182
D.3.1.2.1	UE-initiated IP-CAN Bearer Establishment or IP-CAN Bearer Modification.....	182
D.3.1.2.2	UE-initiated IP-CAN Bearer Termination	185
Annex E (normative): Fixed Broadband Access Interworking with EPC.....		188
E.1	General	188
E.2	Definitions and abbreviations.....	188
E.2.1	Definitions	188
E.2.2	Abbreviations	188
E.3	Binding Mechanisms	188
E.3.1	EPC-routed traffic	188
E.3.2	NSWO traffic	188
E.4	PCC Procedures.....	189
E.4.1	Introduction	189
E.4.2	IP-CAN Session Establishment.....	190
E.4.2.1	IP-CAN Session Establishment for EPC- routed traffic	190
E.4.2.2	IP-CAN Session Establishment for NSWO traffic	194
E.4.3	IP-CAN Session Termination.....	196
E.4.3.1	IP-CAN Session Termination for EPC- routed traffic	196
E.4.3.2	IP-CAN Session Termination for NSWO traffic	200
E.4.3.2.1	BPCF-initiated IP-CAN Session Termination for NSWO traffic	200
E.4.3.2.2	PCRF-initiated IP-CAN Session Termination for NSWO traffic	202
E.4.4	IP-CAN Session Modification.....	203
E.4.4.1	IP-CAN Session Modification for EPC-routed traffic	203
E.4.4.1.1	PCRF-initiated IP-CAN Session Modification	203
E.4.4.1.2	BPCF-initiated IP-CAN Session Modification	204
E.4.4.1.3	PCEF-initiated IP-CAN Session Modification.....	206
E.4.4.1.4	BBERF-initiated IP-CAN Session Modification.....	207
E.4.4.2	IP-CAN Session Modification for NSWO traffic	209

E.4.4.2.1	PCRF-initiated IP-CAN Session Modification	209
E.4.4.2.2	BPCF-initiated IP-CAN Session Modification	211
E.5	3GPP HNB Procedures – CS Support	213
E.5.1	S9a CS Session Establishment	213
E.5.2	PCRF initiated S9a CS Session Modification	214
E.5.2a	BPCF initiated S9a CS Session Modification	215
E.5.3	S9a CS Session Termination	215
E.6	PCRF Addressing	216
E.6.1	General	216
E.6.2	DRA Definition	217
E.6.3	DRA Procedure	217
E.6.3.1	DRA Information Storage.....	217
E.6.3.2	Capabilities Exchange.....	217
E.6.3.3	Redirect DRA	218
E.6.3.4	Proxy DRA	218
E.6.3.5	PCRF selection by BPCF.....	218
E.6.3.6	PCRF selection by AF and TDF in Unsolicited application reporting mode for NSW traffic.....	219
E.6.3.7	PCRF selection in a roaming scenario	219
E.6.3.8	PCRF selection for the HNB CS Service.....	219
E.6.4	DRA flows.....	220
E.6.4.1	General.....	220
E.6.4.2	Proxy DRA	220
E.6.4.2.1	S9 session establishment trigger	220
E.6.4.2.2	S9 session termination notification	221
E.6.4.3	Redirect DRA	222
E.6.4.3.1	S9 session establishment trigger	222
E.6.4.3.2	S9 session termination notification	222
E.7	BPCF Addressing	223
E.7.1	General	223
E.8	Session Linking Function	223
Annex F (normative):	Access specific aspects, Fixed Broadband Access network convergence	224
F.1	General	224
F.2	Definitions and abbreviations.....	224
F.2.1	Definitions	224
F.2.2	Abbreviations.....	224
F.3	Binding Mechanisms.....	224
F.3.1	NSWO traffic	224
F.3.2	Traffic from fixed devices.....	225
F.4	PCC procedures.....	225
F.4.1	Introduction	225
F.4.2	IP-CAN Session Establishment.....	225
F.4.3	IP-CAN Session Termination.....	225
F.4.3.1	UE-Initiated	225
F.4.3.2	PCEF-Initiated	226
F.4.3.3	PCRF-Initiated.....	226
F.4.4	IP-CAN Session Modification.....	226
F.4.4.1	PCRF-Initiated IP-CAN Session Modification.....	226
F.4.4.2	PCEF-Initiated IP-CAN Session Modification.....	226
F.5	PCRF Addressing	226
F.5.1	General	226
F.5.2	DRA Definition	226
F.5.3	DRA Procedure	226
F.5.3.1	Redirect DRA	226
F.5.3.2	Proxy DRA	226

F.5.3.3	PCRF selection by AF and TDF in unsolicited application reporting mode.....	227
F.5.3.4	PCRF selection in a roaming scenario	227
F.5.4	DRA flows.....	227
Annex G (normative):	Diameter overload control mechanism	228
G.1	General	228
G.2	Reporting Node	228
G.3	Reacting Node	228
G.4	DRA Diameter Overload Behavior	228
G.4.1	DRA reacting to Host Reports.....	228
Annex H (normative):	Access specific procedures for 3GPP EPS	230
H.1	General	230
H.2	Binding Mechanisms	230
Annex I (normative):	APN matching procedures	231
Annex J (normative):	Diameter message priority mechanism.....	232
J.1	General	232
J.2	PCC functional element behaviour.....	232
J.3	Interactions	232
Annex K (normative):	Diameter load control mechanism.....	233
K.1	General	233
K.2	Endpoint or Agent Reporting Node.....	233
K.3	Receiving Node	233
K.4	DRA Behaviour.....	233
Annex L (informative):	Change history	235
History	238

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

x the first digit:

- 1 presented to TSG for information;
- 2 presented to TSG for approval;
- 3 or greater indicates TSG approved document under change control.

Y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present specification adds detailed flows of Policy and Charging Control (PCC) over the Diameter-based Rx, Gx, Gxx, Sd, Sy, S9, Nt, Diameter-based St and Np reference points and their relationship with the bearer level signalling flows over the Gn/Gp, S4, S5/S8, S2a and S2c interfaces.

The calls flows depicted in this Technical Specification represent usual cases, i.e. not all situations are covered. Detailed information provided in 3GPP TS 29.212 [9], 3GPP TS 29.214 [10], 3GPP TS 29.215 [22], 3GPP TS 29.217 [36], 3GPP TS 29.154 [56] and 3GPP TS 29.219 [28] shall be taken into consideration.

The present specification also describes the binding and the mapping of QoS parameters among SDP, UMTS QoS parameters, and QoS authorization parameters.

The present specification also describes the PCRF addressing using DRA.

The present specification also describes Diameter race condition handling for Gx based applications, i.e Gx, Gxx, Sd and S9.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.203: "Policy Control and charging architecture".
- [3] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2".
- [4] 3GPP TS 23.107: "Quality of Service (QoS) concept and architecture".
- [5] 3GPP TS 24.229: "IP Multimedia Call Control Protocol based on SIP and SDP; Stage 3".
- [6] 3GPP TS 26.234: "End-to-end transparent streaming service; Protocols and codecs".
- [7] Void.
- [8] Void
- [9] 3GPP TS 29.212: "Policy and Charging Control (PCC); Reference points".
- [10] 3GPP TS 29.214: "Policy and Charging Control over Rx reference point".
- [11] IETF RFC 2327: "SDP: Session Description Protocol".
- [12] IETF RFC 3264: "An Offer/Answer model with the Session Description Protocol (SDP)".
- [13] IETF RFC 3556: "Session Description Protocol (SDP) Bandwidth Modifiers for RTP Control Protocol (RTCP) Bandwidth".
- [14] Void.
- [15] IETF RFC 5245: "Interactive Connectivity Establishment (ICE): A Protocol for Network Address Translator (NAT) Traversal for Offer/Answer Protocols".