

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Electric vehicle conductive charging system –
Part 23: DC electric vehicle supply equipment**

**Système de charge par conduction pour véhicules électriques –
Partie 23: Système d'alimentation en courant continu pour véhicules électriques**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



IEC 61851-23

Edition 2.0 2023-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Electric vehicle conductive charging system –
Part 23: DC electric vehicle supply equipment**

**Système de charge par conduction pour véhicules électriques –
Partie 23: Système d'alimentation en courant continu pour véhicules électriques**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 43.120

ISBN 978-2-8322-8868-9

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	15
1 Scope.....	18
2 Normative references	19
3 Terms and definitions	22
3.1 Electric supply equipment	22
3.2 Insulation	22
3.3 Functions	26
3.4 Vehicle	30
3.5 Cords, cables and connection means	31
3.6 Service and usage	32
3.7 General terms	33
4 General requirements	40
5 Classification	40
5.101 Characteristics of EV supply equipment	40
5.101.1 Separation type	40
5.101.2 Control system	40
5.101.3 System	40
5.101.4 Thermal management system	40
5.101.5 Power distribution system	41
6 Charging modes and functions	41
6.2 Charging modes.....	41
6.2.1 Mode 1	41
6.2.2 Mode 2	41
6.2.3 Mode 3	41
6.3 Functions provided in Mode 4	41
6.3.1 Mandatory functions in Mode 4	41
6.3.2 Optional functions for Mode 4	62
7 Communications	63
7.1 Digital communication between the EV supply equipment and the EV	63
7.1.101 Basic communication interface	64
8 Protection against electric shock	64
8.101 General provisions.....	64
8.101.1 General	64
8.101.2 Intended use and reasonably foreseeable misuse	65
8.101.3 Limitation of touch current or touch voltage	65
8.101.4 Threshold of perception and startle reaction	65
8.102 Basic protection	68
8.102.1 General	68
8.102.2 Protection by means of basic insulation of live parts	68
8.102.3 Protection by means of enclosures or barriers	68
8.102.4 Protection by means of limitation of voltage	68
8.102.5 Protection by means of limitation of steady-state touch current.....	70
8.103 Fault protection.....	70
8.103.1 General	70
8.103.2 Protective-equipotential-bonding.....	70

8.103.3	Effective protective conductor continuity between the enclosure and the external protective circuit.....	70
8.103.4	Automatic disconnection of supply	71
8.103.5	Supplementary insulation.....	71
8.103.6	Electrically protective screening	71
8.104	Enhanced protective provision	71
8.104.1	General	71
8.104.2	Double or reinforced insulation	71
8.104.3	Protective separation between circuits.....	72
8.105	Requirements for separated EV supply equipment	72
8.105.1	General	72
8.105.2	Equipotential bonding on side B.....	74
8.105.3	Impedance to protective conductor on side B.....	74
8.105.4	Degrees of protection against access to hazardous-live-parts.....	75
8.105.5	Insulation barriers.....	76
8.105.6	Stored energy.....	77
8.105.7	Disconnection from vehicle	78
8.105.8	Protective (earthing) conductor from the supply network.....	78
8.105.9	Residual current protective devices	79
8.105.10	Safety requirements for auxiliary circuits between the EV supply equipment and the EV	79
8.105.11	Protective conductor dimension cross-sectional area.....	79
9	Conductive electrical interface requirements.....	80
9.1	General.....	80
9.5	Functional description of the DC interface.....	80
9.7	Wiring of the neutral conductor	80
9.101	Avoidance of breaking under load.....	80
10	Requirements for adaptors	81
11	Cable assembly requirements.....	82
11.1	General.....	82
11.6	Strain relief.....	82
11.6.101	Strain relief of the EV supply equipment's side B cable assembly	82
11.6.102	Test of the anchorage of the side B cable assembly	83
11.101	Cable breakaway	85
11.102	Surface temperature of the side B cable assembly.....	85
12	EV supply equipment constructional requirements and tests.....	87
12.1	General.....	87
12.2	Characteristics of mechanical switching devices	87
12.2.5	Relays	87
12.3	Clearances and creepage distances.....	87
12.4	IP degrees	87
12.4.1	Degrees of protection against solid foreign objects and water for the enclosures.....	87
12.5	Insulation resistance	88
12.6	Touch current	88
12.6.101	Touch current limit.....	88
12.6.102	Test.....	88
12.6.103	Protection measures for the test touch current more than 3,5 mA	89
12.7	Dielectric withstand voltage	90

12.7.2	Impulse dielectric withstand (1,2 µs/50 µs)	90
12.7.101	Suppression of transient overvoltage at side A (insulation coordination)	90
12.7.102	Protection against transient overvoltages of atmospheric origin or due to switching	92
12.8	Temperature rise	94
12.9	Damp heat functional test	94
12.10	Minimum temperature functional test	94
12.11	Mechanical strength	94
12.101	Side A current	95
12.102	Power supply cords	96
12.102.1	General	96
12.102.2	Cross-sectional area	96
12.102.3	Cord anchorages and strain relief for non-detachable power supply cords	97
12.103	Stress relief test	98
12.104	Abnormal operation and simulated fault condition tests	99
12.104.1	General	99
12.104.2	Pass criteria	99
12.104.3	Breakdown of components test	100
12.104.4	Loss of AC supply phase test	100
12.104.5	Inoperative blower/fan motor test	100
12.104.6	Clogged filter test	101
12.105	Protection against electrically caused fire	101
12.105.1	General	101
12.105.2	Fire enclosure	101
12.106	Protection against chemical hazards	101
12.106.1	Type of coolant	101
12.106.2	Flammability	102
12.106.3	Material compatibility	102
12.107	Enclosures	102
12.107.1	General	102
12.107.2	Strength of materials and parts	103
12.107.3	Enclosure integrity tests	103
12.108	Components bridging insulation	103
12.108.1	General	103
12.108.2	Capacitors	104
12.109	Isolating transformers	104
13	Overload and short-circuit protection	104
13.1	General	104
13.2	Overload protection of the cable assembly	104
13.3	Short-circuit protection of the charging cable	104
13.101	Short-circuit protection of the DC connection during energy transfer	105
14	Automatic reclosing of protective devices	106
15	Emergency switching or disconnect (optional)	106
16	Marking and instructions	106
16.1	Installation manual of EV charging stations	106
16.2	User manual for EV supply equipment	107
16.3	Marking of EV supply equipment	108
16.4	Marking of charging cable assemblies case B	108

101	Specific requirements for EV supply equipment	108
101.1	Specific requirements for separated EV supply equipment	108
101.1.1	Operating ranges for voltage, current, and power at side B.....	108
101.1.2	Voltage and current tolerance at side B	109
101.1.3	Control delay of present current at side B in CCM	111
101.1.4	Descending rate of present current at side B	114
101.1.5	Periodic and random deviation (current ripple at side B during CCM).....	114
101.1.6	Periodic and random deviation (voltage ripple at side B during CVM)	115
101.1.7	Load dump	117
101.1.8	Side B inductance.....	117
101.2	Specific requirement for energy transfer with a thermal management system or thermal sensing only	118
101.2.1	General	118
101.2.2	Temperature limits and self-diagnostics	118
101.2.3	Temperature monitoring.....	119
101.2.4	Tests for thermal management system performance of the EV supply equipment	120
101.3	Specific requirements for temperature-controlled energy transfer	129
102	Test methods.....	130
102.1	Technical data	130
102.2	General test conditions	130
102.2.1	Ambient test conditions.....	130
102.2.2	Measuring instruments	131
102.2.3	Test setups.....	131
102.2.4	Test load	134
102.2.5	Operating points for tests	136
Annexes	138
Annex AA (normative)	EV supply equipment of system A.....	139
AA.1	General.....	139
AA.2	Circuit diagram	139
AA.3	Specific safety requirements	142
AA.3.1	Fault protection in side B	142
AA.3.2	De-energization of the power supply to the EV	146
AA.3.3	Voltage measurement of side B live parts (DC+/DC–) for vehicle connector unlatch	147
AA.3.4	Overcurrent protection of side B	147
AA.3.5	Short-circuit protection of side B	147
AA.3.6	Latch monitoring for the vehicle connector.....	148
AA.3.7	Protection of the EV disconnection device	149
AA.3.8	Fault conditions and criteria for transfer to error and emergency shutdown	149
AA.3.9	Inrush current limitation by the EV supply equipment.....	154
AA.3.10	Regulation of the present current at side B in CCM.....	155
AA.3.11	Periodic and random deviation (current ripple at side B during CCM).....	156
AA.3.12	Overvoltage protection including load dump.....	157
AA.3.13	Power supply to the EV for the actuation of EV disconnection device	158
AA.3.14	Impedance of the side B circuit.....	158
AA.3.15	Assistance of welding detection	158
AA.3.16	Specific requirements for temperature-controlled energy transfer	159

AA.4	FPT process and communication between the EV supply equipment and the EV for energy transfer control	159
AA.4.1	Forward power transfer states	159
AA.4.2	Communication measures.....	161
AA.4.3	Forward power transfer control process	162
AA.4.4	Measuring current and voltage at side B	168
AA.5	Response to an EV command on charge current.....	170
AA.6	Bidirectional power transfer (optional).....	172
AA.6.1	General	172
AA.6.2	Circuit diagram	172
AA.6.3	Functional requirements	174
AA.6.4	Bidirectional power transfer control process.....	176
AA.7	Optional functions	181
AA.7.1	General	181
AA.7.2	Compatibility check.....	181
AA.7.3	Dynamic control.....	181
AA.7.4	High-current control	182
AA.7.5	High-voltage control.....	182
AA.8	Compliance test for user-initiated shutdown	182
AA.9	Specific requirement for energy transfer with thermal management system.....	183
Annex BB (normative)	EV supply equipment of system B.....	184
BB.1	General.....	184
BB.2	Circuit diagrams.....	184
BB.2.1	Circuit diagram	184
BB.2.2	Requirements of IMD and discharge circuit.....	186
BB.3	Parameters of control pilot circuit.....	186
BB.4	Forward power transfer control process under normal condition	187
BB.4.1	Side B regulation	187
BB.4.2	Measuring current and voltage.....	187
BB.4.3	Vehicle coupler mating confirmation	189
BB.4.4	Forward power transfer control sequence	189
BB.4.5	Normal shutdown.....	191
BB.5	Safety requirements under failure mode.....	191
BB.5.1	Error shutdown and emergency shutdown.....	191
BB.5.2	Terminate energy transfer due to an EV supply equipment fault.....	193
BB.5.3	Terminate energy transfer due to an EV fault.....	194
BB.5.4	Digital communication timeout	194
BB.5.5	Loss of electrical continuity of the control pilot.....	195
BB.5.6	Overvoltage fault	195
BB.5.7	Load dump	196
BB.5.8	Short-circuit protection of side B.....	197
BB.5.9	Lock and latch monitoring for vehicle connector.....	198
BB.5.10	Overcurrent protection of side B	198
BB.5.11	Insulation fault monitoring.....	198
BB.6	Timing sequence diagram of forward power transfer	199
BB.7	Side B current regulation in CCM.....	200
BB.8	Insulation resistance check before energy transfer.....	202
BB.9	Side B voltage regulation in CVM.....	204
BB.10	Periodic and random deviation (voltage ripple at side B in CVM).....	206

BB.11	Energy transfer control mode	206
BB.11.1	Definition	206
BB.11.2	Typical forward power transfer process	207
BB.12	Standby mode	208
BB.13	Smart charging	209
BB.14	Minimum cross-sectional area of the protective conductor	209
Annex CC	(normative) EV supply equipment of system C	210
CC.1	General	210
CC.2	Circuit diagrams	210
CC.2.1	General	210
CC.2.2	Circuit diagram for configuration EE	210
CC.2.3	Circuit diagram for configuration FF	213
CC.2.4	Disabled side B	216
CC.3	Process of energy transfer	217
CC.3.1	General	217
CC.3.2	Normal startup	219
CC.3.3	Normal shutdown or pause after energy transfer	225
CC.3.4	Error and emergency handling	229
CC.3.5	Pause by EV supply equipment using ISO 15118-2:2014	241
CC.3.6	Renegotiation initiated by EV or EV supply equipment using ISO 15118-2:2014	251
CC.4	Safety related functions	255
CC.4.1	Safety measures for side B	255
CC.4.2	Vehicle coupler latching function	259
CC.4.3	Loss of electrical continuity of the control pilot conductor	259
CC.4.4	Loss of electrical continuity of the proximity detection conductor	259
CC.4.5	Voltage check at initialization	259
CC.4.6	Minimum cross-sectional area of the protective conductor	259
CC.4.7	Loss of electrical continuity of the protective conductor	259
CC.5	Additional functions	260
CC.5.1	Pre-charge	260
CC.5.2	Sleep mode and communication session restart methods	262
CC.5.3	Configuration EE vehicle connector latch position switch (S _{S3}) activation	269
CC.5.4	Configuration EE vehicle connector latch position switch (S _{S3}) verification	269
CC.5.5	Handling of operating ranges	270
CC.5.6	Compatibility check	277
CC.5.7	Considerations for CCM, CVM and CPM (informative)	281
CC.6	Specific requirements	283
CC.6.1	Requirements for load dump	283
CC.6.2	Side B current regulation	283
CC.6.3	Measuring current and voltage at side B	283
CC.6.4	Overcurrent protection of side B	284
CC.7	General test conditions	284
CC.7.1	Operating points – Definitions	284
CC.7.2	Standard test setup	286
CC.7.3	Definition of measured values at side B	286
CC.7.4	Exemplary approach to set a test point in CCM	286

CC.7.5	Test cases	289
Annex DD (informative)	Bidirectional power transfer control	354
DD.1	General.....	354
DD.2	Forward power transfer (FPT) and reverse power transfer (RPT)	354
Annex EE (normative)	Test load impedance verification.....	355
EE.1	General.....	355
EE.2	Response curve verification	355
EE.3	Test setup for test load verification (informative).....	358
EE.4	Result	359
Annex FF (normative)	Multi-side B separated EV supply equipment.....	360
FF.1	General.....	360
FF.2	Classification and use case of multi-side B EV supply equipment.....	360
FF.2.1	System operation.....	360
FF.2.2	Side B system	360
FF.2.3	Configuration	360
FF.3	Constructional requirements of a side B system.....	363
FF.3.1	Constructional requirements of a side B system according to Annex AA	363
FF.3.2	Constructional requirements of a side B system according to Annex BB	364
FF.3.3	Constructional requirements of a side B system according to Annex CC	364
FF.4	Side B system performance	364
FF.4.1	General performance requirements.....	364
FF.4.2	Performance of multi-side B EV supply equipment providing simultaneous operation.....	364
FF.5	Safety requirements.....	364
FF.5.1	General safety requirements.....	364
FF.5.2	Short-circuit protection	365
FF.5.3	Overload protection	365
FF.5.4	Access to live parts through an unmated vehicle connector during energy transfer	365
FF.5.5	Additional safety requirements for multi-side B EV supply equipment providing simultaneous operation	366
FF.5.6	Diagnostic check of mechanical disconnection device in the side B system.....	366
FF.5.7	Interconnected side B live parts (DC+/DC-) in multi-side B EV supply equipment	366
Annex GG (informative)	Communication and energy transfer process between the EV supply equipment and the EV	367
GG.1	General.....	367
GG.2	System configuration	367
GG.3	Energy transfer control process and state	367
GG.3.1	General	367
GG.3.2	Description of the initialization stage	368
GG.3.3	Description of the energy transfer stage	368
GG.3.4	Description of the shutdown stage	369
Annex HH (informative)	Touch current and touch impulse current.....	370
HH.1	General.....	370
HH.2	Current through the human body.....	375
HH.3	Conditional dependent thresholds	376
HH.4	Hazards due to leakage between side B live parts and the protective conductor.....	376

HH.5	Balanced versus unbalanced voltages at side B live parts (DC+/DC–)	377
HH.6	Insulation monitoring device	378
HH.7	IMD reaction time	379
HH.8	Conclusion	379
	Bibliography	380
Figure 101	– Example of a coupling session	27
Figure 102	– Voltage V_{T8} to apply to simulate short period overvoltage at side B between DC+ and DC–	52
Figure 103	– Typical voltages between side B live parts (DC+/DC–) and protective conductor under normal operation	55
Figure 104	– IMD connection which results in a voltage more than the maximum voltage limits	56
Figure 105	– Examples of a fault between the secondary circuit and the protective conductor	59
Figure 106	– Measurement of the touch leakage current	67
Figure 107	– Touch time – DC voltage under single fault condition (water wet, fingertip to feet)	69
Figure 108	– Insulation barriers	76
Figure 109	– Construction types of vehicle adapters	81
Figure 110	– Apparatus to test the side B cable assembly anchorage	83
Figure 111	– Test setup the side B cable assembly anchorage	84
Figure 112	– Example of a side B cable assembly equipped with handle and a warning label attached to the cable	86
Figure 113	– Example setup of SPD for the protection of the EV supply equipment against transients	91
Figure 114	– Example of an SPD-assembly having one voltage switching type SPD between side B live conductors (DC+/DC–) and protective conductor	93
Figure 115	– Symbol ISO 7000-0434B:2004-01	107
Figure 116	– Side B voltage tolerances in CVM	110
Figure 117	– Current control delay for an increasing current request	112
Figure 118	– Current control delay for a decreasing current control request	113
Figure 119	– Voltage at side B in CVM operation in steady state with ripple	116
Figure 120	– Setup to measure the maximum side B inductance	117
Figure 121	– Reference device (RD) A_0	121
Figure 122	– Test arrangement A_0	122
Figure 123	– Reference device RD A_1	122
Figure 124	– Test arrangement A_1	123
Figure 125	– Reference device RD C_0	124
Figure 126	– Test arrangement C_0	125
Figure 127	– Reference device RD C_1	125
Figure 128	– Test arrangement C_1	126
Figure 129	– General test setup for system A	132
Figure 130	– General test setup for system B	133
Figure 131	– General test setup for system C	134
Figure 132	– Test load example	135

Figure 133 – Operating points.....	137
Figure AA.1 – Overall circuit diagram of system A EV supply equipment and EV	140
Figure AA.2 – Failure detection principle by detection of DC leakage current.....	144
Figure AA.3 – Example of vehicle connector latch monitoring circuit	148
Figure AA.4 – Example of vehicle inlet with the latch holder covered by a metal plate that inhibits latch holding	149
Figure AA.5 – Flow diagram for forward power transfer.....	162
Figure AA.6 – Sequence diagram for forward power transfer.....	163
Figure AA.7 – Representation of the delay between the measurement and the digital communication transmission for system A.....	169
Figure AA.8 – Acceptable range of the measured current at side B (target current of the EV $I_{EV_trg} = 50\text{ A}$)	170
Figure AA.9 – Change in the target current requested by the EV.....	171
Figure AA.10 – Side B performance of EV supply equipment	172
Figure AA.11 – Circuit diagram of a system A BPT EV supply equipment and EV	173
Figure AA.12 – Flow diagram for bidirectional power transfer.....	179
Figure AA.13 – Sequence diagram for bidirectional power transfer	180
Figure AA.14 – Transition of applicable maximum current of the EV supply equipment at side B and target current of the EV during dynamic control	181
Figure BB.1 – System B EV supply equipment circuit diagram	185
Figure BB.2 – Representation of delay between the measures current and voltage at side B and the digital communication transmission for system B	187
Figure BB.3 – FPT control sequence for system B	190
Figure BB.4 – Timing sequence diagram of FPT	200
Figure BB.5 – Operating points and test points for side B current regulation in CCM.....	201
Figure BB.6 – Operating points and test points for side B voltage regulation in CVM	206
Figure BB.7 – Definition of CCM, CVM and CPM	207
Figure BB.8 – Typical FTP process	208
Figure CC.1 – Circuit diagram for a system C EV supply equipment of configuration EE.....	211
Figure CC.2 – Circuit diagram of a system C EV supply equipment of configuration FF	214
Figure CC.3 – Equivalent disabled side B of the EV supply equipment.....	216
Figure CC.4 – Example of a sequence diagram	219
Figure CC.5 – Sequence diagram for normal startup.....	220
Figure CC.6 – Sequence diagram for normal shutdown or pause after energy transfer by EV or EV supply equipment.....	226
Figure CC.7 – Sequence diagram for EV supply equipment and EV initiated error shutdown	230
Figure CC.8 – Sequence diagram for EV initiated error shutdown based on DIN SPEC 70121 during energy transfer	233
Figure CC.9 – Sequence diagram for an emergency shutdown executed by the EV	236
Figure CC.10 – Sequence diagram for an emergency shutdown executed by the EV supply equipment.....	239
Figure CC.11 – Sequence diagram for pause before cable-check phase by EV supply equipment using ISO 15118-2:2014	242
Figure CC.12 – Sequence diagram for pause after pre-charge phase and before energy transfer stage by the EV supply equipment using ISO 15118-2:2014	246

Figure CC.13 – Sequence diagram for renegotiation initiated by EV or EV supply equipment using ISO 15118-2:2014	252
Figure CC.14 – Worst case equivalent circuit during pre-charge	260
Figure CC.15 – Restart methods sequence for the EV supply equipment	263
Figure CC.16 – Restart method verification on the EV supply equipment	264
Figure CC.17 – Example of a B1 – B2 transition	265
Figure CC.18 – Example of a B1 – E – B1 – B2 transition	266
Figure CC.19 – Example of a B1 – F – B1 – B2 transition	266
Figure CC.20 – Restart methods sequence for the EV	268
Figure CC.21 – Example of a B – C – B toggle.....	269
Figure CC.22 – Operating points.....	285
Figure CC.23 – Approaching a single test point TP in CCM (example 1)	288
Figure CC.24 – Approaching multiple test points TP _n CCM (example 2).....	289
Figure CC.25 – Test points TP _n	298
Figure CC.26 – Voltage at the vehicle connector.....	306
Figure CC.27 – Test points TP _n for the load dump test	309
Figure CC.28 – Test point matrix for side B current regulation in CCM including static deviation and ripple	314
Figure CC.29 – Test point sequence for side B current regulation in CCM	317
Figure CC.30 – Test point matrix for 0 A mode during energy transfer	318
Figure CC.31 – Test point matrix for side B voltage regulation in CVM during pre-charge	321
Figure CC.32 – Test point matrix for control delay of charging current in CCM.....	327
Figure CC.33 – Test point sequence	329
Figure CC.34 – Test points for voltage measurement during welding detection	344
Figure CC.35 – Test setup for IMD measurement connections	351
Figure EE.1 – Magnitude of the impedance of the test load between DC+ and DC– for system A and system B.....	356
Figure EE.2 – Magnitude of the impedance of the test load between DC+ and DC– for system A for current ripple measurements	357
Figure EE.3 – Magnitude of the impedance of the test load between DC+ and DC– for system C	357
Figure EE.4 – Test setup for test load verification	358
Figure FF.1 – Example of a multi-side B EV supply equipment with a single PEC	362
Figure FF.2 – Example of a multi-side B EV supply equipment with multiple PECs.....	363
Figure HH.1 – EV and EV supply equipment equivalent circuit	370
Figure HH.2 – Circuit diagram simplification of the circuit in Figure HH.1	373
Figure HH.3 –Thevenin equivalent circuit diagram of the circuit in Figure HH.1.....	373
Figure HH.4 – Leakage current and impulse current in relation to limits in IEC 60479 series	374
Figure HH.5 – Examples of circuits with equivalent impulse current and leakage current through a human body	375
Table 101 – Verification criterion	43
Table 102 – Data/message for the compatibility check test	47

Table 103 – Voltage threshold for emergency shutdown reaction for system B and system C	49
Table 104 – EV supply equipment reaction depending on the present voltage at side B condition	49
Table 105 – Compliance tests for protection against overvoltage at side B between DC+ and DC–	50
Table 106 – Test load setup for protection against overvoltage test	50
Table 107 – Data/messages for protection against overvoltage test	51
Table 108 – Overvoltage condition and verification criterion.....	51
Table 109 – Control circuit supply integrity test.....	52
Table 110 – Touch voltage under normal operation.....	69
Table 111 – Touch voltage under single fault conditions	69
Table 112 – Safety provisions for protection against electric shock for EV supply equipment at side B	72
Table 113 – Minimum protective measures	77
Table 114 – Pull force and torque test values for side B cable assembly anchorage	85
Table 115 – Touch current limits	88
Table 116 – Sizes of conductors of power supply cord	96
Table 117 – Cord strain relief pull force	98
Table 118 – Current ripple limit of the EV supply equipment	115
Table 119 – Test parameter values	126
Table 120 – Recommended circuit parameters of the test load	136
Table AA.1 – Definition of symbols of the overall circuit diagram of a system A EV supply equipment.....	141
Table AA.2 – Parameters and values of the circuit diagram for a system A EV supply equipment.....	142
Table AA.3 – Principle of fault protection	143
Table AA.4 – Requirements for earth leakage current fault monitoring	145
Table AA.5 – Error shutdown times and criteria	150
Table AA.6 – Action and message parameter for error shutdown triggered by the EV supply equipment.....	152
Table AA.7 – Action and message parameter for error shutdown triggered by the EV	152
Table AA.8 – Emergency shutdown times and criteria.....	153
Table AA.9 – Actions and criteria for emergency shutdown	154
Table AA.10 – System A setup of the test load for regulation of the present current at side B in CCM.....	155
Table AA.11 – System A recommended steps for regulation of the present current at side B in CCM.....	155
Table AA.12 – Specification of measuring instrument.....	157
Table AA.13 – Voltage threshold for emergency shutdown.....	157
Table AA.14 – Maximum boost current for system A EV supply equipment.....	159
Table AA.15 – FPT states of the FPT EV supply equipment	160
Table AA.16 – FPT control process and states of the FPT EV supply equipment.....	161
Table AA.17 – Test scenarios	165
Table AA.18 – Normal shutdown times and criteria	166
Table AA.19 – Actions and message parameters for normal shutdown.....	166

Table AA.20 – Recommended specification of target current of the EV	171
Table AA.21 – Requirements for the side B performance of EV supply equipment	171
Table AA.22 – Setup of test load for protection against under-voltage at the vehicle connector.....	176
Table AA.23 – BPT states of BPT EV supply equipment.....	176
Table AA.24 – BPT control process of BPT EV supply equipment	178
Table AA.25 – Selection of protection measures against over-temperature	183
Table AA.26 – Protection measures against over-temperature	183
Table BB.1 – Parameters values of the control circuit for FPT.....	186
Table BB.2 – Error shutdown times and criteria	192
Table BB.3 – Emergency shutdown times and criteria.....	192
Table BB.4 – EV simulator voltage ranges emergency shutdown reaction test	196
Table BB.5 – Setup of the test load for side B current regulation in CCM.....	201
Table BB.6 – Recommended steps for minimum side B current regulation in CCM.....	202
Table BB.7 – Recommended steps for side B voltage regulation in CVM	204
Table CC.1 – Vehicle couplers for system C	210
Table CC.2 – Component values and tolerances for configuration EE	212
Table CC.3 – Proximity pilot voltages.....	213
Table CC.4 – Component values and tolerances for configuration FF	215
Table CC.5 – Component limits for the disabled side B of the EV supply equipment	217
Table CC.6 – Message code mapping for sequence diagram	218
Table CC.7 – Example of a sequence description	219
Table CC.8 – Sequence description for normal startup.....	221
Table CC.9 – Sequence description for normal shutdown or pause after energy transfer by EV or EV supply equipment.....	227
Table CC.10 – Overview of error and emergency shutdown cases	229
Table CC.11 – Sequence description for EV supply equipment and EV initiated error shutdown	231
Table CC.12 – Sequence description for EV initiated error shutdown based on DIN SPEC 70121 during energy transfer.....	234
Table CC.13 – Sequence diagram an emergency shutdown executed by the EV.....	237
Table CC.14 – Sequence diagram an emergency shutdown executed by the EV supply equipment.....	240
Table CC.15 – Sequence description for pause before cable-check phase by EV supply equipment using ISO 15118-2:2014	243
Table CC.16 – Sequence description for pause after pre-charge phase and before energy transfer stage by the EV supply equipment using ISO 15118-2:2014	247
Table CC.17 – Sequence description for renegotiation initiated by EV or EV supply equipment using ISO 15118-2:2014	253
Table CC.18 – Insulation states and EV supply equipment reaction based on the insulation resistance	258
Table CC.19 – Values to design the EV supply equipment during pre-charge based on Figure CC.14	261
Table CC.20 – Energy transfer control modes at different communication session stage/phase.....	282
Table CC.21 – EV simulator target current and voltage.....	301

Table CC.22 – Current ripple limits	301
Table CC.23 – Component valued for the inrush current limit test	311
Table CC.24 – Current ripple limits	318
Table CC.25 – Test setup values to measure side B voltage regulation in CVM during pre-charge	323
Table CC.26 – Current ripple limits	332
Table CC.27 – EV simulator characteristics	342
Table CC.28 – Test cases for the functional check of the IMD.....	352
Table EE.1 – Test load parameters	356
Table FF.1 – Possible combinations for multi-side B EV supply equipment	361
Table HH.1 – Key(s) and exemplary values for design verification	371

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRIC VEHICLE CONDUCTIVE CHARGING SYSTEM –**Part 23: DC electric vehicle supply equipment**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61851-23 has been prepared by IEC technical committee 69: Electric power/energy transfer systems for electrically propelled road vehicles and industrial trucks. It is an International Standard.

This second edition cancels and replaces the first edition published in 2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) the structure has been rearranged according to IEC 61851-1:2017;
- b) electrical safety requirements in Clause 8 and Clause 12 have been revised based on the requirements in IEC 62477-1 and inspired by the hazard based safety approach of IEC 62368-1;

- c) test methods for checking conformity to the stated requirements have been mostly added; general provisions for compliance tests have been specified in Clause 102;
- d) specific requirements and/or information for the following functions have been added: energy transfer with thermal management system (101.2), bi-directional power transfer control (Annex DD), multi- side B separated EV supply equipment (Annex FF), and communication and energy transfer process (Annex GG);
- e) Annex AA (system A), Annex BB (system B) and Annex CC (system C) have been updated including additions in conjunction with b) and c). This document has been limited to be applicable to system A, system B and system C;
- f) the former Annex DD and Annex EE have been deleted. A new Annex EE, with the requirements for the artificial test load, has been added.
- g) a new informative annex for the touch current and the touch impulse current (Annex HH) has been added.

The text of this International Standard is based on the following documents:

Draft	Report on voting
69/907/FDIS	69/925/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

This document is to be read in conjunction with IEC 61851-1:2017.

The clauses of particular requirements in this document supplement or modify the corresponding clauses in IEC 61851-1:2017. Where the text of subsequent clauses indicates an "addition" to or a "replacement" of the relevant requirement, test specification or explanation of IEC 61851-1:2017, these changes are made to the relevant text of IEC 61851-1:2017, which then becomes part of this document. Where no change is necessary, the words "This clause of IEC 61851-1:2017 is applicable" are used. The new clauses which are not included in IEC 61851-1:2017 have a clause number starting from 101, for example 3.101, 101.1, etc. The annexes of this document are numbered using double-alphabet, for example Annex AA, to avoid confusion with the annexes in IEC 61851-1:2017.

In this document, the following print types are used:

- *test specifications: italic type.*
- notes: smaller roman type.

Figures in this document use L1 and N to represent the connection of the side A of the EV supply equipment to the AC supply network or DC supply network. This is only to simplify the figures and not to impose requirements.

A list of all parts in the IEC 61851 series, published under the general title *Electric vehicle conductive charging system*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

ELECTRIC VEHICLE CONDUCTIVE CHARGING SYSTEM –

Part 23: DC electric vehicle supply equipment

1 Scope

This part of IEC 61851 applies to the EV supply equipment to provide energy transfer between the supply network and electric vehicles (EVs), with a rated maximum voltage at side A of up to 1 000 V AC or up to 1 500 V DC and a rated maximum voltage at side B up to 1 500 V DC.

This document specifies the EV supply equipment of system A, system B and system C as defined in Annex AA, Annex BB and Annex CC. Other systems are under consideration.

This document provides the requirements for bidirectional power transfer (BPT) EV supply equipment for system A, with a rated maximum voltage at side A up to 1 000 V AC or 1 500 V DC. The requirements for reverse power transfer (RPT) and BPT for system B and system C are under consideration and are not specified in this document.

Annex DD provides information about BPT.

This document does not cover all safety aspects related to maintenance.

Requirements for systems not providing simple separation or protective separation between side A and side B are under consideration.

The requirements for digital communication between EV supply equipment and the EV to control energy transfer are defined in IEC 61851-24.

Requirements for energy transfer with an automated connection device are given in IEC 61851-23-1¹.

Specific requirements for EV supply equipment with multiple vehicle connectors are provided in Annex FF.

General information about energy transfer control, signalling and digital communication is provided in Annex GG.

General information on the touch current and touch impulse current is provided in Annex HH.

Requirements for EV supply equipment without current, voltage and/or power control are under consideration.

EV supply equipment in compliance with this document are not intended to provide energy transfer to a single EV with

- multiple vehicle connectors of the same EV supply equipment, or
- multiple EV supply equipment.

Requirements for such use case are under consideration.

¹ Under preparation. Stage at the time of publication: IEC AFDIS 61851-23-1:2023.