

BS ISO/IEC 18000-61:2012



BSI Standards Publication

Information technology — Radio frequency identification for item management

Part 61: Parameters for air interface
communications at 860 MHz to
960 MHz Type A

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

raising standards worldwide™



National foreword

This British Standard is the UK implementation of ISO/IEC 18000-61:2012. Together with BS ISO/IEC 18000-6:2013, BS ISO/IEC 18000-62:2012, BS ISO/IEC 18000-63:2012, and BS ISO/IEC 18000-64:2012, it supersedes BS ISO/IEC 18000-6:2010, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee IST/34, Automatic identification and data capture techniques.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2013.
Published by BSI Standards Limited 2013.

ISBN 978 0 580 75345 9

ICS 35.040

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 28 February 2013.

Amendments issued since publication

Date	Text affected
------	---------------

**Information technology — Radio
frequency identification for item
management —**

**Part 61:
Parameters for air interface
communications at 860 MHz to 960 MHz
Type A**

*Technologies de l'information — Identification par radiofréquence
(RFID) pour la gestion d'objets —*

*Partie 61: Paramètres de communications d'une interface radio entre
860 MHz et 960 MHz, Type A*



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction.....	vi
1 Scope	1
2 Conformance	2
2.1 Claiming conformance	2
2.2 Interrogator conformance and obligations	2
2.3 Tag conformance and obligations	2
3 Normative references	3
4 Terms, definitions, symbols and abbreviated terms	3
4.1 Terms and definitions	3
4.2 Symbols	4
4.3 Abbreviated terms	4
5 Overview	5
5.1 Parameter tables	5
6 Type A	9
6.1 Physical layer and data coding	9
6.1.1 Interrogator power-up waveform	9
6.1.2 Interrogator power-down	10
6.1.3 Frequency hopping carrier rise and fall times	11
6.1.4 FM0 return link	12
6.1.5 PIE (Pulse interval encoding) forward link	15
6.2 Data elements	20
6.2.1 Unique identifier (Tag ID)	20
6.2.2 Sub-UID	20
6.2.3 Application family identifier	21
6.2.4 Data storage format identifier (DSFID)	21
6.3 Protocol elements	22
6.3.1 Tag memory organisation	22
6.3.2 Support of battery assisted passive (BAP) tags	22
6.3.3 Block lock status	22
6.3.4 Tag signature	23
6.4 Protocol description	23
6.4.1 Protocol concept	23
6.4.2 Command format	24
6.4.3 Command flags	25
6.4.4 Round size	26
6.4.5 Command code definition and structure	26
6.4.6 Command classes	26
6.4.7 Command codes and CRC	28
6.4.8 Response format	31
6.4.9 Tag states	33
6.4.10 Collision arbitration	34
6.4.11 General explanation of the collision arbitration mechanism	34
6.5 Timing specifications	36
6.5.1 Timing specifications general	36
6.5.2 Tag state storage	36
6.5.3 Forward link to return link handover	37
6.5.4 Return link to forward link handover	37
6.5.5 Acknowledgement time window	37

6.6	Command format examples.....	39
6.7	Mandatory commands.....	39
6.7.1	Mandatory commands general.....	39
6.7.2	Next_slot.....	39
6.7.3	Standby_round.....	41
6.7.4	Reset_to_ready.....	42
6.7.5	Init_round_all.....	43
6.8	Optional commands.....	45
6.8.1	Optional commands general.....	45
6.8.2	Init_round.....	46
6.8.3	Close_slot.....	47
6.8.4	New_round.....	48
6.8.5	Select (by SUID).....	50
6.8.6	Read_blocks.....	51
6.8.7	Get_system_information.....	55
6.8.8	Begin_round.....	58
6.8.9	Write_single_block.....	60
6.8.10	Write_multiple_blocks.....	62
6.8.11	Lock_blocks.....	64
6.8.12	Write_AFI.....	66
6.8.13	Lock_AFI.....	68
6.8.14	Write_DSFID command.....	70
6.8.15	Lock_DSFID.....	72
6.8.16	Get_blocks_lock_status.....	74
6.8.17	Init_Fast_Slots.....	76
6.9	Custom commands.....	79
6.10	Proprietary commands.....	80
	Annex A (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks.....	81
A.1	Example CRC-5 encoder/decoder.....	81
A.2	Example CRC-16 encoder/decoder.....	82
	Bibliography.....	83

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

ISO/IEC 18000-61 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

ISO/IEC 18000 consists of the following parts, under the general title *Information technology — Radio frequency identification for item management*:

- *Part 1: Reference architecture and definition of parameters to be standardized*
- *Part 2: Parameters for air interface communications below 135 kHz*
- *Part 3: Parameters for air interface communications at 13,56 MHz*
- *Part 4: Parameters for air interface communications at 2,45 GHz*
- *Part 6: Parameters for air interface communications at 860 MHz to 960 MHz General*
- *Part 61: Parameters for air interface communications at 860 MHz to 960 MHz Type A*
- *Part 62: Parameters for air interface communications at 860 MHz to 960 MHz Type B*
- *Part 63: Parameters for air interface communications at 860 MHz to 960 MHz Type C*
- *Part 64: Parameters for air interface communications at 860 MHz to 960 MHz Type D*
- *Part 7: Parameters for active air interface communications at 433 MHz*

Introduction

This part of ISO/IEC 18000 describes a passive backscatter radio frequency identification (RFID) system that supports the following system capabilities:

- identification and communication with multiple tags in the field;
- selection of a subgroup of tags for identification or with which to communicate;
- reading from and writing to or rewriting data many times to individual tags;
- user-controlled permanently lockable memory;
- data integrity protection;
- Interrogator-to-tag communications link with error detection;
- tag-to-Interrogator communications link with error detection;
- support for both passive back-scatter tags with or without batteries.

This part of ISO/IEC 18000 specifies the physical and logical requirements for a passive-backscatter, RFID system operating in the 860 MHz to 960 MHz frequency range. The system comprises Interrogators, also known as readers, and tags, also known as labels.

An Interrogator transmits information to a tag by modulating an RF signal in the 860 MHz to 960 MHz frequency range. The tag receives both information and operating energy from this RF signal. Passive tags are those which receive all of their operating energy from the Interrogator's RF waveform. If tags maintain a battery then they may operate using some passive principles; however, they do not necessarily get all their operating energy from the Interrogator's RF waveform.

An Interrogator receives information from a tag by transmitting a continuous-wave (CW) RF signal to the tag; the tag responds by modulating the reflection coefficient of its antenna, thereby backscattering an information signal to the Interrogator. The system is Interrogator-Talks-First (ITF), meaning that a tag modulates its antenna reflection coefficient with an information signal only after being directed to do so by an Interrogator.

Interrogators and tags are not required to talk simultaneously; rather, communications are half-duplex, meaning that Interrogators talk and tags listen, or vice versa.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of patents concerning radio frequency identification technology.

ISO and IEC take no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured ISO and IEC that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these patent rights are registered with ISO and IEC.

Information on the declared patents may be obtained from:

Contact details	
Patent Holder Legal Name: Impinj, Inc.	Contact for license application Name & Department: Chris Diorio, CTO Address: 701 N 34th St Suite 300, Seattle, WA 98103, USA Tel.: +1 206 834 1115 Fax: +1 206 517 5262 E-mail: diorio@impinj.com URL (optional): www.impinj.com
Patent Holder Legal Name: NXP B.V.	Contact for license application Name & Department: Aaron Waxler, Intellectual Property & Licensing Address: 411 East Plumeria, San José, CA 95134-1924, USA Tel.: +1 914 860 4296 E-mail: Aaron.Waxler@nxp.com

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The latest information on IP that may be applicable to this part of ISO/IEC 18000 can be found at www.iso.org/patents

Information technology — Radio frequency identification for item management —

Part 61:

Parameters for air interface communications at 860 MHz to 960 MHz Type A

1 Scope

This part of ISO/IEC 18000 defines the air interface for radio frequency identification (RFID) devices operating in the 860 MHz to 960 MHz Industrial, Scientific, and Medical (ISM) band used in item management applications. It provides a common technical specification for RFID devices that can be used by ISO committees developing RFID application standards. This part of ISO/IEC 18000 is intended to allow for compatibility and to encourage inter-operability of products for the growing RFID market in the international marketplace. It defines the forward and return link parameters for technical attributes including, but not limited to, operating frequency, operating channel accuracy, occupied channel bandwidth, maximum effective isotropic radiated power (EIRP), spurious emissions, modulation, duty cycle, data coding, bit rate, bit rate accuracy, bit transmission order, and, where appropriate, operating channels, frequency hop rate, hop sequence, spreading sequence, and chip rate. It further defines the communications protocol used in the air interface.

This part of ISO/IEC 18000 specifies the physical and logical requirements for a passive-backscatter, Interrogator-Talks-First (ITF) systems. The system comprises Interrogators, also known as readers, and tags, also known as labels. An Interrogator receives information from a tag by transmitting a continuous-wave (CW) RF signal to the tag; the tag responds by modulating the reflection coefficient of its antenna, thereby backscattering an information signal to the Interrogator. The system is ITF, meaning that a tag modulates its antenna reflection coefficient with an information signal only after being directed to do so by an Interrogator.

In detail, this part of ISO/IEC 18000 contains Type A.

Type A is ITF. Type A uses Pulse-Interval Encoding (PIE) in the forward link and an adaptive ALOHA collision-arbitration algorithm.

This part of ISO/IEC 18000 specifies

- physical interactions (the signalling layer of the communication link) between Interrogators and tags,
- Interrogator and tag operating procedures and commands,
- the collision arbitration scheme used to identify a specific tag in a multiple-tag environment.