

ETSI TS 125 104 V12.6.0 (2015-10)



**Universal Mobile Telecommunications System (UMTS);
Base Station (BS) radio transmission and reception (FDD)
(3GPP TS 25.104 version 12.6.0 Release 12)**



Reference

RTS/TSGR-0425104vc60

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	7
1 Scope	8
2 References	8
3 Definitions and abbreviations.....	8
3.1 Definitions	8
3.2 Abbreviations	10
3.3 Symbols.....	11
4 General	11
4.1 Relationship between Minimum Requirements and Test Requirements	11
4.2 Base station classes	12
4.3 Regional requirements.....	13
4.4 Environmental requirements for the BS equipment	14
4.5 Applicability of requirements.....	14
4.6 Requirements for contiguous and non-contiguous spectrum.....	14
4.7 Requirements for BS capable of multi-band operation	15
5 Frequency bands and channel arrangement.....	15
5.1 General	15
5.2 Frequency bands.....	16
5.3 Tx-Rx frequency separation	18
5.4 Channel arrangement.....	18
5.4.1 Channel spacing.....	18
5.4.2 Channel raster	19
5.4.3 Channel number	19
6 Transmitter characteristics	20
6.1 General	20
6.2 Base station output power	21
6.2.1 Base station maximum output power.....	21
6.2.1.1 Minimum requirement	21
6.3 Frequency error	22
6.3.1 Minimum requirement	22
6.4 Output power dynamics.....	22
6.4.1 Inner loop power control in the downlink.....	22
6.4.1.1 Power control steps	22
6.4.1.1.1 Minimum requirement.....	22
6.4.2 Power control dynamic range	23
6.4.2.1 Minimum requirements	23
6.4.3 Total power dynamic range	23
6.4.3.1 Minimum requirement	23
6.4.4 Primary CPICH power.....	23
6.4.4.1 Minimum requirement	23
6.4.4A Secondary CPICH power.....	23
6.4.4A.1 Minimum Requirement for MIMO mode.....	24
6.4.4A.2 Minimum Requirement for MIMO mode with four transmit antennas	24
6.4.4B Demodulation CPICH power for MIMO mode with four transmit antennas.....	24
6.4.4B.1 Minimum Requirement.....	24
6.4.5 IPDL time mask	24
6.4.5.1 Minimum Requirement	24
6.4.6 Home base station output power for adjacent channel protection.....	25

6.4.6.1	Minimum requirement	26
6.5	(void)	26
6.6	Output RF spectrum emissions.....	26
6.6.1	Occupied bandwidth	26
6.6.1.1	Minimum requirement	26
6.6.2	Out of band emission	26
6.6.2.1	Spectrum emission mask	26
6.6.2.2	Adjacent Channel Leakage power Ratio (ACLR).....	31
6.6.2.2.1	Minimum requirement	32
6.6.2.2.2	Cumulative ACLR requirement in non-contiguous spectrum	33
6.6.3	Spurious emissions	34
6.6.3.1	Mandatory Requirements	34
6.6.3.1.1	Spurious emissions (Category A)	34
6.6.3.1.2	Spurious emissions (Category B)	34
6.6.3.2	Protection of the BS receiver of own or different BS	36
6.6.3.2.1	Minimum Requirement	36
6.6.3.3	Co-existence with other systems in the same geographical area.....	38
6.6.3.3.1	Minimum Requirements	39
6.6.3.4	Co-existence with co-located and co-sited base stations.....	42
6.6.3.4.1	Minimum Requirements	43
6.6.3.5	Co-existence with PHS	48
6.6.3.5.1	Minimum Requirement	48
6.6.3.6	Co-existence with services in adjacent frequency bands.....	48
6.6.3.6.1	Minimum requirement.....	48
6.6.3.7	Void.....	49
6.6.3.7.1	Void.....	49
6.6.3.7.2	Void.....	49
6.6.3.8	Protection of Public Safety Operations	49
6.6.3.8.1	Minimum Requirement	49
6.6.3.9	Co-existence with Home BS operating in other bands.....	49
6.6.3.9.1	Minimum Requirements	50
6.7	Transmitter intermodulation.....	51
6.7.1	Minimum requirement	51
6.8	Transmit modulation	51
6.8.1	Transmit pulse shape filter.....	52
6.8.2	Error Vector Magnitude.....	52
6.8.2.1	Minimum requirement	52
6.8.3	Peak code Domain error	52
6.8.3.1	Minimum requirement	52
6.8.4	Time alignment error	52
6.8.4.1	Minimum Requirements.....	53
6.8.5	Relative Code Domain Error for 64QAM modulation.....	53
6.8.5.1	Minimum requirement	53
7	Receiver characteristics.....	53
7.1	General	53
7.2	Reference sensitivity level.....	54
7.2.1	Minimum requirement	54
7.2.2	Maximum Frequency Deviation for Receiver Performance	54
7.3	Dynamic range	54
7.3.1	Minimum requirement	54
7.4	Adjacent Channel Selectivity (ACS).....	55
7.4.1	Minimum requirement	55
7.4.2	Minimum requirement - Co-location with UTRA-TDD.....	55
7.5	Blocking characteristics	55
7.5.1	Minimum requirement	55
7.5.2	Minimum Requirement - Co-location with GSM, DCS, PCS, CDMA, UTRA and/or E-UTRA, UTRA TDD and/or E-UTRA TDD	64
7.5.3	Void	70
7.6	Intermodulation characteristics	70
7.6.1	Minimum requirement	70
7.7	Spurious emissions	72

7.7.1	Minimum requirement	73
8	Performance requirement	73
8.1	General	73
8.2	Demodulation in static propagation conditions	74
8.2.1	Demodulation of DCH.....	74
8.2.1.1	Minimum requirement	74
8.3	Demodulation of DCH in multipath fading conditions	75
8.3.1	Multipath fading Case 1.....	75
8.3.1.1	Minimum requirement	75
8.3.2	Multipath fading Case 2.....	75
8.3.2.1	Minimum requirement	75
8.3.3	Multipath fading Case 3.....	76
8.3.3.1	Minimum requirement	76
8.3.4	Multipath fading Case 4.....	76
8.3.4.1	Minimum requirement	77
8.4	Demodulation of DCH in moving propagation conditions.....	77
8.4.1	Minimum requirement	77
8.5	Demodulation of DCH in birth/death propagation conditions.....	77
8.5.1	Minimum requirement	78
8.5A	Demodulation of DCH in high speed train conditions	78
8.5A.1	General.....	78
8.5A.2	Minimum requirement	78
8.6	(void).....	78
8.7	Performance requirement for RACH.....	78
8.7.1	Performance requirement for RACH preamble detection.....	78
8.7.2	Demodulation of RACH message.....	79
8.7.2.1	Minimum requirements for Static Propagation Condition	79
8.7.2.2	Minimum requirements for Multipath Fading Case 3	80
8.7.2.3	Minimum requirements for high speed train conditions	80
8.8	(void).....	81
8.9	(void).....	81
8.10	Performance of ACK/NACK detection for HS-DPCCH.....	81
8.10.1	ACK false alarm	81
8.10.2	ACK mis-detection	81
8.10A	Performance of ACK/NACK detection for 4C-HSDPA HS-DPCCH.....	81
8.10A.1	Performance requirements	82
8.10A.1.1	ACK false alarm.....	82
8.10A.1.2	ACK mis-detection.....	82
8.10A.2	Applicability of requirements	83
8.10B	Performance of ACK/NACK detection for 8C-HSDPA HS-DPCCH.....	83
8.11	Demodulation of E-DPDCH in multipath fading condition	84
8.11A	Demodulation of E-DPDCH and S-E-DPDCH in multipath fading condition for UL MIMO.....	84
8.12	Performance of signaling detection for E-DPCCH in multipath fading condition	85
Annex A (normative): Measurement channels.....		87
A.1	Summary of UL reference measurement channels.....	87
A.2	UL reference measurement channel for 12.2 kbps.....	88
A.3	UL reference measurement channel for 64 kbps.....	89
A.4	UL reference measurement channel for 144 kbps.....	90
A.5	UL reference measurement channel for 384 kbps.....	91
A.6	(void).....	91
A.7	Reference measurement channels for UL RACH	92
A.8	Reference measurement channel for HS-DPCCH.....	92
A.8A	Reference measurement channel for HS-DPCCH for 4C-HSDPA	93
A.9	Summary of E-DPDCH Fixed reference channels.....	94

A.10	E-DPDCH Fixed reference channel 1 (FRC1)	94
A.11	E-DPDCH Fixed reference channel 2 (FRC2)	95
A.12	E-DPDCH Fixed reference channel 3 (FRC3)	96
A.13	E-DPDCH Fixed reference channel 4 (FRC4)	97
A.14	E-DPDCH Fixed reference channel 5 (FRC5)	98
A.15	E-DPDCH Fixed reference channel 6 (FRC6)	99
A.16	E-DPDCH Fixed reference channel 7 (FRC7)	99
A.17	E-DPDCH Fixed reference channel 8 (FRC8)	100
A.18	E-DPDCH Fixed reference channel 9 (FRC9)	101
A.19	E-DPDCH Fixed reference channel 10 (FRC10)	102
Annex B (normative):	Propagation conditions	104
B.1	Static propagation condition	104
B.2	Multi-path fading propagation conditions	104
B.3	Moving propagation conditions	104
B.4	Birth-Death propagation conditions	105
B.4A	High speed train conditions	106
B.5	Multipath fading propagation conditions for E-DPDCH and E-DPCCH	108
Annex C (normative):	Characteristics of the W-CDMA interference signal	109
Annex D (normative):	Regional requirement for protection of DTT	110
Annex E (informative):	Change History	111
History		115

Foreword

This Technical Specification has been produced by the 3GPP.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of this TS, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version 3.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 Indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the specification.

1 Scope

This document establishes the Base Station minimum RF characteristics of the FDD mode of UTRA.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] ITU-R Recommendation SM.329, " Unwanted emissions in the spurious domain ".
- [2] (void)
- [3] ETSI ETR 273-1-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement of radiated methods of measurement (using test sites) and evaluation of the corresponding measurement uncertainties; Part 1: Uncertainties in the measurement of mobile radio equipment characteristics; Sub-part 2: Examples and annexes".
- [4] 3GPP TR 25.942 "RF System Scenarios".
- [5] 3GPP TS 45.004: "Digital cellular telecommunications system (Phase 2+); Modulation".
- [6] 3GPP TS 25.213: "Spreading and modulation (FDD)".
- [7] ITU-R recommendation SM.328: "Spectra and bandwidth of emissions".
- [8] 3GPP TS 36.104: " Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
- [9] ECC/DEC/(09)03 " Harmonised conditions for MFCN in the band 790-862 MHz", 30 Oct. 2009
- [10] 3GPP TS 37.104: " E-UTRA, UTRA and GSM/EDGE; Multi-Standard Radio (MSR) Base Station (BS) radio transmission and reception".
- [11] 3GPP TS 25.331: " Radio Resource Control. Protocol Specification".
- [12] 3GPP TS 25.214: "Physical layer procedures (FDD) ".
- [13] CEPT ECC Decision (13)03, 'The harmonised use of the frequency band 1452-1492 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)'.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following definitions apply:

Output power: mean power of one carrier of the base station, delivered to a load with resistance equal to the nominal load impedance of the transmitter.