



**Universal Mobile Telecommunications System (UMTS);
Measurements of radio performances for UMTS terminals in
speech mode**
(3GPP TR 25.914 version 13.0.0 Release 13)



Reference

RTR/TSGR-0425914vd00

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Report (TR) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	7
1 Scope	8
2 References	8
3 Symbols and Abbreviations.....	12
3.1 Symbols.....	12
3.2 Abbreviations	12
4 Introduction	13
4.1 Scope	13
4.2 Future extensions.....	14
5 Initial Conditions.....	14
5.1 Phantom specifications.....	14
5.1.1 Head phantom.....	14
5.1.2 DUT Positioning on head phantom.....	15
5.1.3 Laptop Ground Plane Phantom.....	16
5.1.4 DUT Positioning on Laptop Ground Plane Phantom.....	17
5.1.5 Hand Phantoms	18
5.1.5.1 Dimensions.....	18
5.1.5.2 Dielectric properties	19
5.1.5.3 Hand phantom grips	20
5.1.5.4 Mechanical Requirements of Hand Phantoms	22
5.1.6 DUT positioning for speech mode.....	23
5.1.6.1 Mono-blocks and closed sliders	23
5.1.6.2 Folds and open-slides	24
5.1.6.3 PDA.....	25
5.1.7 DUT positioning for browsing mode	26
5.1.7.1 Narrow DUT	26
5.1.7.2 PDA.....	27
5.2 Anechoic chamber constraints.....	27
5.2.1 Quiet zone dimension	28
5.2.2 Minimum distance between the DUT and the measurement antenna	28
5.2.3 Reflectivity of the quiet zone	28
5.2.4 Shielding effectiveness of the chamber	28
5.3 Embedded Devices	28
5.3.1 Notebook	29
5.3.2 Tablet	29
6 Measurement parameters.....	30
6.1 Definition of the Total Radiated Power (TRP).....	30
6.2 Definition of the Mean Effective Gain (MEG).....	31
6.3 Power angular models and channel XPR	31
6.4 Definition of Mean Effective Radiated Power (MERP).....	33
6.5 Definition of Total Radiated Sensitivity (TRS).....	33
6.6 Definition of Mean Effective Radiated Sensitivity (MERS)	33
6.7 Sampling grid	33
6.8 Measurement frequencies	34
7 Measurement procedure – transmitter performance.....	34
7.1 General measurement arrangements.....	34
7.2 Procedure for spherical scanning ranges	34
7.3 Calibration measurement.....	36

7.3	Reference antennas.....	38
8	Measurement procedure – receiver performance	40
8.1	General measurement arrangements.....	40
8.2	Procedure for spherical scanning ranges	40
8.3	Calibration measurement.....	40
9	Radiated power and sensitivity measurement techniques in UMTS system.....	41
9.1	Technical background information.....	41
9.1.1	The common test setup for TRP and TRS testing.....	41
9.2	TRP measurement	42
9.3	TRS measurement	43
9.4	Calibration of absolute levels	43
A	Annex A (informative): Estimation of measurement uncertainty.....	44
A.1	Mismatch uncertainty between measurement receiver and the probe antenna.....	50
A.1.1	Total combined mismatch uncertainty calculations.....	50
A.1.1.1	Mismatch uncertainty through the connector between two elements:	50
A.1.1.2	Mismatch uncertainty due to the interaction of several elements:	51
A.1.2	Total combined mismatch uncertainty:	52
A.2	Mismatch uncertainty of the RF relay	53
A.2.1	First part: RF Relay switched on the co-polarized signal	53
A.2.1.1	The mismatch through the connector between two elements	53
A.2.1.2	Mismatch due to the interaction between two elements or more	54
A.2.2	Second part: RF relay switched on the cross-polarized signal	54
A.2.2.1	The mismatch through the connector between two elements	54
A.2.2.2	Mismatch due to the interaction between two elements or more	54
A.2.3	Total combined mismatch uncertainty:	55
A.3	Insertion loss of the probe antenna cable	55
A.4	Insertion loss of the probe antenna attenuator (if used)	55
A.5	Insertion loss of the RF relays (if used).....	56
A.6	Influence of the antenna cable	56
A.6.1	Probe antenna cable.....	56
A.6.2	Calibration antenna cable	56
A.7	Absolute gain of the probe antenna.....	56
A.8	Measurement receiver: uncertainty of absolute level.....	56
A.9	Measurement distance	56
A.9.1	Offset of DUT phase centre from axis(es) of rotation.....	56
A.9.2	Mutual coupling	57
A.9.3	Phase curvature	57
A.10	Quality of quiet zone	57
A.11	Tx-power drift of DUT	58
A.12	Uncertainty related to the use of phantoms	58
A.12.1	Uncertainty from using different types of SAM phantom.....	58
A.12.2	Simulated tissue liquid uncertainty	58
A.12.3	Uncertainty of dielectric properties and shape of the hand phantom	59
A.12.4	Uncertainty from using different types of Laptop Ground Plane phantom	60
A.13	Coarse sampling grid.....	60
A.14	Random uncertainty	61
A.15	Uncertainty of network analyzer	62
A.16	Uncertainty of the gain/efficiency of the calibration antenna	62
A.17	Base station simulator: uncertainty of the absolute level	62

A.18	BER measurement: output level step resolution	62
A.19	Statistical uncertainty of the BER measurement.....	63
A.20	BER data rate normalization uncertainty	63
A.21	DUT sensitivity drift	63
A.22	Cable loss measurement uncertainty	63
A.23	Signal generator: uncertainty of the absolute output level	64
A.24	Signal generator: output level stability.....	64
A.25	Insertion loss: calibration antenna feed cable.....	64
A.26	Insertion loss: calibration antenna attenuator (if used).....	64
A.27	Chamber Statistical Ripple and Repeatability	65
A.28	Additional Power Loss in EUT Chassis	65
A.29	Void.....	77
A.29.1	Void.....	77
Annex B (informative):	Suggested recipes of liquid to be used inside SAM phantom.....	78
Annex C (informative):	System Parameters	79
C.1	Definition and applicability.....	79
C.2	Establishing the connection.....	79
C.2.1	Required parameters to initiate the communication - basic concepts.....	79
C.2.1.1	Conversational RAB	79
C.2.1.2	Logical, transport, and physical channels in UMTS	79
C.2.1.3	Dedicated physical channel.....	79
C.2.2	Recall on the reference measurement channel (reference to the standard paragraph)	79
C.2.3	Uplink 12.kbps reference measurement channel ([60], annex C, § C.2.1)	80
C.2.4	Downlink 12.2 kbps reference measurement channel ([60], annex C, § C.3.1)	80
Annex D (informative):	Radiated power and sensitivity measurement techniques in 2G systems	81
D.1	Introduction	81
D.1.1	Scope	81
D.1.2	References	81
D.1.3	Definitions, symbols and abbreviations.....	81
D.1.3.1	Definitions	81
D.1.3.2	Symbols	81
D.1.3.3	Abbreviations.....	81
D.2	Initial conditions.....	81
D.2.1	Phantom specifications.....	81
D.2.2	Anechoic chamber constraints.....	82
D.2.3	General arrangement	82
D.2.3.1	Free space	82
D.2.3.2	With SAM head phantom.....	82
D.2.3.3	Test-bed setup	83
D.3	Measurement parameters.....	83
D.3.1	Definition of the TRP parameter	83
D.3.2	Definition of the MEG parameter.....	83
D.3.3	Definition of the MERP parameter.....	83
D.3.4	Definition of the TRS parameter	83
D.3.5	Definition of the MERS parameter.....	83
D.4	Sampling grid	83
D.5	Measurement frequencies.....	84

D.6	Output power measurement.....	84
D.6.1	TRP	84
D.6.2	TRS	84
D.7	Measurement procedure – transmitter performance.....	84
D.7.1	Transmitter performance measurement	84
D.7.1.1	Spherical scanning ranges.....	84
D.7.2	Reference position	84
D.7.3	General measurement arrangements.....	85
D.7.3.1	TRP	85
D.7.3.2	TRS	85
D.7.4	Calibration measurement.....	86
D.8	Measurement uncertainty and corrections in 2G system measurements	86
Annex E (informative):	Alternative measurement technologies: reverberation chamber method	87
E.1	Reverberation chamber constraints	87
E.1.1	Chamber size	87
E.1.2	Mode-stirring facilities	87
E.1.3	Loading of chamber with lossy objects	88
E.1.4	Polarization imbalance and receiving antennas.....	88
E.1.5	Shielding effectiveness.....	89
E.2	Reverberation chamber method.....	89
E.2.1	Measurement procedure – transmitter performance.....	89
E.2.2	Measurement procedure – receiver performance	89
E.3	Calibration of reverberation chamber.....	90
E.3.1	Measurement of S-parameters through the chamber for a complete stirring sequence	91
E.3.2	Calculation of the chamber reference transfer function.....	92
E.3.3	Cable calibration	92
E.4	Estimation of measurement uncertainty	93
Annex F (informative):	Anechoic chamber specifications and validation method	94
F.1	Shielded anechoic chamber specifications	94
F.2	Quiet Zone reflectivity level validation.....	94
F.2.1	Description of a practical method for Quiet Zone characterization.....	94
Annex G (informative):	Reverberation chamber specifications and validation method.....	97
G.1	Shielded reverberation chamber specifications	97
G.2	Reverberation chamber statistical ripple and repeatability validation.....	97
Annex H (informative):	Dielectric Property Measurements of Hand Phantoms.....	99
H.1	Open-ended Coaxial Probe (OCP) Method.....	99
Annex I (informative):	Change history	101
	History	102

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document describes the methods to be used in order to assess the radio performances of the 3G user equipment/mobile stations (UE/MS) in active mode in both the up- and the downlink. The test procedure is based on the test method developed as a result of COST 273 Sub-Working Group (SWG) 2.2 members' contributions and the first draft was published in [1]. Background work has also been made in the former COST259 project [2] [3].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
 - For a specific reference, subsequent revisions do not apply.
 - For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] P. Boutou, J. Krogerus, J. Ø. Nielsen, T. Bolin, I. Egorov, K. Sulonen, "Measurement of Radio Performances for UMTS Mobile in Speech Mode: the First Draft of the Prestandard", COST 273 TD(03) 140, Paris, France, May 2003, 6 p.
- [2] "Feasibility Study of UE antenna efficiency test methods and performance requirement-final report", 3GPP TSG-RAN4 document TSGR#19(01)1086, September 2001.
- [3] L. M. Correia (editor), "Wireless Flexible Personalised Communications – Final Report of COST 259", ISBN: 0-471-49836-X, Wiley Europe, March 2001, 482 p.
- [4] [3GPP TS 25.101 V4.10.0](#): "User Equipment (UE) radio transmission and reception (FDD)".
- [5] [3GPP TD R4-011482](#): "Proposal for establishing co-operation between 3GPP and COST273 WG2.2 for the further development of UE antenna performance test method".
- [6] [3GPP TD R4-020724](#): "Development of Standard Test Procedure for 3G User Equipment Antenna Performance".
- [7] T. Taga, "Analysis for mean effective gain of mobile antennas in land mobile radio environments", IEEE Transactions on Vehicular Technology, 39(2): 117-131, May 1990.
- [8] A. Alayon Glazunov, "MEG of mobile terminal antennas in double directional channels", TD (03) 187, Prague, Czech Republic, September 2003.
- [9] K. Madsen, "Reverberation Chamber for Mobile Phone Radiated Tests", COST 273 TD(04) 087, Gothenburg, Sweden, June 2004.
- [10] P.-S. Kildal, "Accurate Measurements of Small Antennas and Radiation from Mobile Phones in Small Reverberation Chamber", COST273 TD(02)035.
- [11] K. Rosengren, P-S. Kildal, C. Carlsson, J. Carlsson, "Characterization of antennas for mobile and wireless terminals in reverberation chambers: Improved accuracy by platform stirring", Microwave and Optical Technology Letters, Vol. 30, No 20, pp.391-397, Sep. 2001.
- [12] P-S. Kildal, C. Carlsson, "TCP of 20 Mobile Phones Measured in Reverberation Chamber Procedure, Results, Uncertainty and Validation", Feb. 2002, report available from Bluetest AB, www.bluetest.se